

Package ‘CausalGPS’

May 25, 2023

Type Package

Title Matching on Generalized Propensity Scores with Continuous Exposures

Version 0.4.0

Maintainer Naeem Khoshnevis <nkhoshnevis@g.harvard.edu>

Description Provides a framework for estimating causal effects of a continuous exposure using observational data, and implementing matching and weighting on the generalized propensity score.
Wu, X., Mealli, F., Kioumourtzoglou, M.A., Dominici, F. and Braun, D., 2022. Matching on generalized propensity scores with continuous exposures. Journal of the American Statistical Association, pp.1-29.

License GPL-3

Language en-US

URL <https://github.com/NSAPH-Software/CausalGPS>

BugReports <https://github.com/NSAPH-Software/CausalGPS/issues>

Copyright Harvard University

Imports parallel, data.table, SuperLearner, xgboost, gam, MASS, polycor, wCorr, stats, ggplot2, rlang, logger, Rcpp, gnm, locpol, Ecume, KernSmooth

Encoding UTF-8

RoxygenNote 7.2.3

Suggests covr, knitr, rmarkdown, ranger, earth, testthat

VignetteBuilder knitr

Depends R (>= 3.5.0)

LinkingTo Rcpp

NeedsCompilation yes

Author Naeem Khoshnevis [aut, cre] (<<https://orcid.org/0000-0003-4315-1426>>, HUIT),
Xiao Wu [aut] (<<https://orcid.org/0000-0002-4884-657X>>, HSPH),
Danielle Braun [aut] (<<https://orcid.org/0000-0002-5177-8598>>, HSPH)

Repository CRAN

Date/Publication 2023-05-25 21:40:02 UTC

R topics documented:

CausalGPS-package	2
absolute_corr_fun	3
absolute_weighted_corr_fun	4
check_covar_balance	5
compile_pseudo_pop	6
estimate_gps	8
estimate_npmetric_erf	9
estimate_pmetric_erf	11
estimate_semipmetric_erf	12
generate_pseudo_pop	13
generate_syn_data	16
get_logger	17
plot.gpsm_erf	18
plot.gpsm_pspop	19
print.gpsm_erf	19
print.gpsm_pspop	20
set_logger	20
summary.gpsm_erf	21
summary.gpsm_pspop	21
synthetic_us_2010	22
Index	25

CausalGPS-package *The 'CausalGPS' package.*

Description

An R package for implementing matching and weighting on generalized propensity scores with continuous exposures.

Details

We developed an innovative approach for estimating causal effects using observational data in settings with continuous exposures, and introduce a new framework for GPS caliper matching.

Author(s)

Naeem Khoshnevis
 Xiao Wu
 Danielle Braun

References

Wu, X., Mealli, F., Kioumourtzoglou, M.A., Dominici, F. and Braun, D., 2022. Matching on generalized propensity scores with continuous exposures. *Journal of the American Statistical Association*, pp.1-29.

Kennedy, E.H., Ma, Z., McHugh, M.D. and Small, D.S., 2017. Non-parametric methods for doubly robust estimation of continuous treatment effects. *Journal of the Royal Statistical Society. Series B (Statistical Methodology)*, 79(4), pp.1229-1245.

absolute_corr_fun	<i>Check covariate balance using absolute approach</i>
-------------------	--

Description

Checks covariate balance based on absolute correlations for given data sets.

Usage

```
absolute_corr_fun(w, c)
```

Arguments

w	A vector of observed continuous exposure variable.
c	A data.frame of observed covariates variable.

Value

The function returns a list including:

- absolute_corr: the absolute correlations for each pre-exposure covariates;
- mean_absolute_corr: the average absolute correlations for all pre-exposure covariates.

Examples

```
set.seed(291)
n <- 100
mydata <- generate_syn_data(sample_size=100)
year <- sample(x=c("2001", "2002", "2003", "2004", "2005"), size = n,
  replace = TRUE)
region <- sample(x=c("North", "South", "East", "West"), size = n,
  replace = TRUE)
mydata$year <- as.factor(year)
mydata$region <- as.factor(region)
mydata$cf5 <- as.factor(mydata$cf5)
cor_val <- absolute_corr_fun(mydata[,2], mydata[, 3:length(mydata)])
print(cor_val$mean_absolute_corr)
```

`absolute_weighted_corr_fun`*Check Weighted Covariate Balance Using Absolute Approach*

Description

Checks covariate balance based on absolute weighted correlations for given data sets.

Usage

```
absolute_weighted_corr_fun(w, vw, c)
```

Arguments

<code>w</code>	A vector of observed continuous exposure variable.
<code>vw</code>	A vector of weights.
<code>c</code>	A data.table of observed covariates variable.

Value

The function returns a list saved the measure related to covariate balance `absolute_corr`: the absolute correlations for each pre-exposure covairates; `mean_absolute_corr`: the average absolute correlations for all pre-exposure covairates.

Examples

```
set.seed(639)
n <- 100
mydata <- generate_syn_data(sample_size=100)
year <- sample(x=c("2001", "2002", "2003", "2004", "2005"), size = n,
              replace = TRUE)
region <- sample(x=c("North", "South", "East", "West"), size = n,
                replace = TRUE)
mydata$year <- as.factor(year)
mydata$region <- as.factor(region)
mydata$cf5 <- as.factor(mydata$cf5)
cor_val <- absolute_weighted_corr_fun(mydata[,2],
                                    runif(n),
                                    mydata[, 3:length(mydata)])
print(cor_val$mean_absolute_corr)
```

check_covar_balance *Check covariate balance*

Description

Checks the covariate balance of original population or pseudo population.

Usage

```
check_covar_balance(w, c, ci_appr, counter_weight = NULL, nthread = 1, ...)
```

Arguments

w	A vector of observed continuous exposure variable.
c	A data.frame of observed covariates variable.
ci_appr	The causal inference approach.
counter_weight	A weight vector in different situations. If the matching approach is selected, it is an integer data.table of counters. In the case of the weighting approach, it is weight data.table.
nthread	The number of available threads.
...	Additional arguments passed to different models.

Details

Additional parameters:

- For ci_appr == matching:
 - covar_bl_method
 - covar_bl_tr

Value

output object:

- corr_results
 - absolute_corr
 - mean_absolute_corr
- pass (TRUE,FALSE)

Examples

```

set.seed(422)
n <- 100
mydata <- generate_syn_data(sample_size=100)
year <- sample(x=c("2001", "2002", "2003", "2004", "2005"), size = n,
              replace = TRUE)
region <- sample(x=c("North", "South", "East", "West"), size = n,
                replace = TRUE)
mydata$year <- as.factor(year)
mydata$region <- as.factor(region)
mydata$cf5 <- as.factor(mydata$cf5)

pseudo_pop <- generate_pseudo_pop(mydata[, c("id", "Y")],
                                 mydata[, c("id", "w")],
                                 mydata[, c("id", "cf1", "cf2", "cf3",
                                             "cf4", "cf5", "cf6", "year",
                                             "region")],
                                 ci_appr = "matching",
                                 gps_density = "kernel",
                                 exposure_trim_qtls = c(0.01, 0.99),
                                 sl_lib = c("m_xgboost"),
                                 covar_bl_method = "absolute",
                                 covar_bl_trs = 0.1,
                                 covar_bl_trs_type = "mean",
                                 max_attempt = 1,
                                 dist_measure = "l1",
                                 delta_n = 1,
                                 scale = 0.5,
                                 nthread = 1)

adjusted_corr_obj <- check_covar_balance(w = pseudo_pop$pseudo_pop[, c("w")],
                                         c = pseudo_pop$pseudo_pop[,
                                         pseudo_pop$covariate_cols_name],
                                         counter = pseudo_pop$pseudo_pop[,
                                         c("counter_weight")],
                                         ci_appr = "matching",
                                         nthread = 1,
                                         covar_bl_method = "absolute",
                                         covar_bl_trs = 0.1,
                                         covar_bl_trs_type = "mean")

```

compile_pseudo_pop *Compile pseudo population*

Description

Compiles pseudo population based on the original population and estimated GPS value.

Usage

```
compile_pseudo_pop(
  data_obj,
  ci_appr,
  gps_density,
  bin_seq,
  exposure_col_name,
  nthread,
  ...
)
```

Arguments

data_obj	A S3 object including the following: <ul style="list-style-type: none"> • Original data set + GPS values • e_gps_pred • e_gps_std_pred • w_resid • gps_mx (min and max of gps) • w_mx (min and max of w).
ci_appr	Causal inference approach.
gps_density	Model type which is used for estimating GPS value, including normal and kernel.
bin_seq	Sequence of w (treatment) to generate pseudo population. If NULL is passed the default value will be used, which is $\text{seq}(\min(w)+\text{delta}_n/2, \max(w), \text{by}=\text{delta}_n)$.
exposure_col_name	Exposure data column name.
nthread	An integer value that represents the number of threads to be used by internal packages.
...	Additional parameters.

Value

compile_pseudo_pop returns the pseudo population data that is compiled based on the selected causal inference approach.

Examples

```
set.seed(112)
m_d <- generate_syn_data(sample_size = 100)
data_with_gps <- estimate_gps(m_d[, c("id", "Y")],
  m_d[, c("id", "w")],
  m_d[, c("id", "cf1", "cf2", "cf3", "cf4", "cf5", "cf6")],
  gps_density = "normal",
  params = list(xgb_max_depth = c(3,4,5),
```

```

        xgb_nrounds=c(10,20,30,40,50,60)),
      nthread = 1,
      sl_lib = c("m_xgboost")
    )

pd <- compile_pseudo_pop(data_obj = data_with_gps,
  ci_appr = "matching",
  gps_density = "normal",
  bin_seq = NULL,
  exposure_col_name = c("w"),
  nthread = 1,
  dist_measure = "l1",
  covar_bl_method = 'absolute',
  covar_bl_trs = 0.1,
  covar_bl_trs_type= "mean",
  delta_n = 0.5,
  scale = 1)

```

 estimate_gps

Estimate generalized propensity score (GPS) values

Description

Estimates GPS value for each observation using normal or kernel approaches.

Usage

```

estimate_gps(
  w,
  c,
  gps_density = "normal",
  params = list(),
  sl_lib = c("m_xgboost"),
  nthread = 1,
  ...
)

```

Arguments

w	A data frame of observed continuous exposure variable. Including id and w columns.
c	A data frame of observed covariates variable. Also includes id column.
gps_density	Model type which is used for estimating GPS value, including normal (default) and kernel.
params	Includes list of parameters that are used internally. Unrelated parameters will be ignored.

sl_lib	A vector of prediction algorithms.
nthread	An integer value that represents the number threads to be used in a shared memory system.
...	Additional arguments passed to the model.

Value

The function returns a S3 object. Including the following:

- dataset : id, w, gps
- e_gps_pred
- e_gps_std_pred
- w_resid
- gps_mx (min and max of gps)
- w_mx (min and max of w).
- used_params

Note

If `internal.use` is set to be `FALSE`, only original data set + GPS will be returned.

The outcome variable is not used in estimating the GPS value. However, it is used in compiling the data set with GPS values.

Examples

```
m_d <- generate_syn_data(sample_size = 100)
data_with_gps <- estimate_gps(m_d[, c("id", "w")],
                             m_d[, c("id", "cf1", "cf2", "cf3",
                                       "cf4", "cf5", "cf6")],
                             gps_density = "normal",
                             params = list(xgb_max_depth = c(3,4,5),
                                           xgb_nrounds=c(10,20,30,40,50,60)),
                             nthread = 1,
                             sl_lib = c("m_xgboost")
                             )
```

estimate_npmetric_erf *Estimate smoothed exposure-response function (ERF) for pseudo population*

Description

Estimate smoothed exposure-response function (ERF) for matched and weighted data set using non-parametric models.

Usage

```
estimate_npmetric_erf(
  m_Y,
  m_w,
  counter_weight,
  bw_seq,
  w_vals,
  nthread,
  kernel_appr = "locpol"
)
```

Arguments

<code>m_Y</code>	A vector of outcome variable in the matched set.
<code>m_w</code>	A vector of continuous exposure variable in the matched set.
<code>counter_weight</code>	A vector of counter or weight variable in the matched set.
<code>bw_seq</code>	A vector of bandwidth values.
<code>w_vals</code>	A vector of values that you want to calculate the values of the ERF at.
<code>nthread</code>	The number of available cores.
<code>kernel_appr</code>	Internal kernel approach. Available options are <code>locpol</code> and <code>kernsmooth</code> .

Details

Estimate Functions Using Local Polynomial kernel regression.

Value

The function returns a `gpsm_erf` object. The object includes the following attributes:

- `params`
- `m_Y`
- `m_w`
- `bw_seq`
- `w_vals`
- `erf`
- `fcall`

Examples

```
set.seed(697)
m_d <- generate_syn_data(sample_size = 200)
pseudo_pop <- generate_pseudo_pop(m_d[, c("id", "Y")],
  m_d[, c("id", "w")],
  m_d[, c("id", "cf1", "cf2", "cf3",
    "cf4", "cf5", "cf6")],
```

```

ci_appr = "matching",
pred_model = "sl",
sl_lib = c("m_xgboost"),
params = list(xgb_nrounds=c(10,20,30),
  xgb_eta=c(0.1,0.2,0.3)),
nthread = 1,
covar_bl_method = "absolute",
covar_bl_trs = 0.1,
covar_bl_trs_type="mean",
max_attempt = 1,
dist_measure = "l1",
delta_n = 1,
scale = 0.5)

erf_obj <- estimate_npmetric_erf(pseudo_pop$pseudo_pop$Y,
  pseudo_pop$pseudo_pop$w,
  pseudo_pop$pseudo_pop$counter_weight,
  bw_seq=seq(0.2,2,0.2),
  w_vals = seq(2,20,0.5),
  nthread = 1)

```

estimate_pmetric_erf *Estimate Parametric Exposure Response Function*

Description

Estimate a constant effect size for matched and weighted data set using parametric models

Usage

```
estimate_pmetric_erf(formula, family, data, ...)
```

Arguments

formula	a vector of outcome variable in matched set.
family	a description of the error distribution (see ?gnm)
data	dataset that formula is build upon
...	Additional parameters for further fine tuning the gnm model.

Details

This method uses generalized nonlinear model (gnm) from gnm package.

Value

returns an object of class gnm

Examples

```

m_d <- generate_syn_data(sample_size = 100)
pseudo_pop <- generate_pseudo_pop(m_d[, c("id", "Y")],
                                  m_d[, c("id", "w")],
                                  m_d[, c("id", "cf1", "cf2", "cf3", "cf4", "cf5", "cf6")],
                                  ci_appr = "matching",
                                  sl_lib = c("m_xgboost"),
                                  params = list(xgb_nrounds=c(10,20,30),
                                                xgb_eta=c(0.1,0.2,0.3)),
                                  nthread = 1,
                                  covar_bl_method = "absolute",
                                  covar_bl_trs = 0.1,
                                  covar_bl_trs_type= "mean",
                                  max_attempt = 1,
                                  dist_measure = "l1",
                                  delta_n = 1,
                                  scale = 0.5)

outcome_m <- estimate_pmetric_erf(formula = Y ~ w,
                                  family = gaussian,
                                  data = pseudo_pop$pseudo_pop)

```

```
estimate_semipmetric_erf
```

Estimate semi-exposure-response function (semi-ERF).

Description

Estimates the smoothed exposure-response function using a generalized additive model with splines.

Usage

```
estimate_semipmetric_erf(formula, family, data, ...)
```

Arguments

formula	a vector of outcome variable in matched set.
family	a description of the error distribution (see ?gam).
data	dataset that formula is build upon.
...	Additional parameters for further fine tuning the gam model.

Details

This approach uses Generalized Additive Model (gam) using mgcv package.

Value

returns an object of class gam

Examples

```
m_d <- generate_syn_data(sample_size = 100)
pseudo_pop <- generate_pseudo_pop(m_d[, c("id", "Y")],
  m_d[, c("id", "w")],
  m_d[, c("id", "cf1", "cf2", "cf3", "cf4", "cf5", "cf6")],
  ci_appr = "matching",
  sl_lib = c("m_xgboost"),
  params = list(xgb_nrounds=c(10,20,30),
    xgb_eta=c(0.1,0.2,0.3)),
  nthread = 1,
  covar_bl_method = "absolute",
  covar_bl_trs = 0.1,
  covar_bl_trs_type = "mean",
  max_attempt = 1,
  dist_measure = "l1",
  delta_n = 1,
  scale = 0.5)

outcome_m <- estimate_semipmetric_erf (formula = Y ~ w,
  family = gaussian,
  data = pseudo_pop$pseudo_pop)
```

generate_pseudo_pop *Generate pseudo population*

Description

Generates pseudo population data set based on user-defined causal inference approach. The function uses an adaptive approach to satisfies covariate balance requirements. The function terminates either by satisfying covariate balance or completing the requested number of iteration, whichever comes first.

Usage

```
generate_pseudo_pop(
  Y,
  w,
  c,
  ci_appr,
  gps_density = "normal",
  use_cov_transform = FALSE,
  transformers = list("pow2", "pow3"),
```

```

bin_seq = NULL,
exposure_trim_qtls = c(0.01, 0.99),
gps_trim_qtls = c(0, 1),
params = list(),
sl_lib = c("m_xgboost"),
nthread = 1,
include_original_data = FALSE,
gps_obj = NULL,
...
)

```

Arguments

Y	A data.frame comprised of two columns: one contains the observed outcome variable, and the other is labeled as 'id'. The column for the outcome variable can be assigned any name as per your requirements.
w	A data.frame comprised of two columns: one contains the observed exposure variable, and the other is labeled as 'id'. The column for the outcome variable can be assigned any name as per your requirements.
c	A data.frame of includes observed covariate variables. It should also consist of a column named 'id'.
ci_appr	The causal inference approach. Possible values are: <ul style="list-style-type: none"> "matching": Matching by GPS "weighting": Weighting by GPS
gps_density	Model type which is used for estimating GPS value, including normal (default) and kernel.
use_cov_transform	If TRUE, the function uses transformer to meet the covariate balance.
transformers	A list of transformers. Each transformer should be a unary function. You can pass name of customized function in the quotes. Available transformers: <ul style="list-style-type: none"> pow2: to the power of 2 pow3: to the power of 3
bin_seq	Sequence of w (treatment) to generate pseudo population. If NULL is passed the default value will be used, which is $\text{seq}(\min(w) + \text{delta}_n/2, \max(w), \text{by} = \text{delta}_n)$.
exposure_trim_qtls	A numerical vector of two. Represents the trim quantile level for exposure values. Both numbers should be in the range of [0,1] and in increasing order (default: c(0.01, 0.99)).
gps_trim_qtls	A numerical vector of two. Represents the trim quantile level for the gps values. Both numbers should be in the range of [0,1] and in increasing order (default: c(0.0, 1.0)).
params	Includes list of params that is used internally. Unrelated parameters will be ignored.
sl_lib	A vector of prediction algorithms.

nthread	An integer value that represents the number of threads to be used by internal packages.
include_original_data	If TRUE, includes the original data in the outcome.
gps_obj	A gps object that is generated with estimate_gps function. If it is provided, the number of iteration will forced to 1 (Default: NULL).
...	Additional arguments passed to different models.

Details

Additional parameters:

Causal Inference Approach (ci.appr):

- if ci.appr = 'matching':
 - *dist_measure*: Matching function. Available options:
 - * 11: Manhattan distance matching
 - *delta_n*: caliper parameter.
 - *scale*: a specified scale parameter to control the relative weight that is attributed to the distance measures of the exposure versus the GPS.
 - *covar_bl_method*: covariate balance method. Available options:
 - * 'absolute'
 - *covar_bl_trs*: covariate balance threshold
 - *covar_bl_trs_type*: covariate balance type (mean, median, maximal)
 - *max_attempt*: maximum number of attempt to satisfy covariate balance.
 - See [create_matching\(\)](#) for more details about the parameters and default values.
- if ci.appr = 'weighting':
 - *covar_bl_method*: Covariate balance method.
 - *covar_bl_trs*: Covariate balance threshold
 - *max_attempt*: Maximum number of attempt to satisfy covariate balance.

Value

Returns a pseudo population (gspm_pspop) object that is generated or augmented based on the selected causal inference approach (ci_appr). The object includes the following objects:

- params
 - ci_appr
 - params
- pseudo_pop
- adjusted_corr_results
- original_corr_results
- best_gps_used_params
- effect size of generated pseudo population

Examples

```

m_d <- generate_syn_data(sample_size = 100)
pseuoo_pop <- generate_pseudo_pop(m_d[, c("id", "Y")],
  m_d[, c("id", "w")],
  m_d[, c("id", "cf1", "cf2", "cf3", "cf4", "cf5", "cf6")],
  ci_appr = "matching",
  gps_density = "normal",
  bin_seq = NULL,
  expos_trim_qlts = c(0.01, 0.99),
  gps_trim_qlts = c(0.01, 0.99),
  use_cov_transform = FALSE,
  transformers = list(),
  params = list(xgb_nrounds=c(10, 20, 30),
    xgb_eta=c(0.1, 0.2, 0.3)),
  sl_lib = c("m_xgboost"),
  nthread = 1,
  covar_bl_method = "absolute",
  covar_bl_trs = 0.1,
  covar_bl_trs_type = "mean",
  max_attempt = 1,
  dist_measure = "l1",
  delta_n = 1,
  scale = 0.5)

```

generate_syn_data

Generate synthetic data for the CausalGPS package

Description

Generates synthetic data set based on different GPS models and covariates.

Usage

```

generate_syn_data(
  sample_size = 1000,
  outcome_sd = 10,
  gps_spec = 1,
  cova_spec = 1,
  vectorized_y = FALSE
)

```

Arguments

sample_size	A positive integer number that represents a number of data samples.
outcome_sd	A positive double number that represents standard deviation used to generate the outcome in the synthetic data set.

gps_spec	<p>A numerical integer values ranging from 1 to 7. The complexity and form of the relationship between covariates and treatment variables are determined by the gps_spec. Below, you will find a concise definition for each of these values:</p> <ul style="list-style-type: none"> • <i>gps_spec: 1</i>: The treatment is generated using a normal distribution (stats::rnorm) and a linear function of covariates (cf1 to cf6). • <i>gps_spec: 2</i>: The treatment is generated using a Student's t-distribution (stats::rt) and a linear function of covariates, but is also truncated to be within a specific range (-5 to 25). • <i>gps_spec: 3</i>: The treatment includes a quadratic term for the third covariate. • <i>gps_spec: 4</i>: The treatment is calculated using an exponential function within a fraction, creating logistic-like model. • <i>gps_spec: 5</i>: The treatment also uses logistic-like model but with different parameters. • <i>gps_spec: 6</i>: The treatment is calculated using the natural logarithm of the absolute value of a linear combination of the covariates. • <i>gps_spec: 7</i>: The treatment is generated similarly to gps_spec = 2, but without truncation.
cova_spec	<p>A numerical value (1 or 2) to modify the covariates. It determines how the covariates in the synthetic data set are transformed. If cova_spec equals 2, the function applies non-linear transformation to the covariates, which can add complexity to the relationships between covariates and outcomes in the synthetic data. See the code for more details.</p>
vectorized_y	<p>A Boolean value indicates how Y internally is generated. (Default = FALSE). This parameter is introduced for backward compatibility. vectorized_y = TRUE performs better.</p>

Value

synthetic_data: The function returns a data.frame saved the constructed synthetic data.

Examples

```
set.seed(298)
s_data <- generate_syn_data(sample_size = 100,
                           outcome_sd = 10,
                           gps_spec = 1,
                           cova_spec = 1)
```

get_logger

Get Logger Settings

Description

Returns current logger settings.

Usage

```
get_logger()
```

Value

Returns a list that includes **logger_file_path** and **logger_level**.

Examples

```
set_logger("mylogger.log", "INFO")  
log_meta <- get_logger()
```

plot.gpsm_erf	<i>Extend generic plot functions for gpsm_erf class</i>
---------------	---

Description

A wrapper function to extend generic plot functions for gpsm_erf class.

Usage

```
## S3 method for class 'gpsm_erf'  
plot(x, ...)
```

Arguments

x	A gpsm_erf object.
...	Additional arguments passed to customize the plot.

Value

Returns a ggplot2 object, invisibly. This function is called for side effects.

plot.gpsm_pspop	<i>Extend generic plot functions for gpsm_eref class</i>
-----------------	--

Description

A wrapper function to extend generic plot functions for gpsm_eref class.

Usage

```
## S3 method for class 'gpsm_pspop'  
plot(x, ...)
```

Arguments

x	A gpsm_eref object.
...	Additional arguments passed to customize the plot.

Value

Returns a ggplot2 object, invisibly. This function is called for side effects.

print.gpsm_eref	<i>Extend print function for gpsm_eref object</i>
-----------------	---

Description

Extend print function for gpsm_eref object

Usage

```
## S3 method for class 'gpsm_eref'  
print(x, ...)
```

Arguments

x	A gpsm_eref object.
...	Additional arguments passed to customize the results.

Value

No return value. This function is called for side effects.

print.gpsm_pspop	<i>Extend print function for gpsm_pspop object</i>
------------------	--

Description

Extend print function for gpsm_pspop object

Usage

```
## S3 method for class 'gpsm_pspop'
print(x, ...)
```

Arguments

x	A gpsm_pspop object.
...	Additional arguments passed to customize the results.

Value

No return value. This function is called for side effects.

set_logger	<i>Set Logger Settings</i>
------------	----------------------------

Description

Updates logger settings, including log level and location of the file.

Usage

```
set_logger(logger_file_path = "CausalGPS.log", logger_level = "INFO")
```

Arguments

logger_file_path	A path (including file name) to log the messages. (Default: CausalGPS.log)
logger_level	The log level. Available levels include: <ul style="list-style-type: none"> • TRACE • DEBUG • INFO (Default) • SUCCESS • WARN • ERROR • FATAL

Value

No return value. This function is called for side effects.

Examples

```
set_logger("Debug")
```

```
summary.gpsm_erf      print summary of gpsm_erf object
```

Description

print summary of gpsm_erf object

Usage

```
## S3 method for class 'gpsm_erf'
summary(object, ...)
```

Arguments

object A gpsm_erf object.
... Additional arguments passed to customize the results.

Value

Returns summary of data

```
summary.gpsm_pspop   print summary of gpsm_pspop object
```

Description

print summary of gpsm_pspop object

Usage

```
## S3 method for class 'gpsm_pspop'
summary(object, ...)
```

Arguments

object A gpsm_pspop object.
... Additional arguments passed to customize the results.

Value

Returns summary of data

synthetic_us_2010	<i>Public data set for air pollution and health studies, case study: 2010 county-Level data set for the contiguous United States</i>
-------------------	--

Description

A dataset containing exposure, confounders, and outcome for causal inference studies. The dataset is hosted on Harvard dataverse [doi:10.7910/DVN/L7YF2G](https://dataverse.harvard.edu/dataset.xhtml?persistentId=doi:10.7910/DVN/L7YF2G). This dataset was produced from five different resources. Please see https://github.com/NSAPH-Projects/synthetic_data/ for the data processing pipelines. In the following

Exposure Data

The exposure parameter is PM2.5. Di et al. (2019) provided daily, and annual PM2.5 estimates at 1 km×1 km grid cells in the entire United States. The data can be downloaded from Di et al. (2021). Features in this category starts with *qd_* prefix.

Census Data

The main reference for getting the census data is the United States Census Bureau. There are numerous studies and surveys for different geographical resolutions. We use 2010 county level American County Survey at the county level (*acs5*). Features in this category starts with *cs_* prefix.

CDC Data

The Centers for Disease Control and Prevention (CDC), provides the Behavioral Risk Factor Surveillance System (Centers for Disease Control and Prevention (2021)), which is the nation's premier system of health-related telephone surveys that collect state data about U.S. residents regarding their health-related risk behaviors.

GridMET Data

Climatology Lab at the University of California, Merced, provides the GridMET data (Abatzoglou (2013)). The data set is daily surface meteorological data covering the contiguous United States.

CMS Data

The Centers for Medicare and Medicaid Services(CMS) provides synthetic data at the county level for 2008-2010 (Centers for Medicare & Medicaid Services (2021)).

The definition of each variables are provided below. All data are collected for 2010 and aggregated into the county level and in the contiguous United States.

Usage

```
data(synthetic_us_2010)
```

Format

A data frame with 3109 rows and 46 variables:

qd_mean_pm25 Mean PM2.5 (microgram/m3)

cs_poverty The proportion of below poverty level population among 65+ years old.

cs_hispanic The proportion of Hispanic or Latino population among 65+ years old.

cs_black The proportion of Black or African American population among 65+ years old.

cs_white The proportion of White population among 65 years and over.

cs_native The proportion of American Indian or Alaska native population among 65 years and over.

cs_asian The proportion of Asian population among 65 years and over.

cs_other The proportion of other races population among 65 years and over.

cs_ed_below_highschool The proportion of the population with below high school level education among 65 years and over.

cs_household_income Median Household income in the past 12 months (in 2010 inflation-adjusted dollars) where householder is 65 years and over.

cs_median_house_value Median house value (USD)

cs_total_population Total Population

cs_area Area of each county (square miles)

cs_population_density The number of the population in one square mile.

cdc_mean_bmi Body Mass Index.

cdc_pct_cusmoker The proportion of current smokers.

cdc_pct_sdsmoker The proportion of some days smokers.

cdc_pct_fmoker The proportion of former smokers.

cdc_pct_nvsmoker The proportion of never smokers.

cdc_pct_nnsoker The proportion of not known smokers.

gmet_mean_tmmn Annual mean of daily minimum temperature (K)

gmet_mean_summer_tmmn The mean of daily minimum temperature during summer (K)

gmet_mean_winter_tmmn The mean of daily minimum temperature during winter (K)

gmet_mean_tmmx Annual mean of daily maximum temperature (K)

gmet_mean_summer_tmmx The mean of daily maximum temperature during summer (K)

gmet_mean_winter_tmmx The mean of daily maximum temperature during winter (K)

gmet_mean_rmn Annual mean of daily minimum relative humidity (%)

gmet_mean_summer_rmn The mean of daily minimum relative humidity during summer (%)

gmet_mean_winter_rmn The mean of daily minimum relative humidity during winter (%)

gmet_mean_rmx Annual mean of daily maximum relative humidity (%)

gmet_mean_summer_rmx The mean of daily maximum relative humidity during summer (%)

gmet_mean_winter_rmx The mean of daily maximum relative humidity during winter (%)

gmet_mean_sph Annual mean of daily mean specific humidity (kg/kg)
gmet_mean_summer_sph The mean of daily mean specific humidity during summer(kg/kg)
gmet_mean_winter_sph The mean of daily mean specific humidity during winter(kg/kg)
cms_mortality_pct The proportion of deceased patients.
cms_white_pct The proportion of White patients.
cms_black_pct The proportion of Black patients.
cms_hispanic_pct The proportion of Hispanic patients.
cms_others_pct The proportion of Other patients.
cms_female_pct The proportion of Female patients.
region The region that the county is located in.

```
NORTHEAST=("NY", "MA", "PA", "RI", "NH", "ME", "VT", "CT", "NJ")
SOUTH=("DC", "VA", "NC", "WV", "KY", "SC", "GA", "FL", "AL", "TN", "MS", "AR", "MD", "DE", "OK", "TX", "LA")
MIDWEST=c("OH", "IN", "MI", "IA", "MO", "WI", "MN", "SD", "ND", "IL", "KS", "NE")
WEST=c("MT", "CO", "WY", "ID", "UT", "NV", "CA", "OR", "WA", "AZ", "NM")
```

FIPS Federal Information Processing Standards, a unique ID for each county.

NAME County, State name.

STATE State abbreviation.

STATE_CODE State numerical code.

References

Abatzoglou, John T. 2013. "Development of Gridded Surface Meteorological Data for Ecological Applications and Modelling." *International Journal of Climatology* 33 (1): 121–31. doi:10.1002/joc.3413.

Centers for Disease Control and Prevention. 2021. "Behavioral Risk Factor Surveillance System." https://www.cdc.gov/brfss/annual_data/annual_2010.htm/.

Centers for Medicare & Medicaid Services. 2021. "CMS 2008-2010 Data Entrepreneurs' Synthetic Public Use File (DE-SynPUF)." https://www.cms.gov/research-statistics-data-and-systems/downloadable-public-use-files/synpufs/de_syn_puf.

Di, Qian, Heresh Amini, Liuhua Shi, Itai Kloog, Rachel Silvern, James Kelly, M Benjamin Sabath, et al. 2019. "An Ensemble-Based Model of Pm2.5 Concentration Across the Contiguous United States with High Spatiotemporal Resolution." *Environment International* 130: 104909. doi:10.1016/j.envint.2019.104909.

Di, Qian, Yaguang Wei, Alexandra Shtein, Carolynne Hultquist, Xiaoshi Xing, Heresh Amini, Liuhua Shi, et al. 2021. "Daily and Annual Pm2.5 Concentrations for the Contiguous United States, 1-Km Grids, V1 (2000 - 2016)." NASA Socioeconomic Data; Applications Center (SEDAC). doi:10.7927/0rvr4538.

Index

* datasets

synthetic_us_2010, [22](#)

absolute_corr_fun, [3](#)

absolute_weighted_corr_fun, [4](#)

CausalGPS (CausalGPS-package), [2](#)

CausalGPS-package, [2](#)

check_covar_balance, [5](#)

compile_pseudo_pop, [6](#)

create_matching(), [15](#)

estimate_gps, [8](#)

estimate_npmetric_erf, [9](#)

estimate_pmetric_erf, [11](#)

estimate_semipmetric_erf, [12](#)

generate_pseudo_pop, [13](#)

generate_syn_data, [16](#)

get_logger, [17](#)

plot.gpsm_erf, [18](#)

plot.gpsm_pspop, [19](#)

print.gpsm_erf, [19](#)

print.gpsm_pspop, [20](#)

set_logger, [20](#)

summary.gpsm_erf, [21](#)

summary.gpsm_pspop, [21](#)

synthetic_us_2010, [22](#)