

Package ‘SAMtool’

September 16, 2021

Type Package

Title Stock Assessment Methods Toolkit

Version 1.2.2

Date 2021-09-16

Maintainer Quang Huynh <quang@bluematterscience.com>

Description Simulation tools for closed-loop simulation are provided for the 'MSEtool' operating model to inform data-rich fisheries. 'SAMtool' provides a conditioning model, assessment models of varying complexity with standardized reporting, model-based management procedures, and diagnostic tools for evaluating assessments inside closed-loop simulation.

License GPL-3

Depends R (>= 3.5.0), MSEtool (>= 3.0.0)

Imports TMB, corpcor, dplyr, gplots, graphics, methods, rmarkdown, snowfall, stats, utils, vars

LinkingTo TMB, RcppEigen

Suggests abind, caret, covr, ggplot2, knitr, mvtnorm, numDeriv, reshape2, shiny, testthat

LazyData yes

LazyLoad yes

RoxygenNote 7.1.1

Encoding UTF-8

VignetteBuilder knitr

URL <https://github.com/Blue-Matter/SAMtool>

BugReports <https://github.com/Blue-Matter/SAMtool/issues>

NeedsCompilation yes

Author Quang Huynh [aut, cre],
Tom Carruthers [aut],
Adrian Hordyk [aut]

Repository CRAN

Date/Publication 2021-09-16 21:20:02 UTC

R topics documented:

SAMtool-package	3
Assessment-class	4
cDD	6
check_RCMdata	10
compare_models	17
DD_TMB	18
diagnostic	22
getinds	23
HCRlin	24
HCR_escapement	25
HCR_FB	27
HCR_MSX	28
HCR_ramp	29
HCR_segment	31
mahplot	33
make_interim_MP	33
Model-based-MP	36
pcod	37
plot.Assessment	38
plot.prof	39
plot.RCModel	40
plot.retro	42
plot_betavar	43
plot_composition	44
plot_crosscorr	45
plot_lognormalvar	46
plot_residuals	47
plot_SR	48
plot_steepness	49
plot_timeseries	50
PRBcalc	52
prelim_AM	53
Probs	54
prof-class	55
profile	55
project-class	57
projection	57
RCMdata-class	59
RCModel-class	61
retro-class	63
retrospective	63
retrospective_AM	64

SCA	66
SCA_CAL	72
SCA_DDM	75
SCA_RWM	78
Shortcut	82
SP	84
SP_production	89
SSS	90
summary.Assessment	92
swordfish	92
TAC_MSY	93
userguide	93
VPA	94
Index	98

SAMtool-package	<i>Stock Assessment Methods Toolkit</i>
-----------------	---

Description

Simulation tools for closed-loop simulation are provided for the 'MSEtool' operating model to inform data-rich fisheries. SAMtool provides an OM conditioning model, assessment models of varying complexity with standardized reporting, diagnostic tools for evaluating assessments within closed-loop simulation, and helper functions for building more complex operating models and model-based management procedures.

How to use SAMtool

The main features of SAMtool are the assessment models and the ability to make model-based management procedures by combining assessment models with harvest control rules. Such MPs can be used and tested in management strategy evaluation with MSEtool operating models. An overview of these features is available in the [SAMtool vignette](#).

The [RCM](#) (Rapid Conditioning Model) can be used to condition operating models from real data.

The following articles are available on the openMSE website:

- [Description of assessment models](#)
- [General overview of RCM](#)

Author(s)

Quang Huynh <quang@bluematterscience.com>

Tom Carruthers <tom@bluematterscience.com>

Adrian Hordyk <adrian@bluematterscience.com>

References

Carruthers, T.R., Punt, A.E., Walters, C.J., MacCall, A., McAllister, M.K., Dick, E.J., Cope, J. 2014. Evaluating methods for setting catch limits in data-limited fisheries. *Fisheries Research*. 153: 48-68.

Carruthers, T.R., Kell, L.T., Butterworth, D.S., Maunder, M.N., Geromont, H.F., Walters, C., McAllister, M.K., Hillary, R., Levontin, P., Kitakado, T., Davies, C.R. Performance review of simple management procedures. *ICES Journal of Marine Science*. 73: 464-482.

Assessment-class	<i>Class-Assessment</i>
------------------	-------------------------

Description

An S4 class that contains assessment output. Created from a function of class `Assess`.

Slots

`Model` Name of the assessment model.

`Name` Name of Data object.

`conv` Logical. Whether the assessment model converged (defined by whether TMB returned a positive-definite covariance matrix for the model).

`UMSY` Estimate of exploitation at maximum sustainable yield.

`FMSY` Estimate of instantaneous fishing mortality rate at maximum sustainable yield.

`MSY` Estimate of maximum sustainable yield.

`BMSY` Biomass at maximum sustainable yield.

`SSBMSY` Spawning stock biomass at maximum sustainable yield.

`VBMSY` Vulnerable biomass at maximum sustainable yield.

`B0` Biomass at unfished equilibrium.

`R0` Recruitment at unfished equilibrium.

`N0` Abundance at unfished equilibrium.

`SSB0` Spawning stock biomass at unfished equilibrium.

`VB0` Vulnerable biomass at unfished equilibrium.

`h` Steepness.

`U` Time series of exploitation.

`U_UMSY` Time series of relative exploitation.

`FMort` Time series of instantaneous fishing mortality.

`F_FMSY` Time series of fishing mortality relative to MSY.

`B` Time series of biomass.

`B_BMSY` Time series of biomass relative to MSY.

`B_B0` Time series of depletion.

SSB Time series of spawning stock biomass.

SSB_SSBMSY Time series of spawning stock biomass relative to MSY.

SSB_SSB0 Time series of spawning stock depletion.

VB Time series of vulnerable biomass.

VB_VBMSY Time series of vulnerable biomass relative to MSY.

VB_VB0 Time series of vulnerable biomass depletion.

R Time series of recruitment.

N Time series of population abundance.

N_at_age Time series of numbers-at-age matrix.

Selectivity Selectivity-at-age matrix.

Obs_Catch Observed catch.

Obs_Index Observed index.

Obs_C_at_age Observed catch-at-age matrix.

Catch Predicted catch.

Index Predicted index.

C_at_age Predicted catch-at-age matrix.

Dev A vector of estimated deviation parameters.

Dev_type A description of the deviation parameters, e.g. "log recruitment deviations".

NLL Negative log-likelihood. A vector for the total likelihood, integrated across random effects if applicable, components, and penalty term (applied when $U > 0.975$ in any year).

SE_UMSY Standard error of UMSY estimate.

SE_FMSY Standard error of FMSY estimate.

SE_MSY Standard error of MSY estimate.

SE_U_UMSY Standard error of U/UMSY.

SE_F_FMSY Standard error of F/FMSY.

SE_B_BMSY Standard error of B/BMSY.

SE_B_B0 Standard error of B/B0.

SE_SSB_SSBMSY Standard error of SSB/SSBMSY.

SE_SSB_SSB0 Standard error of SSB/SSB0.

SE_VB_VBMSY Standard error of VB/VBMSY.

SE_VB_VB0 Standard error of VB/VB0.

SE_Dev A vector of standard errors of the deviation parameters.

info A list containing the data and starting values of estimated parameters for the assessment.

forecast A list containing components for forecasting:

- per_recruit A data frame of SPR (spawning potential ratio) and YPR (yield-per-recruit), calculated for a range of exploitation rate of 0 - 0.99 or instantaneous F from 0 - 2.5 FMSY.

- `catch_eq` A function that calculates the catch for the next year (after the model terminal year) when an apical F is provided.

`obj` A list with components returned from [MakeADFun](#).

`opt` A list with components from calling [nlminb](#) to `obj`.

`SD` A list (class `sdreport`) with parameter estimates and their standard errors, obtained from [sdreport](#).

`TMB_report` A list of model output reported from the TMB executable, i.e. `obj$report()`, and derived quantities (e.g. `MSY`).

`dependencies` A character string of data types required for the assessment.

Author(s)

Q. Huynh

See Also

[plot.Assessment.summary.Assessment retrospective profile make_MP](#)

Examples

```
output <- DD_TMB(Data = MSEtool::SimulatedData)
class(output)
```

cDD

Continuous Delay-differential assessment model

Description

A catch and index-based assessment model. Compared to the discrete delay-difference (annual time-step in production and fishing), the delay-differential model (cDD) is based on continuous recruitment and fishing mortality within a time-step. The continuous model works much better for populations with high turnover (e.g. high F or M, continuous reproduction). This model is conditioned on catch and fits to the observed index. In the state-space version (cDD_SS), recruitment deviations from the stock-recruit relationship are estimated.

Usage

```
cDD(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker"),
  rescale = "mean1",
  MW = FALSE,
  start = NULL,
```

```

prior = list(),
fix_h = TRUE,
dep = 1,
LWT = list(),
n_itF = 5L,
silent = TRUE,
opt_hess = FALSE,
n_restart = ifelse(opt_hess, 0, 1),
control = list(iter.max = 5000, eval.max = 10000),
...
)

cDD_SS(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker"),
  rescale = "mean1",
  MW = FALSE,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_sigma = FALSE,
  fix_tau = TRUE,
  dep = 1,
  LWT = list(),
  n_itF = 5L,
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 5000, eval.max = 10000),
  inner.control = list(),
  ...
)

```

Arguments

x	An index for the objects in Data when running in closed loop simulation. Otherwise, equals to 1 when running an assessment.
Data	An object of class Data .
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd.
SR	Stock-recruit function (either "BH" for Beverton-Holt or "Ricker").
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time

	series mean is 1, otherwise a numeric. Output is re-converted back to original units.
MW	Logical, whether to fit to mean weight. In closed-loop simulation, mean weight will be grabbed from <code>Data@Misc[[x]]\$MW</code> , otherwise calculated from <code>Data@CAL</code> .
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
fix_h	Logical, whether to fix steepness to value in <code>Data@steep</code> in the assessment model.
dep	The initial depletion in the first year of the model. A tight prior is placed on the model objective function to estimate the equilibrium fishing mortality corresponding to the initial depletion. Due to this tight prior, this F should not be considered to be an independent model parameter. Set to zero to eliminate this prior.
LWT	A named list of likelihood weights. For <code>LWT\$Index</code> , a vector of likelihood weights for each survey, while for <code>LWT\$MW</code> a numeric.
n_itF	Integer, the number of iterations to solve F conditional on the observed catch.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of parameters regarding optimization to be passed to <code>nlminb</code> .
...	Additional arguments (not currently used).
fix_sigma	Logical, whether the standard deviation of the index is fixed. If TRUE, sigma is fixed to value provided in <code>start</code> (if provided), otherwise, value based on <code>Data@CV_Ind</code> .
fix_tau	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, tau is fixed to value provided in <code>start</code> (if provided), otherwise, equal to 1.
integrate	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a state-space variable). Otherwise, recruitment deviations are penalized parameters.
inner.control	A named list of arguments for optimization of the random effects, which is passed on to <code>newton</code> via <code>MakeADFun</code> .

Details

For start (optional), a named list of starting values of estimates can be provided for:

- R_0 Unfished recruitment. Otherwise, `Data@OM$R0[x]` is used in closed-loop, and 400% of mean catch otherwise.
- h Steepness. Otherwise, `Data@steep[x]` is used, or 0.9 if empty.
- Kappa Delay-differential Kappa parameter. Otherwise, calculated from biological parameters in the Data object.
- $F_{equilibrium}$ Equilibrium fishing mortality leading into first year of the model (to determine initial depletion). By default, 0.
- τ Lognormal SD of the recruitment deviations (process error) for DD_SS. By default, `Data@sigmaR[x]`.
- σ Lognormal SD of the index (observation error). By default, `Data@CV_Ind[x]`. Not used if multiple indices are used.
- σ_W Lognormal SD of the mean weight (observation error). By default, 0.1.

Multiple indices are supported in the model. `Data@Ind`, `Data@VInd`, and `Data@SpInd` are all assumed to be biomass-based. For `Data@AddInd`, `Data@I_units` are used to identify a biomass vs. abundance-based index.

Value

An object of [Assessment](#) containing objects and output from TMB.

Online Documentation

Model description and equations are available on the openMSE [website](#).

Required Data

- cDD: Cat, Ind, Mort, L50, vbK, vbLinf, vbt0, wla, wlb, MaxAge
- cDD_SS: Cat, Ind, Mort, L50, vbK, vbLinf, vbt0, wla, wlb, MaxAge

Optional Data

- cDD: steep
- cDD_SS: steep, CV_Ind, sigmaR

Author(s)

Q. Huynh

References

Hilborn, R., and Walters, C., 1992. Quantitative Fisheries Stock Assessment: Choice, Dynamics and Uncertainty. Chapman and Hall, New York.

See Also

[DD_TMB plot.Assessment summary.Assessment retrospective profile make_MP](#)

Examples

```
#### Observation-error delay difference model
res <- cDD(Data = MSEtool::Red_snapper)

### State-space version
### Also set recruitment variability SD = 0.6 (since fix_tau = TRUE)
res <- cDD_SS(Data = MSEtool::Red_snapper, start = list(tau = 0.6))

summary(res@SD) # Parameter estimates
```

check_RCMdata

Rapid Conditioning Model (RCM)

Description

Intended for conditioning operating models for MSEtool. For data-limited stocks, this function can generate a range of potential depletion scenarios inferred from sparse data. From a historical time series of total catch or effort, and potentially age/length compositions and multiple indices of abundance, the RCM returns a range of values for depletion, selectivity, unfished recruitment (R0), historical fishing effort, and recruitment deviations for the operating model. This is done by sampling life history parameters provided by the user and fitting a statistical catch-at-age model (with the predicted catch equal to the observed catch). Alternatively one can do a single model fit and sample the covariance matrix to generate an operating model with uncertainty based on the model fit. Either a full catch (conditioned on catch) or effort (conditioned on effort) time series is needed but missing data (as NAs) are allowed for all other data types. check_RCMdata evaluates whether the inputs in the S4 RCMdata object are correctly formatted.

Usage

```
check_RCMdata(RCMdata, OM, condition = c("catch", "catch2", "effort"))

RCM(OM, data, ...)

## S4 method for signature 'OM,RCMdata'
RCM(
  OM,
  data,
  condition = c("catch", "catch2", "effort"),
  selectivity = "logistic",
  s_selectivity = NULL,
  LWT = list(),
  comp_like = c("multinomial", "lognormal"),
  prior = list(),
```

```
    max_F = 3,
    cores = 1L,
    integrate = FALSE,
    mean_fit = FALSE,
    drop_nonconv = FALSE,
    drop_highF = FALSE,
    control = list(iter.max = 2e+05, eval.max = 4e+05),
    ...
)

## S4 method for signature 'OM,list'
RCM(
  OM,
  data,
  condition = c("catch", "catch2", "effort"),
  selectivity = "logistic",
  s_selectivity = NULL,
  LWT = list(),
  comp_like = c("multinomial", "lognormal"),
  ESS = c(30, 30),
  prior = list(),
  max_F = 3,
  cores = 1L,
  integrate = FALSE,
  mean_fit = FALSE,
  drop_nonconv = FALSE,
  drop_highF = FALSE,
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  ...
)

## S4 method for signature 'OM,Data'
RCM(
  OM,
  data,
  condition = c("catch", "catch2", "effort"),
  selectivity = "logistic",
  s_selectivity = NULL,
  LWT = list(),
  comp_like = c("multinomial", "lognormal"),
  ESS = c(30, 30),
  prior = list(),
  max_F = 3,
  cores = 1L,
  integrate = FALSE,
  mean_fit = FALSE,
  drop_nonconv = FALSE,
  drop_highF = FALSE,
```

```

control = list(iter.max = 2e+05, eval.max = 4e+05),
...
)

```

Arguments

RCMdata	An RCMdata object.
OM	An object of class OM that specifies natural mortality (M), growth (Linf, K, t0, a, b), stock-recruitment relationship, steepness, maturity parameters (L50 and L50_95), standard deviation of recruitment variability (Perr), as well as index uncertainty (Iobs).
condition	String to indicate whether the RCM is conditioned on "catch" (where F are estimated parameters), "catch2" (where F is solved internally using Newton's method), or "effort".
data	Data inputs formatted in a RCMdata (preferred) or Data object. Use of a list is deprecated. See Data section below.
...	Other arguments to pass in for starting values of parameters and fixing parameters. See details.
selectivity	A character vector of length nfleet to indicate "logistic", "dome", or "free" selectivity for each fleet in Chist. If there is time-varying selectivity, this is a character vector of length nsel_block (see Data section below). "free" indicates independent selectivity parameters for each age, and additional modifications for fixing selectivity parameters will likely be needed. See Additional arguments section.
s_selectivity	A vector of length nsurvey to indicate the selectivity of the corresponding columns in data\$Index. Use "B" for total biomass, or "SSB" for spawning biomass (by default, "B" is used). Use numbers if the survey selectivity follows a fleet (corresponding to the columns in data\$Chist, e.g., 1 = first fleet/column and so on). If the survey selectivity is otherwise independent of anything else in the model, use "logistic", "dome", or "free" to specify the functional form of selectivity, and see Additional arguments section for setup of survey selectivity parameters and Articles section for more information.
LWT	A named list of likelihood weights for the RCM. See below.
comp_like	A string indicating either "multinomial" (default) or "lognormal" distributions for the composition data.
prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See Articles section for full description.
max_F	The maximum F for any fleet in the scoping model (higher F's in the model are penalized in the objective function). See also drop_highF.
cores	Integer for the number of CPU cores for the stock reduction analysis.

integrate	Logical, whether to treat recruitment deviations as penalized parameters in the likelihood (FALSE) or random effects to be marginalized out of the likelihood (TRUE).
mean_fit	Logical, whether to run an additional with mean values of life history parameters from the OM.
drop_nonconv	Logical, whether to drop non-converged fits of the RCM, including fits where $F = NA$.
drop_highF	Logical, whether to drop fits of the RCM where $F = \max_F$.
control	A named list of arguments (e.g. max. iterations, etc.) for optimization, to be passed to the control argument of <code>nlm</code> .
ESS	A vector of length two. A shortcut method to setting the maximum multinomial sample size of the age and length compositions. Not used when data are provided in a <code>RCMdata</code> object.

Details

Fleet selectivity is fixed to values sampled from OM if no age or length compositions are provided.

Survey selectivity is estimable only if IAA or IAL is provided. Otherwise, the selectivity should be mirrored to a fleet (vulnerable biomass selectivity) or indexed to total or spawning biomass (see `s_selectivity`).

Parameters that were used in the fitting model are placed in the `RCM@OM@cpars` list.

If the operating model OM uses time-varying growth or M, then those trends will be used in the RCM as well. Non-stationary productivity creates ambiguity in the calculation and interpretation of depletion and MSY reference points.

The easiest way to turn off time-varying growth/M is by setting: `OM@Msd <- OM@Linf` `sd <- OM@Ksd <- c(0, 0)`.

To play with alternative fits by excluding indices, for example, or other optional data, set the corresponding likelihood weight to zero. The model will still generate the inferred index but the data won't enter the likelihood. See section on likelihood weights.

Value

An object of class `RCMModel` (see link for description of output).

`check_RCMdata` returns a list of updated `RCMdata` object, OM, and StockPars, ObsPars, and FleetPars from the Hist object generated from the OM.

Online Documentation

Several articles are available for the RCM:

- [General overview of approach](#)
- [Mathematical description](#)
- [Setup of selectivity settings](#) (useful for more data-rich cases)
- [Description of priors](#)

Data

One of indices, age compositions, or length compositions should be provided in addition to the historical catch or effort. Not all arguments are needed to run the model (some have defaults, while others are ignored if not applicable depending on the data provided).

The data variable can be an object of class `RCMdata`. See help file for description of inputs.

Alternatively, the data input can be a `Data S4` object which will retrieve data from the following slots:

- `Data@Cat` - catch series (single fleet with the `Data S4` object)
- `Data@Effort` - effort series
- `Data@CAA` - fishery age composition
- `Data@CAL`, `Data@CAL_mids` - fishery length composition and corresponding length bins
- `Data@Ind`, `Data@SpInd`, `Data@VInd`, `Data@AddInd` - indices of abundance
- `Data@CV_Ind`, `Data@CV_SpInd`, `Data@CV_VInd`, `Data@CV_AddInd` - annual coefficients of variation for the corresponding indices of abundance. CVs will be converted to lognormal standard deviations.
- `Data@ML` - fishery mean lengths
- `Data@AddIndV`, `Data@AddIndType`, `Data@AddIunits` - Additional information for indices in `Data@AddInd`: selectivity and units (i.e., biomass or abundance).

There is no slot in the `Data S4` object for the equilibrium catch/effort. These can be passed directly in the function call, i.e., `RCM(OM, Data, C_eq = C_eq, . . .)`.

Use of a list is deprecated. For backwards compatibility, here is the list of supported entries:

- `Chist` - A vector of historical catch, should be of length `OM@nyears`. If there are multiple fleets: a matrix of `OM@nyears` rows and `nfleet` columns. Ideally, the first year of the catch series represents unfished conditions (see also `C_eq`).
- `C_sd` - A vector or matrix of standard deviations (lognormal distribution) for the catches in `Chist`. If not provided, the default is 0.01. Only used if `condition = "catch"`.
- `Ehist` - A vector of historical effort, should be of length `OM@nyears` (see also `E_eq`).
- `Index` - A vector of values of an index (of length `OM@nyears`). If there are multiple indices: a matrix of historical indices of abundances, with rows indexing years and columns indexing the index.
- `I_sd` - A vector or matrix of standard deviations (lognormal distribution) for the indices corresponding to the entries in `Index`. If not provided, this function will use values from `OM@Iobs`.
- `I_type` - Obsolete as of version 2.0. See `s_selectivity` argument.
- `CAA` - Fishery age composition matrix with `nyears` rows and `OM@maxage+1` columns. If multiple fleets: an array with dimension: `nyears`, `OM@maxage`, and `n fleets`.
- `CAL` - Fishery length composition matrix with `nyears` rows and columns indexing the length bin. If multiple fleets: an array with dimension: `nyears`, `length bins`, and `n fleets`.
- `MS` - A vector of fishery mean size (`MS`, either mean length or mean weight) observations (length `OM@nyears`), or if multiple fleets: matrix of dimension: `nyears` and `n fleets`. Generally, mean lengths should not be used if `CAL` is also provided, unless mean length and length comps are independently sampled.

- **MS_type** - A character (either "length" (default) or "weight") to denote the type of mean size data.
- **MS_cv** - The coefficient of variation of the observed mean size. If there are multiple fleets, a vector of length nfleet. Default is 0.2.
- **s_CAA** - Survey age composition data, an array of dimension nyears, maxage+1, nsurvey.
- **s_CAL** - Survey length composition data, an array of dimension nyears, length(length_bin), nsurvey.
- **length_bin** - A vector for the midpoints of the length bins for CAL and s_CAL. All bin widths should be equal in size.
- **C_eq** - A numeric vector of length nfleet for the equilibrium catch for each fleet in Chist prior to the first year of the operating model. Zero (default) implies unfished conditions in year one. Otherwise, this is used to estimate depletion in the first year of the data. Alternatively, if one has a full CAA matrix, one could instead estimate "artificial" rec devs to generate the initial numbers-at-age (and hence initial depletion) in the first year of the model (see additional arguments).
- **C_eq_sd** - A vector of standard deviations (lognormal distribution) for the equilibrium catches in C_eq. If not provided, the default is 0.01. Only used if condition = "catch".
- **E_eq** - The equilibrium effort for each fleet in Ehist prior to the first year of the operating model. Zero (default) implies unfished conditions in year one. Otherwise, this is used to estimate depletion in the first year of the data.
- **abs_I** - Optional, an integer vector to indicate which indices are in absolute magnitude. Use 1 to set $q = 1$, otherwise use 0 to estimate q .
- **I_units** - Optional, an integer vector to indicate whether indices are biomass based (1) or abundance-based (0). By default, all are biomass-based.
- **age_error** - Optional, a square matrix of maxage + 1 rows and columns to specify ageing error. The aa-th column assigns a proportion of the true age in the a-th row to observed age. Thus, all rows should sum to 1. Default is an identity matrix (no ageing error).
- **sel_block** - Optional, for time-varying fleet selectivity (in time blocks), a integer matrix of nyears rows and nfleet columns to assigns a selectivity function to a fleet for certain years.

Additional arguments

For RCM, additional arguments can be passed to the model via . . . :

- **vul_par**: A matrix of 3 rows and nfleet columns for starting values for fleet selectivity. The three rows correspond to LFS (length of full selectivity), L5 (length of 5 percent selectivity), and Vmaxlen (selectivity at length Linf). By default, the starting values are values from the OM object. If any selectivity = "free", then this matrix needs to be of maxage+1 rows where the row specifies the selectivity at age. See Articles section.
- **ivul_par**: A matrix of 3 rows and nsurvey columns for starting values for fleet selectivity. Same setup as vul_par. Values in the column are ignored if s_selectivity is mapped to a fishing fleet (add NA placeholders in that case). If any s_selectivity = "free", then this matrix needs to be of maxage+1 rows where the row specifies the selectivity at age.
- **log_rec_dev**: A numeric vector of length nyears for the starting values of the log-recruitment deviations.

- `log_early_rec_dev`: A numeric vector of length `OM@maxage` for the starting values of the recruitment deviations controlling the abundance-at-age in the first year of the model.
- `map_vul_par`: An integer matrix of the same dimension as `vul_par`. This is the 'map' argument for `vul_par` in TMB, see [MakeADFun](#), which indicates whether selectivity parameters are fixed or estimated. If an entry is NA, the corresponding parameter is fixed in the model to the starting value. Otherwise, an integer for each independent parameter. By default, selectivity is fixed if there are no age or length composition for that fleet or survey, otherwise estimated. Unused cells in the `vul_par` matrix should be given NA in the map matrix.
- `map_ivul_par`: The map argument for the survey selectivity parameters (same dimension as `ivul_par`). Placeholder parameters should have a map value of NA.
- `map_log_early_rec_dev`: A vector of length `OM@maxage` that indexes which recruitment deviates for the cohorts in the first year of the model are fixed (using NA) or estimated (a separate integer). By default, no deviates are estimated (all are NA).
- `map_log_rec_dev`: A vector of length `OM@nyears` that indexes which recruitment deviates are fixed (using NA) or estimated (a separate integer). By default, all deviates are estimated.
- `plusgroup`: Logical for whether the maximum age is a plusgroup or not. By default, TRUE.
- `fix_dome`: Logical for whether the dome selectivity parameter for fleets is fixed. Used primarily for backwards compatibility, this is overridden by `map_vul_par`.
- `resample`: Logical, whether the OM conditioning parameters (recruitment, fishing mortality, SSB, selectivity, etc.) are obtained by sampling the Hessian matrix from a single model fit. By default FALSE. This feature requires identical biological parameters among simulations.

Likelihood weights

LWT is an optional named list containing the likelihood weights (values ≥ 0) with the possible options:

- `Chist`, `CAA`, `CAL`, `MS`, `C_eq`: A vector of length `nfleet` for each.
- `Index`, `IAA`, `IAL`: A vector of length `nsurvey` for each.

By default, all likelihood weights are equal to one if not specified by the user.

Annual multinomial sample sizes for the age and length comps can now be provided directly in the [RCMdata](#) object. For a list or [Data](#) object, use the `ESS` argument.

Author(s)

Q. Huynh

See Also

[plot.RCMModel](#) [RCModel](#) [compare_RCM](#) [pcod](#)

Examples

```
# An example that conditions a Pacific cod operating model. There are 48 simulations,
# where values of natural mortality and steepness are sampled from distributions.
# The model is fitted with priors on the index catchability. Maturity and selectivity
```



```

# are knife-edge at the age of 2 years. See online tutorial for more information.

data(pcod)
mat_ogive <- pcod$OM@cpars$Mat_age[1, , 1]
out <- RCM(OM = pcod$OM, data = pcod$data,
          condition = "catch", mean_fit = TRUE,
          selectivity = "free", s_selectivity = rep("SSB", ncol(pcod$data@Index)),
          vul_par = matrix(mat_ogive, length(mat_ogive), 1),
          map_vul_par = matrix(NA, length(mat_ogive), 1),
          map_log_early_rec_dev = rep(1, pcod$OM@maxage),
          prior = pcod$prior)
plot(out, s_name = colnames(pcod$data@Index))

# Alternative OM with age-3 maturity and selectivity instead.
out_age3 <- local({
  pcod$OM@cpars$Mat_age[, 2, ] <- 0
  mat_ogive_age3 <- pcod$OM@cpars$Mat_age[1, , 1]
  RCM(OM = pcod$OM, data = pcod$data,
      condition = "catch", mean_fit = TRUE,
      selectivity = "free", s_selectivity = rep("SSB", ncol(pcod$data@Index)),
      vul_par = matrix(mat_ogive_age3, length(mat_ogive_age3), 1),
      map_vul_par = matrix(NA, length(mat_ogive_age3), 1),
      map_log_early_rec_dev = rep(1, pcod$OM@maxage),
      prior = pcod$prior)
})

compare_RCM(out, out_age3, scenario = list(names = c("Age-2 maturity", "Age-3 maturity")),
            s_name = colnames(pcod$data@Index))

```

compare_models

Compare output from several assessment models

Description

Plot biomass, recruitment, and fishing mortality time series from several . This function can be used to compare outputs among different assessment models from the same Data object.

Usage

```
compare_models(..., label = NULL, color = NULL)
```

Arguments

...	Objects of class Assessment .
label	A character vector of the models for the legend.
color	A vector of colors for each assessment model.

Value

A set of figures of biomass, recruitment, and fishing mortality estimates among the models.

Author(s)

Q. Huynh

Examples

```
res <- cDD_SS(x = 3, Data = MSEtool::SimulatedData)
res2 <- SCA(x = 3, Data = MSEtool::SimulatedData)
res3 <- SP(x = 3, Data = MSEtool::SimulatedData)

compare_models(res, res2, res3)
```

DD_TMB

Delay - Difference Stock Assessment in TMB

Description

A simple delay-difference assessment model using a time-series of catches and a relative abundance index and coded in TMB. The model can be conditioned on either (1) effort and estimates predicted catch or (2) catch and estimates a predicted index. In the state-space version DD_SS, recruitment deviations from the stock-recruit relationship are estimated.

Usage

```
DD_TMB(
  x = 1,
  Data,
  condition = c("catch", "effort"),
  AddInd = "B",
  SR = c("BH", "Ricker"),
  rescale = "mean1",
  MW = FALSE,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  dep = 1,
  LWT = list(),
  n_itF = 3L,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 5000, eval.max = 10000),
  ...
)
```

```

DD_SS(
  x = 1,
  Data,
  condition = c("catch", "effort"),
  AddInd = "B",
  SR = c("BH", "Ricker"),
  rescale = "mean1",
  MW = FALSE,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_sd = FALSE,
  fix_tau = TRUE,
  dep = 1,
  LWT = list(),
  n_itF = 3L,
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 5000, eval.max = 10000),
  inner.control = list(),
  ...
)

```

Arguments

x	An index for the objects in Data when running in closed loop simulation. Otherwise, equals to 1 when running an assessment.
Data	An object of class Data .
condition	A string to indicate whether to condition the model on catch or effort (ratio of catch and index).
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd.
SR	Stock-recruit function (either "BH" for Beverton-Holt or "Ricker").
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
MW	Logical, whether to fit to mean weight. In closed-loop simulation, mean weight will be grabbed from Data@Misc[[x]]\$MW, otherwise calculated from Data@CAL.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.

prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
fix_h	Logical, whether to fix steepness to value in Data@steep in the assessment model. Automatically false if a prior is used.
dep	The initial depletion in the first year of the model. A tight prior is placed on the model objective function to estimate the equilibrium fishing mortality rate that corresponds to the initial depletion. Due to this tight prior, this F should not be considered to be an independent model parameter. Set to zero to eliminate this prior.
LWT	A named list of likelihood weights. For LWT\$Index, a vector of likelihood weights for each survey, while for LWT\$MW a numeric.
n_itF	Integer, the number of iterations to solve F within an annual time step when conditioning on catch.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of parameters regarding optimization to be passed to <code>nlminb</code> .
...	Additional arguments (not currently used).
fix_sd	Logical, whether the standard deviation of the data in the likelihood (index for conditioning on catch or catch for conditioning on effort). If TRUE, the SD is fixed to value provided in <code>start</code> (if provided), otherwise, value based on either <code>Data@CV_Cat</code> or <code>Data@CV_Ind</code> .
fix_tau	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, tau is fixed to value provided in <code>start</code> (if provided), otherwise, equal to 1.
integrate	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a random effects/state-space variable). Otherwise, recruitment deviations are penalized parameters.
inner.control	A named list of arguments for optimization of the random effects, which is passed on to <code>newton</code> via <code>MakeADFun</code> .

Details

For `start` (optional), a named list of starting values of estimates can be provided for:

- R_0 Unfished recruitment. Otherwise, `Data@OM$R0[x]` is used in closed-loop, and 400% of mean catch otherwise.
- h Steepness. Otherwise, `Data@steep[x]` is used, or 0.9 if empty.
- M Natural mortality. Otherwise, `Data@Mort[x]` is used.
- k Age of knife-edge maturity. By default, the age of 50% maturity calculated from the slots in the Data object.
- ρ Delay-difference ρ parameter. Otherwise, calculated from biological parameters in the Data object.
- α Delay-difference α parameter. Otherwise, calculated from biological parameters in the Data object.
- q_{effort} Scalar coefficient when conditioning on effort (to scale to F). Otherwise, 1 is the default.
- $F_{\text{equilibrium}}$ Equilibrium fishing mortality rate leading into first year of the model (to determine initial depletion). By default, 0.
- ω Lognormal SD of the catch (observation error) when conditioning on effort. By default, `Data@CV_Cat[x]`.
- τ Lognormal SD of the recruitment deviations (process error) for DD_SS. By default, `Data@sigmaR[x]`.
- σ Lognormal SD of the index (observation error) when conditioning on catch. By default, `Data@CV_Ind[x]`. Not used if multiple indices are used.
- σ_W Lognormal SD of the mean weight (observation error). By default, 0.1.

Multiple indices are supported in the model. `Data@Ind`, `Data@VInd`, and `Data@SpInd` are all assumed to be biomass-based. For `Data@AddInd`, `Data@I_units` are used to identify a biomass vs. abundance-based index.

Similar to many other assessment models, the model depends on assumptions such as stationary productivity and proportionality between the abundance index and real abundance. Unsurprisingly the extent to which these assumptions are violated tends to be the biggest driver of performance for this method.

Value

An object of [Assessment](#) containing objects and output from TMB.

Online Documentation

Model description and equations are available on the openMSE [website](#).

Required Data

- DD_TMB: Cat, Ind, Mort, L50, vbK, vbLinf, vbt0, wla, wlb, MaxAge
- DD_SS: Cat, Ind, Mort, L50, vbK, vbLinf, vbt0, wla, wlb, MaxAge

Optional Data

- DD_TMB: steep
- DD_SS: steep, CV_Cat

Author(s)

T. Carruthers & Z. Siders. Zach Siders coded the TMB function.

References

Carruthers, T, Walters, C.J., and McAllister, M.K. 2012. Evaluating methods that classify fisheries stock status using only fisheries catch data. *Fisheries Research* 119-120:66-79.

Hilborn, R., and Walters, C., 1992. *Quantitative Fisheries Stock Assessment: Choice, Dynamics and Uncertainty*. Chapman and Hall, New York.

See Also

[plot.Assessment summary.Assessment retrospective profile make_MP](#)

Examples

```
#### Observation-error delay difference model
res <- DD_TMB(x = 3, Data = MSEtool::SimulatedData)

# Provide starting values
start <- list(h = 0.95)
res <- DD_TMB(x = 3, Data = MSEtool::SimulatedData, start = start)

summary(res@SD) # Parameter estimates

### State-space version
### Set recruitment variability SD = 0.3 (since fix_tau = TRUE)
res <- DD_SS(x = 3, Data = MSEtool::SimulatedData, start = list(tau = 0.3))
```

diagnostic

Diagnostic of assessments in MSE: did Assess models converge during MSE?

Description

Diagnostic check for convergence of Assess models during closed-loop simulation. Use when the MP was created with [make_MP](#) with argument `diagnostic = "min"` or `"full"`. This function summarizes and plots the diagnostic information.

Usage

```
diagnostic(MSE, MP, gradient_threshold = 0.1, figure = TRUE)

diagnostic_AM(...)
```

Arguments

MSE	An object of class MSE created by runMSE .
MP	Optional, a character vector of MPs that use assessment models.
gradient_threshold	The maximum magnitude (absolute value) desired for the gradient of the likelihood.
figure	Logical, whether a figure will be drawn.
...	Arguments to pass to <code>diagnostic</code> .

Value

A matrix with diagnostic performance of assessment models in the MSE. If `figure = TRUE`, a set of figures: traffic light (red/green) plots indicating whether the model converged (defined if a positive-definite Hessian matrix was obtained), the optimizer reached pre-specified iteration limits (as passed to [nlminb](#)), and the maximum gradient of the likelihood in each assessment run. Also includes the number of optimization iterations function evaluations reported by [nlminb](#) for each application of the assessment model.

Author(s)

Q. Huynh

See Also

[retrospective_AM](#)

Examples

```
OM <- MSEtool::testOM; OM@proyears <- 20
myMSE <- runMSE(OM, MPs = "SCA_4010")
diagnostic(myMSE)
```

getinds

Characterize posterior predictive data

Description

Characterize posterior predictive data

Usage

```
getinds(
  PPD,
  styr,
  res = 6,
  tsd = c("Cat", "Cat", "Cat", "Ind", "ML"),
  stat = c("slp", "AAV", "mu", "slp", "slp")
)
```

Arguments

PPD	An object of class Data stored in the Misc slot of an MSE object following a call of runMSE(PPD = TRUE).
styr	Positive integer, the starting year for calculation of quantities
res	Positive integer, the temporal resolution (chunks - normally years) over which to calculate quantities
tsd	Character vector of names of types of data: Cat = catch, Ind = relative abundance index, ML = mean length in catches
stat	Character vector of types of quantity to be calculated: slp = slope(log(x)), AAV = average annual variability, mu = mean(log(x))

Value

A 3D array of results (type of data/stat (e.g. mean catches), time period (chunk), simulation)

Author(s)

T. Carruthers

References

Carruthers and Hordyk 2018

HCRlin

Generic linear harvest control rule based on biomass

Description

A general function used by [HCR_ramp](#) that adjusts the output (e.g., F) by a linear ramp based on the value of the OCP relative to target and limit values.

Usage

```
HCRlin(OCP_val, LOCP, TOCP, relF_min = 0, relF_max = 1)
```


Arguments

OCP_val	The value of the operational control point (OCP).
LOCP	Numeric, the limit value for the OCP in the HCR.
TOCP	Numeric, the target value for the OCP in the HCR.
relF_min	The relative maximum value (e.g. a multiple of FMSY) if OCP < LOCP.
relF_max	The relative maximum value (e.g. a multiple of FMSY) if OCP > TOCP.

Value

Numeric adjustment factor.

Author(s)

T. Carruthers

Examples

```
#40-10 linear ramp
Brel <- seq(0, 1, length.out = 200)
plot(Brel, HCRlin(Brel, 0.1, 0.4), xlab = "Estimated B/B0", ylab = "Relative change in F",
     main = "A 40-10 harvest control rule", type = 'l', col = 'blue')
abline(v = c(0.1,0.4), col = 'red', lty = 2)
```

HCR_escapement

Fixed escapement harvest control rule

Description

A simple control rule that allows fishing when the operational control point (OCP) is above some threshold. By default, this function sets the TAC at F = 100% FMSY when spawning depletion > 0.1.

Usage

```
HCR_escapement(
  Assessment,
  reps = 1,
  OCP_type = "SSB_SSB0",
  OCP_threshold = 0.2,
  Ftarget_type = "FMSY",
  relF_max = 1,
  ...
)
```

Arguments

Assessment	An object of class Assessment with estimates of FMSY or UMSY and vulnerable biomass in terminal year.
reps	The number of stochastic samples of the TAC recommendation.
OCP_type	The type of operational control points (OCPs) for the harvest control rule used to determine whether there is fishing. By default, use ("SSB_SSB0" for spawning depletion. Other biomass OCPs include "SSB_SSBMSY" for spawning biomass relative to MSY and "SSB_dSSB0", for dynamic depletion (dynamic SSB0 is the historical reconstructed biomass with $F = 0$). For F-based OCPs, the terminal year fishing mortality relative F01 or Fmax (using yield-per-recruit) or F-SPR% (see SPR_OCP argument) can be used.
OCP_threshold	The value of the OCP above which fishing can occur.
Ftarget_type	The type of F used for the target fishing mortality rate.
relF_max	The relative value of Ftarget if OCP > OCP_treshold.
...	Miscellaneous arguments.

Value

An object of class [Rec](#) with the TAC recommendation.

Author(s)

Q. Huynh

References

Deroba, J.J. and Bence, J.R. 2008. A review of harvest policies: Understanding relative performance of control rules. *Fisheries Research* 94:210-223.

See Also

[make_MP HCR_ramp](#)

Examples

```
# create an MP to run in closed-loop MSE (fishes at FMSY when B/B0 > 0.2)
SP_escapement <- make_MP(SP, HCR_escapement)

# The MP which fishes at 75% of FMSY
SP_escapement75 <- make_MP(SP, HCR_escapement, relF_max = 0.75)

# The MP which fishes at FMSY when BMSY > 0.5
SP_BMSY_escapement <- make_MP(SP, HCR_escapement, OCP_type = "SSB_SSBMSY",
                              OCP_threshold = 0.5, relF_max = 1)

myOM <- MSEtool::runMSE(MSEtool::testOM, MPs = c("FMSYref", "SP_escapement", "SP_BMSY_escapement"))
```

HCR_FB	<i>A Harvest Control Rule using B/BMSY and F/FMSY to adjust TAC or TAE.</i>
--------	---

Description

A Harvest Control Rule using B/BMSY and F/FMSY to adjust TAC or TAE.

Usage

```
HCR_FB(Brel, Frel, Bpow = 2, Bgrad = 1, Fpow = 1, Fgrad = 1)
```

Arguments

Brel	improper fraction: an estimate of Biomass relative to BMSY
Frel	improper fraction: an estimate of Fishing mortality rate relative to FMSY
Bpow	non-negative real number: controls the shape of the biomass adjustment, when zero there is no adjustment
Bgrad	non-negative real number: controls the gradient of the biomass adjustment
Fpow	non-negative real number: controls the adjustment speed relative to F/FMSY. When set to 1, next recommendation is FMSY. When less than 1 next recommendation is between current F and FMSY.
Fgrad	improper fraction: target Fishing rate relative to FMSY

Value

a TAC or TAE adjustment factor.

Author(s)

T. Carruthers

References

Made up for this package

Examples

```
res <- 100
Frel <- seq(1/2, 2, length.out = res)
Brel <- seq(0.05, 2, length.out=res)
adj <- array(HCR_FB(Brel[rep(1:res, res)], Frel[rep(1:res, each = res)]),
             Bpow = 2, Bgrad = 1, Fpow = 1, Fgrad = 0.75), c(res, res))
contour(Brel, Frel, adj, nlevels = 20, xlab = "B/BMSY", ylab = "F/FMSY",
        main = "FBsurface TAC adjustment factor")
abline(h = 1, col = 'red', lty = 2)
abline(v = 1, col = 'red', lty = 2)
legend('topright', c("Bpow = 2", "Bgrad = 1", "Fpow = 1", "Fgrad = 0.75"), text.col = 'blue')
```

HCR_MSY	<i>Harvest control rule to fish at some fraction of maximum sustainable yield</i>
---------	---

Description

A simple control rule that specifies the total allowable catch (TAC) to be the product of current vulnerable biomass and UMSY.

Usage

```
HCR_MSY(Assessment, reps = 1, MSY_frac = 1, ...)
```

Arguments

Assessment	An object of class Assessment with estimates of FMSY or UMSY and vulnerable biomass in terminal year.
reps	The number of stochastic samples of the TAC recommendation.
MSY_frac	The fraction of FMSY or UMSY for calculating the TAC (e.g. MSY_frac = 0.75 fishes at 75% of FMSY).
...	Miscellaneous arguments.

Value

An object of class [Rec](#) with the TAC recommendation.

Author(s)

Q. Huynh

References

Punt, A. E, Dorn, M. W., and Haltuch, M. A. 2008. Evaluation of threshold management strategies for groundfish off the U.S. West Coast. *Fisheries Research* 94:251-266.

See Also

[make_MP HCR_ramp](#)

Examples

```
# create an MP to run in closed-loop MSE (fishes at UMSY)
SPMSY <- make_MP(SP, HCR_MSY)

# The MP which fishes at 75% of FMSY
SP75MSY <- make_MP(SP, HCR_MSY, MSY_frac = 0.75)
```

```
myOM <- MSEtool::runMSE(MSEtool::testOM, MPs = c("FMSYref", "SPMSY", "SP75MSY"))
```

HCR_ramp

Linearly ramped harvest control rules

Description

An output control rule with a ramp that reduces the target F (used for the TAC recommendation) linearly as a function of an operational control point (OCP) such as spawning depletion or spawning biomass relative to that at MSY. The reduction in F is linear when the OCP is between the target OCP (TOCP) and the limit OCP (LOCP). Above the TOCP, the target F is maximized. Below the LOCP, the target F is minimized. For example, the TOCP and LOCP for 40% and 10% spawning depletion, respectively, in the 40-10 control rule. F_{target} is FMSY above the TOCP and zero below the LOCP. This type of control rule can be generalized with more control points (>2) in [HCR_segment](#). Class HCR objects are typically used with function [make_MP](#).

Usage

```
HCR_ramp(
  Assessment,
  reps = 1,
  OCP_type = c("SSB_SSB0", "SSB_SSBMSY", "SSB_dSSB0", "F_FMSY", "F_F01", "F_FSPR"),
  Ftarget_type = c("FMSY", "F01", "Fmax", "FSPR"),
  LOCP = 0.1,
  TOCP = 0.4,
  relF_min = 0,
  relF_max = 1,
  SPR_OCP = 0.4,
  SPR_targ = 0.4,
  ...
)
```

```
HCR40_10(Assessment, reps = 1, Ftarget_type = "FMSY", SPR_targ = 0.4, ...)
```

```
HCR60_20(Assessment, reps = 1, Ftarget_type = "FMSY", SPR_targ = 0.4, ...)
```

```
HCR80_40MSY(Assessment, reps = 1, Ftarget_type = "FMSY", SPR_targ = 0.4, ...)
```

Arguments

Assessment	An object of class Assessment with estimates of FMSY or UMSY, vulnerable biomass, and spawning biomass depletion in terminal year.
reps	The number of stochastic samples of the TAC recommendation.
OCP_type	The type of operational control points (OCPs) for the harvest control rule used to determine the reduction in F . By default, use "SSB_SSB0" for spawning depletion. Other biomass OCPs include "SSB_SSBMSY" for spawning biomass relative

to MSY and "SSB_dSSB0", for dynamic depletion (dynamic SSB0 is the historical reconstructed biomass with $F = 0$). For F-based OCPs, the terminal year fishing mortality relative F01 or Fmax (using yield-per-recruit) or F-SPR% (see SPR_OCP argument) can be used.

Ftarget_type	The type of F used for the target fishing mortality rate.
LOCP	Numeric, the limit value for the OCP in the HCR.
TOCP	Numeric, the target value for the OCP in the HCR.
relF_min	The relative value of Ftarget (i.e., as a proportion) if OCP < LOCP.
relF_max	The relative value of Ftarget if OCP > TOCP.
SPR_OCP	The value of spawning potential ratio for the OCP if OCP_type = "F_FSPR". By default, 0.4 (F40%).
SPR_targ	The target value of spawning potential ratio if Ftarget_type = "FSPR". By default, 0.4 (F40%).
...	Miscellaneous arguments.

Details

HCR_ramp is the generic ramped-HCR function where user specifies OCP and corresponding limit and target points, as well as minimum and maximum relative F target.

HCR40_10 is a common U.S. west coast control rule (LOCP and TOCP of 0.1 and 0.4 spawning depletion, respectively), while HCR60_20 is more conservative than 40-10, with LOCP and TOCP of 0.2 and 0.6 spawning depletion, respectively).

HCR80_40MSY uses 0.8 and 0.4 SSBMSY as the LOCP and TOCP, respectively.

Value

An object of class [Rec](#) with the TAC recommendation.

Author(s)

Q. Huynh & T. Carruthers

References

- Deroba, J.J. and Bence, J.R. 2008. A review of harvest policies: Understanding relative performance of control rules. *Fisheries Research* 94:210-223.
- Edwards, C.T.T. and Dankel, D.J. (eds.). 2016. *Management Science in Fisheries: an introduction to simulation methods*. Routledge, New York, NY. 460 pp.
- Punt, A. E, Dorn, M. W., and Haltuch, M. A. 2008. Evaluation of threshold management strategies for groundfish off the U.S. West Coast. *Fisheries Research* 94:251-266.
- Restrepo, V.R. and Power, J.E. 1999. Precautionary control rules in US fisheries management: specification and performance. *ICES Journal of Marine Science* 56:846-852.

See Also

[HCR_segment](#) [HCR_MSY](#) [HCRlin](#) [make_MP](#)

Examples

```
# 40-10 linear ramp
Brel <- seq(0, 1, length.out = 200)
plot(Brel, HCRLin(Brel, 0.1, 0.4),
      xlab = expression("Operational control point: Estimated"~SSB/SSB[0]),
      ylab = expression(F[target]~": proportion of"~F[MSY]),
      main = "40-10 harvest control rule", type = "l")
abline(v = c(0.1, 0.4), col = "red", lty = 2)

# create a 40-10 MP to run in closed-loop MSE
DD_40_10 <- make_MP(DD_TMB, HCR40_10)

# Alternatively,
DD_40_10 <- make_MP(DD_TMB, HCR_ramp, OCP_type = "SSB_SSB0", LOCP = 0.1, TOCP = 0.4)

# An SCA with LOCP and TOCP at 0.4 and 0.8, respectively, of SSB/SSBMSY
SCA_80_40 <- make_MP(SCA, HCR_ramp, OCP_type = "SSB_SSBMSY", LOCP = 0.4, TOCP = 0.8)

# A conservative HCR that fishes at 75% of FMSY at B > 80% BMSY but only reduces F
# to 10% of FMSY if B < 40% BMSY.
SCA_conservative <- make_MP(SCA, HCR_ramp, OCP_type = "SSB_SSBMSY", LOCP = 0.4, TOCP = 0.8,
  relF_min = 0.1, relF_max = 0.75)

# Figure of this conservative HCR
Brel <- seq(0, 1, length.out = 200)
Frel <- HCRLin(Brel, 0.4, 0.8, 0.1, 0.75)
plot(Brel, Frel,
      xlab = expression("Operational control point: Estimated"~SSB/SSB[MSY]),
      ylab = expression(F[target]~": "F/F[MSY]),
      ylim = c(0, 1), type = "l")
abline(v = c(0.4, 0.8), col = "red", lty = 2)
```

HCR_segment

Segmented harvest control rules

Description

A linear segmented output control rule where the target F (used for the TAC recommendation) is a function of an operational control point (OCP) such as spawning depletion or spawning biomass relative to that at MSY. The joints of the HCR are specified by arguments OCP and relF. Beyond the range of OCP, the response will be flat. [HCR_ramp](#) uses HCR_segment with two control points.

Usage

```
HCR_segment(
  Assessment,
  reps = 1,
  OCP_type = c("SSB_SSB0", "SSB_SSBMSY", "SSB_dSSB0", "F_FMSY", "F_F01", "F_FSPR"),
  Ftarget_type = c("FMSY", "F01", "Fmax", "FSPR"),
```

```

    OCP = c(0.1, 0.4),
    reIF = c(0, 1),
    SPR_OCP,
    SPR_targ,
    ...
  )

```

Arguments

Assessment	An object of class Assessment with estimates of FMSY or UMSY, vulnerable biomass, and spawning biomass depletion in terminal year.
reps	The number of stochastic samples of the TAC recommendation.
OCP_type	The type of operational control points (OCPs) for the harvest control rule used to determine the reduction in F. By default, use "SSB_SSB0" for spawning depletion. Other biomass OCPs include "SSB_SSBMSY" for spawning biomass relative to MSY and "SSB_dSSB0", for dynamic depletion (dynamic SSB0 is the historical reconstructed biomass with F = 0). For F-based OCPs, the terminal year fishing mortality relative F01 or Fmax (using yield-per-recruit) or F-SPR% (see SPR_OCP argument) can be used.
Ftarget_type	The type of F used for the target fishing mortality rate.
OCP	Numeric vector of operational control points for the HCR (in increasing order).
reIF	Numeric vector of Ftarget corresponding to the values in OCP.
SPR_OCP	The value of spawning potential ratio for the OCP if OCP_type = "F_FSPR". By default, 0.4 (F40%).
SPR_targ	The target value of spawning potential ratio if Ftarget_type = "FSPR". By default, 0.4 (F40%).
...	Miscellaneous arguments.

Value

An object of class [Rec](#) with the TAC recommendation.

Author(s)

Q. Huynh

Examples

```

# This is an MP with a 40-10 harvest control rule
DD_40_10 <- make_MP(DD_TMB, HCR_segment, OCP_type = "SSB_SSB0", OCP = c(0.1, 0.4), reIF = c(0, 1))

```

mahplot	<i>Plot statistical power of the indicator with increasing time blocks</i>
---------	--

Description

Plot statistical power of the indicator with increasing time blocks

Usage

```
mahplot(outlist, res = 6, maxups = 5, MPs)
```

Arguments

outlist	A list object produced by the function PRBcalc
res	Integer, the resolution (time blocking) for the calculation of PPD
maxups	Integer, the maximum number of update time blocks to plot
MPs	Character vector of MP names

Value

Density plots of Mahalanobis distance.

Author(s)

T. Carruthers

References

Carruthers and Hordyk 2018

make_interim_MP	<i>Make a custom management procedure (MP)</i>
-----------------	--

Description

Function operator that creates a management procedure (MP) by combining an assessment model (function of class `Assess`) with a harvest control rule (function of class `HCR`). The resulting function can then be tested in closed-loop simulation via [runMSE](#). Use `make_MP` to specify constant TAC between assessments; the frequency of assessments is specified in `OM@interval`. Use `make_interim_MP` to use an interim procedure to adjust the TAC between assessments using an index (Huynh et al. 2020), with the frequency of assessments specified in argument `assessment_interval` when making the MP; ensure that `OM@interval <-1`.

Usage

```

make_interim_MP(
  .Assess = "SCA",
  .HCR = "HCR_MSY",
  AddInd = "VB",
  assessment_interval = 5,
  type = c("buffer", "mean", "loess", "none"),
  type_par = NULL,
  diagnostic = c("min", "full", "none"),
  ...
)

make_MP(.Assess, .HCR, diagnostic = c("min", "full", "none"), ...)

```

Arguments

.Assess	Assessment model, a function of class Assess.
.HCR	Harvest control rule, a function of class HCR.
AddInd	A vector of integers or character strings indicating the indices to be used in the assessment model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd. For the interim procedure, the function will use the first index in AddInd.
assessment_interval	The time interval for when the assesment model is applied (number of years). In all other years, the interim procedure is applied.
type	How the index is used to calculate the TAC in the interim procedure. See details.
type_par	A control parameter for the interim procedure. See details.
diagnostic	A character string describing if any additional diagnostic information from the assessment models will be collected during the closed-loop simulation. "min" (minimal) will collect information on convergence (default) and "full" will also collect the model estimates of biomass and F generated by .Assess. "none" skips this step.
...	Additional arguments to be passed to .Assess and .HCR.

Details

make_interim_MP creates an MP that runs the interim procedure (updating the TAC according to index observations in between periodic assessment intervals. **Always ensure to set:** OM@interval <-1. The assessment frequency is specified in argument assessment_interval.

In the year when the assessment is applied, the TAC is set by fitting the model and then running the harvest control rule. Between assessments, the TAC is updated as

$$TAC_{y+1} = Cref(I_y + b \times s) / (Iref + b \times s)$$

where C_{ref} is the TAC calculated from the most recent assessment, I_{ref} is the value of the index when C_{ref} was calculated (see Equations 6 and 7 of Huynh et al. 2020). The value of I_y depends on type, with b and s equal zero unless type = "buffer":

- "buffer" - I_y is the most recent index with b is specified by type_par (default = 1), and s is the standard deviation of index residuals from the most recent assessment.
- "mean" - I_y is the mean value of the index over the most recent type_par years (default = 3).
- "loess" - I_y is the most recent index predicted by a [loess](#) smoother applied over the entire time series of the index. Use type_par to adjust the span parameter (default = 0.75).
- "none" - I_y is the most recent index. Index values are not adjusted in the interim procedure.

Value

A function of class MP.

References

Huynh et al. 2020. The interim management procedure approach for assessed stocks: Responsive management advice and lower assessment frequency. *Fish Fish.* 21:663–679. doi: [10.1111/faf.12453](https://doi.org/10.1111/faf.12453)

See Also

[HCR_ramp](#) [HCR_MSY diagnostic retrospective_AM](#)

Examples

```
# Interim MPs
MP_buffer_5 <- make_interim_MP(assessment_interval = 5)
MP_buffer_10 <- make_interim_MP(assessment_interval = 10)
OM <- MSEtool::testOM
OM@interval <- 1

MSE <- MSEtool::runMSE(OM, MPs = c("MP_buffer_5", "MP_buffer_10"))

# A statistical catch-at-age model with a 40-10 control rule
SCA_40_10 <- make_MP(SCA, HCR40_10)

# An SCA that will produce convergence diagnostics
SCA_40_10 <- make_MP(SCA, HCR40_10, diagnostic = "min")

# MP with an SCA that uses a Ricker stock-recruit function.
SCA_Ricker <- make_MP(SCA, HCR_MSY, SR = "Ricker")
show(SCA_Ricker)
```

 Model-based-MP

Model-based management procedures

Description

A suite of model-based management procedures (MPs) included in the package. Additional MPs, with specific model configurations (e.g., stock-recruit function or fixing certain parameters) or alternative ramped harvest control rules can be created with [make_MP](#) and the available Assess and HCR objects with constant TAC between assessment years.

Usage

```
SCA_MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SCA_75MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SCA_4010(x, Data, reps = 1, diagnostic = "min")
```

```
DDSS_MSX(x, Data, reps = 1, diagnostic = "min")
```

```
DDSS_75MSX(x, Data, reps = 1, diagnostic = "min")
```

```
DDSS_4010(x, Data, reps = 1, diagnostic = "min")
```

```
SP_MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SP_75MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SP_4010(x, Data, reps = 1, diagnostic = "min")
```

```
SSS_MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SSS_75MSX(x, Data, reps = 1, diagnostic = "min")
```

```
SSS_4010(x, Data, reps = 1, diagnostic = "min")
```

Arguments

x	A position in the Data object.
Data	An object of class Data
reps	Numeric, the number of stochastic replicates for the management advice.
diagnostic	Character string describing the assessment diagnostic to save, see make_MP .

Value

An object of class [Rec](#) which contains the management recommendation.

Functions

- SCA_MSJ: A statistical catch-at-age model with a TAC recommendation based on fishing at FMSY, and default arguments for configuring [SCA](#).
- SCA_75MSJ: An SCA with a TAC recommendation based on fishing at 75% of FMSY.
- SCA_4010: An SCA with a 40-10 control rule.
- DDSS_MSJ: A state-space delay difference model with a TAC recommendation based on fishing at FMSY, and default arguments for configuring [DD_SS](#).
- DDSS_75MSJ: A state-space delay difference model with a TAC recommendation based on fishing at 75% of FMSY.
- DDSS_4010: A state-space delay difference model with a 40-10 control rule.
- SP_MSJ: A surplus production model with a TAC recommendation based on fishing at FMSY, and default arguments for configuring [SP](#).
- SP_75MSJ: A surplus production model with a TAC recommendation based on fishing at 75% of FMSY.
- SP_4010: A surplus production model with a 40-10 control rule.
- SSS_MSJ: Simple stock synthesis (terminal depletion fixed to 0.4 in [SSS](#)) with a TAC recommendation based on fishing at FMSY.
- SSS_75MSJ: Simple stock synthesis (terminal depletion fixed to 0.4) with with a TAC recommendation based on fishing at 75% FMSY.
- SSS_4010: Simple stock synthesis (terminal depletion fixed to 0.4) with a 40-10 control rule.

Examples

```
MSEtool::avail("MP", package = "SAMtool")
```

```
myMSE <- MSEtool::runMSE(MSEtool::testOM, MPs = c("FMSYref", "SCA_4010"))
```

pcod	<i>Pacific cod in Area 5ABCD (Hecate Strait and Queen Charlotte Sound), British Columbia, Canada</i>
------	--

Description

A list containing an operating model, data set, and priors for updating the operating model using the conditioning model [RCM](#).

Usage

```
pcod
```

Format

A list containing an object of class [OM](#), [RCMdata](#), and a list of priors for index catchability.

References

Forrest, R.E., Anderson, S.C., Grandin, C.J., and Starr, P.J. 2020. Assessment of Pacific Cod (*Gadus macrocephalus*) for Hecate Strait and Queen Charlotte Sound (Area 5ABCD), and West Coast Vancouver Island (Area 3CD) in 2018. DFO Can. Sci. Advis. Sec. Res. Doc. 2020/070. v + 215 p.

DFO. 2021. Status Update of Pacific Cod (*Gadus macrocephalus*) for West Coast Vancouver Island (Area 3CD), and Hecate Strait and Queen Charlotte Sound (Area 5ABCD) in 2020. DFO Can. Sci. Advis. Sec. Sci. Resp. 2021/002.

See Also

[RCM](#)

Examples

```
data(pcod)
```

plot.Assessment	<i>Plot Assessment object</i>
-----------------	-------------------------------

Description

Produces HTML file (via markdown) figures of parameter estimates and output from an [Assessment](#) object.

Usage

```
## S4 method for signature 'Assessment,missing'  
plot(  
  x,  
  filename = paste0("report_", x@Model),  
  dir = tempdir(),  
  ret_yr = 0L,  
  open_file = TRUE,  
  quiet = TRUE,  
  render_args = list(),  
  ...  
)  
  
## S4 method for signature 'Assessment,retro'  
plot(  
  x,  
  y,  
  filename = paste0("report_", x@Model),  
  dir = tempdir(),  
  open_file = TRUE,
```

```

    quiet = TRUE,
    render_args = list(),
    ...
)

```

Arguments

x	An object of class Assessment .
filename	Character string for the name of the markdown and HTML files.
dir	The directory in which the markdown and HTML files will be saved.
ret_yr	If greater than zero, then a retrospective analysis will be performed and results will be reported. The integer here corresponds to the number of peels (the maximum number of terminal years for which the data are removed).
open_file	Logical, whether the HTML document is opened after it is rendered.
quiet	Logical, whether to silence the markdown rendering function.
render_args	Arguments to pass to render .
...	Other arguments.
y	An object of class retro .

Value

Returns invisibly the output from [render](#).

See Also

[retrospective](#)

Examples

```

output <- DD_TMB(Data = Simulation_1)

plot(output)

```

plot.prof

Plot profile object

Description

Generates a profile plot generated by [profile](#). If a two-parameter profile is performed, then a contour plot of the likelihood surface is returned.

Usage

```

## S4 method for signature 'prof,missing'
plot(x, contour_levels = 20, ...)

```

Arguments

x An object of class `prof` returned by `profile`.
 contour_levels Integer, passed to `nlevels` argument of `contour`.
 ... Miscellaneous. Not used.

Value

A likelihood profile plot, either a one-dimensional line plot or a two-dimensional contour plot.

Author(s)

Q. Huynh

plot.RCModel	<i>Plot RCM scope output</i>
--------------	------------------------------

Description

Produces HTML file (via markdown) figures of parameter estimates and output from an `Assessment` object. Plots histograms of operating model parameters that are updated by the RCM scoping function, as well as diagnostic plots for the fits to the RCM for each simulation. `compare_RCM` plots a short report that compares output from multiple RCM objects, assuming the same model structure, i.e., identical matrix and array dimensions among models, but different data weightings, data omissions, etc.

Usage

```
## S4 method for signature 'RCModel,missing'
plot(
  x,
  compare = FALSE,
  filename = "RCM",
  dir = tempdir(),
  sims = 1:x@OM@nsim,
  Year = NULL,
  f_name = NULL,
  s_name = NULL,
  MSY_ref = c(0.5, 1),
  bubble_adj = 10,
  scenario = list(),
  title = NULL,
  open_file = TRUE,
  quiet = TRUE,
  render_args,
  ...
)
```



```

compare_RCM(
  ...,
  compare = FALSE,
  filename = "compare_RCM",
  dir = tempdir(),
  Year = NULL,
  f_name = NULL,
  s_name = NULL,
  MSY_ref = c(0.5, 1),
  bubble_adj = 10,
  scenario = list(),
  title = NULL,
  open_file = TRUE,
  quiet = TRUE,
  render_args
)

```

Arguments

x	An object of class RCModel (output from RCM).
compare	Logical, if TRUE, the function will run <code>runMSE</code> to compare the historical period of the operating model and the RCM output.
filename	Character string for the name of the markdown and HTML files.
dir	The directory in which the markdown and HTML files will be saved.
sims	A logical vector of length <code>x@OM@nsim</code> or a numeric vector indicating which simulations to keep.
Year	Optional, a vector of years for the historical period for plotting.
f_name	Character vector for fleet names.
s_name	Character vector for survey names.
MSY_ref	A numeric vector for reference horizontal lines for B/BMSY plots.
bubble_adj	A number to adjust the size of bubble plots (for residuals of age and length comps).
scenario	Optional, a named list to label each simulation in the RCM for plotting, e.g.: <code>list(names = c("low M", "high M"), col = c("blue", "red"))</code> .
title	Optional character string for an alternative title for the markdown report.
open_file	Logical, whether the HTML document is opened after it is rendered.
quiet	Logical, whether to silence the markdown rendering function.
render_args	A list of other arguments to pass to render .
...	For <code>compare_RCM</code> , multiple RCM objects for comparison.

Value

Returns invisibly the output from [render](#).

See Also[RCModel RCM](#)

`plot.retro`*Methods for retro object*

Description

plot and summary functions for retro object.

Usage

```
## S4 method for signature 'retro,missing'  
plot(x, color = NULL)  
  
## S4 method for signature 'retro'  
summary(object)
```

Arguments

x	An object of class retro .
color	An optional character vector of colors for plotting.
object	An object of class retro .

Value

A series of plots showing retrospective patterns in fishing mortality, spawning biomass, recruitment, etc.

Author(s)

Q. Huynh

Examples

```
res <- SP(Data = swordfish)  
ret <- retrospective(res, figure = FALSE)  
  
summary(ret)  
plot(ret)
```

plot_betavar	<i>Plots a beta variable</i>
--------------	------------------------------

Description

Plots the probability distribution function of a beta variable from the mean and standard deviation in either transformed (logit) or untransformed space.

Usage

```
plot_betavar(m, sd, label = NULL, is_logit = FALSE, color = "black")
```

Arguments

m	A vector of means of the distribution.
sd	A vector of standard deviations of the distribution.
label	Name of the variable to be used as x-axis label.
is_logit	Logical that indicates whether the means and standard deviations are in logit (TRUE) or normal (FALSE) space.
color	A vector of colors.

Value

A plot of the probability distribution function. Vertical dotted line indicates mean of distribution. This function can plot multiple curves when multiple means and standard deviations are provided.

Author(s)

Q. Huynh

See Also

[plot_lognormalvar](#) [plot_steepness](#)

Examples

```
mu <- 0.5
stddev <- 0.1
plot_betavar(mu, stddev) # mean of plot should be 0.5

#logit parameters
mu <- 0
stddev <- 0.1
plot_betavar(mu, stddev, is_logit = TRUE) # mean of plot should be 0.5
```

plot_composition *Plot composition data*

Description

Plots annual length or age composition data.

Usage

```
plot_composition(
  Year = 1:nrow(obs),
  obs,
  fit = NULL,
  plot_type = c("annual", "bubble_data", "bubble_residuals", "mean"),
  N = rowSums(obs),
  CAL_bins = NULL,
  ages = NULL,
  ind = 1:nrow(obs),
  annual_ylab = "Frequency",
  annual_yscale = c("proportions", "raw"),
  bubble_adj = 5,
  bubble_color = c("black", "white"),
  fit_linewidth = 3,
  fit_color = "red"
)
```

Arguments

Year	A vector of years.
obs	A matrix of either length or age composition data. For lengths, rows and columns should index years and length bin, respectively. For ages, rows and columns should index years and age, respectively.
fit	A matrix of predicted length or age composition from an assessment model. Same dimensions as obs.
plot_type	Indicates which plots to create. Options include annual distributions, bubble plot of the data, and bubble plot of the residuals, and annual means.
N	Annual sample sizes. Vector of length nrow(obs).
CAL_bins	A vector of lengths corresponding to the columns in obs. and fit. Ignored for age data.
ages	An optional vector of ages corresponding to the columns in obs.
ind	A numeric vector for plotting a subset of rows (which indexes year) of obs and fit.
annual_ylab	Character string for y-axis label when plot_type = "annual".
annual_yscale	For annual composition plots (plot_type = "annual"), whether the raw values ("raw") or frequencies ("proportions") are plotted.

bubble_adj	Numeric, for adjusting the relative size of bubbles in bubble plots (larger number = larger bubbles).
bubble_color	Colors for negative and positive residuals, respectively, for bubble plots.
fit_linewidth	Argument lwd for fitted line.
fit_color	Color of fitted line.

Value

Plots depending on plot_type.

Author(s)

Q. Huynh

Examples

```
plot_composition(obs = SimulatedData@CAA[1, 1:16, ])
plot_composition(obs = SimulatedData@CAA[1, , ], plot_type = "bubble_data",
                 ages = 0:SimulatedData@MaxAge)
```

plot_crosscorr	<i>Produce a cross-correlation plot of the derived data arising from getinds(MSE_object)</i>
----------------	--

Description

Produce a cross-correlation plot of the derived data arising from getinds(MSE_object)

Usage

```
plot_crosscorr(
  indPPD,
  indData,
  pp = 1,
  dnam = c("CS", "CV", "CM", "IS", "MLS"),
  res = 1
)
```

Arguments

indPPD	A 3D array of results arising from running getind on an MSE of the Null operating model (type of data/stat (e.g. mean catches),time period (chunk), simulation)
indData	A 3D array of results arising from running getind on an MSE of the Alternative operating model (type of data/stat (e.g. mean catches),time period (chunk), simulation)

pp	Positive integer, the number of time chunks (blocks of years normally, second dimension of indPPD and indData) to produce the plot for.
dnam	A character vector of names of the data for plotting purposes (as long as dimension 1 of indPPD and indData).
res	The size of the temporal blocking that created indPPD and indData - this is just used for labelling purposes

Value

A cross-correlation plot (ndata-1) x (ndata-1)

Author(s)

T. Carruthers

References

Carruthers and Hordyk 2018

plot_lognormalvar *Plots a lognormal variable*

Description

Plots the probability distribution function of a lognormal variable from the mean and standard deviation in either transformed (normal) or untransformed space.

Usage

```
plot_lognormalvar(m, sd, label = NULL, logtransform = FALSE, color = "black")
```

Arguments

m	A vector of means of the distribution.
sd	A vector of standard deviations of the distribution.
label	Name of the variable to be used as x-axis label.
logtransform	Indicates whether the mean and standard deviation are in lognormal (TRUE) or normal (FALSE) space.
color	A vector of colors.

Value

A plot of the probability distribution function. Vertical dotted line indicates mean of distribution. This function can plot multiple curves when multiple means and standard deviations are provided.

Author(s)

Q. Huynh

See Also[plot_betavar](#) [plot_steepness](#)**Examples**

```
mu <- 0.5
stddev <- 0.1
plot_lognormalvar(mu, stddev) # mean of plot should be 0.5

#logtransformed parameters
mu <- 0
stddev <- 0.1
plot_lognormalvar(mu, stddev, logtransform = TRUE) # mean of plot should be 1
```

plot_residuals	<i>Plot residuals</i>
----------------	-----------------------

Description

Plots figure of residuals (or any time series with predicted mean of zero).

Usage

```
plot_residuals(
  Year,
  res,
  res_sd = NULL,
  res_sd_CI = 0.95,
  res_upper = NULL,
  res_lower = NULL,
  res_ind_blue = NULL,
  draw_zero = TRUE,
  zero_linetype = 2,
  label = "Residual"
)
```

Arguments

Year	A vector of years for the data.
res	A vector of residuals.
res_sd	A vector of year specific standard deviation for res.
res_sd_CI	The confidence interval for the error bars based for res_sd.

res_upper	A vector of year-specific upper bounds for the error bars of the residual (in lieu of argument res_CV).
res_lower	A vector of year-specific lower bounds for the error bars of the residual (in lieu of argument res_CV).
res_ind_blue	Indices of obs for which the plotted residuals and error bars will be blue.
draw_zero	Indicates whether a horizontal line should be drawn at zero.
zero_linetype	Passes argument lty (e.g. solid line = 1, dotted = 2) to draw_zero.
label	Character string that describes the data to label the y-axis.

Value

A plot of model residuals by year (optionally, with error bars).

Author(s)

Q. Huynh

See Also

[plot_timeseries](#)

plot_SR

Plot stock-recruitment function

Description

Plot stock-recruitment (with recruitment deviations if estimated).

Usage

```
plot_SR(
  Spawners,
  expectedR,
  R0 = NULL,
  S0 = NULL,
  rec_dev = NULL,
  trajectory = FALSE,
  y_zoom = NULL,
  ylab = "Recruitment"
)
```


Arguments

Spawners	A vector of the number of the spawners (x-axis).
expectedR	A vector of the expected recruitment (from the stock-recruit function) corresponding to values of Spawners.
R0	Virgin recruitment.
S0	Virgin spawners.
rec_dev	If recruitment deviations are estimated, a vector of estimated recruitment (in normal space) corresponding to values of Spawners.
trajectory	Indicates whether arrows will be drawn showing the trajectory of spawners and recruitment deviations over time.
y_zoom	If recruitment deviations are plotted, the y-axis limit relative to maximum expected recruitment expectedR. If NULL, all recruitment values are plotted.
ylab	Character string for label on y-axis.

Value

A stock-recruit plot

Author(s)

Q. Huynh

plot_steepness	<i>Plots probability distribution function of stock-recruit steepness</i>
----------------	---

Description

Plots the probability distribution function of steepness from the mean and standard deviation.

Usage

```
plot_steepness(
  m,
  sd,
  is_transform = FALSE,
  SR = c("BH", "Ricker"),
  color = "black"
)
```

Arguments

m	The mean of the distribution (vectorized).
sd	The standard deviation of the distribution (vectorized).
is_transform	Logical, whether the mean and standard deviation are in normal space (FALSE) or transformed space.
SR	The stock recruitment relationship (determines the range and, if relevant, transformation of steepness).
color	A vector of colors.

Value

A plot of the probability distribution function. Vertical dotted line indicates mean of distribution.

Note

The function samples from a beta distribution with parameters alpha and beta that are converted from the mean and standard deviation. Then, the distribution is transformed from 0 - 1 to 0.2 - 1.

Author(s)

Q. Huynh

See Also

[plot_lognormalvar](#) [plot_betavar](#)

Examples

```
mu <- 0.8
stddev <- 0.1
plot_steepness(mu, stddev)
```

plot_timeseries

Plot time series of data

Description

Plot time series of observed (with lognormally-distributed error bars) vs. predicted data.

Usage

```
plot_timeseries(  
  Year,  
  obs,  
  fit = NULL,  
  obs_CV = NULL,  
  obs_CV_CI = 0.95,  
  obs_upper = NULL,  
  obs_lower = NULL,  
  obs_ind_blue = NULL,  
  fit_linewidth = 3,  
  fit_color = "red",  
  label = "Observed data"  
)
```

Arguments

Year	A vector of years for the data.
obs	A vector of observed data.
fit	A vector of predicted data (e.g., from an assessment model).
obs_CV	A vector of year-specific coefficient of variation in the observed data.
obs_CV_CI	The confidence interval for the error bars based for obs_CV.
obs_upper	A vector of year-specific upper bounds for the error bars of the observed data (in lieu of argument obs_CV).
obs_lower	A vector of year-specific lower bounds for the error bars of the observed data (in lieu of argument obs_CV).
obs_ind_blue	Indices of obs for which the plotted points and error bars will be blue.
fit_linewidth	Argument lwd for fitted line.
fit_color	Color of fitted line.
label	Character string that describes the data to label the y-axis.

Value

A plot of annual observed data and predicted values from a model.

Author(s)

Q. Huynh

See Also

[plot_residuals](#)

Examples

```
data(Red_snapper)
plot_timeseries(Red_snapper@Year, Red_snapper@Cat[1, ],
obs_CV = Red_snapper@CV_Cat, label = "Catch")
```

PRBcalc

Calculate mahalanobis distance (null and alternative MSEs) and statistical power for all MPs in an MSE

Description

Calculate mahalanobis distance (null and alternative MSEs) and statistical power for all MPs in an MSE

Usage

```
PRBcalc(
  MSE_null,
  MSE_alt,
  tsd = c("Cat", "Cat", "Cat", "Ind", "ML"),
  stat = c("slp", "AAV", "mu", "slp", "slp"),
  dnam = c("C_S", "C_V", "C_M", "I_S", "ML_S"),
  res = 6,
  alpha = 0.05,
  plotCC = FALSE,
  removedat = FALSE,
  removethresh = 0.025
)
```

Arguments

MSE_null	An object of class MSE representing the null hypothesis
MSE_alt	An object of class MSE representing the alternative hypothesis
tsd	Character string of data types: Cat = catch, Ind = relative abundance index, ML = mean length in catches
stat	Character string defining the quantity to be calculated for each data type, slp = slope(log(x)), AAV = average annual variability, mu = mean(log(x))
dnam	Character string of names for the quantities calculated
res	Integer, the resolution (time blocking) for the calculation of PPD
alpha	Probability of incorrectly rejecting the null operating model when it is valid
plotCC	Logical, should the PPD cross correlations be plotted?
removedat	Logical, should data not contributing to the mahalanobis distance be removed?
removethresh	Positive fraction: the cumulative percentage of removed data (removedat=TRUE) that contribute to the mahalanobis distance

Value

A list object with two hierarchies of indexing, first by MP, second has two positions as described in [Probs](#): (1) mahalanobis distance, (2) a matrix of type 1 error (first row) and statistical power (second row), by time block.

Author(s)

T. Carruthers

References

Carruthers, T.R, and Hordyk, A.R. In press. Using management strategy evaluation to establish indicators of changing fisheries. Canadian Journal of Fisheries and Aquatic Science.

```
prelim_AM
```

Preliminary Assessments in MSE

Description

Evaluates the likely performance of Assessment models in the operating model. This function will apply the assessment model for Data generated during the historical period of the MSE, and report the convergence rate for the model and total time elapsed in running the assessments.

Usage

```
prelim_AM(x, Assess, ncpus = NULL, ...)
```

Arguments

x	Either a Hist, Data or OM object.
Assess	An Assess function of class Assess.
ncpus	Numeric, the number of CPUs to run the Assessment model (will run in parallel if greater than 1).
...	Arguments to be passed to Assess, e.g., model configurations.

Value

Returns invisibly a list of [Assessment](#) objects of length OM@ns.im. Messages via console.

Author(s)

Q. Huynh

Examples

```
prelim_AM(MSEtool::SimulatedData, SP)
```

Probs	<i>Calculates mahalanobis distance and rejection of the Null operating model</i>
-------	--

Description

Calculates mahalanobis distance and rejection of the Null operating model, used by wrapping function [PRBcalc](#).

Usage

```
Probs(indPPD, indData, alpha = 0.05, removedat = FALSE, removethresh = 0.05)
```

Arguments

indPPD	A 3D array of results arising from running getind on an MSE of the Null operating model (type of data/stat (e.g. mean catches),time period (chunk), simulation)
indData	A 3D array of results arising from running getind on an MSE of the Alternative operating model (type of data/stat (e.g. mean catches),time period (chunk), simulation)
alpha	Positive fraction: rate of type I error, alpha
removedat	Logical, should data not contributing to the mahalanobis distance be removed?
removethresh	Positive fraction: the cumulative percentage of removed data (removedat=TRUE) that contribute to the mahalanobis distance

Value

A list object. Position 1 is an array of the mahalanobis distances. Dimension 1 is length 2 for the Null OM (indPPD) and the alternative OM (indData). Dimension 2 is the time block (same length as indPPD dim 2). Dimension 3 is the simulation number (same length at indPPD dim 3.), Position 2 is a matrix (2 rows, ntimeblock columns) which is (row 1) alpha: the rate of false positives, and row 2 the power (1-beta) the rate of true positives

Author(s)

T. Carruthers

References

Carruthers and Hordyk 2018

prof-class	<i>Class-prof</i>
------------	-------------------

Description

An S4 class that contains output from [profile](#).

Slots

Model Name of the assessment model.

Name Name of Data object.

Par Character vector of parameters that were profiled.

MLE Numeric vector of the estimated values of the parameters (corresponding to Par) from the assessment.

grid A data.frame of the change in negative log-likelihood (nll) based on the profile of the parameters.

Author(s)

Q. Huynh

See Also

[plot.prof](#) [profile](#)

profile	<i>Profile likelihood of assessment models</i>
---------	--

Description

Profile the likelihood for parameters of assessment models.

Usage

```
profile(fitted, ...)
```

```
## S4 method for signature 'Assessment'
profile(fitted, figure = TRUE, ...)
```

```
## S4 method for signature 'RCModel'
profile(fitted, figure = TRUE, ...)
```

Arguments

fitted, Assessment	An object of class Assessment .
...	A sequence of values of the parameter(s) for the profile. See details and example below. See details for name of arguments to be passed on.
figure	Logical, indicates whether a figure will be plotted.

Details

For the following assessment models, possible sequence of values for profiling are:

- DD_TMB and DD_SS: R_0 and h
- SP and SP_SS: FMSY and MSY
- DD and cDD_SS: R_0 and h
- SCA and SCA_Pope: R_0 and h
- SCA2: meanR
- VPA: F_term
- SSS: R_0

For RCM: D (spawning biomass depletion), R_0 , and h are used.

Value

An object of class [prof](#) that contains a data frame of negative log-likelihood values from the profile and, optionally, a figure of the likelihood surface.

Author(s)

Q. Huynh

Examples

```
output <- SCA(Data = MSEtool::SimulatedData)

# Profile R0 only
pro <- profile(output, R0 = seq(1000, 2000, 50))

# Profile both R0 and steepness
pro <- profile(output, R0 = seq(1000, 2000, 100), h = seq(0.8, 0.95, 0.025))

# Ensure your grid is of proper resolution. A grid that is too coarse
# will likely distort the shape of the likelihood surface.
```

 project-class

 Class-project

Description

An S4 class for the output from [projection](#).

Slots

Model Name of the assessment model.

Name Name of Data object.

FMort A matrix of fishing mortality over p_sim rows and p_years columns.

B An matrix of biomass with p_sim rows and p_years columns.

SSB A matrix of spawning biomass with p_sim rows and p_years columns.

VB A matrix of vulnerable biomass with p_sim rows and p_years columns.

R A matrix of recruitment over p_sim rows and p_years columns.

N A matrix of abundance over p_sim rows and p_years columns.

Catch A matrix of simulated observed catch over p_sim rows and p_years columns.

Index An array of simulated observed index of dimension c(p_sim, p_years, nsurvey).

C_at_age An array for catch-at-age with dimension c(p_sim, p_years, n_age).

Author(s)

Q. Huynh

See Also

[projection](#)

 projection

 Projections for assessment models

Description

This function takes an assessment model and runs a stochastic projection based on future F or catch.

Usage

```

projection(
  Assessment,
  constrain = c("F", "Catch"),
  Ftarget,
  Catch,
  p_years = 50,
  p_sim = 200,
  obs_error,
  process_error,
  max_F = 3,
  seed = 499
)

```

Arguments

Assessment	An object of class Assessment .
constrain	Whether to project on future F or catch. By default, projects on F.
Ftarget	The projection F, either of length 1 for constant F for the entirety of the projection or length p_years.
Catch	The projection catch, either of length 1 for constant catch for the entirety of the projection or length p_years.
p_years	Integer for the number of projection years.
p_sim	Integer for the number of simulations for the projection.
obs_error	A list of length two. In the first entry, a vector of length nsurvey giving the standard deviations of each future index, or alternatively an array of dimension p_sim, p_years, and nsurvey giving the deviates. The second entry is the standard deviation of the projected catch. Alternatively, a matrix of simulation and year-specific error structure for the catch (p_sim rows and p_year columns; a matrix of ones indicates perfect data).
process_error	Numeric, standard deviation for process error (e.g., recruitment or biomass deviates). If NULL, uses values from assessment model. Alternatively, a matrix of simulation and year-specific recruitment deviates (p_sim rows and p_year columns, a matrix of ones indicates no recruitment deviates).
max_F	The maximum allowable F if the projection is constrained on catch.
seed	An integer to set the seed for the sampling observation and process error deviates.

Value

An object of class [project](#) that contains future predicted values of F, catch, biomass, recruitment, etc.

Examples

```
myAssess <- SCA(Data = SimulatedData)
do_projection <- projection(myAssess, Ftarget = myAssess@FMSY)
```

RCMdata-class

*Class-RCMdata***Description**

An S4 class for the data inputs into [RCM](#).

Slots

Chist A vector of historical catch, should be of length `OM@nyears`. If there are multiple fleets: a matrix of `OM@nyears` rows and `nfleet` columns. Ideally, the first year of the catch series represents unfisher conditions (see also `C_eq`).

C_sd A vector or matrix of lognormal distribution standard deviations (by year and fleet) for the catches in `Chist`. If not provided, the default is 0.01. Not used if `RCM(condition = "catch2")`.

Ehist A vector of historical effort, should be of length `OM@nyears`. If there are multiple fleets: a matrix of `OM@nyears` rows and `nfleet` columns. See also `E_eq`.

CAA Fishery age composition matrix with `nyears` rows and `OM@maxage+1` columns. If multiple fleets: an array with dimension: `nyears`, `OM@maxage`, and `nfleets`. Raw numbers will be converted to annual proportions (see `CAA_ESS` for sample sizes).

CAA_ESS Annual sample size (for the multinomial distribution) of the fishery age comps. A vector of length `OM@nyears`. If there are multiple fleets: a matrix of `OM@nyears` rows and `nfleet` columns.

CAL Fishery length composition matrix with `nyears` rows and columns indexing the length bin. If multiple fleets: an array with dimension: `nyears`, `n_bins`, and `nfleets`. Raw numbers will be converted to annual proportions (see `CAL_ESS` for sample sizes).

CAL_ESS Annual sample size (for the multinomial distribution) of the fishery length comps. A vector of length `OM@nyears`. If there are multiple fleets: a matrix of `OM@nyears` rows and `nfleet` columns.

length_bin - A vector (length `n_bin`) for the midpoints of the length bins for `CAL` and `IAL`, as well as the population model, if all bin widths are equal in size. If length bins are unequal in bin width, then provide a vector of the boundaries of the length bins (vector of length `n_bin + 1`).

MS A vector of fishery mean size (`MS`, either mean length or mean weight) observations (length `OM@nyears`), or if multiple fleets: matrix of dimension: `nyears` and `nfleets`. Generally, mean lengths should not be used if `CAL` is also provided, unless mean length and length comps are independently sampled.

MS_type A character (either "length" (default) or "weight") to denote the type of mean size data.

- MS_cv** The coefficient of variation of the observed mean size. If there are multiple fleets, a vector of length `nfleet`. Default is 0.2.
- Index** A vector of values of an index (of length `OM@nyears`). If there are multiple surveys: a matrix of historical indices of abundances, with rows indexing years and columns indexing surveys.
- I_sd** A vector or matrix of standard deviations (lognormal distribution) for the indices corresponding to the entries in `Index`. If not provided, this function will use values from `OM@Iobs`.
- IAA** Index age composition data, an array of dimension `nyears`, `maxage+1`, `nsurvey`. Raw numbers will be converted to annual proportions (see `IAA_ESS` for sample sizes).
- IAA_ESS** Annual sample size (for the multinomial distribution) of the index age comps. A vector of length `OM@nyears`. If there are multiple indices: a matrix of `OM@nyears` rows and `nsurvey` columns.
- IAL** Index length composition data, an array of dimension `nyears`, `n_bin`, `nsurvey`. Raw numbers will be converted to annual proportions (see `IAL_ESS` for sample sizes).
- IAL_ESS** Annual sample size (for the multinomial distribution) of the index length comps. A vector of length `OM@nyears`. If there are multiple indices: a matrix of `OM@nyears` rows and `nsurvey` columns.
- C_eq** A numeric vector of length `nfleet` for the equilibrium catch for each fleet in `Chist` prior to the first year of the operating model. Zero (default) implies unfished conditions in year one. Otherwise, this is used to estimate depletion in the first year of the data. Alternatively, if one has a full CAA matrix, one could instead estimate "artificial" rec devs to generate the initial numbers-at-age (and hence initial depletion) in the first year of the model (see additional arguments in [RCM](#)).
- C_eq_sd** - A vector of standard deviations (lognormal distribution) for the equilibrium catches in `C_eq`. If not provided, the default is 0.01. Only used if `RCM(condition = "catch")`.
- E_eq** The equilibrium effort for each fleet in `Ehist` prior to the first year of the operating model. Zero (default) implies unfished conditions in year one. Otherwise, this is used to estimate depletion in the first year of the data.
- abs_I** An integer vector to indicate which indices are in absolute magnitude. Use 1 to set $q = 1$, otherwise use 0 (default) to estimate q .
- I_units** An integer vector to indicate whether indices are biomass based (1) or abundance-based (0). By default, all are biomass-based.
- age_error** A square matrix of `maxage + 1` rows and columns to specify ageing error. The a -th column assigns a proportion of the true age in the a -th row to observed age. Thus, all rows should sum to 1. Default is an identity matrix (no ageing error).
- sel_block** For time-varying fleet selectivity (in time blocks), a integer matrix of `nyears` rows and `nfleet` columns to assigns a selectivity function to a fleet for certain years. By default, constant selectivity for each individual fleet. See the [selectivity](#) article for more details.
- Misc** A list of miscellaneous inputs. Used internally.

Author(s)

Q. Huynh

See Also[RCM](#)

RCModel-class

Class-RCModel

Description

An S4 class for the output from [RCM](#).

Slots

OM An updated operating model, class [OM](#).

SSB A matrix of estimated spawning biomass with `OM@nsim` rows and `OM@years+1` columns.

NAA An array for the predicted numbers at age with dimension `OM@nsim`, `OM@years+1`, and `OM@maxage+1`.

CAA An array for the predicted catch at age with dimension `OM@nsim`, `OM@years`, `OM@maxage`, and `nfleet`.

CAL An array for the predicted catch at length with dimension `OM@nsim`, `OM@years`, length bins, and `nfleet`.

conv A logical vector of length `OM@nsim` indicating convergence of the RCM in the *i*-th simulation.

Misc A list of length `OM@nsim` with more output from the fitted RCM. Within each simulation, a named list containing items of interest include:

- B - total biomass - vector of length `nyears+1`
- E0 - annual unfished spawning biomass - vector of length `nyears`
- E0_SR - unfished spawning biomass for the stock-recruit relationship - numeric
- CR_SR - compensation ratio corresponding to `Arec` and unfished spawning biomass for the stock-recruit relationship - numeric
- CR - annual compensation ratio - vector of length `nyears`
- Arec - alpha parameter of the stock-recruit relationship - numeric
- Brec - beta parameter of the stock-recruit relationship - numeric
- R - recruitment - vector of length `nyears+1`
- R_early - recruitment for the cohorts in first year of the model - vector `n_age-1` (where `n_age = maxage + 1`)
- VB - vulnerable biomass - matrix of `nyears x nfleet`
- N - abundance at age - matrix of `nyears+1 x n_age`
- F - apical fishing mortality - matrix of `nyears x nfleet`
- F_at_age - fishing mortality at age - matrix of `nyears x n_age`
- F_equilibrium - equilibrium fishing mortality prior to first year - vector of length `nfleet`
- M - natural mortality - matrix of `nyears x n_age`
- Z - total mortality - matrix of `nyears x n_age`
- q - index catchability - vector of length `nsurvey`
- ivul - index selectivity at age - array of dim `nyears+1, n_age, nsurvey`

- `ivul_len` - corresponding index selectivity at length - matrix of `nbins` x `nsurvey`
- `Ipred` - predicted index values - matrix of `nyears` x `nsurvey`
- `IAApred` - predicted index catch at age - array of dim `nyears`, `n_age`, `nsurvey`
- `vul` - fleet selectivity at age - array of dim `nyears+1`, `n_age`, `nfleet` (or `n_sel_block`)
- `vul_len` - corresponding fleet selectivity at length - matrix of `nbins` x `nfleet` (or `n_sel_block`)
- `IALpred` - predicted index catch at length - array of dim `nyears`, `nbins`, `nsurvey`
- `MLpred` - predicted mean length - matrix of `nyears` x `nfleet`
- `MWpred` - predicted mean weight - matrix of `nyears` x `nfleet`
- `CAApred` - predicted catch at age - array of `nyears`, `n_age`, `nfleet`
- `CALpred` - predicted catch at length - array of `nyears`, `nbins`, `nfleet`
- `Cpred` - predicted catch in weight - matrix of `nyears` x `nfleet`
- `CN` - predicted catch in numbers - matrix of `nyears` x `nfleet`
- `dynamic_SSB0` - the dynamic unfished spawning biomass calculated by projecting the historical model with zero catches - vector of length `nyears+1`
- `SPR_eq` - equilibrium spawning potential ratio calculated from annual F-at-age - vector of length `nyears`
- `SPR_dyn` - dynamic (transitional) spawning potential ratio calculated from cumulative survival of cohorts - vector of length `nyears`
- `nll` - total objective function of the model - numeric
- `nll_fleet` - objective function values for each annual data point(s) from fleets - array of `nyears` x `nfleet` x 5 (for Catch, equilibrium catch, CAA, CAL, and mean size)
- `nll_index` - objective function values for each annual data point(s) in the index - array of `nyears` x `nsurvey` x 3 (for Index, IAA, and IAL)
- `prior` - penalty value added to the objective function from priors - numeric
- `penalty` - additional penalty values added to the objective function due to high F - numeric
- `conv` - whether the model converged (whether a positive-definite Hessian was obtained) - logical

`mean_fit` A list of output from fit to mean values of life history parameters in the operating model. The named list consists of:

- `obj` - a list with components returned from `MakeADFun`.
- `opt` - a list with components from calling `nlm` to `obj`.
- `SD` - a list (class `sdreport`) with parameter estimates and their standard errors, obtained from `sdreport`.
- `report` - a list of model output reported from the TMB executable, i.e. `obj$report()`. See `Misc`.

`data` A `RCMdata` object containing data inputs for the RCM.

`config` A list describing configuration of the RCM:

- `drop_sim` - a vector of simulations that were dropped for the output

Author(s)

Q. Huynh

See Also

[plot.RCModel](#) `RCM`

retro-class	<i>Class-retro</i>
-------------	--------------------

Description

An S4 class that contains output from [retrospective](#).

Slots

Model Name of the assessment model.

Name Name of Data object.

TS_var Character vector of time series variables, e.g. recruitment, biomass, from the assessment.

TS An array of time series assessment output of dimension, indexed by: peel (the number of terminal years removed from the base assessment), years, and variables (corresponding to TS_var).

Est_var Character vector of estimated parameters, e.g. R0, steepness, in the assessment.

Est An array for estimated parameters of dimension, indexed by: peel, variables (corresponding to Est_var), and value (length 2 for estimate and standard error).

Author(s)

Q. Huynh

See Also

[plot.retro](#) [summary.retro](#) [plot.Assessment](#)

retrospective	<i>Retrospective analysis of assessment models</i>
---------------	--

Description

Perform a retrospective analysis, successive removals of most recent years of data to evaluate resulting parameter estimates.

Usage

```
retrospective(x, ...)
```

```
## S4 method for signature 'Assessment'
retrospective(x, nyr = 5, figure = TRUE)
```

```
## S4 method for signature 'RCModel'
retrospective(x, nyr = 5, figure = TRUE)
```

Arguments

x	An S4 object of class <code>Assessment</code> of <code>RCModel</code> .
...	More arguments.
nyr	The maximum number of years to remove for the retrospective analysis.
figure	Indicates whether plots will be drawn.

Value

A list with an array of model output and of model estimates from the retrospective analysis.

Figures showing the time series of biomass and exploitation and parameter estimates with successive number of years removed. For a variety of time series output (SSB, recruitment, etc.) and estimates (R0, steepness, etc.), also returns a matrix of Mohn's rho (Mohn 1999).

Author(s)

Q. Huynh

References

Mohn, R. 1999. The retrospective problem in sequential population analysis: an investigation using cod fishery and simulated data. *ICES Journal of Marine Science* 56:473-488.

Examples

```
output <- SP(Data = swordfish)
get_retro <- retrospective(output, nyr = 5, figure = FALSE)
```

retrospective_AM *retrospective_AM (retrospective of Assessment model in MSE)*

Description

Plots the true retrospective of an assessment model during the closed-loop simulation. A series of time series estimates of SSB, F, and VB are plotted over the course of the MSE are plotted against the operating model (true) values (in black).

Usage

```
retrospective_AM(MSE, MP, sim = 1, plot_legend = FALSE)
```


Arguments

MSE	An object of class MSE .
MP	Character. The name of the management procedure created by make_MP containing the assessment model.
sim	Integer between 1 and MSE@nsim. The simulation number for which the retrospectives will be plotted.
plot_legend	Logical. Whether to plot legend to reference year of assessment in the MSE.

Details

For assessment models that utilize annual exploitation rates (u), the instantaneous fishing mortality rates are obtained as $F = -\log(1 - u)$.

Value

A series of figures for SSB, depletion, fishing mortality, and vulnerable biomass (VB) estimated in the MP over the course of the closed-loop simulation against the values generated in the operating model (both historical and projected).

Note

This function only plots retrospectives from a single simulation in the MSE. Results from one figure may not be indicative of general assessment behavior and performance overall.

Author(s)

Q. Huynh

See Also

[diagnostic](#)

Examples

```
SCA_40_10 <- make_MP(SP, HCR_MSY, diagnostic = "full")
OM <- MSEtool::testOM; OM@proyears <- 20
myMSE <- MSEtool::runMSE(OM = OM, MPs = "SCA_40_10")
retrospective_AM(myMSE, MP = "SCA_40_10", sim = 1)
```

Description

A generic statistical catch-at-age model (single fleet, single season) that uses catch, index, and catch-at-age composition data. SCA parameterizes R_0 and steepness as leading productivity parameters in the assessment model. Recruitment is estimated as deviations from the resulting stock-recruit relationship. In SCA2, the mean recruitment in the time series is estimated and recruitment deviations around this mean are estimated as penalized parameters ($SR = \text{"none"}$, similar to Cadigan 2016). The standard deviation is set high so that the recruitment is almost like free parameters. Unfished and MSY reference points are not estimated, it is recommended to use yield per recruit or spawning potential ratio in harvest control rules. SCA_{Pope} is a variant of SCA that fixes the expected catch to the observed catch, and Pope's approximation is used to calculate the annual exploitation rate (U ; i.e., $catch_{eq} = \text{"Pope"}$).

Usage

```
SCA(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker", "none"),
  vulnerability = c("logistic", "dome"),
  catch_eq = c("Baranov", "Pope"),
  CAA_dist = c("multinomial", "lognormal"),
  CAA_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_F_equilibrium = TRUE,
  fix_omega = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  early_dev = c("comp_onegen", "comp", "all"),
  late_dev = "comp50",
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  inner.control = list(),
  ...
)
```

```

SCA2(
  x = 1,
  Data,
  AddInd = "B",
  vulnerability = c("logistic", "dome"),
  CAA_dist = c("multinomial", "lognormal"),
  CAA_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_F_equilibrium = TRUE,
  fix_omega = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  common_dev = "comp50",
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  inner.control = list(),
  ...
)

```

```

SCA_Pope(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker", "none"),
  vulnerability = c("logistic", "dome"),
  CAA_dist = c("multinomial", "lognormal"),
  CAA_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_U_equilibrium = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  early_dev = c("comp_onegen", "comp", "all"),
  late_dev = "comp50",
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),

```

```

control = list(iter.max = 2e+05, eval.max = 4e+05),
inner.control = list(),
...
)

```

Arguments

x	A position in the Data object (by default, equal to one for assessments).
Data	An object of class Data
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd. Vulnerability to the survey is fixed in the model.
SR	Stock-recruit function (either "BH" for Beverton-Holt, "Ricker", or "none" for constant mean recruitment).
vulnerability	Whether estimated vulnerability is "logistic" or "dome" (double-normal). See details for parameterization.
catch_eq	Whether to use the Baranov equation or Pope's approximation to calculate the predicted catch at age in the model.
CAA_dist	Whether a multinomial or lognormal distribution is used for likelihood of the catch-at-age matrix. See details.
CAA_multiplier	Numeric for data weighting of catch-at-age matrix if CAA_hist = "multinomial". Otherwise ignored. See details.
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
max_age	Integer, the maximum age (plus-group) in the model.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
fix_h	Logical, whether to fix steepness to value in Data@steep in the model for SCA. This only affects calculation of reference points for SCA2.
fix_F_equilibrium	Logical, whether the equilibrium fishing mortality prior to the first year of the model is estimated. If TRUE, F_equilibrium is fixed to value provided in start (if provided), otherwise, equal to zero (assumes unfisher conditions).

<code>fix_omega</code>	Logical, whether the standard deviation of the catch is fixed. If TRUE, omega is fixed to value provided in <code>start</code> (if provided), otherwise, value based on <code>Data@CV_Cat</code> .
<code>fix_tau</code>	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, tau is fixed to value provided in <code>start</code> (if provided), otherwise, value based on <code>Data@sigmaR</code> .
<code>LWT</code>	A named list (Index, CAA, Catch) of likelihood weights for the data components. For the index, a vector of length survey. For CAL and Catch, a single value.
<code>early_dev</code>	Numeric or character string describing the years for which recruitment deviations are estimated in SCA. By default, equal to <code>"comp_onegen"</code> , where rec devs are estimated one full generation prior to the first year when catch-at-age (CAA) data are available. With <code>"comp"</code> , rec devs are estimated starting in the first year with CAA. With <code>"all"</code> , rec devs start at the beginning of the model. If numeric, the number of years after the first year of the model for which to start estimating rec devs. Use negative numbers for years prior to the first year.
<code>late_dev</code>	Typically, a numeric for the number of most recent years in which recruitment deviations will not be estimated in SCA (recruitment in these years will be based on the mean predicted by stock-recruit relationship). By default, <code>"comp50"</code> uses the number of ages (smaller than the mode) for which the catch-at-age matrix has less than half the abundance than that at the mode.
<code>integrate</code>	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a random effects/state-space variable). Otherwise, recruitment deviations are penalized parameters.
<code>silent</code>	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
<code>opt_hess</code>	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
<code>n_restart</code>	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
<code>control</code>	A named list of arguments for optimization to be passed to <code>nlminb</code> .
<code>inner.control</code>	A named list of arguments for optimization of the random effects, which is passed on to <code>newton</code> .
<code>...</code>	Other arguments to be passed.
<code>common_dev</code>	Typically, a numeric for the number of most recent years in which a common recruitment deviation will be estimated (in SCA2, uninformative years will have a recruitment closer to the mean, which can be very misleading, especially near the end of the time series). By default, <code>"comp50"</code> uses the number of ages (smaller than the mode) for which the catch-at-age matrix has less than half the abundance than that at the mode.
<code>fix_U_equilibrium</code>	Logical, same as <code>'fix_F_equilibrium'</code> for <code>'SCA_Pope'</code> .

Details

The basic data inputs are catch (by weight), index (by weight/biomass), and catch-at-age matrix (by numbers).

With `catch_eq = "Baranov"` (default in SCA and SCA2), annual F 's are estimated parameters assuming continuous fishing over the year, while an annual exploitation rate from pulse fishing in the middle of the year is estimated in SCA_Pope or SCA(`catch_eq = "Pope"`).

The annual sample sizes of the catch-at-age matrix is provided to the model (used in the likelihood for catch-at-age assuming a multinomial distribution) and is manipulated via argument `CAA_multiplier`. This argument is interpreted in two different ways depending on the value provided. If `CAA_multiplier > 1`, then this value will cap the annual sample sizes to that number. If `CAA_multiplier <= 1`, then all the annual samples sizes will be re-scaled by that number, e.g. `CAA_multiplier = 0.1` multiplies the sample size to 10% of the original number. By default, sample sizes are capped at 50.

Alternatively, a lognormal distribution with inverse proportion variance can be used for the catch at age (Punt and Kennedy, 1994, as cited by Maunder 2011).

For start (optional), a named list of starting values of estimates can be provided for:

- R_0 Unfished recruitment, except when `SR = "none"` where it is mean recruitment. By default, `150% Data@OM$R0[x]` is used as the start value in closed-loop simulation, and 400% of mean catch otherwise.
- h Steepness. Otherwise, `Data@steep[x]` is used, or 0.9 if empty.
- M Natural mortality. Otherwise, `Data@Mort[x]` is used.
- `vul_par` Vulnerability parameters, see next paragraph.
- F A vector of length `nyears` for year-specific fishing mortality.
- $F_{equilibrium}$ Equilibrium fishing mortality leading into first year of the model (to determine initial depletion). By default, 0.
- $U_{equilibrium}$ Same as $F_{equilibrium}$ when `catch_eq = "Pope"`. By default, 0.
- ω Lognormal SD of the catch (observation error) when `catch_eq = "Baranov"`. By default, `Data@CV_Cat[x]`.
- τ Lognormal SD of the recruitment deviations (process error). By default, `Data@sigmaR[x]`.

Vulnerability can be specified to be either logistic or dome. If logistic, then the parameter vector `vul_par` is of length 2:

- `vul_par[1]` corresponds to a_{95} , the age of 95% vulnerability. a_{95} is a transformed parameter via logit transformation to constrain a_{95} to less than 75% of the maximum age: $a_{95} = 0.75 * \text{max_age} * \text{plogis}(x[1])$, where x is the estimated vector.
- `vul_par[2]` corresponds to a_{50} , the age of 50% vulnerability. Estimated as an offset, i.e., $a_{50} = a_{95} - \exp(x[2])$.

With dome vulnerability, a double Gaussian parameterization is used, where `vul_par` is an estimated vector of length 4:

- `vul_par[1]` corresponds to a_{asc} , the first age of full vulnerability for the ascending limb. In the model, a_{asc} is estimated via logit transformation to constrain a_{95} to less than 75% of the maximum age: $a_{asc} = 0.75 * \text{maxage} * \text{plogis}(x[1])$, where x is the estimated vector.

- `vul_par[2]` corresponds to `a_50`, the age of 50% vulnerability for the ascending limb. Estimated as an offset, i.e., $a_{50} = a_{asc} - \exp(x[2])$.
- `vul_par[3]` corresponds to `a_des`, the last age of full vulnerability (where the descending limb starts). Generated via logit transformation to constrain between `a_asc` and `max_age`, i.e., $a_{des} = (\max_age - a_{asc}) * \text{plogis}(x[3]) + a_{asc}$. By default, fixed to a small value so that the dome is effectively a three-parameter function.
- `vul_par[4]` corresponds to `vul_max`, the vulnerability at the maximum age. Estimated in logit space: $vul_max = \text{plogis}(x[4])$.

Vague priors of $vul_par[1] \sim N(0, sd = 3)$, $vul_par[2] \sim N(0, 3)$, $vul_par[3] \sim \text{Beta}(1.01, 1.01)$ are used to aid convergence when parameters may not be well estimated, for example, when vulnerability $\gg 0.5$ for the youngest age class.

Value

An object of class [Assessment](#).

Online Documentation

Model description and equations are available on the openMSE [website](#).

Required Data

- SCA, SCA_Pope, and SCA_Pope: Cat, Ind, Mort, L50, L95, CAA, vbK, vbLinf, vbt0, wla, wlb, MaxAge

Optional Data

- SCA: Rec, steep, sigmaR, CV_Ind, CV_Cat
- SC2: Rec, steep, CV_Ind, CV_Cat
- SCA_Pope: Rec, steep, sigmaR, CV_Ind

Author(s)

Q. Huynh

References

- Cadigan, N.G. 2016. A state-space stock assessment model for northern cod, including under-reported catches and variable natural mortality rates. *Canadian Journal of Fisheries and Aquatic Science* 72:296-308.
- Maunder, M.N. 2011. Review and evaluation of likelihood functions for composition data in stock-assessment models: Estimating the effective sample size. *Fisheries Research* 209:311-319.
- Punt, A.E. and Kennedy, R.B. 1997. Population modelling of Tasmanian rock lobster, *Jasus edwardsii*, resources. *Marine and Freshwater Research* 48:967-980.

See Also

[plot.Assessment.summary.Assessment retrospective profile make_MP](#)

Examples

```

res <- SCA(Data = MSEtool::SimulatedData)
res2 <- SCA2(Data = MSEtool::SimulatedData)

# Downweight the index
res3 <- SCA(Data = MSEtool::SimulatedData, LWT = list(Index = 0.1, CAA = 1))

compare_models(res, res2)

```

SCA_CAL

*Age-structured model using fishery length composition***Description**

A single-fleet assessment that fits to catch, indices of abundance, and fishery length compositions. See [SCA](#) for all details.

Usage

```

SCA_CAL(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker", "none"),
  vulnerability = c("logistic", "dome"),
  catch_eq = c("Baranov", "Pope"),
  CAL_dist = c("multinomial", "lognormal"),
  CAL_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_F_equilibrium = TRUE,
  fix_omega = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  early_dev = c("comp_onegen", "comp", "all"),
  late_dev = "comp50",
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  inner.control = list(),
  ...
)

```


Arguments

x	A position in the Data object (by default, equal to one for assessments).
Data	An object of class Data
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd. Vulnerability to the survey is fixed in the model.
SR	Stock-recruit function (either "BH" for Beverton-Holt, "Ricker", or "none" for constant mean recruitment).
vulnerability	Whether estimated vulnerability is "logistic" or "dome" (double-normal). See details for parameterization.
catch_eq	Whether to use the Baranov equation or Pope's approximation to calculate the predicted catch at age in the model.
CAL_dist	Character, the statistical distribution for the likelihood of the catch-at-length.
CAL_multiplier	Numeric for data weighting of catch-at-length matrix if CAL_hist = "multinomial". A value smaller than one rescales annual sample sizes to this fraction of the original sample size. Values greater than one generates a cap of the annual sample size to this value.
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
max_age	Integer, the maximum age (plus-group) in the model.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
fix_h	Logical, whether to fix steepness to value in Data@steep in the model for SCA. This only affects calculation of reference points for SCA2.
fix_F_equilibrium	Logical, whether the equilibrium fishing mortality prior to the first year of the model is estimated. If TRUE, F_equilibrium is fixed to value provided in start (if provided), otherwise, equal to zero (assumes unfished conditions).
fix_omega	Logical, whether the standard deviation of the catch is fixed. If TRUE, omega is fixed to value provided in start (if provided), otherwise, value based on Data@CV_Cat.
fix_tau	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, tau is fixed to value provided in start (if provided), otherwise, value based on Data@sigmaR.

LWT	A named list (Index, CAA, Catch) of likelihood weights for the data components. For the index, a vector of length survey. For CAL and Catch, a single value.
early_dev	Numeric or character string describing the years for which recruitment deviations are estimated in SCA. By default, equal to "comp_onegen", where rec devs are estimated one full generation prior to the first year when catch-at-age (CAA) data are available. With "comp", rec devs are estimated starting in the first year with CAA. With "all", rec devs start at the beginning of the model. If numeric, the number of years after the first year of the model for which to start estimating rec devs. Use negative numbers for years prior to the first year.
late_dev	Typically, a numeric for the number of most recent years in which recruitment deviations will not be estimated in SCA (recruitment in these years will be based on the mean predicted by stock-recruit relationship). By default, "comp50" uses the number of ages (smaller than the mode) for which the catch-at-age matrix has less than half the abundance than that at the mode.
integrate	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a random effects/state-space variable). Otherwise, recruitment deviations are penalized parameters.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of arguments for optimization to be passed to <code>nlminb</code> .
inner.control	A named list of arguments for optimization of the random effects, which is passed on to <code>newton</code> .
...	Other arguments to be passed.

Online Documentation

Model description and equations are available on the openMSE [website](#).

Author(s)

Q. Huynh

Description

A modification of SCA that incorporates density-dependent effects on M based on biomass depletion (Forrest et al. 2018). Set the bounds of M in the `M_bounds` argument, a length-2 vector where the first entry is M_0 , the M as $B/B_0 \geq 1$, and the second entry is M_1 , the M as B/B_0 approaches zero. Note that M_0 can be greater than M_1 (compensatory) or M_0 can be less than M_1 (depensatory).

Usage

```
SCA_DDM(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker", "none"),
  vulnerability = c("logistic", "dome"),
  catch_eq = c("Baranov", "Pope"),
  CAA_dist = c("multinomial", "lognormal"),
  CAA_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_F_equilibrium = TRUE,
  fix_omega = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  early_dev = c("comp_onegen", "comp", "all"),
  late_dev = "comp50",
  M_bounds = NULL,
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  inner.control = list(),
  ...
)
```

Arguments

<code>x</code>	A position in the Data object (by default, equal to one for assessments).
<code>Data</code>	An object of class Data

AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd. Vulnerability to the survey is fixed in the model.
SR	Stock-recruit function (either "BH" for Beverton-Holt, "Ricker", or "none" for constant mean recruitment).
vulnerability	Whether estimated vulnerability is "logistic" or "dome" (double-normal). See details for parameterization.
catch_eq	Whether to use the Baranov equation or Pope's approximation to calculate the predicted catch at age in the model.
CAA_dist	Whether a multinomial or lognormal distribution is used for likelihood of the catch-at-age matrix. See details.
CAA_multiplier	Numeric for data weighting of catch-at-age matrix if CAA_hist = "multinomial". Otherwise ignored. See details.
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
max_age	Integer, the maximum age (plus-group) in the model.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
prior	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
fix_h	Logical, whether to fix steepness to value in Data@steep in the model for SCA. This only affects calculation of reference points for SCA2.
fix_F_equilibrium	Logical, whether the equilibrium fishing mortality prior to the first year of the model is estimated. If TRUE, F_equilibrium is fixed to value provided in start (if provided), otherwise, equal to zero (assumes unfisher conditions).
fix_omega	Logical, whether the standard deviation of the catch is fixed. If TRUE, omega is fixed to value provided in start (if provided), otherwise, value based on Data@CV_Cat.
fix_tau	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, tau is fixed to value provided in start (if provided), otherwise, value based on Data@sigmaR.
LWT	A named list (Index, CAA, Catch) of likelihood weights for the data components. For the index, a vector of length survey. For CAL and Catch, a single value.

early_dev	Numeric or character string describing the years for which recruitment deviations are estimated in SCA. By default, equal to "comp_onegen", where rec devs are estimated one full generation prior to the first year when catch-at-age (CAA) data are available. With "comp", rec devs are estimated starting in the first year with CAA. With "all", rec devs start at the beginning of the model. If numeric, the number of years after the first year of the model for which to start estimating rec devs. Use negative numbers for years prior to the first year.
late_dev	Typically, a numeric for the number of most recent years in which recruitment deviations will not be estimated in SCA (recruitment in these years will be based on the mean predicted by stock-recruit relationship). By default, "comp50" uses the number of ages (smaller than the mode) for which the catch-at-age matrix has less than half the abundance than that at the mode.
M_bounds	A numeric vector of length 2 to indicate the M as B/B0 approaches zero and one, respectively. By default, set to 75% and 125%, respectively, of Data@Mort[x].
integrate	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a random effects/state-space variable). Otherwise, recruitment deviations are penalized parameters.
silent	Logical, passed to MakeADFun , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to nlminb during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if integrate = TRUE.
n_restart	The number of restarts (calls to nlminb) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of arguments for optimization to be passed to nlminb .
inner.control	A named list of arguments for optimization of the random effects, which is passed on to newton .
...	Other arguments to be passed.

Details

See [SCA](#) for more information on all arguments.

Value

An object of class [Assessment](#).

Online Documentation

Model description and equations are available on the openMSE [website](#).

Author(s)

Q. Huynh

References

Forrest, R.E., Holt, K.R., and Kronlund, A.R. 2018. Performance of alternative harvest control rules for two Pacific groundfish stocks with uncertain natural mortality: Bias, robustness and trade-offs. Fisheries Research 2016: 259-286.

See Also

[SCA SCA_RWM plot.Assessment summary.Assessment retrospective profile make_MP](#)

Examples

```
res <- SCA_DDM(Data = MSEtool::SimulatedData)
```

SCA_RWM

SCA with random walk in M

Description

SCA_RWM is a modification of [SCA](#) that incorporates a random walk in M in logit space (constant with age). Set the variance (`start$tau_M`) to a small value (0.001) in order to fix M for all years, which is functionally equivalent to [SCA](#).

Usage

```
SCA_RWM(
  x = 1,
  Data,
  AddInd = "B",
  SR = c("BH", "Ricker", "none"),
  vulnerability = c("logistic", "dome"),
  catch_eq = c("Baranov", "Pope"),
  CAA_dist = c("multinomial", "lognormal"),
  CAA_multiplier = 50,
  rescale = "mean1",
  max_age = Data@MaxAge,
  start = NULL,
  prior = list(),
  fix_h = TRUE,
  fix_F_equilibrium = TRUE,
  fix_omega = TRUE,
  fix_tau = TRUE,
  LWT = list(),
  early_dev = c("comp_onegen", "comp", "all"),
  late_dev = "comp50",
  refyear = expression(length(Data@Year)),
  M_bounds = NULL,
```

```

    integrate = FALSE,
    silent = TRUE,
    opt_hess = FALSE,
    n_restart = ifelse(opt_hess, 0, 1),
    control = list(iter.max = 2e+05, eval.max = 4e+05),
    inner.control = list(),
    ...
)

```

Arguments

<code>x</code>	A position in the Data object (by default, equal to one for assessments).
<code>Data</code>	An object of class Data
<code>AddInd</code>	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in <code>Data@AddInd</code> , "B" (or 0) represents total biomass in <code>Data@Ind</code> , "VB" represents vulnerable biomass in <code>Data@VInd</code> , and "SSB" represents spawning stock biomass in <code>Data@SpInd</code> . Vulnerability to the survey is fixed in the model.
<code>SR</code>	Stock-recruit function (either "BH" for Beverton-Holt, "Ricker", or "none" for constant mean recruitment).
<code>vulnerability</code>	Whether estimated vulnerability is "logistic" or "dome" (double-normal). See details for parameterization.
<code>catch_eq</code>	Whether to use the Baranov equation or Pope's approximation to calculate the predicted catch at age in the model.
<code>CAA_dist</code>	Whether a multinomial or lognormal distribution is used for likelihood of the catch-at-age matrix. See details.
<code>CAA_multiplier</code>	Numeric for data weighting of catch-at-age matrix if <code>CAA_hist = "multinomial"</code> . Otherwise ignored. See details.
<code>rescale</code>	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
<code>max_age</code>	Integer, the maximum age (plus-group) in the model.
<code>start</code>	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
<code>prior</code>	A named list (R0, h, M, and q) to provide the mean and standard deviations of prior distributions for those parameters. R0, index q, and M priors are lognormal (provide the mean in normal space, SD in lognormal space). Beverton-Holt steepness uses a beta prior, while Ricker steepness uses a normal prior. For index q, provide a matrix for nsurvey rows and 2 columns (for mean and SD), with NA in rows corresponding to indices without priors. For all others, provide a length-2 vector for the mean and SD. See vignette for full description.
<code>fix_h</code>	Logical, whether to fix steepness to value in <code>Data@steep</code> in the model for SCA. This only affects calculation of reference points for SCA2.

<code>fix_F_equilibrium</code>	Logical, whether the equilibrium fishing mortality prior to the first year of the model is estimated. If TRUE, <code>F_equilibrium</code> is fixed to value provided in <code>start</code> (if provided), otherwise, equal to zero (assumes unfished conditions).
<code>fix_omega</code>	Logical, whether the standard deviation of the catch is fixed. If TRUE, <code>omega</code> is fixed to value provided in <code>start</code> (if provided), otherwise, value based on <code>Data@CV_Cat</code> .
<code>fix_tau</code>	Logical, the standard deviation of the recruitment deviations is fixed. If TRUE, <code>tau</code> is fixed to value provided in <code>start</code> (if provided), otherwise, value based on <code>Data@sigmaR</code> .
<code>LWT</code>	A named list (<code>Index</code> , <code>CAA</code> , <code>Catch</code>) of likelihood weights for the data components. For the index, a vector of length survey. For <code>CAL</code> and <code>Catch</code> , a single value.
<code>early_dev</code>	Numeric or character string describing the years for which recruitment deviations are estimated in SCA. By default, equal to <code>"comp_onegen"</code> , where rec devs are estimated one full generation prior to the first year when catch-at-age (<code>CAA</code>) data are available. With <code>"comp"</code> , rec devs are estimated starting in the first year with <code>CAA</code> . With <code>"all"</code> , rec devs start at the beginning of the model. If numeric, the number of years after the first year of the model for which to start estimating rec devs. Use negative numbers for years prior to the first year.
<code>late_dev</code>	Typically, a numeric for the number of most recent years in which recruitment deviations will not be estimated in SCA (recruitment in these years will be based on the mean predicted by stock-recruit relationship). By default, <code>"comp50"</code> uses the number of ages (smaller than the mode) for which the catch-at-age matrix has less than half the abundance than that at the mode.
<code>refyear</code>	An expression for the year for which <code>M</code> is used to report <code>MSY</code> reference points. By default, terminal year.
<code>M_bounds</code>	A numeric vector of length 2 to indicate the minimum and maximum <code>M</code> in the random walk as a proportion of the starting <code>M</code> (<code>start\$M</code>). The default min and max are 75% and 125%, respectively.
<code>integrate</code>	Logical, whether the likelihood of the model integrates over the likelihood of the recruitment deviations (thus, treating it as a random effects/state-space variable). Otherwise, recruitment deviations are penalized parameters.
<code>silent</code>	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
<code>opt_hess</code>	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
<code>n_restart</code>	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
<code>control</code>	A named list of arguments for optimization to be passed to <code>nlminb</code> .
<code>inner.control</code>	A named list of arguments for optimization of the random effects, which is passed on to <code>newton</code> .
<code>...</code>	Other arguments to be passed.

Details

The model estimates year-specific M (constant with age) as a random walk in logit space, bounded by a proportion of $startM$ (specified in M_bounds).

The starting value for the first year M ($startM$) is $Data@Mort[x]$ and is fixed, unless a prior is provided ($priorM$). The fixed SD of the random walk (tau_M) is 0.05, by default.

Alternative values can be provided in the start list (see examples):

- $R0$ Unfished recruitment, except when $SR = "none"$ where it is mean recruitment. By default, $150\% Data@OMR0[x]$ is used as the start value in closed-loop simulation, and 400% of mean catch otherwise.
- h Steepness. Otherwise, $Data@steep[x]$ is used, or 0.9 if empty.
- M Natural mortality in the first year. Otherwise, $Data@Mort[x]$ is used.
- $vu1_par$ Vulnerability parameters, see next paragraph.
- F A vector of length $nyears$ for year-specific fishing mortality.
- $F_equilibrium$ Equilibrium fishing mortality leading into first year of the model (to determine initial depletion). By default, 0.
- $omega$ Lognormal SD of the catch (observation error) when $catch_eq = "Baranov"$. By default, $Data@CV_Cat[x]$.
- tau Lognormal SD of the recruitment deviations (process error). By default, $Data@sigmaR[x]$.
- tau_M The fixed SD of the random walk in M . By default, 0.05.

See [SCA](#) for all other information about the structure and setup of the model.

The SCA builds in a stock-recruit relationship into the model. Annual unfished and MSY reference points are calculated and reported in TMB_report of the [Assessment](#) object.

Value

An object of class [Assessment](#).

Online Documentation

Model description and equations are available on the openMSE [website](#).

Author(s)

Q. Huynh

See Also

[SCA SCA_DDM](#)

Examples

```
res <- SCA_RWM(Data = MSEtool::SimulatedData, start = list(M_start = 0.4, tau_M = 0.05))
res2 <- SCA(Data = MSEtool::SimulatedData)
res3 <- SCA_RWM(Data = MSEtool::SimulatedData, start = list(M_start = 0.4, tau_M = 0.001))

compare_models(res, res2, res3)
```

Shortcut

Assessment emulator as a shortcut to model fitting in closed-loop simulation

Description

Functions (class `Assessment`) that emulate a stock assessment by sampling the operating model biomass, abundance, and fishing mortality (with observation error, autocorrelation, and bias) instead of fitting a model. This output can then be passed onto a harvest control rule (HCR function). `Shortcut` is the base function that samples the OM with an error distribution. `Shortcut2`, the more preferable option, fits `SCA` in the last historical year of the operating model, estimates the error parameters using a vector autoregressive model of the residuals, and then generates model "estimates" using `predict.varest`. `Perfect` assumes no error in the assessment model and is useful for comparing the behavior of different harvest control rules. To utilize the shortcut method in closed-loop simulation, use `make_MP` with these functions as the Assessment model. **N.B. the functions do not work with** `runMSE(parallel = TRUE)`.

Usage

```
Shortcut(
  x = 1,
  Data,
  method = c("B", "N", "RF"),
  B_err = c(0.3, 0.7, 1),
  N_err = c(0.3, 0.7, 1),
  R_err = c(0.3, 0.7, 1),
  F_err = c(0.3, 0.7, 1),
  VAR_model,
  ...
)

Shortcut2(
  x,
  Data,
  method = "N",
  SCA_args = list(),
  VAR_args = list(type = "none"),
  ...
)
```

)
 Perfect(x, Data, ...)

Arguments

x	An index for the objects in Data when running in runMSE . Otherwise, equals to 1 When running an assessment interactively.
Data	An object of class Data.
method	Indicates where the error in the OM is located. For "B", OM biomass is directly sampled with error. For "N", OM abundance-at-age is sampled and biomass subsequently calculated. For "RF", recruitment and F are sampled to calculate abundance and biomass. There is no error in biological parameters for "N" and "RF". By default, "B" is used for Shortcut and "N" for Shortcut2.
B_err	If method = "B", a vector of length three that specifies the standard deviation (in logspace), autocorrelation, and bias (1 = unbiased) for biomass.
N_err	Same as B_err, but for abundance when method = "N".
R_err	Same as B_err, but for recruitment when method = "RF".
F_err	Same as B_err. Always used regardless of method to report F and selectivity for HCR.
VAR_model	An object returned by VAR to generate emulated assessment error. Used by Shortcut2.
...	Other arguments (not currently used).
SCA_args	Additional arguments to pass to SCA . Currently, arguments SR and vulnerability are obtained from the operating model.
VAR_args	Additional arguments to pass to VAR . By default, argument type = "none" (stationary time series with mean zero is assumed).

Details

Currently there is no error in FMSY (frequently the target F in the HCR).

See Wiedenmann et al. (2015) for guidance on the magnitude of error for the shortcut emulator.

Value

An object of class [Assessment](#).

Author(s)

Q. Huynh

References

Wiedenmann, J., Wilberg, M.J., Sylvia, A., and Miller, T.J. 2015. Autocorrelated error in stock assessment estimates: Implications for management strategy evaluation. *Fisheries Research* 172: 325-334.

Examples

```

Shortcut_4010 <- make_MP(Shortcut, HCR40_10)
Shortcut_Nerr <- make_MP(Shortcut, HCR40_10, method = "N", N_err = c(0.1, 0.1, 1)) # Highly precise!

# Fits SCA first and then emulate it in the projection period
Shortcut2_4010 <- make_MP(Shortcut2, HCR40_10)

# Compare the shortcut method vs. fitting an SCA model with a 40-10 control rule
MSE <- runMSE(testOM, MPs = c("Shortcut_4010", "SCA_4010"))

# Compare the performance of three HCRs
Perfect_4010 <- make_MP(Perfect, HCR40_10)
Perfect_6020 <- make_MP(Perfect, HCR60_20)
Perfect_8040MSY <- make_MP(Perfect, HCR_ramp, OCP_type = "SSB_SSBMSY", TOCP = 0.8, LOCP = 0.4)

MSE <- runMSE(testOM, MPs = c("Perfect_4010", "Perfect_6020", "Perfect_8040MSY"))

```

 SP

Surplus production model with FMSY and MSY as leading parameters

Description

A surplus production model that uses only a time-series of catches and a relative abundance index and coded in TMB. The base model, SP, is conditioned on catch and estimates a predicted index. Continuous surplus production and fishing is modeled with sub-annual time steps which should approximate the behavior of ASPIC (Prager 1994). The Fox model, SP_Fox, fixes $BMSY/K = 0.37$ ($1/e$). The state-space version, SP_SS estimates annual deviates in biomass. An option allows for setting a prior for the intrinsic rate of increase. The function for the spict model (Pedersen and Berg, 2016) is available in [MSEextra](#).

Usage

```

SP(
  x = 1,
  Data,
  AddInd = "B",
  rescale = "mean1",
  start = NULL,
  fix_dep = TRUE,
  fix_n = TRUE,
  LWT = NULL,
  n_seas = 4L,
  n_itF = 3L,
  use_r_prior = FALSE,

```

```

    r_reps = 100,
    SR_type = c("BH", "Ricker"),
    silent = TRUE,
    opt_hess = FALSE,
    n_restart = ifelse(opt_hess, 0, 1),
    control = list(iter.max = 5000, eval.max = 10000),
    ...
)

SP_SS(
  x = 1,
  Data,
  AddInd = "B",
  rescale = "mean1",
  start = NULL,
  fix_dep = TRUE,
  fix_n = TRUE,
  fix_sigma = TRUE,
  fix_tau = TRUE,
  LWT = NULL,
  early_dev = c("all", "index"),
  n_seas = 4L,
  n_itF = 3L,
  use_r_prior = FALSE,
  r_reps = 100,
  SR_type = c("BH", "Ricker"),
  integrate = FALSE,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 5000, eval.max = 10000),
  inner.control = list(),
  ...
)

SP_Fox(x = 1, Data, ...)

```

Arguments

x	An index for the objects in Data when running in runMSE . Otherwise, equals to 1 When running an assessment interactively.
Data	An object of class Data.
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd.
rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time

	series mean is 1, otherwise a numeric. Output is re-converted back to original units.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
fix_dep	Logical, whether to fix the initial depletion (ratio of biomass to carrying capacity in the first year of the model). If TRUE, uses the value in start, otherwise equal to 1 (unfished conditions).
fix_n	Logical, whether to fix the exponent of the production function. If TRUE, uses the value in start, otherwise equal to $n = 2$, where the biomass at MSY is half of carrying capacity.
LWT	A vector of likelihood weights for each survey.
n_seas	Integer, the number of seasons in the model for calculating continuous surplus production.
n_itF	Integer, the number of iterations to solve F conditional on the observed catch given multiple seasons within an annual time step. Ignored if $n_seas = 1$.
use_r_prior	Logical, whether a prior for the intrinsic rate of increase will be used in the model. See details.
r_reps	If $use_r_prior = TRUE$, the number of samples of natural mortality and steepness for calculating the mean and standard deviation of the r prior. To override and directly provide the r-prior mean and standard deviation, use the start list, e.g. <code>start = list(r_prior = c(0.1, 0.05))</code> (mean of 0.1 and s.d. of 0.05).
SR_type	If $use_r_prior = TRUE$, the stock-recruit relationship used to calculate the stock-recruit alpha parameter from steepness and unfished spawners-per-recruit. Used to develop the r prior.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if $integrate = TRUE$.
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of parameters regarding optimization to be passed to <code>nlminb</code> .
...	For <code>SP_Fox</code> , additional arguments to pass to SP.
fix_sigma	Logical, whether the standard deviation of the index is fixed. If TRUE, sigma is fixed to value provided in start (if provided), otherwise, value based on <code>Data@CV_Ind</code> .
fix_tau	Logical, the standard deviation of the biomass deviations is fixed. If TRUE, tau is fixed to value provided in start (if provided), otherwise, equal to 0.1.
early_dev	Character string describing the years for which biomass deviations are estimated in <code>SP_SS</code> . By default, deviations are estimated in each year of the model ("all"), while deviations could also be estimated once index data are available ("index").

integrate	Logical, whether the likelihood of the model integrates over the likelihood of the biomass deviations (thus, treating it as a state-space variable).
inner.control	A named list of arguments for optimization of the random effects, which is passed on to newton via MakeADFun .

Details

For `start` (optional), a named list of starting values of estimates can be provided for:

- `MSY` Maximum sustainable yield.. Otherwise, 300% of mean catch by default.
- `FMSY` Steepness. Otherwise, `Data@Mort[x]` or 0.2 is used.
- `dep` Initial depletion (`B/B0`) in the first year of the model. By default, 1.
- `n` The production function exponent that determines `BMSY/B0`. By default, 2 so that `BMSY/B0 = 0.5`.
- `sigma` Lognormal SD of the index (observation error). By default, 0.05. Not used with multiple indices.
- `tau` Lognormal SD of the biomass deviations (process error) in `SP_SS`. By default, 0.1.

Multiple indices are supported in the model.

If `use_r_prior = TRUE`, `SP` and `SP_SS` will use a prior for the intrinsic rate of increase in the objective function. A vector of length two can be passed in the `start` list for the mean and standard deviation of the prior (see example). The normal distribution is used.

If no values are provided, a prior is created using the Euler-Lotka method (Equation 15a of McAllister et al. 2001). The Euler-Lotka method is modified to multiply the left-hand side of equation 15a by the `alpha` parameter of the stock-recruit relationship (Stanley et al. 2009). Natural mortality and steepness are sampled in order to generate a prior distribution for `r`. See `vignette("Surplus_production")` for more details.

Value

An object of [Assessment](#) containing objects and output from TMB.

Online Documentation

Model description and equations are available on the openMSE [website](#).

Required Data

- `SP`: Cat, Ind
- `SP_SS`: Cat, Ind

Optional Data

`SP_SS`: CV_Ind

Note

The model uses the Fletcher (1978) formulation and is parameterized with FMSY and MSY as leading parameters. The default conditions assume unfished conditions in the first year of the time series and a symmetric production function ($n = 2$).

Tip: to create the Fox model (Fox 1970), just fix $n = 1$. See example.

Author(s)

Q. Huynh

References

- Fletcher, R. I. 1978. On the restructuring of the Pella-Tomlinson system. *Fishery Bulletin* 76:515:521.
- Fox, W.W. 1970. An exponential surplus-yield model for optimizing exploited fish populations. *Transactions of the American Fisheries Society* 99:80-88.
- McAllister, M.K., Pikitch, E.K., and Babcock, E.A. 2001. Using demographic methods to construct Bayesian priors for the intrinsic rate of increase in the Schaefer model and implications for stock rebuilding. *Can. J. Fish. Aquat. Sci.* 58: 1871-1890.
- Pedersen, M. W. and Berg, C. W. 2017. A stochastic surplus production model in continuous time. *Fish and Fisheries*. 18:226-243.
- Pella, J. J. and Tomlinson, P. K. 1969. A generalized stock production model. *Inter-Am. Trop. Tuna Comm., Bull.* 13:419-496.
- Prager, M. H. 1994. A suite of extensions to a nonequilibrium surplus-production model. *Fishery Bulletin* 92:374-389.
- Stanley, R.D., M. McAllister, P. Starr and N. Olsen. 2009. Stock assessment for bocaccio (*Sebastes paucispinis*) in British Columbia waters. *DFO Can. Sci. Advis. Sec. Res. Doc.* 2009/055. xiv + 200 p.

See Also

[SP_production plot.Assessment summary.Assessment retrospective profile make_MP](#)

Examples

```
data(swordfish)

#### Observation-error surplus production model
res <- SP(Data = swordfish)

# Provide starting values, assume B/K = 0.875 in first year of model
# and symmetrical production curve (n = 2)
start <- list(dep = 0.875, n = 2)
res <- SP(Data = swordfish, start = start)

plot(res)
profile(res, FMSY = seq(0.1, 0.4, 0.01))
retrospective(res)
```



```
#### State-space version
res_SS <- SP_SS(Data = swordfish, start = list(dep = 0.875, sigma = 0.1, tau = 0.1))

plot(res_SS)

#### Fox model
res_Fox <- SP(Data = swordfish, start = list(n = 1), fix_n = TRUE)
res_Fox2 <- SP_Fox(Data = swordfish)

#### SP with r_prior
res_prior <- SP(Data = SimulatedData, use_r_prior = TRUE)

#### Pass an r_prior to the model with mean = 0.35, sd = 0.10
res_prior2 <- SP(Data = SimulatedData, use_r_prior = TRUE, start = list(r_prior = c(0.35, 0.10)))
```

SP_production

Find the production parameter based on depletion that produces MSY

Description

For surplus production models, this function returns the production exponent n corresponding to $BMSY/K$ (Fletcher 1978).

Usage

```
SP_production(depletion, figure = TRUE)
```

Arguments

depletion	The hypothesized depletion that produces MSY.
figure	Local, plots figure of production function as a function of depletion (B/K)

Value

The production function exponent n (numeric).

Note

May be useful for parameterizing n in [SP](#) and [SP_SS](#).

Author(s)

Q. Huynh

References

Fletcher, R. I. 1978. On the restructuring of the Pella-Tomlinson system. *Fishery Bulletin* 76:515:521.

See Also

[SP SP_SS](#)

Examples

```
SP_production(0.5)
SP_production(0.5)
```

SSS

Simple Stock Synthesis

Description

A simple age-structured model ([SCA_Pope](#)) fitted to a time series of catch going back to unfished conditions. Terminal depletion (ratio of current total biomass to unfished biomass) is by default fixed to 0.4. Selectivity is fixed to the maturity ogive, although it can be overridden with the `start` argument. The sole parameter estimated is R_0 (unfished recruitment), with no process error.

Usage

```
SSS(
  x = 1,
  Data,
  dep = 0.4,
  SR = c("BH", "Ricker"),
  rescale = "mean1",
  start = NULL,
  silent = TRUE,
  opt_hess = FALSE,
  n_restart = ifelse(opt_hess, 0, 1),
  control = list(iter.max = 2e+05, eval.max = 4e+05),
  ...
)
```

Arguments

<code>x</code>	A position in the <code>Data</code> object (by default, equal to one for assessments).
<code>Data</code>	An object of class <code>Data</code>
<code>dep</code>	Depletion value to use in the model. Can be an expression that will be evaluated inside the function.
<code>SR</code>	Stock-recruit function (either <code>"BH"</code> for Beverton-Holt or <code>"Ricker"</code>).

rescale	A multiplicative factor that rescales the catch in the assessment model, which can improve convergence. By default, "mean1" scales the catch so that time series mean is 1, otherwise a numeric. Output is re-converted back to original units.
start	Optional named list of starting values. Entries can be expressions that are evaluated in the function: <ul style="list-style-type: none"> • R_0 Unfished recruitment • <code>vu1_par</code> A length-two vector for the age of 95% and 50% fleet selectivity. Fixed to maturity otherwise.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate).
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of arguments for optimization to be passed to <code>nlminb</code> .
...	Other arguments to be passed (not currently used).

Details

In SAMtool, SSS is an implementation of `SCA_Pope` with fixed final depletion (in terms of total biomass, not spawning biomass) assumption.

Value

An object of class `Assessment`.

Author(s)

Q. Huynh

References

Cope, J.M. 2013. Implementing a statistical catch-at-age model (Stock Synthesis) as a tool for deriving overfishing limits in data-limited situations. *Fisheries Research* 142:3-14.

Examples

```
res <- SSS(Data = Red_snapper)

SSS_MP <- make_MP(SSS, HCR40_10, dep = 0.3) # Always assume depletion = 0.3
```

summary.Assessment *Summary of Assessment object*

Description

Returns a summary of parameter estimates and output from an [Assessment](#) object.

Usage

```
## S4 method for signature 'Assessment'  
summary(object)
```

Arguments

object An object of class [Assessment](#)

Value

A list of parameters.

Examples

```
output <- DD_TMB(Data = MSEtool::SimulatedData)  
summary(output)
```

swordfish *North Atlantic Swordfish dataset*

Description

An S4 object containing catch and index time series for North Atlantic swordfish.

Usage

```
swordfish
```

Format

An object of class [Data](#).

Source

ASPIC Software at <https://www.mhprager.com/aspic.html>

Examples

```
data(swordfish)
```

TAC_MSY	<i>Calculate MSY-based TAC from Assessment object</i>
---------	---

Description

A function to calculate the total allowable catch (TAC). Based on the MSY (maximum sustainable yield) principle, the TAC is the product of either UMSY or FMSY and the available biomass, i.e. vulnerable biomass, in terminal year.

Usage

```
TAC_MSY(Assessment, reps, MSY_frac = 1)
```

Arguments

Assessment	An Assessment object with estimates of UMSY or FMSY and terminal year vulnerable biomass.
reps	The number of stochastic draws of UMSY or FMSY.
MSY_frac	The fraction of FMSY or UMSY for calculating the TAC (e.g. MSY_frac = 0.75 fishes at 75% of FMSY).

Value

A vector of length reps of stochastic samples of TAC recommendation. Returns NA's if missing either UMSY/FMSY or vulnerable biomass.

Note

calculate_TAC is deprecated as of version 1.2 in favor of TAC_MSY because the latter has a more informative name.

See Also

[HCR_MSY](#) [HCR40_10](#) [HCR60_20](#)

userguide	<i>Get the SAMtool vignettes</i>
-----------	----------------------------------

Description

A convenient function to open a web browser with the SAMtool package vignettes

Usage

```
userguide()
```

Value

Displays a browser webpage to the package vignette.

Examples

```
userguide()
```

VPA

Virtual population analysis (VPA)

Description

A VPA model that back-calculates abundance-at-age assuming that the catch-at-age is known without error and tuned to an index. The population dynamics equations are primarily drawn from VPA-2BOX (Porch 2018). MSY reference points and per-recruit quantities are then calculated from the VPA output.

Usage

```
VPA(  
  x = 1,  
  Data,  
  AddInd = "B",  
  expanded = FALSE,  
  SR = c("BH", "Ricker"),  
  vulnerability = c("logistic", "dome", "free"),  
  start = list(),  
  fix_h = TRUE,  
  fix_Fratio = TRUE,  
  fix_Fterm = FALSE,  
  LWT = NULL,  
  shrinkage = list(),  
  n_itF = 5L,  
  min_age = "auto",  
  max_age = "auto",  
  refpt = list(),  
  silent = TRUE,  
  opt_hess = FALSE,  
  n_restart = ifelse(opt_hess, 0, 1),  
  control = list(iter.max = 2e+05, eval.max = 4e+05),  
  ...  
)
```

Arguments

x	A position in the Data object (by default, equal to one for assessments).
Data	An object of class Data
AddInd	A vector of integers or character strings indicating the indices to be used in the model. Integers assign the index to the corresponding index in Data@AddInd, "B" (or 0) represents total biomass in Data@Ind, "VB" represents vulnerable biomass in Data@VInd, and "SSB" represents spawning stock biomass in Data@SpInd.
expanded	Whether the catch at age in Data has been expanded. If FALSE, then the catch in weight should be provided in Data@Cat so that the function can calculate annual expansion factors.
SR	Stock-recruit function (either "BH" for Beverton-Holt or "Ricker") for calculating MSY reference points.
vulnerability	Whether the terminal year vulnerability is "logistic" or "dome" (double-normal). If "free", independent F's are calculated in the terminal year (subject to the assumed ratio of F of the plus-group to the previous age class). See details for parameterization.
start	Optional list of starting values. Entries can be expressions that are evaluated in the function. See details.
fix_h	Logical, whether to fix steepness to value in Data@steep. This only affects calculation of MSY and unfished reference points.
fix_Fratio	Logical, whether the ratio of F of the plus-group to the previous age class is fixed in the model.
fix_Fterm	Logical, whether to fix the value of the terminal F.
LWT	A vector of likelihood weights for each survey.
shrinkage	A named list of up to length 2 to constrain parameters: <ul style="list-style-type: none"> • vul - a length two vector that constrains the vulnerability-at-age in the most recent years. The first number is the number of years in which vulnerability will be constrained (as a random walk in log space), the second number is the standard deviation of the random walk. The default • R - a length two vector that constrains the recruitment estimates in the most recent years. The first number is the number of years in which recruitment will be constrained (as a random walk in log space), the second number is the standard deviation of the random walk.
n_itF	The number of iterations for solving F in the model (via Newton's method).
min_age	An integer to specify the smallest age class in the VPA. By default, the youngest age with non-zero CAA in the terminal year is used.
max_age	An integer to specify the oldest age class in the VPA. By default, the oldest age with non-zero CAA for all years is used.
refpt	A named list of how many years to average parameters for calculating reference points, yield per recruit, and spawning potential ratio: <ul style="list-style-type: none"> • vul An integer for the number of most recent years to average the vulnerability schedule (default is 3).

	<ul style="list-style-type: none"> • R A length two for the quantile used to calculate recruitment in the year following the terminal year and the number of years from which that quantile is used, i.e., $c(0.5, 5)$ is the default that calculates median recruitment from the most recent 5 years of the model.
silent	Logical, passed to <code>MakeADFun</code> , whether TMB will print trace information during optimization. Used for diagnostics for model convergence.
opt_hess	Logical, whether the hessian function will be passed to <code>nlminb</code> during optimization (this generally reduces the number of iterations to convergence, but is memory and time intensive and does not guarantee an increase in convergence rate). Ignored if <code>integrate = TRUE</code> .
n_restart	The number of restarts (calls to <code>nlminb</code>) in the optimization procedure, so long as the model hasn't converged. The optimization continues from the parameters from the previous (re)start.
control	A named list of arguments for optimization to be passed to <code>nlminb</code> .
...	Other arguments to be passed.

Details

The VPA is initialized by estimating the terminal F-at-age. Parameter `Fterm` is the apical terminal F if a functional form for vulnerability is used in the terminal year, i.e., when `vulnerability = "logistic" or "free"`. If the terminal F-at-age are otherwise independent parameters, `Fterm` is the F for the reference age which is half the maximum age. Once terminal-year abundance is estimated, the abundance in historical years can be back-calculated. The oldest age group is a plus-group, and requires an assumption regarding the ratio of F's between the plus-group and the next youngest age class. The F-ratio can be fixed (default) or estimated.

For `start` (optional), a named list of starting values of estimates can be provided for:

- `Fterm` The terminal year fishing mortality. This is the apical F when `vulnerability = "logistic" or "free"`.
- `Fratio` The ratio of F in the plus-group to the next youngest age. If not provided, a value of 1 is used.
- `vul_par` Vulnerability parameters in the terminal year. This will be of length 2 vector for "logistic" or length 4 for "dome", see [SCA](#) for further documentation on parameterization. For option "free", this will be a vector of length A-2 where A is the number of age classes in the model. To estimate parameters, vulnerability is initially set to one at half the max age (and subsequently re-calculated relative to the maximum F experienced in that year). Vulnerability in the plus-group is also constrained by the `Fratio`.

MSY and depletion reference points are calculated by fitting the stock recruit relationship to the recruitment and SSB estimates. Per-recruit quantities are also calculated, which may be used in harvest control rules.

Value

An object of class `Assessment`. The F vector is the apical fishing mortality experienced by any age class in a given year.

Online Documentation

Model description and equations are available on the openMSE [website](#).

References

Porch, C.E. 2018. VPA-2BOX 4.01 User Guide. NOAA Tech. Memo. NMFS-SEFSC-726. 67 pp.

Examples

```
out <- VPA(x = 2, Data = MSEtool::SimulatedData, vulnerability = "dome")
```

Index

- * **datasets**
 - pcod, [37](#)
 - swordfish, [92](#)
- * **evaluation**
 - SAMtool-package, [3](#)
- * **fisheries**
 - SAMtool-package, [3](#)
- * **management**
 - SAMtool-package, [3](#)
- * **strategy**
 - SAMtool-package, [3](#)
- Assessment, [9](#), [17](#), [21](#), [26](#), [28](#), [29](#), [32](#), [38–40](#),
[53](#), [56](#), [58](#), [64](#), [71](#), [77](#), [81](#), [83](#), [87](#), [91](#),
[92](#), [96](#)
- Assessment (Assessment-class), [4](#)
- Assessment-class, [4](#)
- calculate_TAC (TAC_MSY), [93](#)
- cDD, [6](#)
- cDD_SS (cDD), [6](#)
- check_RCMdata, [10](#)
- compare_models, [17](#)
- compare_RCM, [16](#)
- compare_RCM (plot.RCModel), [40](#)
- contour, [40](#)
- Data, [7](#), [12](#), [14](#), [16](#), [19](#), [92](#)
- Data-rich-MP (Model-based-MP), [36](#)
- DD_SS, [37](#)
- DD_SS (DD_TMB), [18](#)
- DD_TMB, [10](#), [18](#)
- DDSS_4010 (Model-based-MP), [36](#)
- DDSS_75MSY (Model-based-MP), [36](#)
- DDSS_MSY (Model-based-MP), [36](#)
- diagnostic, [22](#), [35](#), [65](#)
- diagnostic_AM (diagnostic), [22](#)
- getinds, [23](#)
- HCR40_10, [93](#)
- HCR40_10 (HCR_ramp), [29](#)
- HCR60_20, [93](#)
- HCR60_20 (HCR_ramp), [29](#)
- HCR80_40MSY (HCR_ramp), [29](#)
- HCR_escapement, [25](#)
- HCR_FB, [27](#)
- HCR_MSY, [28](#), [30](#), [35](#), [93](#)
- HCR_ramp, [24](#), [26](#), [28](#), [29](#), [31](#), [35](#)
- HCR_segment, [29](#), [30](#), [31](#)
- HCRlin, [24](#), [30](#)
- loess, [35](#)
- mahplot, [33](#)
- make_interim_MP, [33](#)
- make_MP, [6](#), [10](#), [22](#), [26](#), [28–30](#), [36](#), [65](#), [71](#), [78](#),
[82](#), [88](#)
- make_MP (make_interim_MP), [33](#)
- MakeADFun, [6](#), [8](#), [16](#), [20](#), [62](#), [69](#), [74](#), [77](#), [80](#), [86](#),
[87](#), [91](#), [96](#)
- Model-based-MP, [36](#)
- MP (Model-based-MP), [36](#)
- MSE, [65](#)
- MSEextra, [84](#)
- newton, [8](#), [20](#), [69](#), [74](#), [77](#), [80](#), [87](#)
- nlinb, [6](#), [8](#), [13](#), [20](#), [23](#), [62](#), [69](#), [74](#), [77](#), [80](#), [86](#),
[91](#), [96](#)
- OM, [12](#), [37](#), [61](#)
- pcod, [16](#), [37](#)
- Perfect (Shortcut), [82](#)
- plot, Assessment, missing-method
(plot.Assessment), [38](#)
- plot, Assessment, retro-method
(plot.Assessment), [38](#)
- plot, prof, missing-method (plot.prof), [39](#)
- plot, RCModel, missing-method
(plot.RCModel), [40](#)

- plot,retro,missing-method (plot.retro),
42
- plot.Assessment, 6, 10, 22, 38, 63, 71, 78, 88
- plot.prof, 39, 55
- plot.RCModel, 16, 40, 62
- plot.retro, 42, 63
- plot_betavar, 43, 47, 50
- plot_composition, 44
- plot_crosscorr, 45
- plot_lognormalvar, 43, 46, 50
- plot_residuals, 47, 51
- plot_SR, 48
- plot_steepness, 43, 47, 49
- plot_timeseries, 48, 50
- PRBcalc, 33, 52, 54
- predict.varest, 82
- prelim_AM, 53
- Probs, 53, 54
- prof, 40, 56
- prof (prof-class), 55
- prof-class, 55
- profile, 6, 10, 22, 39, 40, 55, 55, 71, 78, 88
- profile,Assessment-method (profile), 55
- profile,RCModel-method (profile), 55
- project, 58
- project (project-class), 57
- project-class, 57
- projection, 57, 57

- RCM, 3, 37, 38, 41, 42, 59–62
- RCM (check_RCMdata), 10
- RCM,OM,Data-method (check_RCMdata), 10
- RCM,OM,list-method (check_RCMdata), 10
- RCM,OM,RCMdata-method (check_RCMdata),
10
- RCMdata, 12–14, 16, 37, 62
- RCMdata (RCMdata-class), 59
- RCMdata-class, 59
- RCModel, 13, 16, 41, 42, 64
- RCModel (RCModel-class), 61
- RCModel-class, 61
- Rec, 26, 28, 30, 32, 36
- render, 39, 41
- retro, 39, 42
- retro (retro-class), 63
- retro-class, 63
- retrospective, 6, 10, 22, 39, 63, 63, 71, 78,
88
- retrospective,Assessment-method
(retrospective), 63
- retrospective,RCModel-method
(retrospective), 63
- retrospective_AM, 23, 35, 64
- runMSE, 23, 33, 83, 85

- SAMtool (SAMtool-package), 3
- SAMtool-package, 3
- SCA, 37, 66, 72, 77, 78, 81–83, 96
- SCA2 (SCA), 66
- SCA_4010 (Model-based-MP), 36
- SCA_75MSY (Model-based-MP), 36
- SCA_CAL, 72
- SCA_DDM, 75, 81
- SCA_MSY (Model-based-MP), 36
- SCA_Pope, 90, 91
- SCA_Pope (SCA), 66
- SCA_RWM, 78, 78
- sdreport, 6, 62
- Shortcut, 82
- Shortcut2 (Shortcut), 82
- SP, 37, 84, 89, 90
- SP_4010 (Model-based-MP), 36
- SP_75MSY (Model-based-MP), 36
- SP_Fox (SP), 84
- SP_MSY (Model-based-MP), 36
- SP_production, 88, 89
- SP_SS, 89, 90
- SP_SS (SP), 84
- SSS, 37, 90
- SSS_4010 (Model-based-MP), 36
- SSS_75MSY (Model-based-MP), 36
- SSS_MSY (Model-based-MP), 36
- summary,Assessment-method
(summary.Assessment), 92
- summary,retro-method (plot.retro), 42
- summary.Assessment, 6, 10, 22, 71, 78, 88, 92
- summary.retro, 63
- summary.retro (plot.retro), 42
- swordfish, 92

- TAC_MSY, 93

- userguide, 93

- VAR, 83
- VPA, 94