

Package ‘dbcsp’

July 9, 2021

Title Distance-Based Common Spatial Patterns

Version 0.0.1.0

Maintainer Itsaso Rodríguez-Moreno <itsaso.rodriguez@ehu.eus>

Description A way to apply Distance-Based Common Spatial Patterns (DB-CSP) techniques in different fields, both classical Common Spatial Patterns (CSP) as well as DB-CSP. The method is composed of two phases: applying the DB-CSP algorithm and performing a classification. The main idea behind the CSP is to use a linear transform to project data into low-dimensional subspace with a projection matrix, in such a way that each row consists of weights for signals. This transformation maximizes the variance of two-class signal matrices. The dbcsp object is created to compute the projection vectors. For exploratory and descriptive purpose, plot and boxplot functions can be used. Functions train, predict and selectQ are implemented for the classification step.

License GPL (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports plyr, parallelDist, Matrix, geigen, caret, MASS, stats,
ggplot2, methods

Depends R (>= 2.10), TSdist (>= 3.7)

NeedsCompilation no

Author Itziar Irigoien [aut],
Concepción Arenas [aut],
Itsaso Rodríguez-Moreno [cre, aut]

Repository CRAN

Date/Publication 2021-07-09 08:40:05 UTC

R topics documented:

dbcsp-package	2
AR.data	3
boxplot.dbcsp	4

dbcsp-class	5
plot.dbcsp	7
predict.dbcsp	8
print.dbcsp	9
selectQ	10
summary.dbcsp	12
train	13

Index	15
--------------	-----------

dbcsp-package	<i>Distance-Based Common Spatial Patterns</i>
---------------	---

Description

dbcsp is a package which offers a way to apply Distance-Based Common Spatial Patterns (DB-CSP) techniques in different fields, both classical Common Spatial Patterns (CSP) as well as DB-CSP.

Author(s)

Itsaso Rodriguez Moreno <itsaso.rodriguez@ehu.eus>

Itziar Irigoien <itziar.irigoien@ehu.eus>

Concepción Arenas <carenas@ub.edu>

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [selectQ](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# There is an example dataset called AR.data shipped with the package.

# It contains the skeleton data extracted from videos of people performing six different actions,
# recorded by a humanoid robot. So, it has 6 different classes.

# As the whole process is performed pairwise, first two classes are selected (some instances are
# saved to use later as test)

handshake <- AR.data$handshake[1:15]
ignore <- AR.data$ignore[1:15]

# Now, the dbcsp object can be created, where q represents the number of vectors used in
# the projection, the obtained filter will have 2*q dimension.

# By default, euclidean distance is used. To change it, just select another distance type.
# A mixture with euclidean distance and another one can be performed too, changing the mixture
# parameter value.

# Regarding the classification, train, predict and selectQ functions can be used.
```

```

# An LDA model can be train with the features extracted after performing the CSP, both with the
# train function or using the training=TRUE parameter when creating the dbcsp object

mydbcsp <- new('dbcsp', handshake, ignore, q=10, training=TRUE, fold = 1)

# Once the object is created, print and summary functions can be used to see some details

print(mydbcsp)
summary(mydbcsp)

# The predict function returns the predicted labels for the selected test data.
# And if true_labels are indicated, the obtained accuracy is also printed

handshake_test <- AR.data$handshake[41:45]
ignore_test <- AR.data$ignore[41:45]
test_data <- c(handshake_test, ignore_test)
true_labels <- c(rep('handshake', length(handshake_test)), rep('ignore', length(ignore_test)))
predictions <- predict(mydbcsp, test_data, true_labels)

# To help us deciding which is the best dimension to use when performing the CSP algorithm, the
# selectQ function can be used. Instead of using train_size to validate with train/test split,
# cross validation can be performed too.

bestQ <- selectQ(mydbcsp, Q=c(2,3,5), train_size=0.8)

# A plot can also be obtained, which displays the signals before and after the CSP projection
# With the vectors parameter it can be decided which dimensions to show and if we just want to
# plot the transformed signals, the before parameter must be set to FALSE

plot(mydbcsp, class=2, index=1, before=FALSE, vectors = 1:5, legend=TRUE)

# A boxplot can also be obtained to show the features achieved after the CSP (the variances of
# the transformed signals) which are used to perform the classification
# In the CSP algorithm the vectors work in pairs (the first q vectors maximize the variance of
# one class and minimize the variance of the other, while the last q vectors do the opposite),
# by default the vectors are showed in pairs, but this can be changed.
# The logarithm of the variances are plotted, but the value of the variances are shown
# when changing show_log parameter to FALSE

boxplot(mydbcsp, vectors=c(2,4,8))

```

AR.data

Skeleton data for 6 different actions.

Description

A dataset containing the skeleton data extracted from videos of people performing six different actions, recorded by a humanoid robot. Each class has several instances with 50 values (25 XY body keypoints extracted using OpenPose <https://github.com/CMU-Perceptual-Computing-Lab/openpose>) per frame of the video (92 frames).

Usage

```
AR.data
```

Format

A list of 6 different actions:

come Gesture for telling the robot to come to you. 46 instances of [50x92] matrices.

five Gesture of 'high five'. 45 instances of [50x92] matrices.

handshake Gesture of handshaking with the robot. 45 instances of [50x92] matrices.

hello Gesture for telling hello to the robot. 44 instances of [50x92] matrices.

ignore Ignore the robot, pass by. 46 instances of [50x92] matrices.

look_at Stare at the robot in front of it. 46 instances of [50x92] matrices.

Examples

```
X1 <- AR.data$come
X2 <- AR.data$five
mydbcsp <- new('dbcsp',X1,X2)
```

boxplot.dbcsp

Boxplot for dbcsp object

Description

This function plots the variance of the selected vectors in a boxplot.

Usage

```
## S3 method for class 'dbcsp'
boxplot(x, vectors=1, pairs=TRUE, ordered_pairs=TRUE, show_log=TRUE, ...)
```

Arguments

x	object of class dbcsp .
vectors	integer or array of integers, indicating the index of the projected vectors to plot, by default vectors=1.
pairs	logical, if TRUE the pairs of the indicated vectors are also shown, by default pairs=TRUE.
ordered_pairs	logical, if TRUE the pairs are plotted next to each other, else pairs are plotted at the end, by default ordered_pairs=TRUE.
show_log	logical, if TRUE the logarithms of the variances are displayed, else the variances are displayed, by default show_log=TRUE.
...	optional arguments inherited from the generic boxplot method.

Details

A boxplot with the variances of the selected vectors. Vectors values must lie between 1 and $2*q$, being q the number of dimensions used to perform the DB-CSP algorithm when creating the `dbcsp` object. The following should be taken into account when plotting:

- The first q values (1,..., q) are indicated as $a1...aq$
- The last q values ($q+1, \dots, 2*q$) are indicated as $b1...bq$.

If `pairs=TRUE`, it is recommended that `vectors<q` for better understanding, since their pairs are plotted as well. In case that `vectors>q`, it should be noted that the values are displayed from $b1$ to bq , where $b1$ and bq represent $q+1$ vector and $2*q$ vector, respectively.

For example if $q=15$ and `boxplot(object,vectors=16,pairs=FALSE)`, $b1$ ($16-q=1$) vector is shown.

Value

Displays the boxplot of the variances of the selected vectors.

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [selectQ](#), [predict](#), [plot](#)

Examples

```
# Read data from 2 classes
x <- AR.data$come
y <- AR.data$five
mydbcsp <- new("dbcsp", X1 = x, X2 = y)
boxplot(mydbcsp)
boxplot(mydbcsp, vectors=1:4, pairs=FALSE)
boxplot(mydbcsp, vectors=c(1,4,7), ordered_pairs=FALSE)
```

dbcsp-class

S4 class for representing DB-CSP (Distance-Based Common Spatial Patterns)

Description

An object of class `dbcsp`. 'dbcsp' stands for Distance-Based Common Spatial Patterns. The object includes the Common Spatial Patterns filter obtained with the input lists and using the distance method indicated.

Details

The output is a list containing this information (object@out):

- `vectors` The projection vectors obtained after applying CSP.
- `eig` The eigenvalues obtained after applying CSP.
- `proy` The variance values of the projected signals obtained after applying CSP.

And if `training=TRUE` the following values are also saved:

- `acc` The mean accuracy value obtained for training data applying cross validation.
- `used_folds` List of the folds used in the cross validation.
- `folds_acc` Accuracy values for each of the folds of the cross validation.
- `model` The trained LDA classifier.
- `selected_q` The number of vectors used when training.

Slots

`X1` list of matrices for data class 1.

`X2` list of matrices for data class 2.

`q` integer value indicating the number of vectors used in the projection, by default `q=15`.

`labels` vector of two strings indicating labels names, by default names of variables `X1` and `X2`.

`type` sets the type of distance to be considered, by default `type='EUCL'`. The supported distances are these ones

- Included in `TSdist`: `infnorm`, `ccor`, `sts`, `lb.keogh`, `edr`, `erp`, `lcss`, `fourier`, `tquest`, `dissim`, `acf`, `pacf`, `ar.lpc.ceps`, `ar.mah`, `ar.mah.statistic`, `ar.mah.pvalue`, `ar.pic`, `cdm`, `cid`, `cor`, `cort`, `int.per`, `per`, `mindist.sax`, `ncd`, `pred`, `spec.glk`, `spec.isd`, `spec.llr`, `pdcc`, `frechet`, `tam`.
- Included in `parallelDist`: `bhattacharyya`, `bray`, `canberra`, `chord`, `divergence`, `dtw`, `euclidean`, `fjaccard`, `geodesic`, `hellinger`, `kullback`, `mahalanobis`, `manhattan`, `maximum`, `minkowski`, `podani`, `soergel`, `wave`, `whittaker`.

`w` weight for the distances mixture $D_{mixture} = w * D_{euclidean} + (1-w) * D_{type}$, by default `w=0.5`.

`mixture` logical value indicating whether to use distances mixture or not (EUCL + other), by default `mixture=FALSE`.

`training` logical value indicating whether to perform the training or not.

`fold` integer value, by default `fold=10`. It controls the number of partitions when training. If `fold==1` a train/test split is performed, with `p=0.2` for test indices.

`seed` numeric value, by default `seed=NULL`. Set a seed in case the results want to be replicable.

`eig.tol` numeric value, by default `eig.tol=1e-06`, tolerance to convert distance matrix to be definite positive.

`verbose` logical

`out` list containing the output.

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [selectQ](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# To create an instance of a class dbcsp given data from 2 classes
x <- AR.data$come
y <- AR.data$five
dbcsp <- new("dbcsp", X1 = x, X2 = y)
```

plot.dbcsp

*Plot function implemented by dbcsp class***Description**

This function plots an instance before and/or after its DB-CSP projection.

Usage

```
## S3 method for class 'dbcsp'
plot(x, class = 1, index = 1, vectors = 1:(x@q*2), pairs=TRUE,
     before = TRUE, after = TRUE, legend = FALSE, ...)
```

Arguments

x	object of class <code>dbcsp</code> .
class	integer, which of both classes to access (1 or 2), by default class=1
index	an integer, representing which instance of the class to plot, by default index=1.
vectors	an integer or vector of integers, representing the vectors to plot after the projection, by default all the vectors used in the projection are plotted vectors=1:(x@q*2).
pairs	logical, if TRUE the pairs of the indicated vectors are also shown, by default pairs=TRUE.
before	logical, if TRUE the original signals are plotted, by default before=TRUE.
after	logical, if TRUE the signals after projection are plotted, by default after=TRUE.
legend	logical, if true the legend of the transformed signals is shown, by default legend=FALSE. When plotting more than 15 pairs of signals (15*2=30 signals), the legend is not shown. If before=TRUE legends are not displayed.
...	optional arguments inherited from the generic <code>plot</code> method.

Details

It plots an instance before and/or after being projected with the DB-CSP filter. Vectors values must lie between 1 and 2*q, being q the number of dimensions used to perform the DB-CSP algorithm when creating the `dbcsp` object. The following should be taken into account when plotting:

- The first q values (1,...,q) are indicated as a1...aq, and are plotted with solid lines.
- The last q values (q+1,...,2*q) are indicated as b1...bq, and are plotted with dashed lines.

If `pairs=TRUE`, it is recommended that `vectors<q` for better understanding, since their pairs are plotted as well. In case that `vectors>q`, it should be noted that the values are displayed from `b1` to `bq`, where `b1` and `bq` represent $q+1$ vector and $2*q$ vector, respectively. The paired vectors (`a1-b1`, `a2-b2`, ...) are plotted with the same color, but different line type.

For example if `q=15` and `plot(object, vectors=16, pairs=FALSE)`, `b1` ($16-q=1$) vector is shown.

Value

Displays a plot of the selected instance before and/or after the DB-CSP filter projection. The vectors shown after the projection are differentiated by the q first and q last vectors, since the former maximize the variance of one class and minimize the variance of the other, while the latter do the opposite.

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [selectQ](#), [predict](#), [boxplot](#)

Examples

```
# Read data from 2 classes
x <- AR.data$come
y <- AR.data$five
mydbcsp <- new("dbcsp", X1 = x, X2 = y)
plot(mydbcsp)
plot(mydbcsp, class=2, index=30, vectors=1:5, before=FALSE, legend=TRUE)
```

predict.dbcsp

Predict function implemented by dbcsp class

Description

This function returns the labels predicted for the input instances. If `true_targets` are passed as parameter, the accuracy obtained is printed too.

Usage

```
## S3 method for class 'dbcsp'
predict(object, X_test, true_targets=NULL, ...)
```

Arguments

<code>object</code>	object of class dbcsp .
<code>X_test</code>	list of matrices for test data.
<code>true_targets</code>	vector of true labels of the instances. Note that they must match the names of the labels used when training the model.
<code>...</code>	optional arguments inherited from the generic predict method.

Details

It gives the predictions for the test data using the model saved in the object, which has been previously trained with the [train](#) function. If the `true_targets` are indicated, the confusion matrix and obtained accuracy value are returned too.

Value

The values returned by the LDA [predict](#) function, a list with these components:

- `class` The MAP classification (a factor)
- `posterior` Posterior probabilities for the classes
- `x` The scores of test cases on up to `dimen` discriminant variables

If the `true_targets` are indicated, two more items are added to the output list:

- `confusion_matrix` The confusion matrix obtained with predicted labels and true labels.
- `acc` The accuracy value obtained for the test instances.

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [selectQ](#), [plot](#), [boxplot](#)

Examples

```
# Read data from 2 classes
x <- AR.data$come[1:20]
y <- AR.data$five[1:20]
mydbcsp <- new("dbcsp", X1 = x, X2 = y)
mydbcsp <- train(mydbcsp, fold=3)
test_data <- c(AR.data$come[20:24], AR.data$five[20:24])
test_labels <- c(rep('x', 5), rep('y', 5))
predictions <- predict(mydbcsp, test_data, test_labels)
# Predicted classes
print(predictions$class)
# Confusion matrix
print(predictions$confusion_matrix)
# Accuracy
print(predictions$acc)
```

print.dbcsp

Print function implemented by dbcsp class

Description

This function prints information about [dbcsp](#) class.

Usage

```
## S3 method for class 'dbcsp'  
print(x, ...)
```

Arguments

x object of class `dbcsp`.
... optional arguments inherited from the generic `print` method.

Details

It provides information about the object and the class.

Value

No return value, called for side effects.

See Also

[dbcsp](#), [summary](#), [train](#), [selectQ](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# Read data from 2 classes  
x <- AR.data$come[1:30]  
y <- AR.data$five[1:30]  
mydbcsp <- new("dbcsp", X1 = x, X2 = y)  
print(mydbcsp)
```

selectQ

Select Q best dimension

Description

This function applies DB-CSP and classification with different dimensions to see which gets the best outcomes.

Usage

```
selectQ(  
  object,  
  Q = c(1, 2, 3, 5, 10, 15),  
  train_size = 0.75,  
  CV = FALSE,  
  folds = 10,  
  seed = NULL  
)
```

```
## S4 method for signature 'dbcsp'  
selectQ(  
  object,  
  Q = c(1, 2, 3, 5, 10, 15),  
  train_size = 0.75,  
  CV = FALSE,  
  folds = 10,  
  seed = NULL  
)
```

Arguments

object	object of class dbcsp .
Q	list of integers which represents the dimensions to use, by default Q=c(1, 2, 3, 5, 10, 15).
train_size	float between 0.0 and 1.0 representing the proportion of the dataset to include in the train split, by default train_size=0.75.
CV	logical indicating if a cross validation must be performed or not (if TRUE, train_size is not used), by default CV=FALSE.
folds	integer, number of folds to use if CV is performed.
seed	numeric value, by default seed=NULL. Set a seed in case the results want to be replicable.

Value

A data.frame including the dimensions and their corresponding accuracies. If CV=TRUE, for each dimension, the standard deviation of the accuracy values of the folds is also included in the data frame.

See Also

[dbcsp](#), [print](#), [summary](#), [train](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# Read data from 2 classes  
x <- AR.data$come  
y <- AR.data$five  
mydbcsp <- new("dbcsp", X1 = x, X2 = y)  
result <- selectQ(mydbcsp)  
print(result)
```

`summary.dbcsp`*Summary function implemented by dbcsp class*

Description

This function provides a summary of the `dbcsp` object and information about the performed process.

Usage

```
## S3 method for class 'dbcsp'  
summary(object, ...)
```

Arguments

<code>object</code>	object of class <code>dbcsp</code> .
<code>...</code>	optional arguments inherited from the generic <code>summary</code> method.

Details

It prints the following information:

- Length and shape of the list of matrices of each class.
- The number of vectors (dimensions) used in the CSP projection.
- Distance used when performing the Common Spatial Patterns algorithm.
- If the training process has already been performed, the obtained training accuracy value.

Value

No return value, called for side effects.

See Also

[dbcsp](#), [print](#), [train](#), [selectQ](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# Read data from 2 classes  
x <- AR.data$come[1:30]  
y <- AR.data$five[1:30]  
mydbcsp <- new("dbcsp", X1 = x, X2 = y)  
summary(mydbcsp)
```

train	<i>Training process of a dbcsp object, using LDA classifier.</i>
-------	--

Description

This function applies DB-CSP to the instances and perform the training of a Linear Discriminant Analysis (LDA) classifier using the object data.

Usage

```
train(
  object,
  selected_q = object@q,
  fold = object@fold,
  seed = object@seed,
  verbose = TRUE
)

## S4 method for signature 'dbcsp'
train(
  object,
  selected_q = object@q,
  fold = object@fold,
  seed = object@seed,
  verbose = TRUE
)
```

Arguments

object	object of class <code>dbcsp</code> .
selected_q	integer value indicating the number of vectors to use when training the model, by default <code>selected_q=object@q</code> .
fold	integer value, by default <code>fold=object@fold</code> . It controls the number of partitions. If <code>fold==1</code> a train/test split is performed, with $p=0.2$ for test indices.
seed	numeric value, by default <code>fold=object@seed</code> . Set a seed in case the results want to be replicable.
verbose	logical

Value

The `dbcsp` object with the training results saved as list in `object@out`:

- `vectors` The projection vectors obtained after applying CSP.
- `eig` The eigenvalues obtained after applying CSP.
- `proy` The variance values of the projected signals obtained after applying CSP.

- `acc` The mean accuracy value obtained for training data applying cross validation.
- `used_folds` List of the folds used in the cross validation.
- `folds_acc` Accuracy values for each of the folds of the cross validation.
- `model` The trained LDA classifier.
- `selected_q` The number of vectors used when training.

See Also

[dbcsp](#), [print](#), [summary](#), [selectQ](#), [predict](#), [plot](#), [boxplot](#)

Examples

```
# Read data from 2 classes
x <- AR.data$come[1:20]
y <- AR.data$five[1:20]
mydbcsp <- new("dbcsp", X1 = x, X2 = y)
mydbcsp <- train(mydbcsp, fold=3)
print(mydbcsp@out$acc)
```

Index

* datasets

AR.data, 3

AR.data, 3

boxplot, 2, 4, 6, 8–12, 14

boxplot.dbcsp, 4

dbcsp, 2, 4–14

dbcsp-class, 5

dbcsp-package, 2

plot, 2, 5–7, 9–12, 14

plot.dbcsp, 7

predict, 2, 5, 6, 8–12, 14

predict.dbcsp, 8

print, 2, 5, 6, 8–12, 14

print.dbcsp, 9

selectQ, 2, 5, 6, 8–10, 10, 12, 14

selectQ,dbcsp-method (selectQ), 10

summary, 2, 5, 6, 8–12, 14

summary.dbcsp, 12

train, 2, 5, 6, 8–12, 13

train,dbcsp-method (train), 13