

Package ‘dsm’

March 27, 2021

Maintainer Laura Marshall <lhm@st-andrews.ac.uk>

License GPL (>= 2)

Title Density Surface Modelling of Distance Sampling Data

LazyLoad yes

Author David L. Miller, Eric Rexstad, Louise Burt, Mark V. Bravington,
Sharon Hedley.

Description Density surface modelling of line transect data. A Generalized Additive Model-based approach is used to calculate spatially-explicit estimates of animal abundance from distance sampling (also presence/absence and strip transect) data. Several utility functions are provided for model checking, plotting and variance estimation.

Version 2.3.1

Language en-GB

URL <https://github.com/DistanceDevelopment/dsm>

BugReports <https://github.com/DistanceDevelopment/dsm/issues>

Depends R (>= 3.5.0), mgcv (>= 1.8-23), mrds (>= 2.1.16), numDeriv

Imports nlme, ggplot2, plyr, statmod

Suggests Distance, sp, tweedie, testthat

RoxygenNote 7.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2021-03-27 02:10:02 UTC

R topics documented:

dsm-package	2
block.info.per.su	3
check.cols	3
dsm	4
dsm-data	7

dsm.cor	8
dsm.var.gam	10
dsm.var.movblk	11
dsm.var.prop	13
dsm_varprop	15
dummy_ddf	17
generate.ds.uncertainty	17
generate.mb.sample	18
latlong2km	19
make.soapgrid	19
matrixnotposdef.handler	20
mexdolphins	21
obs_exp	21
plot.dsm	22
plot.dsm.var	23
plot_pred_by_term	24
predict.dsm	25
predict.fake_ddf	26
print.dsm	27
print.dsm.var	28
print.dsm_varprop	28
print.summary.dsm.var	29
print.summary.dsm_varprop	29
rqgam.check	30
summary.dsm	31
summary.dsm.var	32
summary.dsm_varprop	33
trim.var	33
vis.concurvity	34
Index	36

dsm-package

Density surface modelling

Description

dsm implements spatial models for distance sampling data.

Details

Further information on distance sampling methods and example code is available at <http://distancesampling.org/R/>.

For help with distance sampling and this package, there is a Google Group <https://groups.google.com/forum/#!forum/distance-sampling>.

A example analyses are available at <http://examples.distancesampling.org>.

block.info.per.su *Find the block information*

Description

Takes the transect data and works out how many blocks of a given size (in segment terms) fit into each.

Usage

```
block.info.per.su(block.size, data, name.su)
```

Arguments

block.size	number of segments per block
data	data used to build the model
name.su	names of the sampling units (ie. transects)

Value

a data.frame with the following columns

name	the sample unit name (e.g. transect label)
num.seg	number of segments in that transect
num.block	number of blocks available
start.block	block # for first block
end.block	block # for last block
num.req	number of blocks needed for the unit

check.cols *Check column names exist*

Description

Internal function to check that supplied 'data.frames' have the correct columns and checks that sample labels are all unique.

Usage

```
check.cols(ddf.obj, segment.data, observation.data, segment.area)
```

Arguments

ddf.obj a ddf object from ‘mrds’
 segment.data segment data as defined in [dsm](#)
 observation.data observation data as defined in [dsm](#)
 segment.area area of segments

Value

nothing, but throws an error if something went wrong

Author(s)

David Lawrence Miller

dsm *Fit a density surface model to segment-specific estimates of abundance or density.*

Description

Fits a density surface model (DSM) to detection adjusted counts from a spatially-referenced distance sampling analysis. [dsm](#) takes observations of animals, allocates them to segments of line (or strip transects) and optionally adjusts the counts based on detectability using a supplied detection function model. A generalized additive model, generalized mixed model or generalized linear model is then used to model these adjusted counts based on a formula involving environmental covariates.

Usage

```
dsm(
  formula,
  ddf.obj,
  segment.data,
  observation.data,
  engine = "gam",
  convert.units = 1,
  family = quasipoisson(link = "log"),
  group = FALSE,
  control = list(keepData = TRUE),
  availability = 1,
  segment.area = NULL,
  weights = NULL,
  method = "REML",
  ...
)
```

Arguments

formula	formula for the surface. This should be a valid glm/gam/gamm formula. See "Details", below, for how to define the response.
ddf.obj	result from call to ddf or ds . If multiple detection functions are required a list can be provided. For strip/circle transects where it is assumed all objects are observed, see dummy_ddf . Mark-recapture distance sampling (mrds) models of type io (independent observers) are allowed.
segment.data	segment data, see dsm-data .
observation.data	observation data, see dsm-data .
engine	which fitting engine should be used for the DSM (glm/gam/gamm/bam).
convert.units	conversion factor to multiply the area of the segments by. See 'Units' below.
family	response distribution (popular choices include quasipoisson , Tweedie/tw and negbin/nb). Defaults to quasipoisson .
group	if TRUE the abundance of groups will be calculated rather than the abundance of individuals. Setting this option to TRUE is equivalent to setting the size of each group to be 1.
control	the usual control argument for a gam; keepData must be TRUE for variance estimation to work (though this option cannot be set for GLMs or GAMMs).
availability	an estimate of availability bias. For count models used to multiply the effective strip width (must be a vector of length 1 or length the number of rows in <code>segment.data</code>); for estimated abundance/estimated density models used to scale the response (must be a vector of length 1 or length the number of rows in <code>observation.data</code>). Uncertainty in the availability is not handled at present.
segment.area	if 'NULL' (default) segment areas will be calculated by multiplying the 'Effort' column in 'segment.data' by the (right minus left) truncation distance for the 'ddf.obj' or by 'strip.width'. Alternatively a vector of segment areas can be provided (which must be the same length as the number of rows in 'segment.data') or a character string giving the name of a column in 'segment.data' which contains the areas. If <code>segment.area</code> is specified it takes precedent.
weights	weights for each observation used in model fitting. The default, <code>weights=NULL</code> , weights each observation by its area (see Details). Setting a scalar value (e.g. <code>weights=1</code>) all observations are equally weighted.
method	The smoothing parameter estimation method. Default is "REML", using Restricted Maximum Likelihood. See gam for other options. Ignored for <code>engine="glm"</code> .
...	anything else to be passed straight to glm/gam/gamm/bam .

Details

The response (LHS of 'formula') can be one of the following (with restrictions outlined below):

count	count in each segment
abundance.est	estimated abundance per segment, estimation is via a Horvitz-Thompson estimator.
density.est	density per segment

The offset used in the model is dependent on the response:

count	area of segment multiplied by average probability of detection in the segment
estimated count	area of the segment
density	zero

The count response can only be used when detection function covariates only vary between segments/points (not within). For example, weather conditions (like visibility or sea state) or foliage cover are usually acceptable as they do not change within the segment, but animal sex or behaviour will not work. The `abundance.est` response can be used with any covariates in the detection function.

In the density case, observations can be weighted by segment areas via the `weights=` argument. By default (`weights=NULL`), when density is estimated the weights are set to the segment areas (using `segment.area` or by calculated from detection function object metadata and `Effort` data). Alternatively `weights=1` will set the weights to all be equal. A third alternative is to pass in a vector of length equal to the number of segments, containing appropriate weights.

A example analyses are available at <http://examples.distancesampling.org>.

Value

a `glm/gam/gamm` object, with an additional element, `ddf` which holds the detection function object.

Units

It is often the case that distances are collected in metres and segment lengths are recorded in kilometres. `dsm` allows you to provide a conversion factor (`convert.units`) to multiply the areas by. For example: if distances are in metres and segment lengths are in kilometres setting `convert.units=1000` will lead to the analysis being in metres. Setting `convert.units=1/1000` will lead to the analysis being in kilometres. The conversion factor will be applied to ‘`segment.area`’ if that is specified.

Large models

For large models, `engine="bam"` with `method="fREML"` may be useful. Models specified for `bam` should be as `gam`. READ `bam` before using this option; this option is considered EXPERIMENTAL at the moment. In particular note that the default basis choice (thin plate regression splines) will be slow and that in general fitting is less stable than when using `gam`. For negative binomial response, `theta` must be specified when using `bam`.

Author(s)

David L. Miller

References

- Hedley, S. and S. T. Buckland. 2004. Spatial models for line transect sampling. *JABES* 9:181-199.
- Miller, D. L., Burt, M. L., Rexstad, E. A., Thomas, L. (2013), Spatial models for distance sampling data: recent developments and future directions. *Methods in Ecology and Evolution*, 4: 1001-1010.

doi: 10.1111/2041-210X.12105 (Open Access, available at <http://onlinelibrary.wiley.com/doi/10.1111/2041-210X.12105/abstract>)

Wood, S.N. 2006. *Generalized Additive Models: An Introduction with R*. CRC/Chapman & Hall.

Examples

```
## Not run:
library(Distance)
library(dsm)

# load the Gulf of Mexico dolphin data (see ?mexdolphins)
data(mexdolphins)

# fit a detection function and look at the summary
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
summary(hr.model)

# fit a simple smooth of x and y to counts
mod1 <- dsm(count~s(x,y), hr.model, segdata, obsdata)
summary(mod1)

# predict over a grid
mod1.pred <- predict(mod1, preddata, preddata$area)

# calculate the predicted abundance over the grid
sum(mod1.pred)

# plot the smooth
plot(mod1)

## End(Not run)
```

dsm-data

Data format for DSM

Description

Two data.frames must be provided to `dsm`. They are referred to as `observation.data` and `segment.data`.

Details

The `segment.data` table has the sample identifiers which define the segments, the corresponding effort (line length) expended and the environmental covariates that will be used to model abundance/density. `observation.data` provides a link table between the observations used in the detection function and the samples (segments), so that we can aggregate the observations to the segments (i.e. `observation.data` is a "look-up table" between the observations and the segments).

`observation.data` - the observation data.frame must have (at least) the following columns:

object	unique object identifier
Sample.Label	the identifier for the segment that the observation occurred in
size	the size of each observed group (e.g 1 if all animals occurred individually)
distance	distance to observation

One can often also use `observation.data` to fit a detection function (so additional columns for detection function covariates are allowed in this table).

`segment.data`: the segment data. frame must have (at least) the following columns:

Effort	the effort (in terms of length of the segment)
Sample.Label	identifier for the segment (unique!)
???	environmental covariates, for example location (projected latitude and longitude), and other relevant covariates

Multiple detection functions

If multiple detection functions are to be used, then a column named `ddfobj` must be included in `observation.data` and `segment.data`. This lets the model know which detection function each observation is from. These are numeric and ordered as the `ddf.obj` argument to `dsm`, e.g., `ddf.obj=list(ship_ddf,aerial_ddf)` means ship detections have `ddfobj=1` and aerial detections have `ddfobj=2` in the observation data.

Mark-recapture distance sampling models

When using `mrds` models that include mark-recapture components (currently independent observer and trial modes are supported) then the format of the observation data needs to be checked to ensure that observations are not duplicated. The `observer` column is also required in the `observation.data` frame.

Independent observer mode	only unique observations (unique object IDs) are required.
Trial mode	only observations made by observer 1 are required.\

dsm.cor

Check for autocorrelation in residuals

Description

Once a DSM has been fitted to data, this function can be used to check for autocorrelation in the residuals.

Usage

```
dsm.cor(
  dsm.obj,
  Transect.Label = "Transect.Label",
  Segment.Label = "Segment.Label",
  max.lag = 10,
```



```

  resid.type = "scaled.pearson",
  fun = cor,
  ylim = c(0, 1),
  subset = "all",
  ...
)

```

Arguments

dsm.obj	a fitted dsm object.
Transect.Label	label for the transect (default: Transect.Label). Using different labels can be useful when transects are split over geographical features or when transects are surveyed multiple times.
Segment.Label	label for the segments (default: Segment.Label).The result of calling order() must make sense.
max.lag	maximum lag to calculate at.
resid.type	the type of residuals used, see residuals.gam and residuals.gam . Defaults to "scaled.pearson" in the GAM case and "normalized" in the GAMM case (which are equivalent).
fun	the function to use, by default cor , must take two column vectors as arguments.
ylim	user defined limits in y direction.
subset	which subset of the data should the correlation function be calculated on?
...	other options to pass to plot.

Value

a plot or a vector of fun applied at the lags.

Details

Within each Transect.Label, segments will be sorted according to their Segment.Labels. This may require some time to get right for your particular data. If one has multiple surveys where transects are revisited, for example, one may want to make Transect.Label a unique transect-survey id. Neither label need to be included in the model, they must just be present in the \$data field in the model. This usually means that they have to be in the segment data passed to dsm.

The current iteration of this function will only plot correlations nicely, other things are up to you but you can get the function to return the data (by assigning the result to an object).

If there are NA values in the residuals then the correlogram will not be calculated. This usually occurs due to NA values in the covariates (so the smoother will not have fitted values there). Code like `'any(is.na(dsm.obj$data))'` might be helpful.

Author(s)

David L. Miller

Examples

```

library(Distance)
library(dsm)

# load the data, see ?mexdolphins
data(mexdolphins)

# fit a model
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
mod1<-dsm(count~s(x,y), hr.model, segdata, obsdata)

# look at lag 1 differences up to a maximum of lag 9, using deviance
# residuals
dsm.cor(mod1, resid.type="deviance", max.lag=9,
        Segment.Label="Sample.Label")

```

dsm.var.gam

Prediction variance estimation assuming independence

Description

If one is willing to assume the the detection function and spatial model are independent, this function will produce estimates of variance of predictions of abundance, using the result that squared coefficients of variation will add.

Usage

```

dsm.var.gam(
  dsm.obj,
  pred.data,
  off.set,
  seglen.varname = "Effort",
  type.pred = "response"
)

```

Arguments

dsm.obj	a model object returned from running dsm .
pred.data	either: a single prediction grid or list of prediction grids. Each grid should be a data.frame with the same columns as the original data.
off.set	a a vector or list of vectors with as many elements as there are in pred.data. Each vector is as long as the number of rows in the corresponding element of pred.data. These give the area associated with each prediction cell. If a single number is supplied it will be replicated for the length of pred.data.
seglen.varname	name for the column which holds the segment length (default value "Effort").
type.pred	should the predictions be on the "response" or "link" scale? (default "response").

Details

This is based on `dsm.var.prop` taken from code by Mark Bravington and Sharon Hedley.

Value

a list with elements

<code>model</code>	the fitted model object
<code>pred.var</code>	variance of the regions given in <code>pred.data</code> .
<code>bootstrap</code>	logical, always FALSE
<code>model</code>	the fitted model with the extra term
<code>dsm.object</code>	the original model, as above

Author(s)

David L. Miller

Examples

```
## Not run:
library(Distance)
library(dsm)

# load the Gulf of Mexico dolphin data (see ?mexdolphins)
data(mexdolphins)

# fit a detection function and look at the summary
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
summary(hr.model)

# fit a simple smooth of x and y
mod1 <- dsm(count~s(x, y), hr.model, segdata, obsdata)

# Calculate the variance
# this will give a summary over the whole area in mexdolphins$preddata
mod1.var <- dsm.var.gam(mod1, preddata, off.set=preddata$area)

## End(Not run)
```

dsm.var.movblk

Variance estimation via parametric moving block bootstrap

Description

Estimate the variance in abundance over an area using a moving block bootstrap. Two procedures are implemented, one incorporating detection function uncertainty, one not.

Usage

```

dsm.var.movblk(
  dsm.object,
  pred.data,
  n.boot,
  block.size,
  off.set,
  ds.uncertainty = FALSE,
  samp.unit.name = "Transect.Label",
  progress.file = NULL,
  bs.file = NULL,
  bar = TRUE
)

```

Arguments

dsm.object	object returned from dsm .
pred.data	either: a single prediction grid or list of prediction grids. Each grid should be a <code>data.frame</code> with the same columns as the original data.
n.boot	number of bootstrap resamples.
block.size	number of segments in each block.
off.set	a a vector or list of vectors with as many elements as there are in <code>pred.data</code> . Each vector is as long as the number of rows in the corresponding element of <code>pred.data</code> . These give the area associated with each prediction cell. If a single number is supplied it will be replicated for the length of <code>pred.data</code> .
ds.uncertainty	incorporate uncertainty in the detection function? See Details, below. Note that this feature is EXPERIMENTAL at the moment.
samp.unit.name	name sampling unit to resample (default 'Transect.Label').
progress.file	path to a file to be used (usually by Distance) to generate a progress bar (default NULL – no file written).
bs.file	path to a file to store each bootstrap round. This stores all of the bootstrap results rather than just the summaries, enabling outliers to be detected and removed. (Default NULL).
bar	should a progress bar be printed to screen? (Default TRUE).

Details

Setting `ds.uncertainty=TRUE` will incorporate detection function uncertainty directly into the bootstrap. This is done by generating observations from the fitted detection function and then re-fitting a new detection function (of the same form), then calculating a new effective strip width. Rejection sampling is used to generate the observations (except in the half-normal case) so the procedure can be rather slow. Note that this is currently not supported with covariates in the detection function.

Setting `ds.uncertainty=FALSE` will incorporate detection function uncertainty using the delta method. This assumes that the detection function and the spatial model are INDEPENDENT. This is probably not reasonable.

Examples

```
## Not run:
library(Distance)
library(dsm)

# load the Gulf of Mexico dolphin data (see ?mexdolphins)
data(mexdolphins)

# fit a detection function and look at the summary
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
summary(hr.model)

# fit a simple smooth of x and y
mod1 <- dsm(count~s(x, y), hr.model, segdata, obsdata)
summary(mod1)

# calculate the variance by 500 moving block bootstraps
mod1.movblk <- dsm.var.movblk(mod1, preddata, n.boot = 500,
                             block.size = 3, samp.unit.name = "Transect.Label",
                             off.set = preddata$area,
                             bar = TRUE, bs.file = "mexico-bs.csv", ds.uncertainty = TRUE)

## End(Not run)
```

 dsm.var.prop

Prediction variance propagation for DSMs

Description

To ensure that uncertainty from the detection function is correctly propagated to the final variance estimate of abundance, this function uses a method first detailed in Williams et al (2011).

Usage

```
dsm.var.prop(
  dsm.obj,
  pred.data,
  off.set,
  seglen.varname = "Effort",
  type.pred = "response"
)
```

Arguments

dsm.obj	a model object returned from running dsm .
pred.data	either: a single prediction grid or list of prediction grids. Each grid should be a data.frame with the same columns as the original data.

off.set	a a vector or list of vectors with as many elements as there are in pred.data. Each vector is as long as the number of rows in the corresponding element of pred.data. These give the area associated with each prediction cell. If a single number is supplied it will be replicated for the length of pred.data.
seglen.varname	name for the column which holds the segment length (default value "Effort").
type.pred	should the predictions be on the "response" or "link" scale? (default "response").

Details

The idea is to refit the spatial model but including an extra random effect. This random effect has zero mean and hence to effect on point estimates. Its variance is the Hessian of the detection function. Variance estimates then incorporate detection function uncertainty. Further mathematical details are given in the paper in the references below.

Many prediction grids can be supplied by supplying a list of data.frames to the function.

Note that this routine simply calls `dsm_varprop`. If you don't require multiple prediction grids, the other routine will probably be faster.

This routine is only useful if a detection function with covariates has been used in the DSM.

Value

a list with elements

model	the fitted model object
pred.var	variance of each region given in pred.data.
bootstrap	logical, always FALSE
pred.data	as above
off.set	as above
model	the fitted model with the extra term
dsm.object	the original model, as above
model.check	simple check of subtracting the coefficients of the two models to see if there is a large difference
deriv	numerically calculated Hessian of the offset

Diagnostics

The summary output from the function includes a simple diagnostic that shows the average probability of detection from the "original" fitted model (the model supplied to this function; column `Fitted.model`) and the probability of detection from the refitted model (used for variance propagation; column `Refitted.model`) along with the standard error of the probability of detection from the fitted model (`Fitted.model.se`), at the unique values of any factor covariates used in the detection function (for continuous covariates the 5

Limitations

Note that this routine is only useful if a detection function has been used in the DSM. It cannot be used when the `abundance.est` or `density.est` responses are used. Importantly this requires that if the detection function has covariates, then these do not vary within a segment (so, for example covariates like sex cannot be used).

Author(s)

Mark V. Bravington, Sharon L. Hedley. Bugs added by David L. Miller.

References

Bravington, M. V., Miller, D. L., & Hedley, S. L. (2021). Variance Propagation for Density Surface Models. *Journal of Agricultural, Biological and Environmental Statistics*. <https://doi.org/10.1007/s13253-021-00438-2>

Williams, R., Hedley, S.L., Branch, T.A., Bravington, M.V., Zerbini, A.N. and Findlay, K.P. (2011). Chilean Blue Whales as a Case Study to Illustrate Methods to Estimate Abundance and Evaluate Conservation Status of Rare Species. *Conservation Biology* 25(3), 526-535.

 dsm_varprop

Variance propagation for density surface models

Description

Calculate the uncertainty in predictions from a fitted DSM, including uncertainty from the detection function.

Usage

```
dsm_varprop(model, newdata = NULL, trace = FALSE, var_type = "Vp")
```

Arguments

model	a fitted dsm .
newdata	the prediction grid. Set to NULL to avoid making predictions and just return model objects.
trace	for debugging, see how the scale parameter estimation is going.
var_type	which variance-covariance matrix should be used ("Vp" for variance-covariance conditional on smoothing parameter(s), "Vc" for unconditional). See gamObject for an details/explanation. If in doubt, stick with the default, "Vp".

Details

When we make predictions from a spatial model, we also want to know the uncertainty about that abundance estimate. Since density surface models are 2 (or more) stage models, we need to incorporate the uncertainty from the earlier stages (i.e. the detection function) into our "final" uncertainty estimate.

This function will refit the spatial model but include the Hessian of the offset as an extra term. Variance estimates using this new model can then be used to calculate the variance of predicted abundance estimates which incorporate detection function uncertainty. Importantly this requires that if the detection function has covariates, then these do not vary within a segment (so, for example covariates like sex cannot be used).

For more information on how to construct the prediction grid `data.frame`, `newdata`, see `predict.dsm`.

This routine is only useful if a detection function with covariates has been used in the DSM.

Note that we can use `var_type="Vc"` here (see `gamObject`), which is the variance-covariance matrix for the spatial model, corrected for smoothing parameter uncertainty. See Wood, Pya & Svanafken (2016) for more information.

Models with fixed scale parameters (e.g., negative binomial) do not require an extra round of optimisation.

Value

a list with elements

<code>old_model</code>	fitted model supplied to the function as <code>model</code>
<code>refit</code>	refitted model object, with extra term
<code>pred</code>	point estimates of predictions at <code>newdata</code>
<code>var</code>	total variance calculated over all of <code>newdata</code>
<code>ses</code>	standard error for each prediction cell in <code>newdata</code>

if `newdata=NULL` then the last three entries are NA.

Diagnostics

The summary output from the function includes a simple diagnostic that shows the average probability of detection from the "original" fitted model (the model supplied to this function; column `Fitted.model`) and the probability of detection from the refitted model (used for variance propagation; column `Refitted.model`) along with the standard error of the probability of detection from the fitted model (`Fitted.model.se`), at the unique values of any factor covariates used in the detection function (for continuous covariates the 5

Author(s)

David L. Miller, based on code from Mark V. Bravington and Sharon L. Hedley.

References

- Bravington, M. V., Miller, D. L., & Hedley, S. L. (2021). Variance Propagation for Density Surface Models. *Journal of Agricultural, Biological and Environmental Statistics*. <https://doi.org/10.1007/s13253-021-00438-2>
- Williams, R., Hedley, S.L., Branch, T.A., Bravington, M.V., Zerbini, A.N. and Findlay, K.P. (2011). Chilean Blue Whales as a Case Study to Illustrate Methods to Estimate Abundance and Evaluate Conservation Status of Rare Species. *Conservation Biology* 25(3), 526-535.
- Wood, S.N., Pya, N. and Svanafken, B. (2016) Smoothing parameter and model selection for general smooth models. *Journal of the American Statistical Association*, 1-45.

dummy_ddf	<i>Detection function objects when detection is certain</i>
-----------	---

Description

Create a detection function object for strip/plot surveys for use in density surface models.

Usage

```
dummy_ddf(object, size = 1, width, left = 0, transect = "line")
```

Arguments

object	numeric vector of object identifiers, relating to the object field in the observation data of the DSM.
size	group size for each observation (default all groups size 1)
width	right truncation
left	left truncation (default 0, no left truncation)
transect	"line" or "point" transect

Author(s)

David L Miller

generate.ds.uncertainty	<i>Generate data from a fitted detection function</i>
-------------------------	---

Description

When ds.uncertainty is TRUE, this procedure generates data from the fitted detection function (assuming that it is correct).

Usage

```
generate.ds.uncertainty(ds.object)
```

Arguments

ds.object	a fitted detection function object (as returned by a call to ddf.ds()).
-----------	---

Note

This function changes the random number generator seed. To avoid any potential side-effects, use something like: `seed <- get(".Random.seed", envir=.GlobalEnv)` before running code and `assign(".Random.seed", seed, envir=.GlobalEnv)` after.

Author(s)

David L. Miller

`generate.mb.sample` *Moving block bootstrap sampler*

Description

Not usually used on its own, called from within `dsm.var.movblk`.

Usage

```
generate.mb.sample(  
  num.blocks.required,  
  block.size,  
  which.blocks,  
  dsm.data,  
  unit.info,  
  n.units  
)
```

Arguments

<code>num.blocks.required</code>	number of blocks that we need.
<code>block.size</code>	number of segments per block.
<code>which.blocks</code>	which blocks should be sampled.
<code>dsm.data</code>	the <code>\$data</code> element of the result of a call to <code>dsm</code> .
<code>unit.info</code>	result of calling <code>block.info.per.su</code> .
<code>n.units</code>	number of sampling units.

Value

vector of log-residuals

latlong2km	<i>Convert latitude and longitude to Northings and Eastings</i>
------------	---

Description

Convert longitude and latitude co-ordinates to kilometres west-east and south-north from axes through (lon0,lat0) using the "spherical law of cosines".

Usage

```
latlong2km(lon, lat, lon0 = sum(range(lon))/2, lat0 = sum(range(lat))/2)
```

Arguments

lon	longitude
lat	latitude
lon0	longitude reference point (defaults to mean longitude)
lat0	latitude reference point (defaults to mean latitude)

Details

WARNING: This is an approximate procedure for converting between latitude/ longitude and Northing/Easting. Consider using projection conversions available in packages `sp` and `rgdal` for better results.

Value

list with elements `km.e` and `km.n`.

Author(s)

Simon N. Wood

make.soapgrid	<i>Create a knot grid for the internal part of a soap film smoother.</i>
---------------	--

Description

This routine simply creates a grid of knots (in the correct format) to be used as in the "internal" part of the soap film smoother

Usage

```
make.soapgrid(bnd, n.grid)
```

Arguments

- bnd list with elements x and y which give the locations of the boundary vertices. The first and last elements should be the same.
- n.grid either one number giving the number of points along the x and y axes that should be used to create the grid, or a vector giving the number in the x direction, then y direction.

Value

a list with elements x and y, containing the knot locations.

Author(s)

David L Miller

matrixnotposdef.handler

Handler to suppress the "matrix not positive definite" warning

Description

Internal function to suppress an annoying warnings from chol()

Usage

```
matrixnotposdef.handler(w)
```

Arguments

w a warning

Details

See: <https://stat.ethz.ch/pipermail/r-help/2012-February/302407.html> See: <http://romainfrancois.blog.free.fr/index.php?post/specific-warnings>

Value

not a warning if the warning was "matrix not positive definite" or "the matrix is either rank-deficient or indefinite"

Author(s)

David L. Miller

mexdolphins

Pan-tropical spotted dolphins in the Gulf of Mexico

Description

Data from a combination of several NOAA shipboard surveys conducted on pan-tropical spotted dolphins in the Gulf of Mexico. 47 observations of groups of dolphins. The group size was recorded, as well as the Beaufort sea state at the time of the observation. Coordinates for each observation and bathymetry data were also available as covariates for the analysis. A complete example analysis (and description of the data) is provided at <http://distancesampling.org/R/vignettes/mexico-analysis.html>.

References

Halpin, P.N., A.J. Read, E. Fujioka, B.D. Best, B. Donnelly, L.J. Hazen, C. Kot, K. Urian, E. LaBrecque, A. Dimatteo, J. Cleary, C. Good, L.B. Crowder, and K.D. Hyrenbach. 2009. OBIS-SEAMAP: The world data center for marine mammal, sea bird, and sea turtle distributions. *Oceanography* 22(2):104-115

NOAA Southeast Fisheries Science Center. 1996. Report of a Cetacean Survey of Oceanic and Selected Continental Shelf Waters of the Northern Gulf of Mexico aboard NOAA Ship Oregon II (Cruise 220)

obs_exp

Observed versus expected diagnostics for fitted DSMs

Description

Given a covariate, calculate the observed and expected counts for each unique value of the covariate. This can be a useful goodness of fit check for DSMs.

Usage

```
obs_exp(model, covar, cut = NULL)
```

Arguments

model	a fitted dsm model object
covar	covariate to aggregate by (character)
cut	vector of cut points to aggregate at. If not supplied, the unique values of covar are used.

Details

One strategy for model checking is to calculate observed and expected counts at different aggregations of the variable. If these match well then the model fit is good.

Value

data.frame with values of observed and expected counts.

Author(s)

David L Miller, on the suggestion of Mark Bravington.

Examples

```
library(Distance)
library(dsm)

# example with the Gulf of Mexico dolphin data
data(mexdolphins)
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
mod1 <- dsm(count~s(x,y), hr.model, segdata, obsdata)
```

plot.dsm

Plot a density surface model.

Description

See [plot.gam](#).

Usage

```
## S3 method for class 'dsm'
plot(x, ...)
```

Arguments

x	a dsm object
...	other arguments passed to plot.gam .

Value

a plot!

Author(s)

David L. Miller

See Also

dsm [plot.gam](#)

plot.dsm.var *Create plots of abundance uncertainty*

Description

Note that the prediction data set must have x and y columns even if these were not used in the model.

Usage

```
## S3 method for class 'dsm.var'
plot(
  x,
  poly = NULL,
  limits = NULL,
  breaks = NULL,
  legend.breaks = NULL,
  xlab = "x",
  ylab = "y",
  observations = TRUE,
  plot = TRUE,
  boxplot.coef = 1.5,
  x.name = "x",
  y.name = "y",
  gg.grad = NULL,
  ...
)
```

Arguments

x	a dsm.var object
poly	a list or data.frame with columns x and y, which gives the coordinates of a polygon to draw. It may also optionally have a column group, if there are many polygons.
limits	limits for the fill colours
breaks	breaks for the colour fill
legend.breaks	breaks as they should be displayed
xlab	label for the x axis
ylab	label for the y axis
observations	should observations be plotted?
plot	actually plot the map, or just return a ggplot2 object?
boxplot.coef	control trimming (as in summary.dsm.var), only has an effect if the bootstrap file was saved.
x.name	name of the variable to plot as the x axis.

y.name	name of the variable to plot as the y axis.
gg.grad	optional <code>ggplot</code> gradient object.
...	any other arguments

Value

a plot

Details

In order to get plotting to work with `dsm.var.prop` and `dsm.var.gam`, one must first format the data correctly since these functions are designed to compute very general summaries. One summary is calculated for each element of the list `pred` supplied to `dsm.var.prop` and `dsm.var.gam`.

For a plot of uncertainty over a prediction grid, `pred` (a `data.frame`), say, we can create the correct format by simply using `pred.new <- split(pred, 1:nrow(pred))`.

Author(s)

David L. Miller

See Also

`dsm.var.prop`, `dsm.var.gam`, `dsm.var.movblk`

plot_pred_by_term *Spatially plot predictions per model term*

Description

Plot the effect of each smooth in the model spatially. For each term in the model, plot its effect in space. Plots are made on the same scale, so that the relative influence of each smooth can be seen.

Usage

```
plot_pred_by_term(dsm.obj, data, location_cov = c("x", "y"))
```

Arguments

dsm.obj	fitted dsm object
data	data to use to plot (often the same as the precision grid), data should also include width and height columns for plotting
location_cov	which covariates to plot by (usually 2, spatial covariates, by default =c("x", "y"))

Value

a `ggplot2` plot

Author(s)

David L Miller (idea taken from inlabru)

Examples

```
## Not run:
library(Distance)
library(dsm)

# load the Gulf of Mexico dolphin data and fit a model
data(mexdolphins)
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)
mod1 <- dsm(count~s(x,y) + s(depth), hr.model, segdata, obsdata)

preddata$width <- preddata$height <- sqrt(preddata$area)

# make the plot
plot_pred_by_term(mod1, preddata, c("x", "y"))

# better plot would be
# library(viridis)
# plot_pred_by_term(mod1, preddata, c("x", "y")) + scale_fill_viridis()

## End(Not run)
```

predict.dsm

Predict from a fitted density surface model

Description

Make predictions of density or abundance outside (or inside) the covered area.

Usage

```
## S3 method for class 'dsm'
predict(object, newdata = NULL, off.set = NULL, type = "response", ...)
```

Arguments

object	a fitted <code>dsm</code> object as produced by <code>dsm()</code> .
newdata	spatially referenced covariates e.g. altitude, depth, distance to shore, etc. Covariates in the <code>data.frame</code> must have names <i>identical</i> to variable names used in fitting the DSM.
off.set	area of each of the cells in the prediction grid. Should be in the same units as the segments/distances given to <code>dsm</code> . Replaces the column in <code>newdata</code> called <code>off.set</code> if it is supplied. Ignored if <code>newdata</code> is not supplied.

type what scale should the results be on. The default is "response", see [predict.gam](#) for an explanation of other options (usually not necessary).

... any other arguments passed to [predict.gam](#).

Details

If newdata is not supplied, predictions are made for the data that built the model. Note that the order of the results will not necessarily be the same as the segdata (segment data) data.frame that was supplied to dsm.

The area.off.set is used if that argument is supplied, otherwise it will look for the areas in the column named off.set in the newdata. Either way the link function (usually log) will be applied to the offsets, so there is no need to log them before passing them to this function.

Value

predicted values on the response scale by default (unless type is specified, in which case see [predict.gam](#)).

Author(s)

David L. Miller

See Also

[predict.gam](#) [dsm.var.gam](#) [dsm.var.prop](#)

predict.fake_ddf

Prediction for fake detection functions

Description

Prediction function for dummy detection functions. The function returns as many 1s as there are rows in newdata. If esw=TRUE then the strip width is returned.

Usage

```
## S3 method for class 'fake_ddf'
predict(
  object,
  newdata = NULL,
  compute = FALSE,
  int.range = NULL,
  esw = FALSE,
  ...
)
```

Arguments

object	model object
newdata	how many 1s should we return?
compute	unused, for compatability with predict from mrds
int.range	unused, for compatability with predict from mrds
esw	should the strip width be returned?
...	for S3 consistency

Author(s)

David L Miller

print.dsm	<i>Print a description of a density surface model object</i>
-----------	--

Description

This method just gives a short description of the fitted model. Use the [summary.dsm](#) method for more information.

Usage

```
## S3 method for class 'dsm'  
print(x, ...)
```

Arguments

x	a dsm object
...	unspecified and unused arguments for S3 consistency

Author(s)

David L. Miller

See Also

[summary.ds](#)

print.dsm.var	<i>Print a description of a density surface model variance object</i>
---------------	---

Description

This method only provides a short summary, use the [summary.dsm.var](#) method for information.

Usage

```
## S3 method for class 'dsm.var'  
print(x, ...)
```

Arguments

x	a dsm variance object
...	unspecified and unused arguments for S3 consistency

Author(s)

David L. Miller

See Also

[summary.dsm.var](#)

print.dsm_varprop	<i>Print a description of a density surface model variance object</i>
-------------------	---

Description

This method only provides a short summary, see [summary.dsm_varprop](#).

Usage

```
## S3 method for class 'dsm_varprop'  
print(x, ...)
```

Arguments

x	a dsm variance object
...	unspecified and unused arguments for S3 consistency

Author(s)

David L. Miller

See Also

[summary.dsm_varprop](#)

`print.summary.dsm.var` *Print summary of density surface model variance object*

Description

See [summary.dsm.var](#) for information.

Usage

```
## S3 method for class 'summary.dsm.var'  
print(x, ...)
```

Arguments

x a summary of dsm variance object
... unspecified and unused arguments for S3 consistency

Author(s)

David L. Miller

See Also

[summary.dsm.var](#)

`print.summary.dsm_varprop`
Print summary of density surface model variance object

Description

See [summary.dsm_varprop](#) for information.

Usage

```
## S3 method for class 'summary.dsm_varprop'  
print(x, ...)
```

Arguments

x a summary of dsm variance object
... unspecified and unused arguments for S3 consistency

Author(s)

David L. Miller

See Also[summary.dsm.var](#)

`rqgam.check`*Randomised quantile residuals check plot for GAMs/DSMs*

Description

Reproduces the "Resids vs. linear pred" plot from [gam.check](#) but using randomised quantile residuals, a la Dunn and Smyth (1996). Checks for heteroskedasticity as usual, looking for "funnel"-type structures in the points, which is much easier with randomised quantile residuals than with deviance residuals, when your model uses a count distribution as the response.

Usage

```
rqgam.check(gam.obj, ...)
```

Arguments

<code>gam.obj</code>	a <code>gam</code> , <code>glm</code> or <code>dsm</code> object.
<code>...</code>	arguments passed on to all plotting functions

Details

Note that this function only works with negative binomial and Tweedie response distributions.

Earlier versions of this function produced the full `gam.check` output, but this was confusing as only one of the plots was really useful. Checks of `k` are not computed, these need to be done using [gam.check](#).

Value

just plots!

Author(s)

Based on code provided by Natalie Kelly, bugs added by Dave Miller

Examples

```
library(Distance)
library(dsm)
library(tweedie)

# load the Gulf of Mexico dolphin data (see ?mexdolphins)
data(mexdolphins)

# fit a detection function and look at the summary
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)

# fit a simple smooth of x and y with a Tweedie response with estimated
# p parameter
mod1 <- dsm(count~s(x, y), hr.model, segdata, obsdata, family=tw())
rqgam.check(mod1)
```

summary.dsm

Summarize a fitted density surface model

Description

Gives a brief summary of a fitted dsm object.

Usage

```
## S3 method for class 'dsm'
summary(object, ...)
```

Arguments

object a dsm object
... other arguments passed to [summary.gam](#).

Value

a summary object

Author(s)

David L. Miller

See Also

dsm

summary.dsm.var

*Summarize the variance of a density surface model***Description**

Gives a brief summary of a fitted dsm variance object.

Usage

```
## S3 method for class 'dsm.var'
summary(
  object,
  alpha = 0.05,
  boxplot.coef = 1.5,
  bootstrap.subregions = NULL,
  ...
)
```

Arguments

object	a dsm.var object
alpha	alpha level for confidence intervals (default 0.05 to give a 95% confidence interval, i.e. we generate $100 * c(\alpha/2, 1-\alpha/2)$ confidence intervals)
boxplot.coef	the value of coef used to calculate the outliers see boxplot .
bootstrap.subregions	list of vectors of logicals or indices for subregions for which variances need to be calculated (only for bootstraps (see dsm.var.prop for how to use subregions with variance propagation).
...	unused arguments for S3 compatibility

Value

a summary object

Author(s)

David L. Miller

See Also

dsm.var.movblk dsm.var.prop

summary.dsm_varprop *Summarize the variance of a density surface model*

Description

Gives a brief summary of a fitted dsm_varprop variance object.

Usage

```
## S3 method for class 'dsm_varprop'
summary(object, alpha = 0.05, ...)
```

Arguments

object	a dsm.var object
alpha	alpha level for confidence intervals (default 0.05 to give a 95% confidence interval)
...	unused arguments for S3 compatibility

Value

a summary object

Author(s)

David L. Miller

See Also

dsm_varprop summary.dsm.var

trim.var *Trimmed variance*

Description

Trim the variance estimates from the bootstrap. This is defined as the percentage defined as amount necessary to bring median and trimmed mean within 8

Usage

```
trim.var(untrimmed.bootstraps, boxplot.coef = 1.5)
```

Arguments

untrimmed.bootstraps (usually the `$study.area.total` element of a returned `dsm` bootstrap object.)
boxplot.coef the value of `coef` used to calculate the outliers see [boxplot](#).

Value

trimmed variance

Author(s)

Louise Burt

vis.concurvity *Visualise concurvity between terms in a GAM*

Description

Plot measures of how much one term in the model could be explained by another. When values are high, one should consider re-running variable selection with one of the offending variables removed to check for stability in term selection.

Usage

```
vis.concurvity(model, type = "estimate")
```

Arguments

model fitted model
type concurvity measure to plot, see [concurvity](#)

Details

These methods are considered somewhat experimental at this time. Consult [concurvity](#) for more information on how concurvity measures are calculated.

Author(s)

David L Miller

Examples

```
## Not run:
library(Distance)
library(dsm)

# load the Gulf of Mexico dolphin data (see ?mexdolphins)
data(mexdolphins)

# fit a detection function and look at the summary
hr.model <- ds(distdata, max(distdata$distance),
              key = "hr", adjustment = NULL)

# fit a simple smooth of x and y to counts
mod1 <- dsm(count~s(x,y)+s(depth), hr.model, segdata, obsdata)

# visualise concurvity using the "estimate" metric
vis.concurvity(mod1)

## End(Not run)
```

Index

- * **datasets**
 - mexdolphins, 21
- * **utility**
 - print.dsm, 27
 - print.dsm.var, 28
 - print.dsm_varprop, 28
 - print.summary.dsm.var, 29
 - print.summary.dsm_varprop, 29

- bam, 5, 6
- block.info.per.su, 3, 18
- boxplot, 32, 34

- check.cols, 3
- concurvity, 34
- cor, 9

- ddf, 5
- distdata (mexdolphins), 21
- ds, 5
- dsm, 4, 4, 7, 8, 10, 12, 13, 15, 25
- dsm-data, 7
- dsm-package, 2
- dsm.cor, 8
- dsm.var.gam, 10, 24, 26
- dsm.var.movblk, 11, 18
- dsm.var.prop, 11, 13, 24, 26, 32
- dsm_varprop, 14, 15
- dummy_ddf, 5, 17

- gam, 5, 6
- gam.check, 30
- gamm, 5, 6
- gamObject, 15, 16
- generate.ds.uncertainty, 17
- generate.mb.sample, 18
- ggplot, 24
- glm, 5, 6

- latlong2km, 19

- make.soapgrid, 19
- matrixnotposdef.handler, 20
- mexdolphins, 21

- nb, 5
- negbin, 5

- obs_exp, 21
- obsdata (mexdolphins), 21

- plot.dsm, 22
- plot.dsm.var, 23
- plot.gam, 22
- plot_pred_by_term, 24
- pred.polys (mexdolphins), 21
- preddata (mexdolphins), 21
- predict.dsm, 16, 25
- predict.fake_ddf, 26
- predict.gam, 26
- print.dsm, 27
- print.dsm.var, 28
- print.dsm_varprop, 28
- print.summary.dsm.var, 29
- print.summary.dsm_varprop, 29

- quasipoisson, 5

- residuals.gam, 9
- rqqam.check, 30

- segdata (mexdolphins), 21
- summary.ds, 27
- summary.dsm, 27, 31
- summary.dsm.var, 28–30, 32
- summary.dsm_varprop, 28, 29, 33
- summary.gam, 31
- survey.area (mexdolphins), 21

- trim.var, 33
- tw, 5
- Tweedie, 5

- vis.concurvity, 34