

Package ‘entropart’

January 22, 2020

Type Package

Title Entropy Partitioning to Measure Diversity

Version 1.6-4

Description Measurement and partitioning of diversity, based on Tsallis entropy, following Marcon and Hérault (2015) <doi:10.18637/jss.v067.i08>. 'entropart' provides functions to calculate alpha, beta and gamma diversity of communities, including phylogenetic and functional diversity. Estimation-bias corrections are available.

URL <https://github.com/EricMarcon/entropart>

BugReports <https://github.com/EricMarcon/entropart/issues>

License GNU General Public License

Depends ggplot2

Imports ade4, ape, EntropyEstimation, ggpubr, graphics, grDevices, parallel, reshape2, SPECIES, stats, utils, vegan

Suggests testthat, knitr, pkgdown

LazyData true

VignetteBuilder knitr

SystemRequirements pandoc

Encoding UTF-8

RoxygenNote 6.1.1

NeedsCompilation no

Author Eric Marcon [aut, cre] (<<https://orcid.org/0000-0002-5249-321X>>),
Bruno Hérault [aut] (<<https://orcid.org/0000-0002-6950-7286>>)

Maintainer Eric Marcon <eric.marcon@ecofog.gf>

Repository CRAN

Date/Publication 2020-01-22 15:40:02 UTC

R topics documented:

entropart-package	3
AbdFreqCount	4
Accumulation	6
AllenH	9
AlphaDiversity	10
AlphaEntropy	12
BetaDiversity	13
BetaEntropy	15
ChaoPD	16
CommunityProfile	18
Coverage	20
Diversity	22
DivEst	24
DivPart	26
DivProfile	29
Dqz	32
EightSpAbundance	34
EightSpTree	34
Enq	35
EntropyCI	36
expq	37
GammaDiversity	38
GammaEntropy	40
GenSimpson	41
Hqz	43
HqzBeta	46
Hurlbert	48
KLq	50
lnq	51
MC Utilities	52
MCdiversity	53
MCentropy	55
MetaCommunity	56
Optimal.Similarity	58
Paracou618.dist	59
Paracou618.Functional	60
Paracou618.MC	61
Paracou618.Taxonomy	61
PDFD	62
PhyloApply	63
PhyloBetaEntropy	65
PhyloDiversity	67
PhyloEntropy	70
PhyloValue	73
PPtree	74
RAC	75

Rao	77
rCommunity	78
Richness	81
Shannon	83
ShannonBeta	86
Simpson	88
SimpsonBeta	90
SimTest	93
SpeciesDistribution	94
Tsallis	98
TsallisBeta	101

Index 104

entropart-package *Entropy Partitioning to Measure Diversity*

Description

Functions to calculate alpha, beta and gamma diversity of communities, including phylogenetic and functional diversity.

Estimation-bias corrections are available.

Details

In the entropart package, individuals of different "species" are counted in several "communities" which may (or not) be aggregated to define a "metacommunity". In the metacommunity, the probability to find a species in the weighted average of probabilities in communities. This is a naming convention, which may correspond to plots in a forest inventory or any data organized the same way.

Basic functions allow computing diversity of a community. Data is simply a vector of probabilities (summing up to 1) or of abundances (integer values that are numbers of individuals). Calculate entropy with functions such as [Tsallis](#), [Shannon](#), [Simpson](#), [Hurlbert](#) or [GenSimpson](#) and explicit diversity (i.e. effective number of species) with [Diversity](#) and others. By default, the best available estimator of diversity will be used, according to the data.

Communities can be simulated by [rCommunity](#), explicitly declared as a species distribution ([as.AbdVector](#) or [as.ProbaVector](#)), and plotted.

Phylogenetic entropy and diversity can be calculated if a phylogenetic (or functional), ultrametric tree is provided. See [PhyloEntropy](#), [Rao](#) for examples of entropy and [PhyloDiversity](#) to calculate phylodiversity, with the state-of-the-art estimation-bias correction. Similarity-based diversity is calculated with [Dqz](#), based on a similarity matrix.

The simplest way to import data is to organize it into two text files. The first file should contain abundance data: the first column named Species for species names, and a column for each community.

The second file should contain the community weights in two columns. The first one, named Communities should contain their names and the second one, named Weights, their weights.

Files can be read and data imported by code such as:

```
Abundances <- read.csv(file="Abundances.csv", row.names = 1)
Weights <- read.csv(file="Weights.csv")
MC <- MetaCommunity(Abundances, Weights)
```

The last line of the code calls the `MetaCommunity` function to create an object that will be used by all metacommunity functions, such as `DivPart` (to partition diversity), `DivEst` (to partition diversity and calculate confidence interval of its estimation) or `DivProfile` (to compute diversity profiles).

A full documentation is available in the vignette. Type: `vignette("entropart")`. A quick introduction is in `vignette("introduction", "entropart")`.

Author(s)

Eric Marcon, Bruno Herault

References

- Grabchak, M., Marcon, E., Lang, G., and Zhang, Z. (2017). The Generalized Simpson's Entropy is a Measure of Biodiversity. *Plos One*, 12(3): e0173305.
- Marcon, E. (2015) Practical Estimation of Diversity from Abundance Data. *HAL* 01212435: 1-27.
- Marcon, E. and Herault, B. (2015). entropart: An R Package to Measure and Partition Diversity. *Journal of Statistical Software*, 67(8): 1-26.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

AbdFreqCount

Abundance Frequency Count of a Community

Description

Counts the number of species observed the same number of times.

Usage

```
AbdFreqCount(Ns, Level = NULL, PCorrection="Chao2015", Unveiling="geom",
             RCorrection="Rarefy", CheckArguments = TRUE)
```

Arguments

Ns	A numeric vector containing species abundances.
Level	The level of interpolation or extrapolation. It may be an arbitrary sample size (an integer) or a sample coverage (a number between 0 and 1).
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in as.ProbaVector : "Chao2015" is the default value. Used only for extrapolation.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in as.ProbaVector : "geom" (geometric: the unobserved species distribution is geometric) is the default value. Used only for extrapolation.
RCorrection	A string containing a correction recognized by Richness to evaluate the total number of species in as.ProbaVector . "Rarefy" is the default value to estimate the number of species such that the richness of the asymptotic distribution rarefied to the observed sample size equals the observed number of species in the data. Used only for extrapolation.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The Abundance Frequency Count (Chao *et al.*, 2015) is the number of species observed each number of times.

It is a way to summarize the species distribution.

It can be estimated at a specified level of interpolation or extrapolation. Extrapolation relies on the estimation of the estimation of the asymptotic distribution of the community by [as.ProbaVector](#) and eq. (5) of Chao *et al.* (2014).

Value

A two-column matrix. The first column contains the number of observations, the second one the number of species observed this number of times.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.
- Chao, A., Hsieh, T. C., Chazdon, R. L., Colwell, R. K., Gotelli, N. J. (2015) Unveiling the Species-Rank Abundance Distribution by Generalizing Good-Turing Sample Coverage Theory. *Ecology* 96(5): 1189-1201.

See Also

[PhyloEntropy](#), [ChaoPD](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ns is the vector of abundances of the first plot
Ns <- Paracou618.MC$Nsi[, 1]

# Return the abundance frequency count
(AbdFreqCount(Ns) -> afc)
plot(afc, xlab="Number of observations", ylab="Number of species")
lines(afc)
```

Accumulation

Diversity accumulation.

Description

Diversity and Entropy Accumulation Curves represent the accumulation of entropy with respect to the sample size.

Usage

```
as.AccumCurve(x, y, low = NULL, high = NULL)
is.AccumCurve(x)
EntAC(Ns, q = 0, n.seq = 1:sum(Ns), PCorrection="Chao2015", Unveiling="geom",
      RCorrection="Rarefy", NumberOfSimulations = 0, Alpha = 0.05,
      ShowProgressBar = TRUE, CheckArguments = TRUE)
DivAC(Ns, q = 0, n.seq = 1:sum(Ns), PCorrection="Chao2015", Unveiling="geom",
      RCorrection="Rarefy", NumberOfSimulations = 0, Alpha = 0.05,
      ShowProgressBar = TRUE, CheckArguments = TRUE)
## S3 method for class 'AccumCurve'
plot(x, ..., main = NULL,
      xlab = "Sample Size", ylab = NULL, ylim = NULL,
      LineWidth = 2, ShadeColor = "grey75", BorderColor = "red")
## S3 method for class 'AccumCurve'
autoplot(object, ..., main = NULL,
          xlab = "Sample Size", ylab = NULL,
          ShadeColor = "grey75", alpha = 0.3, BorderColor = "red")
```

Arguments

x An object. A numeric vector in `as.AccumCurve`.

object An object.

y	A numeric vector.
low	A numeric vector.
high	A numeric vector.
Ns	A numeric vector containing species abundances.
q	A number: the order of diversity. Default is 1.
n.seq	A sequence of numbers. Accumulation will be calculated at each value.
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in as.ProbaVector : "Chao2015" is the default value. Used only for extrapolation and q different from 0, 1, 2.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in as.ProbaVector : "geom" (geometric: the unobserved species distribution is geometric) is the default value. Used only for extrapolation and q different from 0, 1, 2.
RCorrection	A string containing a correction recognized by Richness to evaluate the total number of species in as.ProbaVector . "Rarefy" is the default value to estimate the number of species such that the entropy of the asymptotic distribution rarefied to the observed sample size equals the observed entropy of the data. Used only for extrapolation and q different from 0, 1, 2. If q is 0 (extrapolation of richness), "Rarefy" is taken for "Jackknife".
NumberOfSimulations	The number of Simulations to build confidence intervals.
Alpha	The risk level, 5% by default.
...	Additional arguments to be passed to plot . Unused elsewhere.
main	The main title of the plot. if NULL (by default), there is no title.
xlab	The X axis label, "Rank" by default.
ylab	The Y axis label. if NULL (by default), "Probability" or "Abundance" is chosen according to the object class.
ylim	The interval of y values plotted.
LineWidth	The width of the line that represents the actual profile.
ShadeColor	The color of the shaded confidence envelope.
BorderColor	The color of the bounds of the confidence envelope.
alpha	Opacity of the confidence envelope, between 0 and 1.
ShowProgressBar	If TRUE (default), a progress bar is shown.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

DivAC or EntAC estimate the diversity or entropy accumulation curve of a distribution. See [Tsallis](#) for details about the computation of entropy at each level of interpolation and extrapolation. In accumulation curves, extrapolation is done by estimating the asymptotic distribution of the community

and estimating entropy at different levels by interpolation. The asymptotic richness is adjusted so that the extrapolated part of the accumulation joins the observed value at the sample size.

AccumCurve objects include EntAC and DivAC objects for entropy and diversity accumulation. They generalize the classical Species Accumulation Curves (SAC) which are diversity accumulation of order $q=0$.

as.AccumCurve transforms two vectors (where x is the sample size and y the accumulation) into an object of class AccumCurve.

AccumCurve objects can be plotted with either plot or autoplot methods.

Value

A DivAC or an EntAC object. Both are AccumCurve objects, which are a list:

x	The sample size.
y	The value of entropy or diversity.
low	The lower bound of the confidence envelope of the estimation.
high	The upper bound of the confidence envelope of the estimation.

Attributes "Size" and "Value" contain the actual sample size and the corresponding diversity or entropy.

AccumCurve objects can be summarized and plotted.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>, Bruno Hérault <Bruno.Hérault@ecofog.gf>

References

Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.

See Also

[Tsallis, Diversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Accumulation curve of Simpson's diversity
autoplot(DivAC(Ns, q=2))
```


AllenH

*Phylogenetic Entropy of a Community***Description**

Calculates the phylogenetic diversity of order q of a probability vector.

Usage

AllenH(Ps, q = 1, PhyloTree, Normalize = TRUE, Prune = FALSE, CheckArguments = TRUE)

Arguments

Ps	A probability vector, summing to 1.
q	A number: the order of entropy. Default is 1.
PhyloTree	An object of class hclust , phylo , phylog or PPtree . The tree is not necessarily ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree. If FALSE, it is proportional to the height of the tree.
Prune	What to do when some species are in the tree but not in Ps? If TRUE, the tree is pruned to keep species of Ps only. The height of the tree may be changed if a pruned branch is related to the root. If FALSE (default), species with probability 0 are added in Ps.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The phylogenetic entropy is calculated following Allen *et al.* (2009) for order $q = 1$ and Leinster and Cobold (2011) for other orders. The result is identical to the total entropy calculated by [PhyloEntropy](#) but it is much faster. A single value is returned instead of a [PhyloEntropy](#) object, and no bias correction is available.

The `Normalize` argument allows normalizing entropy by the height of the tree, similarly to [ChaoPD](#).

Diversity can be calculated for non ultrametric trees following Leinster and Cobold (2011) even though the meaning of the result is not so clear.

Value

A named number equal the entropy of the community. The name is "None" to recall that no bias correction is available.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Allen, B., Kon, M. and Bar-Yam, Y. (2009). A New Phylogenetic Diversity Measure Generalizing the Shannon Index and Its Application to Phyllostomid Bats. *American Naturalist* 174(2): 236-243.
- Leinster, T. and Cobbold, C. (2011). Measuring diversity: the importance of species similarity. *Ecology* 93(3): 477-489.

See Also

[PhyloEntropy](#), [ChaoPD](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)

# Calculate the phylogenetic Shannon diversity of the plot
AllenH(Ps, 1, Paracou618.Taxonomy, Normalize=TRUE)

# Calculate it using PhyloEntropy: more powerful but much slower is the tree has many periods
PhyloEntropy(Ps, 1, Paracou618.Taxonomy, Normalize=TRUE) -> phyE
summary(phyE)
```

AlphaDiversity	<i>Reduced-bias alpha diversity of a metacommunity</i>
----------------	--

Description

Calculates the reduced-bias total alpha diversity of order q of communities.

Usage

```
AlphaDiversity(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
  Z = NULL, CheckArguments = TRUE)
```

Arguments

- | | |
|------------|--|
| MC | A MetaCommunity object. |
| q | A number: the order of diversity. Default is 1 for Shannon diversity. |
| Correction | A string containing one of the possible corrections accepted by AlphaEntropy or "None" or "Best", the default value. |
| Tree | An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric. |
| Normalize | If TRUE (default), diversity is not affected by the height of the tree.
If FALSE, diversity is proportional to the height of the tree. |

- Z** A relatedness matrix, *i.e.* a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, *i.e.* the diagonal terms equal 1 and other terms are between 0 and 1.
- CheckArguments** Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Entropy is calculated by [AlphaEntropy](#) and transformed into diversity.

Value

An [MCdiversity](#) object containing diversity values of each community and of the metacommunity.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[AlphaEntropy](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Calculate Simpson alpha diversity
summary(AlphaDiversity(Paracou618.MC, 2))
# Compare without correction
summary(AlphaDiversity(Paracou618.MC, 2, Correction = "None"))
# Estimate phylogenetic Simpson alpha diversity
summary(AlphaDiversity(Paracou618.MC, 2, Tree = Paracou618.Taxonomy) -> e)
plot(e)
```

AlphaEntropy	<i>Reduced-bias alpha entropy of a metacommunity</i>
--------------	--

Description

Calculates the reduced-bias total alpha entropy of order q of communities.

Usage

```
AlphaEntropy(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
             Z = NULL, CheckArguments = TRUE)
```

Arguments

MC	A MetaCommunity object.
q	A number: the order of diversity. Default is 1 for Shannon entropy.
Correction	A string containing one of the possible corrections accepted by the bias-corrected entropy function (see details) or "None" or "Best", the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the entropy returned by the function is normalized by the height of the tree (it is the weighted average value of the entropy in each slice). If FALSE, it is the unnormalized weighted sum of the results.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

If Tree is not NULL, then phylogenetic entropy is calculated by [bcPhyloEntropy](#); else, if Z is not NULL, then similarity-based entropy is calculated by [bcHqz](#); else, neutral entropy is calculated by [bcTsallis](#).

The alpha entropy of each community is calculated and summed according to community weights.

The possible corrections are detailed in [Tsallis](#).

Value

An [MEntropy](#) object containing entropy values of each community and of the metacommunity.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylogenetic Diversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[bcTsallis](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Calculate Simpson alpha entropy
summary(AlphaEntropy(Paracou618.MC, 2))
# Compare without correction
summary(AlphaEntropy(Paracou618.MC, 2, Correction = "None"))
# Estimate phylogenetic Simpson alpha entropy
summary(AlphaEntropy(Paracou618.MC, 2, Tree = Paracou618.Taxonomy) -> e)
plot(e)
```

BetaDiversity	<i>Reduced-bias beta diversity of a metacommunity</i>
---------------	---

Description

Calculates the reduced-bias beta diversity of order q between communities.

Usage

```
BetaDiversity(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
  Z = NULL, CheckArguments = TRUE)
```

Arguments

- | | |
|------------|--|
| MC | A MetaCommunity object. |
| q | A number: the order of diversity. Default is 1 for Shannon diversity. |
| Correction | A string containing one of the possible corrections accepted by bcTsallisBeta or "None" or "Best", the default value. |
| Tree | An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric. |
| Normalize | If TRUE (default), diversity is not affected by the height of the tree.
If FALSE, diversity is proportional to the height of the tree. |

- Z** A relatedness matrix, *i.e.* a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, *i.e.* the diagonal terms equal 1 and other terms are between 0 and 1.
- CheckArguments** Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Entropy is calculated by [BetaEntropy](#) and transformed into diversity.

Diversity values of communities are not defined: community entropies are averaged to obtain the metacommunity entropy which is transformed into diversity (Marcon et al., 2014).

Value

An [MCdiversity](#) object containing diversity value of the metacommunity.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[BetaEntropy](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Estimate Shannon beta diversity
summary(BetaDiversity(Paracou618.MC, 1))
# Compare without correction
summary(BetaDiversity(Paracou618.MC, 1, Correction = "None"))
# Estimate phylogenetic Shannon beta diversity
summary(BetaDiversity(Paracou618.MC, 1, Tree = Paracou618.Taxonomy) -> e)
```

BetaEntropy	<i>Reduced-bias beta entropy of a metacommunity</i>
-------------	---

Description

Calculates the reduced-bias beta entropy of order q between communities.

Usage

```
BetaEntropy(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
            Z = NULL, CheckArguments = TRUE)
```

Arguments

MC	A MetaCommunity object.
q	A number: the order of diversity. Default is 1 for Shannon entropy.
Correction	A string containing one of the possible corrections accepted by the bias-corrected entropy function (see details) or "None" or "Best", the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the entropy returned by the function is normalized by the height of the tree (it is the weighted average value of the entropy in each slice). If FALSE, it is the unnormalized weighted sum of the results.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

If Tree is not NULL, then phylogenetic entropy is calculated by [bcPhyloBetaEntropy](#); else, if Z is not NULL, then similarity-based entropy is calculated by [bcHqzBeta](#); else, neutral entropy is calculated by [bcTsallisBeta](#).

The reduced-bias beta entropy of each community is calculated and summed according to community weights.

Note that beta entropy is related to alpha entropy (if q is not 1) and cannot be compared across communities (Jost, 2007). Do rather calculate the [BetaDiversity](#) of the metacommunity.

Value

An [MEntropy](#) object containing entropy values of each community and of the metacommunity.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylogenetic Diversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[bcTsallisBeta](#), [BetaDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Estimate Shannon beta entropy
summary(BetaEntropy(Paracou618.MC, 1))
# Compare without correction
summary(BetaEntropy(Paracou618.MC, 1, Correction = "None"))
# Estimate phylogenetic Shannon beta entropy
summary(BetaEntropy(Paracou618.MC, 1, Tree = Paracou618.Taxonomy) -> e)
plot(e)
```

ChaoPD

Phylogenetic Diversity of a Community

Description

Calculates the phylogenetic diversity of order q of a probability vector.

Usage

```
ChaoPD(Ps, q = 1, PhyloTree, Normalize = TRUE, Prune = FALSE, CheckArguments = TRUE)
```

Arguments

Ps	A probability vector, summing to 1.
q	A number: the order of diversity. Default is 1.
PhyloTree	An object of class hclust , phylo , phylog or PPtree . The tree is not necessarily ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree. If FALSE, it is proportional to the height of the tree.
Prune	What to do when some species are in the tree but not in Ps? If TRUE, the tree is pruned to keep species of Ps only. The height of the tree may be changed if a pruned branch is related to the root. If FALSE (default), species with probability 0 are added in Ps.

CheckArguments Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The phylogenetic diversity is calculated following Chao *et al.* (2010). The result is identical to the total diversity calculated by [PhyloDiversity](#) but it is much faster. A single value is returned instead of a [PhyloDiversity](#) object, and no bias correction is available.

The **Normalize** arguments allows calculating either ${}^q\bar{D}(T)$ (if TRUE) or ${}^qPD(T)$ if FALSE.

Diversity can be calculated for non ultrametric trees following Chao *et al.* (2010) even though the meaning of the result is not so clear (Leinster and Cobold, 2011).

Value

A named number equal the diversity of the community. The name is "None" to recall that no bias correction is available.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Chao, A., Chiu, C.-H. and Jost, L. (2010). Phylogenetic diversity measures based on Hill numbers. *Philosophical Transactions of the Royal Society B* 365(1558): 3599-609.

Leinster, T. and Cobbold, C. (2011). Measuring diversity: the importance of species similarity. *Ecology* 93(3): 477-489.

See Also

[PhyloDiversity](#), [AllenH](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- Paracou618.MC$Ps

# Calculate the phylogenetic Simpson diversity of the plot
(ChaoPD(Paracou618.MC$Ps, 2, Paracou618.Taxonomy, Normalize=TRUE))

# Calculate it using PhyloDiversity
# (more powerful but much slower if the tree has many periods)
PhyloDiversity(Paracou618.MC$Ps, 2, Paracou618.Taxonomy, Normalize=TRUE) -> phyD
summary(phyD)
```

CommunityProfile *Diversity or Entropy Profile of a community*

Description

Calculates the diversity or entropy profile of a community, applying a community function to a vector of orders.

Usage

```
CommunityProfile(FUN, NorP, q.seq = seq(0, 2, 0.1),
  NumberOfSimulations = 0, Alpha = 0.05, BootstrapMethod = "Chao2015",
  size = 1, ..., ShowProgressBar = TRUE, CheckArguments = TRUE)
as.CommunityProfile(x, y, low = NULL, high = NULL)
is.CommunityProfile(x)
## S3 method for class 'CommunityProfile'
plot(x, ..., main = NULL,
  xlab = "Order of Diversity", ylab = "Diversity", ylim = NULL,
  LineWidth = 2, ShadeColor = "grey75", BorderColor = "red")
## S3 method for class 'CommunityProfile'
autoplot(object, ..., main = NULL,
  xlab = "Order of Diversity", ylab = "Diversity",
  ShadeColor = "grey75", alpha = 0.3, BorderColor = "red")
CEnvelope(Profile, LineWidth = 2, ShadeColor = "grey75", BorderColor = "red", ...)
```

Arguments

FUN	The function to be applied to each value of <i>q.seq</i> . Any function accepting a numeric vector (or a two-column matrix) and a number as first two arguments and an argument named <i>CheckArguments</i> is acceptable (other arguments of the functions are passed by ...). See <i>*Details*</i> for useful entropy and diversity functions and <i>*Examples*</i> for an ad-hoc one.
NorP	A numeric vector. Contains either abundances or probabilities.
q.seq	A numeric vector: the sequence of diversity orders to address. Default is from 0 to 2.
NumberOfSimulations	The number of simulations to run, 0 by default.
Alpha	The risk level, 5% by default.
BootstrapMethod	The method used to obtain the probabilities to generate bootstrapped communities from observed abundances. See rCommunity .
size	The size of simulated communities used to compute the bootstrap confidence envelope. 1 (default) means that the actual size must be used.
object	An object.

x	An object to be tested or plotted or the vector of orders of community profiles in <code>as.CommunityProfile</code> .
y	Entropy or diversity values of each order, corresponding to x values.
low	Entropy or diversity lower bound of the confidence envelope, corresponding to x values.
high	Entropy or diversity higher bound of the confidence envelope, corresponding to x values.
Profile	An <code>CommunityProfile</code> to be plotted.
...	Additional arguments to be passed to FUN in <code>CommunityProfile</code> , to plot in <code>plot.CommunityProfile</code> or to lines in <code>CEnvelope</code> .
main	The main title of the plot.
xlab	The x axis label of the plots.
ylab	The y axis label of the plot.
ylim	The interval of y values plotted.
LineWidth	The width of the line that represents the actual profile.
ShadeColor	The color of the shaded confidence envelope.
BorderColor	The color of the bounds of the confidence envelope.
alpha	Opacity of the confidence envelope, between 0 and 1.
ShowProgressBar	If TRUE (default), a progress bar is shown.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The function `CommunityProfile` is used to calculate diversity or entropy profiles based on community functions such as `Tsallis` or `ChaoPD`. The first two arguments of the function must be a probability or abundance vector and a number (q). Additional arguments cannot be checked. Unexpected results may be returned if FUN is not used properly.

If `NumberOfSimulations` is greater than 0, a bootstrap confidence interval is produced by simulating communities with `rCommunity` and calculating their profiles. The size of those communities may be that of the actual community or specified by `size`.

`CommunityProfile` objects can be plotted. They can also be added to the current plot by `CEnvelope`.

Value

A `CommunityProfile`, which is a list:

x	The order q values
y	The entropy or diversity values returned by FUN
low	The lower bound of the confidence interval
high	The upper bound of the confidence interval

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>, Bruno Hérault <Bruno.Hérault@ecofog.gf>

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Plot diversity estimated without bias correction
plot(CommunityProfile(Diversity, Paracou618.MC$Ps, seq(0, 2, 0.2)),
     lty=3, ylim=c(50, 350))
# Estimate diversity, with a confidence envelope
# (only 10 simulations to save time, should be 1000)
Profile <- CommunityProfile(Diversity, as.AbdVector(Paracou618.MC$Ns),
                           seq(0, 2, 0.2), Correction="UnveilJ", NumberOfSimulations=10)
# Complete the plot, and add the legend
CEnvelope(Profile, main="Paracou Plots Diversity")
legend("topright", c("Bias Corrected", "Biased"), lty=c(1,3), inset=0.01)

# Advanced use with beta-diversity functions :
# Profile of the beta entropy of the first community of Paracou618.
# Observed and expected probabilities are bound into a 2-column matrix
# An intermediate function is necessary to separate them before calling TsallisBeta
# The CheckArguments is mandatory but does not need to be set: CommunityProfile() sets it to FALSE
CommunityProfile(function(PandPexp, q, CheckArguments)
  {TsallisBeta(PandPexp[, 1], PandPexp[, 2], q)},
  NorP=cbind(Paracou618.MC$Psi[, 1], Paracou618.MC$Ps), q.seq=seq(0, 2, 0.2))
```

Coverage

Sample coverage of a community

Description

"Coverage" calculates an estimator of the sample coverage of a community described by its abundance vector. "Coverage2Size" estimates the sample size corresponding to the chosen sample coverage.

Usage

```
Coverage(Ns, Estimator = "Best", Level = NULL, CheckArguments = TRUE)
Coverage2Size(Ns, SampleCoverage, CheckArguments = TRUE)
```

Arguments

Ns	A numeric vector containing species abundances.
Estimator	A string containing one of the possible estimators: "ZhangHuang", "Chao", "Turing", "Good". "Best" is for "Chao".
Level	The level of interpolation or extrapolation, i.e. an abundance.
SampleCoverage	The target sample coverage.

CheckArguments Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The sample coverage C of a community is the total probability of occurrence of the species observed in the sample. $1 - C$ is the probability for an individual of the whole community to belong to a species that has not been sampled.

The historical estimator is due to Turing (Good, 1953). It only relies on singletons (species observed only once). Chao's (Chao and Shen, 2010) estimator uses doubletons too and Zhang-Huang's (Chao et al., 1988; Zhang and Huang, 2007) uses the whole distribution.

If Level is not null, the sample coverage is interpolated or extrapolated. Interpolation by the Good estimator relies on the equality between sampling deficit and the generalized Simpson entropy (Good, 1953). The Chao (2014) estimator allows extrapolation, reliable up a level equal to the double size of the sample.

Value

"Coverage" returns a named number equal to the calculated sample coverage. The name is that of the estimator used. "Coverage2Size" returns a number equal to the sample size corresponding to the chosen sample coverage.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Chao, A., Lee, S.-M. and Chen, T.-C. (1988). A generalized Good's nonparametric coverage estimator. *Chinese Journal of Mathematics* 16: 189-199.
- Chao, A. and Shen, T.-J. (2010). *Program SPADE: Species Prediction And Diversity Estimation. Program and user's guide*. CARE, Hsin-Chu, Taiwan.
- Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.
- Good, I. J. (1953). On the Population Frequency of Species and the Estimation of Population Parameters. *Biometrika* 40(3/4): 237-264.
- Zhang, Z. and Huang, H. (2007). Turing's formula revisited. *Journal of Quantitative Linguistics* 14(2-3): 222-241.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the vector of abundances of the metacommunity
Ns <- Paracou618.MC$Ns
# Calculate the sample coverage of the metacommunity
Coverage(Ns) # Stored in Paracou618.SampleCoverage
```

Diversity

*Hill number of a community***Description**

Calculates the HCDT (generalized) diversity of order q of a probability vector.

Usage

```
Diversity(NorP, q = 1, ...)
bcDiversity(Ns, q = 1, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Diversity(NorP, q = 1, ...,
  CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Diversity(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Diversity(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Diversity(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of diversity. Default is 1.
Correction	A string containing one of the possible asymptotic estimators: "None" (no correction), "ChaoShen", "GenCov", "Grassberger", "Holste", "Bonachela", "ZhangGrabchak", or "ChaoJost", "Marcon", "UnveilC", "UnveiliC", "UnveilJ" or "Best", the default value. Currently, "Best" is "UnveilJ".
Level	The level of interpolation or extrapolation. It may be an a chosen sample size (an integer) or a sample coverage (a number between 0 and 1).
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in as.ProbaVector : "Chao2015" is the default value. Used only for extrapolation.

Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in <code>as.ProbaVector</code> : "geom" (the unobserved species distribution is geometric) is the default value. Used only for extrapolation.
RCorrection	A string containing a correction recognized by <code>Richness</code> to evaluate the total number of species in <code>as.ProbaVector</code> . "Rarefy" is the default value to estimate the number of species such that the diversity of the asymptotic distribution rarefied to the observed sample size equals the observed diversity of the data. Used only for extrapolation.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

`Diversity` calls `Tsallis` to calculate entropy and transforms it into diversity by calculating its deformed exponential.

Bias correction requires the number of individuals to estimate sample `Coverage`. See `Tsallis` for details.

The functions are designed to be used as simply as possible. `Diversity` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcDiversity` is called.

`Diversity` can be estimated at a specified level of interpolation or extrapolation, either a chosen sample size or sample coverage (Chao et al., 2014), rather than its asymptotic value. See `Tsallis` for details.

Value

A named number equal to the calculated diversity. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.

Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

See Also

`Tsallis`, `expq`, `AbdVector`, `ProbaVector`

Examples

```

# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)
# Calculate diversity of order 1, i.e. Shannon's diversity
Diversity(Ps, q=1)
# Calculate it with estimation bias correction (asymptotic estimator)
Diversity(Ns, q=1)
# Extrapolate it up to 99.9% sample coverage (close to the asymptotic estimator)
Diversity(Ns, q=1, Level=0.999)
# Rarefy it to half the sample size
Diversity(Ns, q=1, Level=sum(Ns)/2)

```

DivEst

Diversity Estimation of a metacommunity

Description

Estimates diversity of a metacommunity.

Usage

```

DivEst(q = 0, MC, Biased = TRUE, Correction = "Best", Tree = NULL,
       Normalize = TRUE, Z = NULL, Simulations = 100,
       ShowProgressBar = TRUE, CheckArguments = TRUE)
is.DivEst(x)
## S3 method for class 'DivEst'
plot(x, ..., main = NULL, Which = "All")
## S3 method for class 'DivEst'
autoplot(object, ..., main = NULL, Which = "All",
         labels = NULL, font.label = list(size=11, face="plain"))
## S3 method for class 'DivEst'
summary(object, ...)

```

Arguments

q	A number: the order of diversity.
MC	A MetaCommunity object.
Biased	Logical; if FALSE, a bias correction is applied.
Correction	A string containing one of the possible corrections. The correction must be accepted by DivPart . "Best" is the default value.

Tree	An object of class <code>hclust</code> , <code>phylo</code> , <code>phylog</code> or <code>PPtree</code> . The tree must be ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree.. If FALSE, diversity is proportional to the height of the tree.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
Simulations	The number of simulations to build confidence intervals.
ShowProgressBar	If TRUE (default), a progress bar is shown.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.
x	An object to be tested or plotted.
main	The title of the plot.
Which	May be "Alpha", "Beta" or "Gamma" to respectively plot the metacommunity's alpha, beta or gamma diversity. If "All" (default), all three plots are shown.
labels	Vector of labels to be added to multiple plots. "auto" is the same as <code>c("a", "b", "c", "d")</code> .
font.label	A list of arguments to customize labels. See <code>ggarrange</code> .
object	A <code>MCdiversity</code> object to be summarized or plotted.
...	Additional arguments to be passed to the generic methods.

Details

Divest estimates the diversity of the metacommunity and partitions it into alpha and beta components.

If Tree is provided, the phylogenetic diversity is calculated else if Z is not NULL, then similarity-based entropy is calculated.

Bootstrap confidence intervals are calculated by drawing simulated communities from a multinomial distribution following the observed frequencies (Marcon et al, 2012; 2014).

Value

A Divest object which is a `DivPart` object with an additional item in its list:

`SimulatedDiversity`

A matrix containing the simulated values of alpha, beta and gamma diversity.

Divest objects can be summarized and plotted.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf> and Bruno Hérault <Bruno.Hérault@ecofog.gf>

References

- Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

See Also

[DivPart](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Estimate Shannon diversity.
Estimation <- DivEst(q = 1, Paracou618.MC, Biased = FALSE, Correction = "UnveilJ",
Simulations = 20)
plot(Estimation)
summary(Estimation)
```

DivPart

Diversity Partition of a metacommunity

Description

Partitions the diversity of a metacommunity into alpha and beta components.

Usage

```
DivPart(q = 1, MC, Biased = TRUE, Correction = "Best", Tree = NULL,
        Normalize = TRUE, Z = NULL, CheckArguments = TRUE)
is.DivPart(x)
## S3 method for class 'DivPart'
plot(x, ...)
## S3 method for class 'DivPart'
autoplot(object, ...)
## S3 method for class 'DivPart'
summary(object, ...)
```

Arguments

- q** A number: the order of diversity. Default is 1.
- MC** A [MetaCommunity](#) object.
- Biased** Logical; if FALSE, a bias correction is applied.

Correction	A string containing one of the possible corrections. The correction must be accepted by AlphaEntropy , BetaEntropy and GammaEntropy . "Best" is the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree. If FALSE, diversity is proportional to the height of the tree.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.
x	An object to be tested or plotted.
object	A MCdiversity object to be summarized or plotted.
...	Additional arguments to be passed to the generic methods.

Details

DivPart partitions the diversity of the metacommunity into alpha and beta components. It supports estimation-bias correction.

If Tree is provided, the phylogenetic diversity is calculated else if Z is not NULL, then similarity-based entropy is calculated.

Beta diversity/entropy is calculated from Gamma and Alpha when bias correction is required, so community values are not available.

Value

A DivPart object. It is a list:

MetaCommunity	The name of the MetaCommunity object containing inventory data.
Order	The value of q.
Biased	Logical. If FALSE, bias corrected values of diversity have been computed.
Correction	The estimation bias correction used to calculate diversity.
Method	The method used to calculate entropy ("HCDT", "Similarity-based").
Tree	The phylogenetic or functional tree used to calculate phylodiversity.
Normalized	Logical. Indicates whether phylodiversity is normalized or proportional to the height of the tree.
Z	The matrix used to calculate similarity-based entropy.
TotalAlphaDiversity	The alpha diversity of communities.
TotalBetaDiversity	The beta diversity of communities.
GammaDiversity	The gamma diversity of the metacommunity.

CommunityAlphaDiversities
 A vector containing the alpha diversity of each community.

TotalAlphaEntropy
 The alpha entropy of communities.

TotalBetaEntropy
 The beta entropy of communities.

GammaEntropy
 The gamma entropy of the metacommunity.

CommunityAlphaEntropies
 A vector containing the alpha entropy of each community.

DivPart objects can be summarized and plotted.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf> and Bruno Herault <Bruno.Herault@ecofog.gf>

References

- Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[DivProfile](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Estimate Shannon diversity.
summary(DivPart(q = 1, Paracou618.MC, Biased = FALSE) -> dp)
plot(dp)
```

DivProfile

*Diversity Profile of a metacommunity***Description**

Calculate the diversity profiles (alpha, beta, gamma) of a metacommunity.

Usage

```
DivProfile(q.seq = seq(0, 2, 0.1), MC, Biased = TRUE, Correction = "Best",
  Tree = NULL, Normalize = TRUE, Z = NULL,
  NumberOfSimulations = 0, Alpha = 0.05,
  ShowProgressBar = TRUE, CheckArguments = TRUE)
is.DivProfile(x)
## S3 method for class 'DivProfile'
plot(x, ..., main = NULL, xlab = "Order of Diversity",
  ylab = NULL, Which = "All",
  LineWidth = 2, ShadeColor = "grey75", BorderColor = "red")
## S3 method for class 'DivProfile'
autoplot(object, ..., main = NULL, xlab = "Order of Diversity",
  ylab = NULL, Which = "All", ShadeColor = "grey75", alpha = 0.3, BorderColor = "red",
  labels = NULL, font.label = list(size=11, face="plain"))
## S3 method for class 'DivProfile'
summary(object, ...)
```

Arguments

q.seq	A numeric vector.
MC	A MetaCommunity object.
Biased	Logical; if FALSE, a bias correction is applied.
Correction	A string containing one of the possible corrections. The correction must be accepted by AlphaEntropy , BetaEntropy and GammaEntropy . "Best" is the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree. If FALSE, diversity is proportional to the height of the tree.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
NumberOfSimulations	The number of simulations to run, 0 by default.
Alpha	The risk level, 5% by default.
ShowProgressBar	If TRUE (default), a progress bar is shown.

CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.
x	An object to be tested or plotted.
main	The main title of the plot. Ignored if Which = "All".
xlab	The x axis label of the plots.
ylab	The y axis label of the plot. Ignored if Which = "All".
Which	May be "Communities", "Alpha", "Beta" or "Gamma" to respectively plot the alpha diversity of communities or the metacommunity's alpha, beta or gamma diversity. If "All" (default), all four plots are shown.
LineWidth	The width of the line that represents the actual profile.
ShadeColor	The color of the shaded confidence envelope.
BorderColor	The color of the bounds of the confidence envelope.
alpha	Opacity of the confidence envelope, between 0 and 1.
labels	Vector of labels to be added to multiple plots. "auto" is the same as c("a", "b", "c", "d").
font.label	A list of arguments to customize labels. See ggarrange .
object	A MCdiversity object to be summarized or plotted.
...	Additional arguments to be passed to the generic methods.

Details

If Tree is provided, the phylogenetic diversity is calculated.

DivPart partitions the diversity of the metacommunity into alpha and beta components. It supports estimation-bias correction.

If Tree is provided, the phylogenetic diversity is calculated else if Z is not NULL, then similarity-based entropy is calculated.

Beta diversity/entropy is calculated from Gamma and Alpha when bias correction is required, so community values are not available.

If NumberOfSimulations is greater than 0, a bootstrap confidence interval is produced by simulating communities from a multinomial distribution following the observed frequencies (Marcon et al, 2012; 2014) and calculating their profiles.

Value

A DivProfile object. It is a list:

MetaCommunity	The name of the MetaCommunity object containing inventory data.
Order	A vector containing the values of q.
Biased	Logical. If FALSE, bias corrected values of diversity have been computed.
Correction	The estimation bias correction used to calculate diversity. Usually a string, but it may be a list if different corrections have been used in the estimation of phylodiversity.
Method	The method used to calculate entropy ("HCDT", "Similarity-based").

Tree	The phylogenetic or functional tree used to calculate phylodiversity.
Normalized	Logical. Indicates whether phylodiversity is normalized or proportional to the height of the tree.
Z	The matrix used to calculate similarity-based entropy.
CommunityAlphaDiversities	A matrix containing the alpha diversity of each community.
TotalAlphaDiversity	A vector containing the alpha diversity of communities for each order.
BetaDiversity	A vector containing the beta diversity of communities for each order.
GammaDiversity	A vector containing the gamma diversity of the metacommunity for each order.
CommunityAlphaEntropies	A matrix containing the alpha entropy of each community.
TotalAlphaEntropy	A vector containing the alpha entropy of communities for each order.
BetaEntropy	A vector containing the beta entropy of communities for each order.
GammaEntropy	A vector containing the gamma entropy of the metacommunity for each order.
Confidence envelopes	Total Alpha, Beta and Gamma Entropy and Diversity may come with a confidence envelope whose value is stored in twelve more vectors named suffixed Low or High, such as GammaEntropyLow

DivProfile objects can be summarized and plotted.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf> and Bruno Herault <Bruno.Herault@ecofog.gf>

References

- Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

See Also

[DivPart](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Estimate diversity.
Profile <- DivProfile(q.seq = seq(0, 2, 0.1), Paracou618.MC, Biased = FALSE)
plot(Profile)
```

```
autoplot(Profile)
summary(Profile)
```

Dqz

Similarity-based diversity of a community

Description

Calculates the diversity of order q of a probability vector according to a similarity matrix.

Usage

```
Dqz(NorP, q = 1, Z = diag(length(NorP)), ...)
bcDqz(Ns, q = 1, Z = diag(length(Ns)), Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Dqz(NorP, q = 1, Z = diag(length(NorP)), ...,
    CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Dqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best", ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Dqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best", ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Dqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best", ...,
    CheckArguments = TRUE, Ps = NULL, Ns = NULL)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of diversity. Default is 1.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1. Default is the identity matrix to calculate neutral diversity.
Correction	A string containing one of the possible corrections: "None" (no correction), "HorvitzThomson", "MarconZhang" or "Best", the default value. The "MarconZhang" correction assumes a similarity matrix.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Diversity is calculated following Leinster and Cobbold (2012): it is the reciprocal of the (generalized) average (of order q) of the community species ordinariness.

A similarity matrix is used (as for [Dqz](#)), not a distance matrix as in Ricotta and Szeidl (2006). See the example.

Bias correction requires the number of individuals. Use `bcHqz` and choose the Correction. Correction techniques are from Marcon *et al.* (2014).

Currently, the "Best" correction is the max value of "HorvitzThomson" and "MarconZhang".

The functions are designed to be used as simply as possible. `Dqz` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcDqz` is called. Explicit calls to `bcDqz` (with bias correction) or to `Dqz.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated diversity. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Leinster, T. and Cobbold, C. (2012). Measuring diversity: the importance of species similarity. *Ecology* 93(3): 477-489.

Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[Hqz](#), [PhyloDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Prepare the similarity matrix
DistanceMatrix <- as.matrix(Paracou618.dist)
# Similarity can be 1 minus normalized distances between species
Z <- 1 - DistanceMatrix/max(DistanceMatrix)
# Calculate diversity of order 2
Dqz(Paracou618.MC$Ns, 2, Z)
```

EightSpAbundance	<i>Abundances of 8 species to run examples.</i>
------------------	---

Description

This dataset is a light-weight example.

Usage

```
data(Paracou618)
```

Format

A named vector.

Examples

```
data(Paracou618)
EightSpAbundance
```

EightSpTree	<i>Functional tree with 8 species.</i>
-------------	--

Description

This dataset is a light-weight example.

Usage

```
data(Paracou618)
```

Format

An object of class `phylog` containing a functional tree.

Examples

```
data(Paracou618)
# Preprocess the tree to be able to plot it
# without loading ade4 package
plot(Preprocess.Tree(EightSpTree), hang=-0.01)
```

Enq *Grassberger's expectation of n^q*

Description

Expected value of n^q when n follows a Poisson law.

Usage

Enq(n, q)

Arguments

n A positive integer vector.
q A positive number.

Details

The expectation of n^q when n follows a Poisson distribution has been derived by Grassberger (1988).

Value

A vector of the same length as n containing the transformed values.

Note

The function is computed using the [beta](#).function.
Its value is 0 for $n - q + 1 < 0$.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Grassberger, P. (1988). Finite sample corrections to entropy and dimension estimates. Physics Letters A 128(6-7): 369-373.

Examples

```
# Compare
n <- c(2,3)
Enq(n, q=2)
# with
n^2

# Result is 1
Enq(n, q=0)
```

```
# Result is 0
Enq(n, q=5)
```

EntropyCI	<i>Entropy of Monte-Carlo simulated communities</i>
-----------	---

Description

Resamples a community by Monte-Carlo simulations of a multinomial distribution and returns a vector of entropy values to calculate confidence intervals.

Usage

```
EntropyCI(FUN, Simulations = 100, Ns, BootstrapMethod = "Chao2015",
          ShowProgressBar = TRUE, ..., CheckArguments = TRUE)
```

Arguments

FUN	The entropy function to be applied to each simulated community. May be any entropy function accepting a vector of species abundances, such as bcTsallis , bcShannon , bcSimpson or bcPhyloEntropy .
Simulations	The number of simulations to build confidence intervals.
Ns	A numeric vector containing species abundances.
BootstrapMethod	The method used to obtain the probabilities to generate bootstrapped communities from observed abundances. See rCommunity .
...	Additional arguments to be passed to FUN.
ShowProgressBar	If TRUE (default), a progress bar is shown.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

This function is used to obtain the distribution of entropy and eventually calculate confidence intervals. It draws simulated communities according to a multinomial distribution with the same number of individuals and probabilities as the actual community. It calculates the entropy of each simulated community. Last, it recenters the distribution of entropy values around the actual value of entropy according to Marcon *et al.* (2012): the estimation bias of simulated communities entropy can not be corrected analytically, but it does not affect the distribution shape.

Diversity can not be recentered this way so diversity function should not be used. Unexpected results will be obtained if inappropriate functions are used.

Value

A numeric vector containing the entropy value of each simulated community.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Abundance (all estimators will include bias correction)
Ns <- as.AbdVector(Paracou618.MC$Ns)
q <- 1
# Estimate entropy and transform it into diversity
RealEst <- expq(Tsallis(Ns, q), q)
# Transform the distribution of Tsallis entropy into diversity
SimulatedDiversity <- expq(EntropyCI(Tsallis, Simulations=50, Ns, q=q), q)
# Figure
plot(density(SimulatedDiversity), col="black", lwd=2, main="", xlab="Diversity")
abline(v=RealEst, col="red", lwd=2, lty=2)
abline(v=quantile(SimulatedDiversity, probs = 0.025), col="black", lwd=1, lty=3)
abline(v=quantile(SimulatedDiversity, probs = 0.975), col="black", lwd=1, lty=3)
legend("topright", c("Real value", "Confidence interval"), lty=c(2,3),
col=c("red", "black"), inset=0.01)
# Print results
cat("Estimated Diversity:", RealEst)
quantile(SimulatedDiversity, probs = c(0.025, 0.975))
```

expq

Exponential of order q

Description

Calculates the deformed exponential of order q .

Usage

```
expq(x, q)
expq.CommunityProfile(Profile)
```

Arguments

x	A numeric vector.
Profile	A CommunityProfile .
q	A number.

Details

The deformed exponential is defined as $(x(1 - q) + 1)^{\frac{1}{(1-q)}}$.

For $q > 1$, $\ln_q(+\infty) = \frac{1}{(q-1)}$ so $\exp_q(x)$ is not defined for $x > \frac{1}{(q-1)}$.

`expq.CommunityProfile` calculates the deformed exponential of a `CommunityProfile`. Its `$x` item (the order of diversity) is kept unchanged whilst other items are set to their exponential of order `$x`. Thus, an entropy profile is transformed into a diversity profile.

Value

A vector of the same length as `x` containing the transformed values or a `CommunityProfile`.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Scotti, I., Hérault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

Tsallis, C. (1994). What are the numbers that experiments provide? *Quimica Nova* 17(6): 468-471.

See Also

[expq](#)

Examples

```
curve(exp(x), -5, 0, lty=3)
curve(expq(x, 2), -5, 0, lty=2, add=TRUE)
curve(expq(x, 3), -5, 0, lty=1, add=TRUE)
legend("topleft", legend = c("exp(x)", "exp2(x)", "exp3(x)"), lty = c(1, 2, 3), inset=0.02)
```

GammaDiversity

Reduced-bias gamma diversity of a metacommunity

Description

Calculates the reduced-bias diversity of order q of a metacommunity.

Usage

```
GammaDiversity(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
  Z = NULL, CheckArguments = TRUE)
```

Arguments

MC	A MetaCommunity object.
q	A number: the order of diversity. Default is 1.
Correction	A string containing one of the possible corrections accepted by AlphaEntropy or "None" or "Best", the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), diversity is not affected by the height of the tree. If FALSE, diversity is proportional to the height of the tree.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Entropy is calculated by [GammaEntropy](#) and transformed into diversity.

Value

The metacommunity's gamma entropy.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[GammaEntropy](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Calculate Simpson gamma diversity
GammaDiversity(Paracou618.MC, 2)
# Compare without correction
```

```
GammaDiversity(Paracou618.MC, 2, Correction = "None")
# Estimate phylogenetic Simpson gamma diversity
GammaDiversity(Paracou618.MC, 2, Tree = Paracou618.Taxonomy)
```

GammaEntropy	<i>Reduced-bias gamma entropy of a metacommunity</i>
--------------	--

Description

Calculates the reduced-bias Tsallis entropy of order q of a metacommunity.

Usage

```
GammaEntropy(MC, q = 1, Correction = "Best", Tree = NULL, Normalize = TRUE,
             Z = NULL, PhyloDetails = FALSE, CheckArguments = TRUE)
```

Arguments

MC	A MetaCommunity object.
q	A number: the order of entropy. Default is 1.
Correction	A string containing one of the possible corrections accepted by the bias-corrected entropy function (see details) or "None" or "Best", the default value.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the entropy returned by the function is normalized by the height of the tree (it is the weighted average value of the entropy in each slice). If FALSE, it is the unnormalized weighted sum of the results.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1.
PhyloDetails	If FALSE (default), the function always returns a number. If TRUE and Tree is not NULL then a PhyloValue object is returned with all details. That is used internally by DivPart to obtain the corrections used to estimate gamma entropy along the tree and apply them to the estimation of alpha diversity.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

If Tree is not NULL, then phylogenetic entropy is calculated by [bcPhyloEntropy](#).

Else, if Z is not NULL, then similarity-based entropy is calculated by [bcHqz](#).

Else, neutral entropy is calculated by [bcTsallis](#).

Value

A number equal to the calculated entropy.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

Marcon, E., Herault, B. (2015). Decomposing PhyloDiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[bcTsallis](#), [bcPhyloEntropy](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Calculate Simpson gamma entropy
GammaEntropy(Paracou618.MC, 2)
# Compare without correction
GammaEntropy(Paracou618.MC, 2, Correction = "None")
# Estimate phylogenetic Simpson gamma entropy
GammaEntropy(Paracou618.MC, 2, Tree = Paracou618.Taxonomy)
```

GenSimpson

Generalized Simpson's Entropy and Diversity

Description

Calculates the Generalized Simpson's entropy of order r of a probability or abundance vector, and its effective number of species.

Usage

```
GenSimpson(NorP, r = 1, ...)
bcGenSimpson(Ns, r = 1, CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
GenSimpson(NorP, r = 1, ...,
  CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
GenSimpson(NorP, r = 1, ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
GenSimpson(NorP, r = 1, ...,
```

```

    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
GenSimpson(NorP, r = 1, ...,
    CheckArguments = TRUE, Ps = NULL, Ns = NULL)
GenSimpsonD(NorP, r = 1, ...)
bcGenSimpsonD(Ns, r = 1, CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
GenSimpsonD(NorP, r = 1, ...,
    CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
GenSimpsonD(NorP, r = 1, ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
GenSimpsonD(NorP, r = 1, ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
GenSimpsonD(NorP, r = 1, ...,
    CheckArguments = TRUE, Ps = NULL, Ns = NULL)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
r	A number: the order of diversity. Default is 1 for Simpson's diversity.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The Generalized Simpson's Entropy (Zhang and Zhou, 2010) of order r is, in the species accumulation curve, the probability for the individual sampled in rank $r + 1$ to belong to a new species. It is a measure of diversity so long as r is lower than the number of species (Grabchak *et al.*, 2016).

Bias correction requires the number of individuals. Use `bcGenSimpson`. It is limited to orders r less than or equal to the number of individuals in the community.

The effective number of species `GenSimpsonD` (explicit diversity) has been derived by Grabchak *et al.* (2016).

The functions are designed to be used as simply as possible. `GenSimpson` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcGenSimpson` is called. Explicit calls to `bcGenSimpson` (with bias correction) or to `GenSimpson.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated index or diversity. The name is either "Biased" or "Unbiased", depending on the estimator used.

Note

The unbiased estimator is calculated by the [GenSimp.z](#) function of the EntropyEstimation package.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Grabchak, M., Marcon, E., Lang, G., and Zhang, Z. (2017). The Generalized Simpson's Entropy is a Measure of Biodiversity. *Plos One*, 12(3): e0173305.

Zhang Z. and Zhou J. (2010). Re-parameterization of multinomial distributions and diversity indices. *Journal of Statistical Planning and Inference* 140(7): 1731-1738.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Calculate GenSimpson entropy of order 1, equal to Simpson's index of diversity
GenSimpson(Ps, 1)
# Calculate an unbiased estimator of GenSimpson diversity of order 100
GenSimpsonD(Ns, 100)
```

Description

Calculates the entropy of order q of a probability vector according to a similarity matrix.

Usage

```

Hqz(NorP, q = 1, Z = diag(length(NorP)), ...)
bcHqz(Ns, q = 1, Z = diag(length(Ns)), Correction = "Best", SampleCoverage = NULL,
      CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Hqz(NorP, q = 1, Z = diag(length(NorP)),
    ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Hqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best",
    ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Hqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best",
    ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Hqz(NorP, q = 1, Z = diag(length(NorP)), Correction = "Best",
    ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of entropy. Default is 1.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1. Default is the identity matrix to calculate neutral entropy.
Correction	A string containing one of the possible corrections: "None" (no correction), "ChaoShen", "MarconZhang" or "Best", the default value. The "MarconZhang" correction assumes a similarity matrix.
SampleCoverage	The sample coverage of Ns calculated elsewhere. Used to calculate the gamma diversity of meta-communities, see details.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Entropy is calculated following Leinster and Cobbold (2012) after Ricotta and Szeidl (2006): it is the entropy of order q of the community, using species ordinariness as the information function.

A similarity matrix is used (as for [Dqz](#)), not a distance matrix as in Ricotta and Szeidl (2006). See the example.

Bias correction requires the number of individuals. Use `bcHqz` and choose the `Correction`. Correction techniques are from Marcon *et al.* (2014).

Currently, the "Best" correction is the max value of "ChaoShen" and "MarconZhang".

The functions are designed to be used as simply as possible. Hqz is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function bcHqz is called. Explicit calls to bcHqz (with bias correction) or to Hqz.ProbaVector (without correction) are possible to avoid ambiguity. The .integer and .numeric methods accept Ps or Ns arguments instead of NorP for backward compatibility.

The size of a metacommunity (see [MetaCommunity](#)) is unknown so it has to be set according to a rule which does not ensure that its abundances are integer values. Then, classical bias-correction methods do not apply. Providing the SampleCoverage argument allows applying the "ChaoShen" correction to estimate quite well the entropy. [DivPart](#) and [GammaEntropy](#) functions use this tweak.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Leinster, T. and Cobbold, C. (2012). Measuring diversity: the importance of species similarity. *Ecology* 93(3): 477-489.

Marcon, E., Zhang, Z. and Hérault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

Ricotta, C. and Szeidl, L. (2006). Towards a unifying approach to diversity measures: Bridging the gap between the Shannon entropy and Rao's quadratic index. *Theoretical Population Biology* 70(3): 237-243.

See Also

[Dqz](#), [PhyloEntropy](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Prepare the similarity matrix
DistanceMatrix <- as.matrix(EightSpTree$Wdist^2/2)
# Similarity can be 1 minus normalized distances between species
Z <- 1 - DistanceMatrix/max(DistanceMatrix)
# Calculate diversity of order 2
Ps <- EightSpAbundance/sum(EightSpAbundance)
Hqz(Ps, 2, Z)
# Equal to normalized Rao quadratic entropy when q=2
Rao(Ps, EightSpTree)/max(DistanceMatrix)
# But different from PhyloEntropy for all other q, e.g. 1
Hqz(Ps, 1, Z)
summary(PhyloEntropy(Ps, 1, EightSpTree))
```

HqzBeta

*Similarity-based beta entropy of a community***Description**

Calculates the similarity-based beta entropy of order q of a community belonging to a metacommunity.

Usage

```
HqzBeta(NorP, NorPexp = NULL, q = 1, Z = diag(length(NorP)), ...)
bcHqzBeta(Ns, Nexp = NULL, q = 1, Z = diag(length(Ns)), Correction = "Best",
          CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
HqzBeta(NorP, NorPexp = NULL, q = 1, Z = diag(length(NorP)),
        ..., CheckArguments = TRUE, Ps = NULL, Pexp = NULL)
## S3 method for class 'AbdVector'
HqzBeta(NorP, NorPexp = NULL, q = 1, Z = diag(length(NorP)), Correction = "Best",
        ..., CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'integer'
HqzBeta(NorP, NorPexp = NULL, q = 1, Z = diag(length(NorP)), Correction = "Best",
        ..., CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'numeric'
HqzBeta(NorP, NorPexp = NULL, q = 1, Z = diag(length(NorP)), Correction = "Best",
        ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL, Pexp = NULL, Nexp = NULL)
```

Arguments

Ps	The probability vector of species of the community.
Pexp	The probability vector of species of the metacommunity.
Ns	A numeric vector containing species abundances of the community.
Nexp	A numeric vector containing species abundances of the metacommunity.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the community.
NorPexp	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the metacommunity.
q	A number, the order of diversity. Default is 1.
Z	A relatedness matrix, <i>i.e.</i> a square matrix whose terms are all positive, strictly positive on the diagonal. Generally, the matrix is a similarity matrix, <i>i.e.</i> the diagonal terms equal 1 and other terms are between 0 and 1. Default is the identity matrix to calculate neutral entropy.
Correction	A string containing one of the possible corrections: currently, no correction is available so "Best", the default value, is equivalent to "None".

... Additional arguments. Unused.

CheckArguments Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The derivation of similarity-based beta entropy can be found in Marcon *et al.* (2014).

Bias correction requires the number of individuals.

Note that beta entropy value is related to alpha entropy (if q is not 1) and cannot be compared across communities (Jost, 2007). Beta entropy of a community is not meaningful in general, do rather calculate the [BetaDiversity](#) of the metacommunity.

The functions are designed to be used as simply as possible. HqzBeta is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function bchqzbeta is called. Explicit calls to bchqzbeta (with bias correction) or to HqzBeta.ProbaVector (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Jost (2007), Partitioning diversity into independent alpha and beta components. *Ecology* 88(10): 2427-2439.

Marcon, E., Zhang, Z. and Hérault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Probability distribution of the first plot
Ps1 <- as.ProbaVector(Paracou618.MC$Psi[, 1])
# Prepare the similarity matrix
DistanceMatrix <- as.matrix(Paracou618.dist)
# Similarity can be 1 minus normalized distances between species
Z <- 1 - DistanceMatrix/max(DistanceMatrix)
# Divergence of order 2 between plot 1 and the whole forest
HqzBeta(Ps1, Ps, q=2, Z)
```

Description

Calculates the Hurlbert entropy of order k of a probability or abundance vector, and its effective number of species.

Usage

```
Hurlbert(NorP, k = 2, ...)
bcHurlbert(Ns, k = 2, CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Hurlbert(NorP, k = 2, ...,
  CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Hurlbert(NorP, k = 2, ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Hurlbert(NorP, k = 2, ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Hurlbert(NorP, k = 2, ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL)
HurlbertD(NorP, k = 2, ...)
bcHurlbertD(Ns, k = 2, CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
HurlbertD(NorP, k = 2, ...,
  CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
HurlbertD(NorP, k = 2, ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
HurlbertD(NorP, k = 2, ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
HurlbertD(NorP, k = 2, ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
k	A number: the order of diversity. Default is 2 for Simpson's diversity.

... Additional arguments. Unused.

CheckArguments Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Hurlbert's index of diversity (1971) of order k is the expected number of species in a sample of size k .

Bias correction requires the number of individuals. Use `bcHurlbert`. It is limited to orders k less than or equal to the number of individuals in the community.

The effective number of species `HurlbertD` (explicit diversity) has been derived by Dauby & Hardy (2012). It is calculated numerically. `bcHurlbertD` calculates it from the bias-corrected index `bcHurlbert`.

The functions are designed to be used as simply as possible. `Hurlbert` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcHurlbert` is called. Explicit calls to `bcHurlbert` (with bias correction) or to `Hurlbert.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated index or diversity. The name is either "Biased" or "Unbiased", depending on the estimator used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Dauby G. & Hardy O.J. (2012) Sampled-based estimation of diversity sensu stricto by transforming Hurlbert diversities into effective number of species. *Ecography* 35(7): 661-672.

Hurlbert (1971) The Nonconcept of Species Diversity: A Critique and Alternative Parameters. *Ecology* 52(4): 577-586.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Calculate Hurlbert entropy of order 2, equal to Simpson's index of diversity
Hurlbert(Ps, 2)
```

```
# Calculate an unbiased estimator of Hurlbert entropy of order 2
Hurlbert(Ns, 2)
```

KLq

Generalized Kullback-Leibler divergence

Description

Calculates the generalized Kullback-Leibler divergence between an observed and an expected probability distribution.

Usage

```
KLq(Ps, Pexp, q = 1, CheckArguments = TRUE)
```

Arguments

Ps	The observed probability vector.
Pexp	The expected probability vector.
q	A number: the order of entropy. Default is 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The generalized Kullback-Leibler divergence (Borland et al., 1998) converges to the Kullback-Leibler divergence (Kullback and Leibler, 1951) when q tends to 1. It is used to calculate the generalized beta entropy (Marcon et al., 2014).

Value

A number equal to the generalized Kullback-Leibler divergence between the probability distributions.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Borland, L., Plastino, A. R. and Tsallis, C. (1998). Information gain within nonextensive thermostatics. *Journal of Mathematical Physics* 39(12): 6490-6501.

Kullback, S. and Leibler, R. A. (1951). On Information and Sufficiency. *The Annals of Mathematical Statistics* 22(1): 79-86.

Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

See Also[TsallisBeta](#)**Examples**

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- Paracou618.MC$Ps
# Probability distribution of the first plot
Ps1 <- Paracou618.MC$Psi[, 1]
# Divergence of order 2 between the first plot and the whole forest
KLq(Ps1, Ps, 2)
```

lnq

*Logarithm of order q***Description**

Calculates the deformed logarithm of order q .

Usage

```
lnq(x, q)
lnq.CommunityProfile(Profile)
```

Arguments

x	A numeric vector.
Profile	A CommunityProfile .
q	A number.

Details

The deformed logarithm is defined as $\ln_q x = \frac{(x^{(1-q)} - 1)}{(1-q)}$.

The shape of the deformed logarithm is similar to that of the regular one. $\ln_1 x = \log x$.

For $q > 1$, $\ln_q(+\infty) = \frac{1}{(q-1)}$.

`lnq.CommunityProfile` calculates the deformed logarithm of a [CommunityProfile](#). Its `$x` item (the order of diversity) is kept unchanged whilst other items are set to their logarithm of order `$x`. Thus, a diversity profile is transformed into an entropy profile.

Value

A vector of the same length as `x` containing the transformed values or a [CommunityProfile](#).

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Tsallis, C. (1994). What are the numbers that experiments provide? *Quimica Nova* 17(6): 468-471.

See Also

[expq](#)

Examples

```
curve(log(x), 0, 1, lty=1)
curve(lnq(x, 2), 0, 1, lty=2, add=TRUE)
curve(lnq(x, 3), 0, 1, lty=3, add=TRUE)
legend("topleft", legend = c("log(x)", "ln2(x)", "ln3(x)"), lty = c(1, 2, 3), inset=0.02)
```

MC Utilities

Manipulation of meta-communities

Description

Tools to manipulate meta-communities. From a list of meta-communities, MergeMC creates a meta-community whose communities are each original metacommunity. MergeC creates a metacommunity whose communities are each original community. ShuffleMC randomly assigns original communities to a metacommunity, keeping original weights, and returns a list of meta-communities.

Usage

```
MergeMC(MClist, Weights = rep(1, length(MClist)), CheckArguments = TRUE)
MergeC(MClist, Weights = rep(1, length(MClist)), CheckArguments = TRUE)
ShuffleMC(MClist, Weights = rep(1, length(MClist)), CheckArguments = TRUE)
```

Arguments

MClist	A list of MetaCommunity objects.
Weights	A vector of numbers containing the weight of each metacommunity of the list. It does not have to be normalized to sum to 1.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

MergeMC is used for hierarchical partitioning of diversity. The gamma diversity of communities of the list becomes alpha diversity of the merged meta-community.

MergeC creates a new meta-community by mixing original ones. Original communities are kept, their new weight is the product of their original weight and the weight of their original meta-community.

ShuffleMC is used for simulations of the null hypothesis that all metacommunities of the list are identical.

Value

MergeMC and MergeC return a [MetaCommunity](#).

ShuffleMC returns a [list](#) of [MetaCommunity](#) objects.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

See Also

[MetaCommunity](#)

Examples

```
# First meta-community
(df <- data.frame(C1 = c(10, 10, 10, 10), C2 = c(0, 20, 35, 5),
  C3 = c(25, 15, 0, 2), row.names = c("sp1", "sp2", "sp3", "sp4")))
w <- c(1, 2, 1)
MC1 <- MetaCommunity(Abundances = df, Weights = w)
# Second meta-community
(df <- data.frame(C1 = c(10, 4), C2 = c(3, 4), row.names = c("sp1", "sp5")))
w <- c(3, 2)
MC2 <- MetaCommunity(Abundances = df, Weights = w)

# Merge communities
plot(MergeC(list(MC1, MC2)), main="Merged communities")
# Merge metacommunities
plot(MergeMC(list(MC1, MC2)), main="Merged meta-communities")
smc <- ShuffleMC(list(MC1, MC2))
plot(MergeMC(smc), main="Shuffled, then Merged meta-communities")
```

Description

Methods for objects of type "MCdiversity".

Usage

```

is.MCdiversity(x)
## S3 method for class 'MCdiversity'
plot(x, ...)
## S3 method for class 'MCdiversity'
autoplot(object, ...)
## S3 method for class 'MCdiversity'
summary(object, ...)

```

Arguments

x	An object to be tested or plotted.
object	A MCdiversity object to be summarized or plotted.
...	Additional arguments to be passed to the generic methods.

Value

Meta-community diversity objects are lists containing:

MetaCommunity	The name of the <code>MetaCommunity</code> object containing inventory data.
Type	The type of diversity ("alpha", "beta" or "gamma").
Order	The order of diversity q .
Correction	The estimation bias correction used to calculate diversity.
Tree	The phylogenetic or functional tree used to calculate phylodiversity.
Normalized	Logical. Indicates whether phylodiversity is normalized or proportional to the height of the tree.
Weights	A vector containing the weights of communities.
Communities	A vector containing the diversity of communities.
Total	The total diversity.

`is.MCdiversity` returns TRUE if the object is of class MCdiversity.

`summary.MCdiversity` returns a summary of the object's value.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

MEntropy *Meta-Community entropy class.*

Description

Methods for objects of type "MEntropy".

Usage

```
is.MEntropy(x)
## S3 method for class 'MEntropy'
plot(x, ...)
## S3 method for class 'MEntropy'
autoplot(object, ...)
## S3 method for class 'MEntropy'
summary(object, ...)
```

Arguments

x	An object to be tested or plotted.
object	A MEntropy object to be summarized or plotted.
...	Additional arguments to be passed to the generic methods.

Value

Meta-community entropy objects are lists containing:

MetaCommunity	The name of the <code>MetaCommunity</code> object containing inventory data.
Method	The method used to calculate entropy ("HCDT", "Similarity-based").
Type	The type of entropy ("alpha", "beta" or "gamma").
Order	The order of entropy q .
Correction	The estimation bias correction used to calculate entropy.
Tree	The phylogenetic or functional tree used to calculate phyloentropy.
Normalized	Logical. Indicates whether phyloentropy is normalized or proportional to the height of the tree.
Z	The matrix used to calculate similarity-based entropy.
Weights	A vector containing the weights of communities.
Communities	A vector containing the entropy of communities.
Total	The total entropy.

`is.MEntropy` returns TRUE if the object is of class MEntropy.

`summary.MEntropy` returns a summary of the object's value.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

MetaCommunity	<i>Metacommunity class</i>
---------------	----------------------------

Description

Methods for objects of type "MetaCommunity".

Usage

```
MetaCommunity(Abundances, Weights = rep(1, ncol(Abundances)))
is.MetaCommunity(x)
## S3 method for class 'MetaCommunity'
summary(object, ...)
## S3 method for class 'MetaCommunity'
plot(x, ...)
```

Arguments

Abundances	A dataframe containing the number of observations (lines are species, columns are communities). The first column of the dataframe may contain the species names.
Weights	A vector of positive numbers equal to community weights or a dataframe containing a vector named <code>Weights</code> . It does not have to be normalized. Weights are equal by default.
x	An object to be tested or plotted.
object	A <code>MetaCommunity</code> object to be summarized.
...	Additional arguments to be passed to the generic methods.

Details

In the `entropart` package, individuals of different "species" are counted in several "communities" which are aggregated to define a "metacommunity".

This is a naming convention, which may correspond to plots in a forest inventory or any data organized the same way.

Alpha and beta entropies of communities are summed according to `Weights` and the probability to find a species in the metacommunity is the weighted average of probabilities in communities.

The simplest way to import data is to organize it into two text files. The first file should contain abundance data: the first column named `Species` for species names, and a column for each community.

The second file should contain the community weights in two columns. The first one, named `Communities` should contain their names and the second one, named `Weights`, their weights.

Files can be read and data imported by code such as:

```
Abundances <- read.csv(file="Abundances.csv", row.names = 1)
Weights <- read.csv(file="Weights.csv")
MC <- MetaCommunity(Abundances, Weights)
```


Value

An object of class **MetaCommunity** is a list:

Nsi	A matrix containing abundance data, species in line, communities in column.
Ns	A vector containing the number of individuals of each species.
Ni	A vector containing the number of individuals of each community.
N	The total number of individuals.
Psi	A matrix whose columns are the probability vectors of communities (each of them sums to 1).
Wi	A vector containing the normalized community weights (sum to 1).
Ps	A vector containing the probability vector of the metacommunity.
Nspecies	The number of species.
Ncommunities	The number of communities.
SampleCoverage	The sample coverage of the metacommunity.
SampleCoverage.communities	A vector containing the sample coverages of each community.

`is.MetaCommunity` returns TRUE if the object is of class `MetaCommunity`.

`summary.MetaCommunity` returns a summary of the object's value.

`plot.MetaCommunity` plots it.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

Examples

```
# Use BCI data from vegan package
if (require(vegan, quietly = TRUE)) {
  # Load BCI data (number of trees per species in each 1-ha plot of a tropical forest)
  data(BCI)
  # BCI dataframe must be transposed (its lines are plots, not species)
  BCI.df <- as.data.frame(t(BCI))
  # Create a metacommunity object from a matrix of abundances and a vector of weights
  # (here, all plots have a weight equal to 1)
  MC <- MetaCommunity(BCI.df)
}
```

Optimal.Similarity	<i>Optimal scale parameter to transform a distance matrix into a similarity matrix</i>
--------------------	--

Description

Calculates the scale parameter u that maximizes the variance of the similarity matrix $\exp(-u * DistanceMatrix)$.

Usage

```
Optimal.Similarity(Distance, CheckArguments = TRUE)
```

Arguments

Distance	A distance matrix, <i>i.e.</i> a square matrix with zeros on its diagonal or a dist object.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The similarity matrix used by [Dqz](#) can be optimized following Marcon *et al.* (2014) such that the variance of similarities between pairs of species is maximized. See the example.

Value

A list:	
u	The optimal scale u .
Matrix	The optimal similarity matrix Z.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Zhang, Z. and Herault, B. (2014). The decomposition of similarity-based diversity and its bias correction. *HAL* hal-00989454(version 3).

See Also

[Dqz](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Prepare the similarity matrix. The square root of Paracou618.dist is euclidean.
optimal <- Optimal.Similarity(sqrt(Paracou618.dist))
# Optimal scale
optimal$u
# Calculate diversity of order 2
bcDqz(Paracou618.MC$Ns, 2, optimal$Matrix)
```

Paracou618.dist	<i>Functional distances between pairs of species of Paracou field station plots 6 and 18, two 1-ha plots inventoried by the Bridge project.</i>
-----------------	---

Description

This dataset is from Paracou field station, French Guiana, managed by [Cirad](#). Traits are detailed in Marcon and Herault (2014), the distance matrix was built following Paine et al. (2011).

Usage

```
data(Paracou618)
```

Format

An object of class `dist`.

Source

Permanent data census of Paracou.

References

Gourlet-Fleury, S., Guehl, J. M. and Laroussinie, O., Eds. (2004). *Ecology & management of a neotropical rainforest. Lessons drawn from Paracou, a long-term experimental research site in French Guiana*. Paris, Elsevier.

Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Paine, C. E. T., Baraloto, C., Chave, J., and Herault, B. (2011). Functional traits of individual trees reveal ecological constraints on community assembly in tropical rain forests. *Oikos*, 120(5), 720-727.

Examples

```
data(Paracou618)
plot(density(Paracou618.dist, from=0), main="Distances between species")
```

Paracou618.Functional *Functional tree of species of Paracou field station plots 6 and 18, two 1-ha plots inventoried by the Bridge project.*

Description

This dataset is from Paracou field station, French Guiana, managed by [Cirad](#). Traits are detailed in Marcon and Herault (2014), the tree was built following Paine et al. (2011), based on [Paracou618.dist](#).

Usage

```
data(Paracou618)
```

Format

An object of class [hclust](#).

Source

Permanent data census of Paracou.

References

Gourlet-Fleury, S., Guehl, J. M. and Laroussinie, O., Eds. (2004). *Ecology & management of a neotropical rainforest. Lessons drawn from Paracou, a long-term experimental research site in French Guiana*. Paris, Elsevier.

Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Paine, C. E. T., Baraloto, C., Chave, J., and Herault, B. (2011). Functional traits of individual trees reveal ecological constraints on community assembly in tropical rain forests. *Oikos*, 120(5), 720-727.

Examples

```
data(Paracou618)
plot(Paracou618.Functional)
```

Paracou618.MC	<i>Paracou field station plots 6 and 18, two 1-ha plots inventoried by the Bridge project.</i>
---------------	--

Description

This dataset is from Paracou field station, French Guiana, managed by [Cirad](#).

Usage

```
data(Paracou618)
```

Format

An object of class [MetaCommunity](#) made of two communities and 425 species.

Source

Permanent data census of Paracou and Marcon et al. (2012).

References

Gourlet-Fleury, S., Guehl, J. M. and Laroussinie, O., Eds. (2004). *Ecology & management of a neotropical rainforest. Lessons drawn from Paracou, a long-term experimental research site in French Guiana*. Paris, Elsevier.

Marcon, E., F. Puech, et al. (2012). Characterizing the relative spatial structure of point patterns. *International Journal of Ecology* 2012(Article ID 619281): 11.

Examples

```
data(Paracou618)  
summary(Paracou618.MC)
```

Paracou618.Taxonomy	<i>Taxonomy (Family - Genus - Species) of Paracou field station plots 6 and 18, two 1-ha plots inventoried by the Bridge project.</i>
---------------------	---

Description

This dataset is from Paracou field station, French Guiana, managed by [Cirad](#).

Usage

```
data(Paracou618)
```

Format

An object of class `phylo` containing a taxonomy.

Source

Permanent data census of Paracou.

References

Gourlet-Fleury, S., Guehl, J. M. and Laroussinie, O., Eds. (2004). *Ecology & management of a neotropical rainforest. Lessons drawn from Paracou, a long-term experimental research site in French Guiana*. Paris, Elsevier.

Examples

```
data(Paracou618)
plot(Paracou618.Taxonomy, type="fan", show.tip.label=FALSE)
```

PDFD

Phylogenetic Diversity / Functional Diversity of a Community

Description

Calculates Faith's PD / Petchey and Gaston' FD of a community described by a probability vector and a phylogenetic / functional tree.

Usage

```
PDFD(Ps, Tree, CheckArguments = TRUE)
```

Arguments

Ps	A probability vector, summing to 1.
Tree	An object of class <code>hclust</code> , <code>phylo</code> , <code>phylog</code> or <code>PPtree</code> . The tree must be ultrametric.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

PD and FD are defined as the total length of the branches of the tree.

The probability vector is used to select branches: branches with probability 0 are eliminated.

Bias correction requires the number of individuals to estimate sample [Coverage](#).

Use `bcPhyloDiversity(Ps, 0, Tree)` and choose the Correction.

Value

A named number equal to the calculated diversity. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Faith, D. P. (1992). Conservation evaluation and phylogenetic diversity. *Biological Conservation* 61(1): 1-10.

Petchey, O. L. and Gaston, K. J. (2002). Functional diversity (FD), species richness and community composition. *Ecology Letters* 5: 402-411.

See Also

[bcPhyloDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- Paracou618.MC$Ps
# Calculate the phylogenetic Shannon diversity of the plot
PDFD(Ps, Paracou618.Taxonomy)
```

PhyloApply

Apply a Function over a Phylogenetic Tree

Description

Cuts the tree into slices separated by nodes, applies the function to each slice and returns the weighted (by slice lengths) sum of the results.

Usage

```
PhyloApply(Tree, FUN, NorP, Normalize = TRUE, dfArgs = NULL,
           ..., CheckArguments = TRUE)
```

Arguments

Tree	An object of class <code>hclust</code> , <code>phylo</code> , <code>phylog</code> or <code>PPtree</code> . The tree must be ultrametric.
FUN	The function to be applied to each interval of the tree.
NorP	A numeric vector or a two-column matrix. Contains either abundances or probabilities. Two-column matrices should contain the observed abundances (or probabilities) in the first column and the expected ones in the second column, to allow using beta diversity functions.
Normalize	If TRUE (default), the Total value returned by Function is normalized by the height of the tree (it is the weighted average value of the result in each slice). If FALSE, it is the unnormalized weighted sum of the results.
dfArgs	A dataframe. Columns are arguments for FUN: their names are those of valid arguments. Values will be passed to FUN in each slice of the tree, starting from the tips. The number of lines must equal the number of slices.
...	Further arguments to pass to Function.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

This function is generally not used directly. It is a tool to calculate [PhyloEntropy](#) and [PhyloDiversity](#).

Intervals (slices) separate two cuts (nodes) in a tree: no node is found at heights contained in an interval.

Objects of class **PPtree** are returned by [Preprocess.Tree](#).

...allow passing arguments to the function but they can't change along the tree. If necessary, `dfArgs` allow passing a different value for each slice of the tree.

Value

An object of class `PhyloValue`. It is a list:

Distribution	The distribution used to calculate the value
Function	The function used to calculate the value
Tree	The functional or phylogenetic tree used to calculate the value
Normalized	Logical. Indicates whether phylovalue is normalized or proportional to the height of the tree.
Cuts	A named vector containing values along the tree. Names are cut ends, <i>i.e.</i> the ends of intervals (the first interval starts at 0 for leaves, the max value is the height of the tree).
Corrections	A named vector containing the correction used by FUN to obtain each value of Cuts. Names are those of Cuts.
Total	The total value, multiplied by the tree height if <code>Normalize</code> is FALSE.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

See Also

[Preprocess.Tree](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Plot the taxonomy
plot(Paracou618.Taxonomy, type="fan", show.tip.label=FALSE)
# Calculate the mean number of trees (individuals) per species
# (Cuts are 1=species, 2=genus, 3=family)
summary(PhyloApply(Paracou618.Taxonomy, mean, Paracou618.MC$Ns, TRUE))
```

PhyloBetaEntropy

Phylogenetic Beta Entropy of a community

Description

Calculates the phylogenetic beta entropy of order q of a community belonging to a metacommunity.

Usage

```
PhyloBetaEntropy(NorP, NorPexp = NULL, q = 1, Tree, Normalize = TRUE, ...)
bcPhyloBetaEntropy(Ns, Nex, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
PhyloBetaEntropy(NorP, NorPexp = NULL, q = 1, Tree, Normalize = TRUE,
  ..., CheckArguments = TRUE, Ps = NULL, Pexp = NULL)
## S3 method for class 'AbdVector'
PhyloBetaEntropy(NorP, NorPexp = NULL, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ns = NULL, Nex = NULL)
## S3 method for class 'integer'
PhyloBetaEntropy(NorP, NorPexp = NULL, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ns = NULL, Nex = NULL)
## S3 method for class 'numeric'
PhyloBetaEntropy(NorP, NorPexp = NULL, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL,
  Pexp = NULL, Nex = NULL)
```

Arguments

Ps	The probability vector of species of the community.
Pexp	The probability vector of species of the metacommunity.
Ns	A numeric vector containing species abundances of the community.
Nexp	A numeric vector containing species abundances of the metacommunity.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the community.
NorPexp	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the metacommunity.
q	A number: the order of entropy. Default is 1.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the entropy returned by the function is normalized by the height of the tree (it is the weighted average value of the entropy in each slice). If FALSE, it is the unnormalized weighted sum of the results.
Correction	A string containing one of the possible corrections: currently, only "ChaoShen". "Best" is the default value, it is equivalent to "ChaoShen".
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The phylogenetic entropy is the generalization of HCDT entropy to unequal species distances (Pavoine et al., 2009).

Calculation relies on [TsallisBeta](#) and [PhyloApply](#).

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use [bcPhyloBetaEntropy](#) and choose the [Correction](#).

Note that beta entropy value is related to alpha entropy (if q is not 1) and cannot be compared across communities (Jost, 2007). Beta entropy of a community is not meaningful in general, do rather calculate the [PhyloDiversity](#) of the metacommunity.

The functions are designed to be used as simply as possible. [PhyloBetaEntropy](#) is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function [bcPhyloBetaEntropy](#) is called. Explicit calls to [bcPhyloBetaEntropy](#) (with bias correction) or [PhyloBetaEntropy.ProbaVector](#) (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A [PhyloEntropy](#) object containing entropy values at each cut of the tree.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Jost (2007), Partitioning diversity into independent alpha and beta components. *Ecology* 88(10): 2427-2439.

Marcon, E., Herault, B. (2015). Decomposing PhyloDiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Pavoine, S., Love, M. S. and Bonsall, M. B. (2009). Hierarchical partitioning of evolutionary and ecological patterns in the organization of phylogenetically-structured species assemblages: Application to rockfish (genus: *Sebastes*) in the Southern California Bight. *Ecology Letters* 12(9): 898-908.

See Also

[TsallisBeta](#), [bcPhyloBetaEntropy](#), [PhyloDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Probability distribution of the first plot
Ps1 <- as.ProbaVector(Paracou618.MC$Psi[, 1])
# Calculate the phylogenetic Shannon beta entropy of the plot
summary(PhyloBetaEntropy(Ps1, Ps, 1, Paracou618.Taxonomy) -> e)
plot(e)

# Ns is the vector of abundances of the metacommunity
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Abundances in the first plot
Ns1 <- as.AbdVector(Paracou618.MC$Nsi[, 1])
# Calculate the phylogenetic Shannon beta entropy of the plot
summary(bcPhyloBetaEntropy(Ns1, Ns, 1, Paracou618.Taxonomy, Correction = "Best") -> e)
plot(e)
```

Description

Calculates the phylogenetic diversity of order q of a probability vector.

Usage

```

PhyloDiversity(NorP, q = 1, Tree, Normalize = TRUE, ...)
bcPhyloDiversity(Ns, q = 1, Tree, Normalize = TRUE, Correction = "Best",
  CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
PhyloDiversity(NorP, q = 1, Tree, Normalize = TRUE,
  ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
PhyloDiversity(NorP, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
PhyloDiversity(NorP, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
PhyloDiversity(NorP, q = 1, Tree, Normalize = TRUE,
  Correction = "Best", ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL)
is.PhyloDiversity(x)
## S3 method for class 'PhyloDiversity'
summary(object, ...)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of diversity. Default is 1.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the Total diversity is not affected by the height of the tree. If FALSE, it is proportional to the height of the tree.
Correction	A string containing one of the possible corrections: "None" (no correction), "ChaoShen", "Grassberger", "Holste", "Bonachela" or "Best", the default value.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.
x	An object to be tested or plotted
object	A PhyloDiversity object to be summarized.
...	Additional arguments to be passed to the generic methods.

Details

The phylogenetic entropy is its generalization of HCDT entropy to unequal species distances (Pavoine et al., 2009).

Diversity is obtained by transforming generalized entropy.

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use `bcPhyloDiversity` and choose the `Correction`.

The functions are designed to be used as simply as possible. `PhyloDiversity` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcPhyloDiversity` is called. Explicit calls to `bcPhyloDiversity` (with bias correction) or to `PhyloDiversity.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

An object of class `PhyloDiversity` is a list:

Distribution	The distribution used to calculate diversity
Function	The function used to calculate diversity
Tree	The functional or phylogenetic tree used to calculate diversity
Normalized	Logical. Indicates whether phylodiversity is normalized or proportional to the height of the tree.
Type	The type of diversity ("alpha", "beta" or "gamma").
Order	The order of diversity q .
Cuts	A named vector containing values of neutral diversity along the tree. Names are cut ends, <i>i.e.</i> the ends of intervals (the first interval starts at 0 for leaves, the max value is the height of the tree).
Total	A value equal the total diversity (obtained by transforming the total normalized entropy), multiplied by the tree height if <code>Normalize</code> is <code>FALSE</code> .

`is.PhyloDiversity` returns `TRUE` if the object is of class `PhyloDiversity`.

`summary.PhyloDiversity` returns a summary of the object's value.

`PhyloDiversity` objects can be plotted by `plot.PhyloValue` because `PhyloDiversity` objects are also of class `PhyloValue`.

Note

The tree must contain all species of the probability vector. If it contains extra species, computation time will just be increased.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Chao, A., Chiu, C.-H. and Jost, L. (2010). Phylogenetic diversity measures based on Hill numbers. *Philosophical Transactions of the Royal Society B* 365(1558): 3599-609.
- Marcon, E., Hérault, B. (2015). Decomposing PhyloDiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Pavoine, S., Love, M. S. and Bonsall, M. B. (2009). Hierarchical partitioning of evolutionary and ecological patterns in the organization of phylogenetically-structured species assemblages: Application to rockfish (genus: *Sebastes*) in the Southern California Bight. *Ecology Letters* 12(9): 898-908.

See Also

[PhyloEntropy, Diversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Calculate the phylogenetic Shannon diversity of the plot
summary(PhyloDiversity(Ps, 1, Paracou618.Taxonomy) -> d)
plot(d)

# Ns is the vector of abundances of the metacommunity
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Calculate the phylogenetic Shannon diversity of the plot
summary(bcPhyloDiversity(Ns, 1, Paracou618.Taxonomy, Correction = "Best") -> d)
plot(d)
```

PhyloEntropy

Phylogenetic Entropy of a community

Description

Calculates the phylogenetic entropy of order q of a probability vector.

Usage

```
PhyloEntropy(NorP, q = 1, Tree, Normalize = TRUE, ...)
bcPhyloEntropy(Ns, q = 1, Tree, Normalize = TRUE, Correction = "Best",
  SampleCoverage = NULL, CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
PhyloEntropy(NorP, q = 1, Tree, Normalize = TRUE,
  ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
PhyloEntropy(NorP, q = 1, Tree, Normalize = TRUE, Correction = "Best",
  ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
PhyloEntropy(NorP, q = 1, Tree, Normalize = TRUE, Correction = "Best",
  ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
```

```
PhyloEntropy(NorP, q = 1, Tree, Normalize = TRUE, Correction = "Best",
  ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL)
is.PhyloEntropy(x)
## S3 method for class 'PhyloEntropy'
summary(object, ...)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of entropy. Default is 1.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Normalize	If TRUE (default), the Total entropy returned by the function is normalized by the height of the tree (it is the weighted average value of the entropy in each slice). If FALSE, it is the unnormalized weighted sum of the results.
Correction	A string containing one of the possible corrections supported by Tsallis .
SampleCoverage	The sample coverage of Ns calculated elsewhere. Used to calculate the gamma diversity of meta-communities, see details.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.
x	An object to be tested or plotted
object	A PhyloEntropy object to be summarized.
...	Additional arguments to be passed to the generic methods.

Details

The phylogenetic entropy is its generalization of HCDT entropy to unequal species distances (Pavoine et al., 2009).

Calculation relies on [Tsallis](#) and [PhyloApply](#).

Intervals separate two cuts in a tree: no node is found at heights contained in an interval.

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use [bcPhyloEntropy](#) and choose the [Correction](#).

The functions are designed to be used as simply as possible. [PhyloEntropy](#) is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function [bcPhyloEntropy](#) is called. Explicit calls to [bcPhyloEntropy](#) (with bias correction) or to [PhyloEntropy.ProbaVector](#) (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept Ps or Ns arguments instead of NorP for backward compatibility.

The size of a metacommunity (see [MetaCommunity](#)) is unknown so it has to be set according to a rule which does not ensure that its abundances are integer values. Then, classical bias-correction

methods do not apply. Providing the `SampleCoverage` argument allows applying the "ChaoShen" and "Grassberger" corrections to estimate quite well the entropy. `DivPart` and `GammaEntropy` functions use this tweak.

Value

An object of class `PhyloEntropy` is a list:

Distribution	The distribution used to calculate entropy
Function	The function used to calculate entropy
Tree	The functional or phylogenetic tree used to calculate entropy
Normalized	Logical. Indicates whether phyloentropy is normalized or proportional to the height of the tree.
Type	The type of entropy ("alpha", "beta" or "gamma").
Order	The order of entropy q .
Cuts	A named vector containing values of neutral entropy along the tree. Names are cut ends, <i>i.e.</i> the ends of intervals (the first interval starts at 0 for leaves, the max value is the height of the tree).
Total	A value equal the total entropy multiplied by the tree height if <code>Normalize</code> is <code>FALSE</code> .

`is.PhyloEntropy` returns `TRUE` if the object is of class `PhyloEntropy`.

`summary.PhyloEntropy` returns a summary of the object's value.

`PhyloEntropy` objects can be plotted by `plot.PhyloValue` because `PhyloEntropy` objects are also of class `PhyloValue`.

Note

The tree must contain all species of the probability vector. If it contains extra species, computation time will just be increased.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Hérault, B. (2015). Decomposing PhyloDiversity. *Methods in Ecology and Evolution* 6(3): 333-339.

Pavoine, S., Love, M. S. and Bonsall, M. B. (2009). Hierarchical partitioning of evolutionary and ecological patterns in the organization of phylogenetically-structured species assemblages: Application to rockfish (genus: *Sebastes*) in the Southern California Bight. *Ecology Letters* 12(9): 898-908.

See Also

[Tsallis](#), [PhyloDiversity](#)

Examples

```

# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Calculate the phylogenetic Shannon entropy of the plot
summary(PhyloEntropy(Ps, 1, Paracou618.Taxonomy) -> e)
plot(e)

# Ns is the vector of abundances of the metacommunity
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Calculate the phylogenetic Shannon entropy of the plot
summary(bcPhyloEntropy(Ns, 1, Paracou618.Taxonomy, Correction = "Best") -> e)
plot(e)

```

PhyloValue

*Phylogenetic entropy or diversity.***Description**

Entropy or diversity against the height of the phylogenetic or functional tree.

Usage

```

is.PhyloValue(x)
## S3 method for class 'PhyloValue'
autoplot(object, xlab = expression(italic("T")), ylab = NULL, main = NULL, ...)
## S3 method for class 'PhyloValue'
plot(x, xlab = expression(italic("T")), ylab = NULL, main = NULL, ...)
## S3 method for class 'PhyloValue'
summary(object, ...)

```

Arguments

x	An object of class PhyloValue, including PhyloDiversity and PhyloEntropy objects.
xlab	The X axis label, "T" by default for Time.
ylab	The Y axis label. if NULL (by default), "Entropy" or "Diversity" or nothing is chosen according to the object class.
main	The main title of the plot. if NULL (by default), a default value is used.
object	A PhyloValue object to be summarized.
...	Additional arguments to be passed to plot .

Details

PhyloValue objects are the result of [PhyloApply](#).

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest
# and their taxonomy)
data(Paracou618)
# Calculate richness along the tree
# (Cuts are 1=species, 2=genus, 3=family)
summary(r <- PhyloApply(Paracou618.Taxonomy, FUN=Richness,
  NorP=Paracou618.MC$Ns, Normalize=TRUE))
autoplot(r)
```

 PPtree

Preprocessed Trees.

Description

Methods for objects of type "PPtree".

Usage

```
is.PPtree(x)
## S3 method for class 'PPtree'
plot(x, ...)
```

Arguments

x An object to be tested or plotted
 ... Additional arguments to be passed to the generic methods.

Value

An object of class **PPtree** is a list:

phyTree	A phylo tree
hTree	A hclust tree
Height	The height of the tree, that is to say the distance between root and leaves
Cuts	A vector. Cut times of the tree (the distance from nodes to leaves)
Intervals	A vector. The lengths of intervals between cuts

is.PPtree returns TRUE if the object is of class PPtree.

plot.PPtree plots it.

Note

Versions up to 1.3 contained a [phylog](#) tree, now deprecated in ade4. A [phylo](#) tree is now used.
See the dedicated vignette (`vignette("Phylogenies", package="entropart")`) for more details.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

Examples

```
data(Paracou618)
# Preprocess a phylog object
ppt <- Preprocess.Tree(EightSpTree)
# Is it a preprocessed tree?
is.PPtree(ppt)
# Plot it
plot(ppt, hang=-1)
# Alternative plot
ade4::radial.phylog(EightSpTree)
```

RAC

Fit Distributions to Well-Known Rank Abundance Curves.

Description

Observed distributions are fitted to classical RAC's.

Usage

```
RAClnorm(Ns, CheckArguments = TRUE)
RACgeom(Ns, CheckArguments = TRUE)
RAClseries(Ns, CheckArguments = TRUE)
RACbstick(Ns, CheckArguments = TRUE)
```

Arguments

Ns A numeric vector containing species abundances.

CheckArguments Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

SpeciesDistribution or integer vectors can be used to fit classical rank-abundance curves (RAC) of classical distributions: "RAClnorm" for log-normal (Preston, 1948), "RAClseries" for log-series (Fisher *et al.*, 1943), "RACgeom" for geometric (Motomura, 1932) or "RACbstick" for broken stick (MacArthur, 1957). method returns the estimated parameters of the fitted distribution. The broken stick has no parameter, so the maximum abundance is returned.

Value

A list (the parameters of distributions are returned only if the distribution has been fit):

Rank	A numeric vector. The ranks of species in the fitted RAC.
Abundance	The abundance of species in the fitted RAC.
mu	The expectation of the log-normal distribution
sigma	The standard deviation of the log-normal distribution
alpha	Fisher's alpha in the log-series distribution
prob	The proportion of resources taken by successive species in the geometric distribution
max	The maximum abundance in the broken-stick distribution

Note

Fisher's alpha is estimated to fit the log-series distribution. The estimation is done by the `fisher.alpha` function of package `vegan`. It may differ substantially from the estimation returned by `optimal.theta` from package `untb`.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>, Bruno Hérault <Bruno.Hérault@ecofog.gf>

References

- Fisher R.A., Corbet A.S., Williams C.B. (1943) The Relation Between the Number of Species and the Number of Individuals in a Random Sample of an Animal Population. *Journal of Animal Ecology* 12: 42-58.
- MacArthur R.H. (1957) On the Relative Abundance of Bird Species. *PNAS* 43(3): 293-295.
- Motomura I. (1932) On the statistical treatment of communities. *Zoological Magazine* 44: 379-383.
- Preston, F.W. (1948). The commonness, and rarity, of species. *Ecology* 29(3): 254-283.

See Also

[rgeom](#), [rlnorm](#), [rCommunity](#), [plot.SpeciesDistribution](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Fitted parameters
RACln <- RAClnorm(Ns)
RACln$mu
RACln$sigma
RACgeom(Ns)$prob
RAClseries(Ns)$alpha
RACbstick(Ns)$max
```

Rao	<i>Rao Quadratic Entropy of a Community</i>
-----	---

Description

Calculates Rao's quadratic entropy of a community described by a probability vector and a phylogenetic / functional tree.

Usage

```
Rao(NorP, Tree, ...)
bcRao(Ns, Tree, Correction="Lande", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Rao(NorP, Tree, ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Rao(NorP, Tree, Correction = "Lande", ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Rao(NorP, Tree, Correction = "Lande", ...,
    CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Rao(NorP, Tree, Correction = "Lande", ...,
    CheckArguments = TRUE, Ps = NULL, Ns = NULL)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
Tree	An object of class hclust , phylo , phylog or PPtree . The tree must be ultrametric.
Correction	A string containing one of the possible corrections accepted by bcTsallis or "Lande", the default value (equivalent to "Best").
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Bias correction requires the number of individuals. Use `bcRao` and choose the `Correction`.

The unbiased estimator of Rao's entropy is identical to that of Simpson's entropy because Rao's entropy is a linear sum of Simpson entropies, all of them calculated from the same number of individuals (Marcon and Herault, 2014). It equals the plug-in estimator multiplied by $n/(n-1)$ where n is the total number of individuals.

The functions are designed to be used as simply as possible. `Tsallis` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcTsallis` is called. Explicit calls to `bcTsallis` (with bias correction) or to `Tsallis.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Marcon, E., Herault, B. (2015). Decomposing Phylodiversity. *Methods in Ecology and Evolution* 6(3): 333-339.
- Rao, C. R. (1982). Diversity and dissimilarity coefficients: a unified approach. *Theoretical Population Biology* 21: 24-43.

See Also

[bcPhyloDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Calculate Rao's quadratic entropy of the plot
Rao(Ps, Paracou618.Taxonomy)
```

rCommunity

Random Communities

Description

Draws random communities according to a probability distribution.

Usage

```
rCommunity(n, size = sum(NorP), NorP = 1, BootstrapMethod = "Chao2015", S = 300,
  Distribution = "lnorm", sd = 1, prob = 0.1, alpha = 40,
  CheckArguments = TRUE)
```

Arguments

n	The number of communities to draw.
size	The number of individuals to draw in each community.
BootstrapMethod	The method used to obtain the probabilities to generate bootstrapped communities from observed abundances. If "Marcon", the probabilities are simply the abundances divided by the total number of individuals (Marcon <i>et al.</i> , 2012). If "Chao2013" or "Chao2015" (by default), a more sophisticated approach is used (see as.ProbaVector) following Chao <i>et al.</i> (2013) or Chao <i>et al.</i> (2015).
NorP	A numeric vector or a two-column matrix. Contains either abundances or probabilities. Two-column matrices should contain the observed abundances (or probabilities) in the first column and the expected ones in the second column, to allow using beta diversity functions.
S	The number of species.
Distribution	The distribution of species frequencies. May be "lnorm" (log-normal), "lseries" (log-series), "geom" (geometric) or "bstick" (broken stick).
sd	The simulated distribution standard deviation. For the log-normal distribution, this is the standard deviation on the log scale.
prob	The proportion of resources taken by successive species.
alpha	Fisher's alpha.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Communities of fixed size are drawn in a multinomial distribution according to the distribution of probabilities provided by NorP.

An abundance vector may be used instead of probabilities, then size is by default the total number of individuals in the vector. Random communities are built by drawing in a multinomial law following Marcon *et al.* (2012), or trying to estimate the distribution of the actual community with [as.ProbaVector](#). If BootstrapMethod = "Chao2013", the distribution is estimated by a single parameter model and unobserved species are given equal probabilities. If BootstrapMethod = "Chao2015", a two-parameter model is used and unobserved species follow a geometric distribution.

Alternatively, the probabilities may be drawn following a classical distribution: either a lognormal ("lnorm") one (Preston, 1948) with given standard deviation (sd; note that the mean is actually a normalizing constant. Its value is set equal to 0 for the simulation of the normal distribution of unnormalized log-abundances), a log-series ("lseries") one (Fisher *et al.*, 1943) with parameter alpha, a geometric ("geom") one (Motomura, 1932) with parameter prob, or a broken stick ("bstick") one (MacArthur, 1957). The number of simulated species is fixed by S, except for "lseries" where it is obtained from alpha and size: $S = \alpha \ln(1 + \frac{size}{\alpha})$.

Log-normal, log-series and broken-stick distributions are stochastic. The geometric distribution is completely determined by its parameters.

Value

A vector of species abundances ([AbdVector](#)) if a single community has been drawn, or a [MetaCommunity](#) containing simulated communities.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Chao, A., Wang, Y. T. and Jost, L. (2013). Entropy and the species accumulation curve: a novel entropy estimator via discovery rates of new species. *Methods in Ecology and Evolution* 4(11): 1091-1100.

Chao, A., Hsieh, T. C., Chazdon, R. L., Colwell, R. K., Gotelli, N. J. (2015) Unveiling the Species-Rank Abundance Distribution by Generalizing Good-Turing Sample Coverage Theory. *Ecology* 96(5): 1189-1201.

Fisher R.A., Corbet A.S., Williams C.B. (1943) The Relation Between the Number of Species and the Number of Individuals in a Random Sample of an Animal Population. *Journal of Animal Ecology* 12: 42-58.

MacArthur R.H. (1957) On the Relative Abundance of Bird Species. *PNAS* 43(3): 293-295.

Marcon, E., Herault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.

Motomura I. (1932) On the statistical treatment of communities. *Zoological Magazine* 44: 379-383.

Preston, F.W. (1948). The commonness, and rarity, of species. *Ecology* 29(3): 254-283.

Reese G. C., Wilson K. R., Flather C. H. (2013) Program SimAssem: Software for simulating species assemblages and estimating species richness. *Methods in Ecology and Evolution* 4: 891-896.

See Also

[SpeciesDistribution](#) and the program SimAssem (Reese *et al.*, 2013; not an R package) for more distributions.

Examples

```
# Generate communities made of 100000 individuals among 300 species and fit them
par(mfrow = c(2,2))
for (d in c("lnorm", "lseries", "geom", "bstick")) {
  rCommunity(n = 1, size = 1E5, S = 300, Distribution = d) -> AbdVec
  plot(AbdVec, Distribution = d, main = d)
}
```

Richness	<i>Number of species of a community</i>
----------	---

Description

Calculates the number of species from probability vector. The name is that of the estimator (the bias correction) used.

Usage

```
Richness(NorP, ...)
bcRichness(Ns, Correction = "Best", Alpha = 0.05, JackOver = FALSE, JackMax = 10,
           CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Richness(NorP, ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Richness(NorP, Correction = "Best", Alpha = 0.05,
         JackOver = FALSE, JackMax = 10,
         Level = NULL, PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy",
         ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Richness(NorP, Correction = "Best", Alpha = 0.05,
         JackOver = FALSE, JackMax = 10,
         Level = NULL, PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy",
         ..., CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Richness(NorP, Correction = "Best", Alpha = 0.05,
         JackOver = FALSE, JackMax = 10,
         Level = NULL, PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy",
         ..., CheckArguments = TRUE, Ps = NULL, Ns = NULL)
```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
Correction	A string containing one of the possible corrections: "None" (no correction), "Jackknife", "iChao1", or "Chao1". "Best", the default value, is currently "Jackknife". Ignored by richness interpolation, and by extrapolation if PCorrection is not "None".
Alpha	The risk level, 5% by default, used to optimize the jackknife order.
JackOver	If TRUE, retain the jackknife order immediately superior to the optimal one, usually resulting in the overestimation of the number of species. Default is FALSE.
JackMax	The highest jackknife order allowed. Default is 10. Allowed values are between 1 and 9.

Level	The level of interpolation or extrapolation. It may be an chosen sample size (an integer) or a sample coverage (a number between 0 and 1). Richness extrapolation require its asymptotic estimation depending on the choice of Correction.
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in <code>as.ProbaVector</code> : "Chao2015" is the default value. If "None", the asymptotic distribution is not estimated and extrapolation relies only on the asymptotic estimator of richness. Used only for extrapolation.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in <code>as.ProbaVector</code> : "geom" (the unobserved species distribution is geometric) is the default value. Used only for extrapolation.
RCorrection	A string containing a correction recognized by <code>Richness</code> to evaluate the total number of species in <code>as.ProbaVector</code> . "Rarefy" is the default value to estimate the number of species such that the entropy of the asymptotic distribution rarefied to the observed sample size equals the observed entropy of the data. Used only for extrapolation.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Bias correction requires the number of individuals. Use `bcRichness` and choose the Correction.

Chao correction techniques are from Chao (1984) and Chiu *et al.* (2015). The Jackknife estimator is calculated by a straight adaptation of the code by Ji-Ping Wang (`jackknife` in package SPECIES). The optimal order is selected according to Burnham and Overton (1978; 1979). The argument `JackOver` allows selecting one order over the optimal one. Many other estimators are available elsewhere, the ones implemented here are necessary for other entropy estimations.

The functions are designed to be used as simply as possible. `Richness` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcRichness` is called.

`Richness` can be estimated at a specified level of interpolation or extrapolation, either a chosen sample size or sample coverage (Chao *et al.*, 2014), rather than its asymptotic value. Extrapolation relies on the estimation of the asymptotic richness. If `PCorrection` is "None", then the asymptotic estimation of richness is made using the chosen Correction, else the asymptotic distribution of the community is derived and its estimated richness adjusted so that the entropy of a sample of this distribution of the size of the actual sample has the entropy of the actual sample.

Value

A named number equal to the estimated number of species. The name is the Correction, except for "SAC" (Species Accumulation Curve) for interpolation.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Burnham, K. P., and Overton, W. S. (1978), Estimation of the Size of a Closed Population When Capture Probabilities Vary Among Animals. *Biometrika*, 65:625-633.
- Burnham, K. P., and Overton, W. S. (1979), Robust Estimation of Population Size When Capture Probabilities Vary Among Animals. *Ecology* 60:927-936.
- Chao, A. (1984) Nonparametric estimation of the number of classes in a population. *Scandinavian Journal of Statistics* 11:265-270.
- Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.
- Chiu, C.-H., Wang, Y.-T., Walther, B. A., Chao, A. (2014) An Improved Nonparametric Lower Bound of Species Richness via a Modified Good-Turing Frequency Formula. *Biometrics* 70(3):671-682.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Number of observed species
Richness(Ps)
# Estimate the actual number of species
bcRichness(Ns, Correction = "Chao1")
bcRichness(Ns, Correction = "iChao1")
bcRichness(Ns, Correction = "Jackknife")
bcRichness(Ns, Correction = "Jackknife", JackOver=TRUE)
# Jackknife estimation is package SPECIES provides confidence interval
SPECIES::jackknife(AbdFreqCount(Ns))
```

Shannon

Shannon entropy of a community

Description

Calculates the Shannon entropy of a probability vector.

Usage

```
Shannon(NorP, ...)
bcShannon(Ns, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
```

```

Shannon(NorP, ..., CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Shannon(NorP, Correction = "Best", Level = NULL,
  PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Shannon(NorP, Correction = "Best", Level = NULL,
  PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Shannon(NorP, Correction = "Best", Level = NULL,
  PCorrection = "Chao2015", Unveiling = "geom", RCorrection = "Rarefy", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
Correction	A string containing one of the possible asymptotic estimators: "None" (no correction), "ChaoShen", "GenCov", "Grassberger", "Grassberger2003", "Schurmann", "Holste", "Bonachela", "Miller", "ZhangHz", "ChaoJost", "Marcon", "UnveilC", "UnveiliC", "UnveilJ" or "Best", the default value. Currently, "Best" is "UnveilJ".
Level	The level of interpolation or extrapolation. It may be an a chosen sample size (an integer) or a sample coverage (a number between 0 and 1). Entropy extrapolation require its asymptotic estimation depending on the choice of Correction. Entropy interpolation relies on the estimation of Abundance Freqence Counts: then, Correction is passed to AbdFreqCount as its Estimator argument.
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in as.ProbaVector : "Chao2015" is the default value. Used only for extrapolation.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in as.ProbaVector : "geom" (the unobserved species distribution is geometric) is the default value. If "None", the asymptotic distribution is not unveiled and only the asymptotic estimator is used. Used only for extrapolation.
RCorrection	A string containing a correction recognized by Richness to evaluate the total number of species in as.ProbaVector . "Rarefy" is the default value to estimate the number of species such that the entropy of the asymptotic distribution rarefied to the observed sample size equals the observed entropy of the data. Used only for extrapolation.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Bias correction requires the number of individuals to estimate sample [Coverage](#).

Correction techniques are from Miller (1955), Chao and Shen (2003), Grassberger (1988), Grassberger (2003), Schurmann (2003), Holste *et al.* (1998), Bonachela *et al.* (2008), Zhang (2012), Chao, Wang and Jost (2013). More estimators can be found in the entropy package.

Using [MetaCommunity](#) mutual information, Chao, Wang and Jost (2013) calculate reduced-bias Shannon beta entropy (see the last example below) with better results than the Chao and Shen estimator, but community weights cannot be arbitrary: they must be proportional to the number of individuals.

The functions are designed to be used as simply as possible. Shannon is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcShannon` is called.

Entropy can be estimated at a specified level of interpolation or extrapolation, either a chosen sample size or sample coverage (Chao *et al.*, 2014), rather than its asymptotic value. Extrapolation relies on the estimation of the asymptotic entropy. If `Unveiling` is "None", then the asymptotic estimation of entropy is made using the chosen `Correction`, else the asymptotic distribution of the community is derived and its estimated richness adjusted so that the entropy of a sample of this distribution of the size of the actual sample has the entropy of the actual sample.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Bonachela, J. A., Hinrichsen, H. and Munoz, M. A. (2008). Entropy estimates of small data sets. *Journal of Physics A: Mathematical and Theoretical* 41(202001): 1-9.
- Chao, A. and Shen, T. J. (2003). Nonparametric estimation of Shannon's index of diversity when there are unseen species in sample. *Environmental and Ecological Statistics* 10(4): 429-443.
- Chao, A., Wang, Y. T. and Jost, L. (2013). Entropy and the species accumulation curve: a novel entropy estimator via discovery rates of new species. *Methods in Ecology and Evolution* 4(11):1091-1100.
- Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.
- Grassberger, P. (1988). Finite sample corrections to entropy and dimension estimates. *Physics Letters A* 128(6-7): 369-373.
- Grassberger, P. (2003). Entropy Estimates from Insufficient Samplings. *ArXiv Physics e-prints* 0307138.
- Holste, D., Grosse, I. and Herzel, H. (1998). Bayes' estimators of generalized entropies. *Journal of Physics A: Mathematical and General* 31(11): 2551-2566.

Miller, G. (1955) Note on the bias of information estimates. In: Quastler, H., editor. *Information Theory in Psychology: Problems and Methods*: 95-100.

Shannon, C. E. (1948). A Mathematical Theory of Communication. *The Bell System Technical Journal* 27: 379-423, 623-656.

Schurmann, T. (2004). Bias analysis in entropy estimation. *Journal of Physics A: Mathematical and Theoretical* 37(27): L295-L301.

Tsallis, C. (1988). Possible generalization of Boltzmann-Gibbs statistics. *Journal of Statistical Physics* 52(1): 479-487.

Zhang, Z. (2012). Entropy Estimation in Turing's Perspective. *Neural Computation* 24(5): 1368-1389.

See Also

[bcShannon, Tsallis](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Calculate Shannon entropy
Shannon(Ps)

# Calculate the best estimator of Shannon entropy
Shannon(Ns)

# Use metacommunity data to calculate reduced-bias Shannon beta as mutual information
(bcShannon(Paracou618.MC$Ns) + bcShannon(colSums(Paracou618.MC$Nsi))
- bcShannon(Paracou618.MC$Nsi))
```

ShannonBeta

Shannon beta entropy of a community

Description

Calculates the Shannon beta entropy of a community belonging to a metacommunity.

Usage

```

ShannonBeta(NorP, NorPexp = NULL, ...)
bcShannonBeta(Ns, Nexp, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
ShannonBeta(NorP, NorPexp = NULL, ...,
  CheckArguments = TRUE, Ps = NULL, Pexp = NULL)
## S3 method for class 'AbdVector'
ShannonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'integer'
ShannonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'numeric'
ShannonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL, Pexp = NULL, Nexp = NULL)

```

Arguments

Ps	The probability vector of species of the community.
Pexp	The probability vector of species of the metacommunity.
Ns	A numeric vector containing species abundances of the community.
Nexp	A numeric vector containing species abundances of the metacommunity.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the community.
NorPexp	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the metacommunity.
Correction	A string containing one of the possible corrections: currently, "ChaoShen" (Marcon <i>et al.</i> , 2012) equivalent to "Best", and "ZhangGrabchak" (Zhang and Grabchak, 2014).
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The derivation of Shannon beta entropy can be found in Marcon *et al.* (2012).

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use `bcShannonBeta` and choose the `Correction`.

The functions are designed to be used as simply as possible. `ShannonBeta` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcShannonBeta` is called. Explicit calls to `bcShannonBeta` (with bias correction) or to `ShannonBeta.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A number equal to the calculated entropy.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Marcon, E., Hérault, B., Baraloto, C. and Lang, G. (2012). The Decomposition of Shannon's Entropy and a Confidence Interval for Beta Diversity. *Oikos* 121(4): 516-522.

Zhang, Z. and Grabchak M. (2014). Nonparametric Estimation of Kullback-Leibler Divergence. *Neural computation* 26(11): 2570-2593.

See Also

[bcShannonBeta](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Probability distribution of the first plot
Ps1 <- as.ProbaVector(Paracou618.MC$Psi[, 1])
# Shannon beta entropy of the plot
ShannonBeta(Ps1, Ps)

# Ns is the vector of abundances of the metacommunity
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Abundances in the first plot
Ns1 <- as.AbdVector(Paracou618.MC$Nsi[, 1])
# Reduced-bias estimator of Shannon beta entropy of the plot
bcShannonBeta(Ns1, Ns)
```

Simpson

Simpson entropy of a community

Description

Calculates the Simpson entropy of a probability vector.

Usage

```

Simpson(NorP, ...)
bcSimpson(Ns, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Simpson(NorP, ..., CheckArguments = TRUE,
        Ps = NULL)
## S3 method for class 'AbdVector'
Simpson(NorP, Correction="Best", Level = NULL, ...,
        CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Simpson(NorP, Correction="Best", Level = NULL, ...,
        CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Simpson(NorP, Correction="Best", Level = NULL, ...,
        CheckArguments = TRUE, Ps = NULL, Ns = NULL)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
Correction	A string containing one of the possible corrections accepted by bcTsallis or "Lande". "Best", the default value, is currently "Jackknife". Ignored by interpolation and extrapolation.
Level	The level of interpolation or extrapolation. It may be an a chosen sample size (an integer) or a sample coverage (a number between 0 and 1).
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Lande's correction has been derived (Lande, 1996; Good, 1953) especially for Simpson entropy, while other corrections are for generalized Tsallis entropy. It is identical to the unbiased estimator proposed by Simpson, although arguments were different. It equals the plug-in estimator multiplied by $n/(n-1)$ where n is the total number of individuals.

Bias correction requires the number of individuals to estimate sample [Coverage](#).

The functions are designed to be used as simply as possible. Simpson is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcSimpson` is called.

Entropy can be estimated at a specified level of interpolation or extrapolation, either a chosen sample size or sample coverage (Chao et al., 2014), rather than its asymptotic value. Simpson's extrapolated entropy estimator does not rely on the estimation of the asymptotic distribution.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.

Good, I. J. (1953). On the Population Frequency of Species and the Estimation of Population Parameters. *Biometrika* 40(3/4): 237-264.

Lande, R. (1996). Statistics and partitioning of species diversity, and similarity among multiple communities. *Oikos* 76: 5-13.

Simpson, E. H. (1949). Measurement of diversity. *Nature* 163(4148): 688.

See Also

[Tsallis](#), [bcSimpson](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Calculate an unbiased estimator of Simpson's index of diversity
Simpson(Ns)
```

SimpsonBeta

Simpson beta entropy of a community

Description

Calculates the Simpson beta entropy of a community belonging to a metacommunity.

Usage

```

SimpsonBeta(NorP, NorPexp = NULL, ...)
bcSimpsonBeta(Ns, Nexp, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
SimpsonBeta(NorP, NorPexp = NULL, ...,
  CheckArguments = TRUE, Ps = NULL, Pexp = NULL)
## S3 method for class 'AbdVector'
SimpsonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'integer'
SimpsonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'numeric'
SimpsonBeta(NorP, NorPexp = NULL, Correction = "Best", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL, Pexp = NULL, Nexp = NULL)

```

Arguments

Ps	The probability vector of species of the community.
Pexp	The probability vector of species of the metacommunity.
Ns	A numeric vector containing species abundances of the community.
Nexp	A numeric vector containing species abundances of the metacommunity.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the community.
NorPexp	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the metacommunity.
Correction	A string containing one of the possible corrections: currently, only "ChaoShen", identical to "Best".
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The derivation of Tsallis beta entropy (Simpson is Tsallis of order 2) can be found in Marcon et al. (2014).

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use `bcSimpsonBeta` and choose the `Correction`.

Note that Simpson beta entropy value is related to Simpson alpha entropy value and cannot be compared across communities (Jost, 2007). Beta entropy of a community is not meaningful in general, do rather calculate the [BetaDiversity](#) of order 2 of the metacommunity.

The functions are designed to be used as simply as possible. `SimpsonBeta` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not

sum to 1, the bias corrected function `bcSimpsonBeta` is called. Explicit calls to `bcSimpsonBeta` (with bias correction) or to `SimpsonBeta.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

Jost (2007), Partitioning diversity into independent alpha and beta components. *Ecology* 88(10): 2427-2439.

Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

See Also

[Simpson](#), [bcSimpsonBeta](#), [BetaDiversity](#)

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ps)
# Probability distribution of the first plot
Ps1 <- as.ProbaVector(Paracou618.MC$Psi[, 1])

# Simpson beta entropy of the plot
SimpsonBeta(Ps1, Ps)
# Transform into diversity
expq(SimpsonBeta(Ps1, Ps)/(1-Simpson(Ps1)), 2)

# Ns is the vector of abundances of the metacommunity
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Abundances in the first plot
Ns1 <- as.AbdVector(Paracou618.MC$Nsi[, 1])
# Reduced-bias Shannon beta entropy of the plot
bcSimpsonBeta(Ns1, Ns)
```

 SimTest

SimTest class

Description

Methods for objects of type "SimTest", used to test a value against its distribution under a simulated null hypothesis.

Usage

```
as.SimTest(RealValue, SimulatedValues)
is.SimTest(x)
## S3 method for class 'SimTest'
autoplot(object, Quantiles = c(0.025, 0.975), ...,
  colValue = "red", colQuantiles = "black", ltyQuantiles = 2,
  main = NULL, xlab = "Simulated Values", ylab = "Density")
## S3 method for class 'SimTest'
plot(x, Quantiles = c(0.025, 0.975), ...,
  colValue = "red", lwdValue = 2, ltyValue = 2,
  colQuantiles = "black", lwdQuantiles = 1, ltyQuantiles = 2,
  main = NULL, xlab = "Simulated Values", ylab = "Density")
## S3 method for class 'SimTest'
summary(object, Quantiles = c(0.025, 0.975), ...)
```

Arguments

x	An object to be tested or plotted.
object	An object.
RealValue	A numeric Value (the actual one).
SimulatedValues	A numeric vector containing the simulated values.
Quantiles	A vector containing the quantiles of interest.
colValue	The color of the line representing the real value on the plot.
lwdValue	The width of the line representing the real value on the plot.
ltyValue	The line type of the line representing the real value on the plot.
colQuantiles	The color of the lines representing the quantiles on the plot.
lwdQuantiles	The width of the lines representing the quantiles on the plot.
ltyQuantiles	The line type of the lines representing the quantiles on the plot.
main	The main title of the plot. if NULL (by default), there is no title.
xlab	The X axis label.
ylab	The Y axis label.
...	Additional arguments to be passed to the generic methods.

Details

Simulated values should be obtained by simulation. The actual value is compared to simulated quantiles. `SimTest` objects can be plotted and summarized.

Value

`SimTest` objects are lists containing:

`RealValue` The value to test.

`SimulatedValues`

A vector of simulated values, whose quantiles will be used for the test.

`is.SimTest` returns TRUE if the object is of class `SimTest`.

`summary.SimTest` returns a summary of the object, including the empirical quantile of the real value in the simulated distributon.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

Examples

```
# Set the value to test
Real <- 0.8
# Is it a realization of a Gaussian distribution?
Sims <- rnorm(1000)
# Make a Simtest object
st <- as.SimTest(Real, Sims)
summary(st)
# Plot
plot(st)
# ggplot
autoplot(st)
```

SpeciesDistribution *Species Distributions.*

Description

A Species Distribution is a (preferably named) vector containing species abundances or probabilities.

Usage

```

as.SpeciesDistribution(x, ...)
## S3 method for class 'data.frame'
as.SpeciesDistribution(x, ...)
## S3 method for class 'integer'
as.SpeciesDistribution(x, ...)
## S3 method for class 'numeric'
as.SpeciesDistribution(x, ...)
## S3 method for class 'SpeciesDistribution'
autoplot(object, ..., Distribution = NULL,
          ylog = TRUE, main = NULL, xlab = "Rank", ylab = NULL)
## S3 method for class 'SpeciesDistribution'
plot(x, ..., Distribution = NULL,
      type = "b", log = "y", main = NULL, xlab = "Rank", ylab = NULL)
is.SpeciesDistribution(x)
as.ProbaVector(x, ...)
## S3 method for class 'data.frame'
as.ProbaVector(x, ...)
## S3 method for class 'integer'
as.ProbaVector(x, Correction = "None", Unveiling = "None",
               RCorrection = "Jackknife", JackOver = FALSE, JackMax = 10,
               CEstimator = "ZhangHuang", q = 0, ..., CheckArguments = TRUE)
## S3 method for class 'numeric'
as.ProbaVector(x, Correction = "None", Unveiling = "None",
               RCorrection = "Jackknife", JackOver = FALSE, JackMax = 10,
               CEstimator = "ZhangHuang", q = 0, ..., CheckArguments = TRUE)
is.ProbaVector(x)
as.AbdVector(x, ...)
## S3 method for class 'data.frame'
as.AbdVector(x, Round = TRUE, ...)
## S3 method for class 'integer'
as.AbdVector(x, ...)
## S3 method for class 'numeric'
as.AbdVector(x, Round = TRUE, ...)
is.AbdVector(x)

```

Arguments

x	An object.
object	An object.
Distribution	The distribution to fit on the plot. May be "lnorm" (log-normal), "lseries" (log-series), "geom" (geometric) or "bstick" (broken stick). If NULL, no distribution is fitted. See rCommunity for the description of these distributions.
Round	If TRUE (by default), values of x are set to integer to create an AbdVector. This is useful if original abundances are not integers (this is often the case for MetaCommunity abundances which are the product of probabilities by the number of individuals) and integer values are required (for example to calculate the bootstrap confidence interval of a community profile).

Correction	A string containing one of the possible corrections to estimate a probability distribution: "None" (no correction, the default value), or "Chao2013", "Chao2015", "ChaoShen" to estimate the probability of the observed species in the asymptotic distribution.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species: "None" (default, no species is added), "unif" (uniform: all unobserved species have the same probability) or "geom" (geometric: the unobserved species distribution is geometric).
RCorrection	A string containing a correction recognized by Richness to evaluate the total number of species. "Jackknife" is the default value. An alternative is "Rarefy" to estimate the number of species such that the entropy of order q of the asymptotic distribution rarefied to the observed sample size equals the actual entropy of the data.
JackOver	If TRUE, retain the jackknife order immediately superior to the optimal one, usually resulting in the overestimation of the number of species. Default is FALSE. Ignored if RCorrection is not "Jackknife".
JackMax	The highest jackknife order allowed. Default is 10. Allowed values are between 1 and 9.
CEstimator	A string containing an estimator recognized by Coverage to evaluate the sample coverage. "ZhangHuang" is the default value.
q	A number: the order of entropy. Default is 0 for richness. Used only to estimate asymptotic probability distributions with RCorrection equal to "Rarefy". Then, the number of unobserved species is fitted so that the entropy of order q of the asymptotic probability distribution at the observed sample size equals the actual entropy of the data.
type	The plot type, see plot .
log	The axis to plot in log scale, e.g. "xy" for both axes. Default is "y".
main	The main title of the plot. if NULL (by default), there is no title.
xlab	The X axis label, "Rank" by default.
ylab	The Y axis label. if NULL (by default), "Probability" or "Abundance" is chosen according to the object class.
ylog	Logical; if TRUE (by default), the Y-axis of the plot is log scaled.
...	Additional arguments to be passed to plot . Unused elsewhere.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

SpeciesDistribution objects include `AbdVector` and `ProbaVector` objects.

`as.AbdVector` just sets the class of the numeric or integer `x` so that appropriate versions of community functions (generic methods such as [Diversity](#)) are applied. Abundance values are rounded (by default) to the nearest integer.

`as.ProbaVector` normalizes the vector so that it sums to 1. If `Correction` is not "None", the observed abundance distribution is used to estimate the actual species distribution. The list of

species will be changed: zero-abundance species will be cleared, and some unobserved species will be added. First, observed species probabilities are estimated following Chao and Shen (2003), *i.e.* input probabilities are multiplied by the sample coverage, or according to more sophisticated models: Chao *et al.* (2013, single-parameter model), or Chao *et al.* (2015, two-parameter model). The total probability of observed species equals the sample coverage. Then, the distribution of unobserved species can be unveiled: their number is estimated according to RCorrection (if the Jackknife estimator is chosen, the JackOver argument allows using the order immediately over the optimal one). The coverage deficit (1 minus the sample coverage) is shared by the unobserved species equally (Unveiling = "unif", Chao *et al.*, 2013) or according to a geometric distribution (Unveiling = "geom", Chao *et al.*, 2015).

These functions can be applied to data frames to calculate the joint diversity (Gregorius, 2010).

SpeciesDistribution objects can be plotted. The plot method returns the estimated parameters of the fitted distribution. The broken stick has no parameter, so the maximum abundance is returned.

Note

Fisher's alpha (Fisher *et al.*, 1943) is estimated to fit the log-series distribution. The estimation is done by the `fisher.alpha` function of package `vegan`. It may differ substantially from the estimation returned by `optimal.theta` from package `untb`.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>, Bruno Hérault <Bruno.Hérault@ecofog.gf>

References

- Chao, A. and Shen, T. J. (2003). Nonparametric estimation of Shannon's index of diversity when there are unseen species in sample. *Environmental and Ecological Statistics* 10(4): 429-443.
- Chao, A., Wang, Y. T. and Jost, L. (2013). Entropy and the species accumulation curve: a novel entropy estimator via discovery rates of new species. *Methods in Ecology and Evolution* 4(11):1091-1100.
- Chao, A., Hsieh, T. C., Chazdon, R. L., Colwell, R. K., Gotelli, N. J. (2015) Unveiling the Species-Rank Abundance Distribution by Generalizing Good-Turing Sample Coverage Theory. *Ecology* 96(5): 1189-1201.
- Fisher R.A., Corbet A.S., Williams C.B. (1943) The Relation Between the Number of Species and the Number of Individuals in a Random Sample of an Animal Population. *Journal of Animal Ecology* 12: 42-58.
- Gregorius H.-R. (2010) Linking Diversity and Differentiation. *Diversity* 2(3): 370-394.

See Also

`rgeom`, `rlnorm`, `rCommunity`, `RAClnorm`

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
```

```

Ns <- as.AbdVector(Paracou618.MC$Ns)
# Whittaker plot, poorly fitted by a log-normal distribution
plot(Ns, Distribution = "lnorm")
# ggplot version
autoplot(Ns, Distribution = "lnorm")

```

Tsallis

Tsallis (HCDT) Entropy of a community

Description

Calculates the HCDT, also known as Tsallis entropy of order q of a probability vector.

Usage

```

Tsallis(NorP, q = 1, ...)
bcTsallis(Ns, q = 1, Correction = "Best", SampleCoverage = NULL,
  CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
Tsallis(NorP, q = 1, ...,
  CheckArguments = TRUE, Ps = NULL)
## S3 method for class 'AbdVector'
Tsallis(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'integer'
Tsallis(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ns = NULL)
## S3 method for class 'numeric'
Tsallis(NorP, q = 1, Correction = "Best", Level = NULL,
  PCorrection="Chao2015", Unveiling="geom", RCorrection="Rarefy", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL)

```

Arguments

Ps	A probability vector, summing to 1.
Ns	A numeric vector containing species abundances.
NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities.
q	A number: the order of entropy. Some corrections allow only a positive number. Default is 1 for Shannon entropy.
Correction	A string containing one of the possible asymptotic estimators: "None" (no correction), "ChaoShen", "GenCov", "Grassberger", "Holste", "Bonachela", "ZhangGrabchak", or "ChaoJost", "Marcon", "UnveilC", "UnveilIc", "UnveilJ" or "Best", the default value. Currently, "Best" is "UnveilJ".

Level	The level of interpolation or extrapolation. It may be an a chosen sample size (an integer) or a sample coverage (a number between 0 and 1).
PCorrection	A string containing one of the possible corrections to estimate a probability distribution in <code>as.ProbaVector</code> : "Chao2015" is the default value. Used only for extrapolation.
Unveiling	A string containing one of the possible unveiling methods to estimate the probabilities of the unobserved species in <code>as.ProbaVector</code> : "geom" (the unobserved species distribution is geometric) is the default value. Used only for extrapolation.
RCorrection	A string containing a correction recognized by <code>Richness</code> to evaluate the total number of species in <code>as.ProbaVector</code> . "Rarefy" is the default value to estimate the number of species such that the entropy of the asymptotic distribution rarefied to the observed sample size equals the observed entropy of the data. Used only for extrapolation.
SampleCoverage	The sample coverage of N_s calculated elsewhere. Used to calculate the gamma diversity of meta-communities, see details.
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

Tsallis (Havrda and Charvat, 1967; Daroczy, 1970; Tsallis, 1988) generalized entropy is a generalized measure of diversity (Jost, 2006).

Bias correction requires the number of individuals to estimate sample `Coverage`.

Correction techniques are from Chao and Shen (2003), Grassberger (1988), Holste *et al.* (1998), Bonachela *et al.* (2008), (Marcon *et al.*, 2014), which is actually the max value of "ChaoShen" and "Grassberger", Zhang and Grabchak (2014), Chao and Jost (2015) and Marcon (2015).

The "ChaoJost" (Chao, Wang and Jost, 2013 for $q = 1$; Chao and Jost, 2015) estimator contains an unbiased part concerning observed species, equal to that of Zhang and Grabchak (2014), and a (biased) estimator of the remaining bias based on the estimation of the species-accumulation curve. It is very efficient but very slow if the number of individuals is more than a few hundreds. This estimator was named "ChaoWangJost" in previous versions of the package; its old name is still supported for backward compatibility.

The unveiled estimators rely on Chao *et al.* (2015), completed by Marcon (2015). The actual probabilities of observed species are estimated and completed by a geometric distribution of the probabilities of unobserved species. The number of unobserved species is estimated by the Chao1 estimator ("UnveilC"), following Chao *et al.* (2015), or by the iChao1 ("UnveiliC") or the jackknife ("UnveilJ"). The "UnveilJ" correction often has a lower bias but a greater variance (Marcon, 2015). It is a good first choice thanks to the versatility of the jackknife estimator of richness.

The functions are designed to be used as simply as possible. Tsallis is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcTsallis` is called.

The size of a metacommunity (see `MetaCommunity`) is unknown so it has to be set according to a rule which does not ensure that its abundances are integer values. Then, classical bias-correction

methods do not apply. Providing the `SampleCoverage` argument allows applying the "ChaoShen" and "Grassberger" corrections to estimate quite well the entropy. `DivPart` and `GammaEntropy` functions use this tweak.

Entropy can be estimated at a specified level of interpolation or extrapolation, either a chosen sample size or sample coverage (Chao et al., 2014), rather than its asymptotic value. Special cases $q=0$, $q=1$ or $q=2$ are treated by `Richness`, `Shannon` and `Simpson` functions. For extrapolation of entropy of other values of q , the asymptotic distribution of the community must be estimated by `as.ProbaVector`. The default arguments allow joining smoothly the extrapolated entropy and the observed entropy by estimating the number of unobserved species so that the entropy of the observed distribution equals the entropy of the asymptotic distribution rarefied to the actual sample size.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Chao, A., Gotelli, N. J., Hsieh, T. C., Sander, E. L., Ma, K. H., Colwell, R. K., Ellison, A. M. (2014). Rarefaction and extrapolation with Hill numbers: A framework for sampling and estimation in species diversity studies. *Ecological Monographs*, 84(1): 45-67.
- Chao, A. and Jost, L. (2015) Estimating diversity and entropy profiles via discovery rates of new species. *Methods in Ecology and Evolution* 6(8): 873-882.
- Chao, A., Hsieh, T. C., Chazdon, R. L., Colwell, R. K., Gotelli, N. J. (2015) Unveiling the Species-Rank Abundance Distribution by Generalizing Good-Turing Sample Coverage Theory. *Ecology* 96(5): 1189-1201.
- Chao, A., Wang, Y. T. and Jost, L. (2013). Entropy and the species accumulation curve: a novel entropy estimator via discovery rates of new species. *Methods in Ecology and Evolution* 4(11):1091-1100.
- Havrda, J. and Charvat, F. (1967). Quantification method of classification processes. Concept of structural α -entropy. *Kybernetika* 3(1): 30-35.
- Daroczy, Z. (1970). Generalized information functions. *Information and Control* 16(1): 36-51.
- Jost, L. (2006). Entropy and diversity. *Oikos* 113(2): 363-375.
- Marcon, E. (2015) Practical Estimation of Diversity from Abundance Data. *HAL* 01212435: 1-27.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.
- Tsallis, C. (1988). Possible generalization of Boltzmann-Gibbs statistics. *Journal of Statistical Physics* 52(1): 479-487.
- Zhang, Z., and Grabchak, M. (2016). Entropic Representation and Estimation of Diversity Indices. *Journal of Nonparametric Statistics*, 28(3): 563-575.

Examples

```

# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ns is the total number of trees per species
Ns <- as.AbdVector(Paracou618.MC$Ns)
# Species probabilities
Ps <- as.ProbaVector(Paracou618.MC$Ns)
# Whittaker plot
plot(Ns)

# Calculate entropy of order 1, i.e. Shannon's entropy
Tsallis(Ps, 1)
# Calculate it with estimation bias correction
Tsallis(Ns, 1)

```

TsallisBeta

Tsallis beta entropy of a community

Description

Calculates the Tsallis beta entropy of order q of a community belonging to a metacommunity.

Usage

```

TsallisBeta(NorP, NorPexp = NULL, q = 1, ...)
bcTsallisBeta(Ns, Nexp = NULL, q, Correction = "Best", CheckArguments = TRUE)
## S3 method for class 'ProbaVector'
TsallisBeta(NorP, NorPexp = NULL, q = 1, ...,
  CheckArguments = TRUE, Ps = NULL, Pexp = NULL)
## S3 method for class 'AbdVector'
TsallisBeta(NorP, NorPexp = NULL, q = 1, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'integer'
TsallisBeta(NorP, NorPexp = NULL, q = 1, Correction = "Best", ...,
  CheckArguments = TRUE, Ns = NULL, Nexp = NULL)
## S3 method for class 'numeric'
TsallisBeta(NorP, NorPexp = NULL, q = 1, Correction = "Best", ...,
  CheckArguments = TRUE, Ps = NULL, Ns = NULL, Pexp = NULL, Nexp = NULL)

```

Arguments

Ps	The probability vector of species of the community.
Pexp	The probability vector of species of the metacommunity.
Ns	A numeric vector containing species abundances of the community.
Nexp	A numeric vector containing species abundances of the metacommunity.

NorP	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the community.
NorPexp	A numeric vector, an integer vector, an abundance vector (AbdVector) or a probability vector (ProbaVector). Contains either abundances or probabilities of the metacommunity.
q	A number: the order of entropy. Default is 1 for Shannon entropy.
Correction	A string containing one of the possible corrections: currently, only "ChaoShen" or "None". "Best" is the default value, it is equivalent to "ChaoShen".
...	Additional arguments. Unused.
CheckArguments	Logical; if TRUE, the function arguments are verified. Should be set to FALSE to save time when the arguments have been checked elsewhere.

Details

The derivation of Tsallis beta entropy can be found in Marcon et al. (2014).

Bias correction requires the number of individuals to estimate sample [Coverage](#). Use `bcTsallisBeta` and choose the `Correction`.

Note that beta entropy value is related to alpha entropy (if q is not 1) and cannot be compared across communities (Jost, 2007). Beta entropy of a community is not meaningful in general, do rather calculate the [BetaDiversity](#) of the metacommunity.

The functions are designed to be used as simply as possible. `TsallisBeta` is a generic method. If its first argument is an abundance vector, an integer vector or a numeric vector which does not sum to 1, the bias corrected function `bcTsallisBeta` is called. Explicit calls to `bcTsallisBeta` (with bias correction) or to `TsallisBeta.ProbaVector` (without correction) are possible to avoid ambiguity. The `.integer` and `.numeric` methods accept `Ps` or `Ns` arguments instead of `NorP` for backward compatibility.

Value

A named number equal to the calculated entropy. The name is that of the bias correction used.

Author(s)

Eric Marcon <Eric.Marcon@ecofog.gf>

References

- Jost (2007), Partitioning diversity into independent alpha and beta components. *Ecology* 88(10): 2427-2439.
- Marcon, E., Scotti, I., Herault, B., Rossi, V. and Lang, G. (2014). Generalization of the partitioning of Shannon diversity. *PLOS One* 9(3): e90289.

Examples

```
# Load Paracou data (number of trees per species in two 1-ha plot of a tropical forest)
data(Paracou618)
# Ps is the vector of probabilities
Ps <- Paracou618.MC$Ps
# Probability distribution of the first plot
Ps1 <- Paracou618.MC$Psi[, 1]
# Divergence of order 2 between plot 1 and the whole forest
TsallisBeta(Ps1, Ps, 2)

# Ns is the vector of abundances of the metacommunity
Ns <- Paracou618.MC$Ns
# Abundances in the first plot
Ns1 <- Paracou618.MC$Nsi[, 1]
# Divergence of order 2 between plot 1 and the whole forest, with bias correction
bcTsallisBeta(Ns1, Ns, 2)
```

Index

*Topic **datasets**

EightSpAbundance, [34](#)
EightSpTree, [34](#)
Paracou618.dist, [59](#)
Paracou618.Functional, [60](#)
Paracou618.MC, [61](#)
Paracou618.Taxonomy, [61](#)

*Topic **package**

entropart-package, [3](#)

AbdFreqCount, [4](#), [84](#)
AbdVector, [22](#), [23](#), [32](#), [42](#), [44](#), [46](#), [48](#), [66](#), [68](#),
[71](#), [77](#), [80](#), [81](#), [84](#), [87](#), [89](#), [91](#), [98](#), [102](#)
AbdVector (SpeciesDistribution), [94](#)
Accumulation, [6](#)
AllenH, [9](#), [17](#)
AlphaDiversity, [10](#)
AlphaEntropy, [10](#), [11](#), [12](#), [27](#), [29](#), [39](#)
as.AbdVector, [3](#)
as.AbdVector (SpeciesDistribution), [94](#)
as.AccumCurve (Accumulation), [6](#)
as.CommunityProfile (CommunityProfile),
[18](#)
as.ProbaVector, [3](#), [5](#), [7](#), [22](#), [23](#), [79](#), [82](#), [84](#),
[99](#), [100](#)
as.ProbaVector (SpeciesDistribution), [94](#)
as.SimTest (SimTest), [93](#)
as.SpeciesDistribution
(SpeciesDistribution), [94](#)
autoplot.AccumCurve (Accumulation), [6](#)
autoplot.CommunityProfile
(CommunityProfile), [18](#)
autoplot.DivEst (DivEst), [24](#)
autoplot.DivPart (DivPart), [26](#)
autoplot.DivProfile (DivProfile), [29](#)
autoplot.MCdiversity (MCdiversity), [53](#)
autoplot.MCentropy (MCentropy), [55](#)
autoplot.PhyloValue (PhyloValue), [73](#)
autoplot.SimTest (SimTest), [93](#)

autoplot.SpeciesDistribution
(SpeciesDistribution), [94](#)

bcDiversity (Diversity), [22](#)
bcDqz (Dqz), [32](#)
bcGenSimpson (GenSimpson), [41](#)
bcGenSimpsonD (GenSimpson), [41](#)
bcHqz, [12](#), [40](#)
bcHqz (Hqz), [43](#)
bcHqzBeta, [15](#)
bcHqzBeta (HqzBeta), [46](#)
bcHurlbert (Hurlbert), [48](#)
bcHurlbertD (Hurlbert), [48](#)
bcPhyloBetaEntropy, [15](#), [67](#)
bcPhyloBetaEntropy (PhyloBetaEntropy),
[65](#)
bcPhyloDiversity, [62](#), [63](#), [78](#)
bcPhyloDiversity (PhyloDiversity), [67](#)
bcPhyloEntropy, [12](#), [36](#), [40](#), [41](#)
bcPhyloEntropy (PhyloEntropy), [70](#)
bcRao (Rao), [77](#)
bcRichness (Richness), [81](#)
bcShannon, [36](#), [86](#)
bcShannon (Shannon), [83](#)
bcShannonBeta, [88](#)
bcShannonBeta (ShannonBeta), [86](#)
bcSimpson, [36](#), [90](#)
bcSimpson (Simpson), [88](#)
bcSimpsonBeta, [92](#)
bcSimpsonBeta (SimpsonBeta), [90](#)
bcTsallis, [12](#), [13](#), [36](#), [40](#), [41](#), [77](#), [89](#)
bcTsallis (Tsallis), [98](#)
bcTsallisBeta, [13](#), [15](#), [16](#)
bcTsallisBeta (TsallisBeta), [101](#)
beta, [35](#)
BetaDiversity, [13](#), [15](#), [16](#), [47](#), [91](#), [92](#), [102](#)
BetaEntropy, [14](#), [15](#), [27](#), [29](#)

CEnvelope (CommunityProfile), [18](#)
ChaoPD, [6](#), [9](#), [10](#), [16](#), [19](#)

- CommunityProfile, [18](#), [37](#), [38](#), [51](#)
 Coverage, [20](#), [23](#), [62](#), [66](#), [69](#), [71](#), [85](#), [87](#), [89](#),
 [91](#), [96](#), [99](#), [102](#)
 Coverage2Size (Coverage), [20](#)
 dist, [58](#), [59](#)
 DivAC (Accumulation), [6](#)
 Diversity, [3](#), [8](#), [22](#), [70](#), [96](#)
 DivEst, [4](#), [24](#)
 DivPart, [4](#), [24–26](#), [26](#), [31](#), [40](#), [45](#), [72](#), [100](#)
 DivProfile, [4](#), [28](#), [29](#)
 Dqz, [3](#), [32](#), [33](#), [44](#), [45](#), [58](#)

 EightSpAbundance, [34](#)
 EightSpTree, [34](#)
 Enq, [35](#)
 EntAC (Accumulation), [6](#)
 entropart (entropart-package), [3](#)
 entropart-package, [3](#)
 EntropyCI, [36](#)
 expq, [23](#), [37](#), [38](#), [52](#)

 fisher.alpha, [76](#), [97](#)

 GammaDiversity, [38](#)
 GammaEntropy, [27](#), [29](#), [39](#), [40](#), [45](#), [72](#), [100](#)
 GenSimp.z, [43](#)
 GenSimpson, [3](#), [41](#)
 GenSimpsonD (GenSimpson), [41](#)
 ggarrange, [25](#), [30](#)

 hclust, [9](#), [10](#), [12](#), [13](#), [15](#), [16](#), [25](#), [27](#), [29](#), [39](#),
 [40](#), [60](#), [62](#), [64](#), [66](#), [68](#), [71](#), [74](#), [77](#)
 Hqz, [33](#), [43](#)
 HqzBeta, [46](#)
 Hurlbert, [3](#), [48](#)
 HurlbertD (Hurlbert), [48](#)

 is.AbdVector (SpeciesDistribution), [94](#)
 is.AccumCurve (Accumulation), [6](#)
 is.CommunityProfile (CommunityProfile),
 [18](#)
 is.DivEst (DivEst), [24](#)
 is.DivPart (DivPart), [26](#)
 is.DivProfile (DivProfile), [29](#)
 is.MCdiversity (MCdiversity), [53](#)
 is.MCentropy (MCentropy), [55](#)
 is.MetaCommunity (MetaCommunity), [56](#)
 is.PhyloDiversity (PhyloDiversity), [67](#)
 is.PhyloEntropy (PhyloEntropy), [70](#)

 is.PhyloValue (PhyloValue), [73](#)
 is.PPtree (PPtree), [74](#)
 is.ProbaVector (SpeciesDistribution), [94](#)
 is.SimTest (SimTest), [93](#)
 is.SpeciesDistribution
 (SpeciesDistribution), [94](#)

 jackknife, [82](#)

 KLq, [50](#)

 list, [53](#)
 lnq, [51](#)

 MC Utilities, [52](#)
 MCdiversity, [11](#), [14](#), [53](#)
 MCentropy, [12](#), [15](#), [55](#)
 MergeC (MC Utilities), [52](#)
 MergeMC (MC Utilities), [52](#)
 MetaCommunity, [4](#), [10](#), [12](#), [13](#), [15](#), [24](#), [26](#), [27](#),
 [29](#), [30](#), [39](#), [40](#), [45](#), [53–55](#), [56](#), [61](#), [71](#),
 [80](#), [85](#), [95](#), [99](#)

 Optimal.Similarity, [58](#)

 Paracou618.dist, [59](#), [60](#)
 Paracou618.Functional, [60](#)
 Paracou618.MC, [61](#)
 Paracou618.Taxonomy, [61](#)
 PDFD, [62](#)
 phylo, [9](#), [10](#), [12](#), [13](#), [15](#), [16](#), [25](#), [27](#), [29](#), [39](#), [40](#),
 [62](#), [64](#), [66](#), [68](#), [71](#), [74](#), [75](#), [77](#)
 PhyloApply, [63](#), [66](#), [71](#), [73](#)
 PhyloBetaEntropy, [65](#)
 PhyloDiversity, [3](#), [17](#), [33](#), [64](#), [66](#), [67](#), [67](#), [72](#),
 [73](#)
 PhyloEntropy, [3](#), [6](#), [9](#), [10](#), [45](#), [64](#), [66](#), [70](#), [70](#),
 [73](#)
 phylog, [9](#), [10](#), [12](#), [13](#), [15](#), [16](#), [25](#), [27](#), [29](#), [34](#),
 [39](#), [40](#), [62](#), [64](#), [66](#), [68](#), [71](#), [75](#), [77](#)
 PhyloValue, [40](#), [73](#)
 plot, [7](#), [73](#), [96](#)
 plot.AccumCurve (Accumulation), [6](#)
 plot.CommunityProfile
 (CommunityProfile), [18](#)
 plot.DivEst (DivEst), [24](#)
 plot.DivPart (DivPart), [26](#)
 plot.DivProfile (DivProfile), [29](#)
 plot.MCdiversity (MCdiversity), [53](#)
 plot.MCentropy (MCentropy), [55](#)

plot.MetaCommunity (MetaCommunity), 56
plot.PhyloValue, 69, 72
plot.PhyloValue (PhyloValue), 73
plot.PPtree (PPtree), 74
plot.SimTest (SimTest), 93
plot.SpeciesDistribution, 76
plot.SpeciesDistribution
 (SpeciesDistribution), 94
PPtree, 9, 10, 12, 13, 15, 16, 25, 27, 29, 39,
 40, 62, 64, 66, 68, 71, 74, 77
Preprocess.Tree, 64, 65
ProbaVector, 22, 23, 32, 42, 44, 46, 48, 66,
 68, 71, 77, 81, 84, 87, 89, 91, 98, 102
ProbaVector (SpeciesDistribution), 94

RAC, 75
RACbstick (RAC), 75
RACgeom (RAC), 75
RAClnorm, 97
RAClnorm (RAC), 75
RAClseries (RAC), 75
Rao, 3, 77
rCommunity, 3, 18, 19, 36, 76, 78, 95, 97
rgeom, 76, 97
Richness, 5, 7, 23, 81, 82, 84, 96, 99, 100
rlnorm, 76, 97

Shannon, 3, 83, 100
ShannonBeta, 86
ShuffleMC (MC Utilities), 52
Simpson, 3, 88, 92, 100
SimpsonBeta, 90
SimTest, 93
SpeciesDistribution, 80, 94
summary.DivEst (DivEst), 24
summary.DivPart (DivPart), 26
summary.DivProfile (DivProfile), 29
summary.MCdiversity (MCdiversity), 53
summary.MCentropy (MCentropy), 55
summary.MetaCommunity (MetaCommunity),
 56
summary.PhyloDiversity
 (PhyloDiversity), 67
summary.PhyloEntropy (PhyloEntropy), 70
summary.PhyloValue (PhyloValue), 73
summary.SimTest (SimTest), 93

Tsallis, 3, 7, 8, 12, 19, 23, 71, 72, 86, 90, 98
TsallisBeta, 51, 66, 67, 101