

Package ‘extrafrail’

September 26, 2022

Type Package

Title Estimation and Additional Tools for Alternative Shared Frailty Models

Version 1.2

Date 2022-09-26

Author Diego Gallardo [aut, cre],
Marcelo Bourguignon [aut]

Maintainer Diego Gallardo <diego.gallardo@uda.cl>

Description Provide estimation and data generation tools for some new multivariate frailty models. This version includes the gamma, inverse Gaussian and weighted Lindley as the distribution for the frailty terms. For the basal model, it is considered a parametric approach based on the Weibull distribution and a semiparametric approach. For details, see Gallardo and Bourguignon (2022) <[arXiv:2206.12973](https://arxiv.org/abs/2206.12973)>.

Depends R (>= 4.0.0), stats

Imports survival, pracma, expint

Suggests frailtypack

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2022-09-26 21:10:02 UTC

R topics documented:

baseCH	2
frailty.fit	3
rWL	4
tools.extrafrail	5

Index	7
--------------	----------

baseCH*Computes the baseline cumulative hazard function.*

Description

Provides the baseline cumulative hazard function (Λ_0) for an object with `extrafrail` class.

Usage

```
baseCH(t, fit)
```

Arguments

<code>t</code>	the vector of times for which the baseline cumulative hazard function should be computed.
<code>fit</code>	an object with <code>extrafrail</code> class.

Details

Provides the baseline cumulative hazard function. When the baseline distribution is assumed as the Weibull model, this function is $\Lambda_0(t) = \lambda t^p$.

Value

a vector with the same length that `t`, including the baseline cumulative hazard function related to `t`.

Author(s)

Diego Gallardo and Marcelo Bourguignon.

References

Gallardo, D.I., Bourguignon, M. (2022) The multivariate weighted Lindley frailty model for cluster failure time data. Submitted.

Examples

```
#require(frailtypack)
require(survival)
data(readmission, package="frailtypack")
#Example for WL frailty model
fit.WL <- frailty.fit(survival::Surv(time, event) ~ dukes + survival::cluster(id),
  dist.frail="WL", data = readmission)
baseCH(c(500,1000,1500),fit.WL)
```

frailty.fit	<i>Fitted different shared frailty models</i>
-------------	---

Description

frailty.fit computes the maximum likelihood estimates based on the EM algorithm for the shared gamma, inverse gaussian and weighted Lindley frailty models.

Usage

```
frailty.fit(formula, data, dist.frail="gamma", dist = "np", prec = 1e-04,
            max.iter = 1000)
```

Arguments

formula	A formula that contains on the left hand side an object of the type Surv and on the right hand side a +cluster(id) statement, possibly with the covariates definition.
data	A data.frame in which the formula argument can be evaluated
dist.frail	the distribution assumed for the frailty. Supported values: gamma, IG (inverse gaussian) and WL (weighted Lindley).
dist	the distribution assumed for the basal model. Supported values: weibull and np (non-parametric).
prec	The convergence tolerance for parameters.
max.iter	The maximum number of iterations.

Details

For the weibull distribution as the basal model, the M1-step is performed using the optim function. For the non-parametric case, the M1-step is based on the coxph function from the survival package.

Value

an object of class "extrafrail" is returned. The object returned for this functions is a list containing the following components:

coefficients	A named vector of coefficients
se	A named vector of the standard errors for the estimated coefficients.
t	The vector of times.
delta	The failure indicators.
id	A variable indicating the cluster which belongs each observation.
x	The regressor matrix based on cov.formula (without intercept term).
dist	The distribution assumed for the basal model.
dist.frail	The distribution assumed for the frailty variable.
tau	The Kendall's tau coefficient.

logLik	The log-likelihood function (only when the Weibull model is specified for the basal distribution).
Lambda0	The observed times and the associated cumulative hazard function (only when the non-parametric option is specified for the basal distribution)

Author(s)

Diego Gallardo and Marcelo Bourguignon.

References

Gallardo, D.I., Bourguignon, M. (2022) The shared weighted Lindley frailty model for cluster failure time data. Submitted.

Examples

```
require(survival)
#require(frailtypack)
data(readmission, package="frailtypack")
#Fit for WL frailty model
fit.WL <- frailty.fit(survival::Surv(time, event) ~ dukes + survival::cluster(id),
  dist.frail="WL", data = readmission)
summary(fit.WL)
#Fit for gamma frailty model
fit.GA <- frailty.fit(survival::Surv(time, event) ~ dukes + survival::cluster(id),
  dist.frail="gamma", data = readmission)
summary(fit.GA)
```

rWL

Generated random variables from the weighted Lindley distribution.

Description

Generated random variables from the weighted Lindley distribution with mean 1.

Usage

```
rWL(n, theta = 1)
```

Arguments

n	number of observations. If length(n) > 1, the length is taken to be the number required.
theta	variance of the variable.

Details

The weighted Lindley distribution has probability density function

$$f(z; \theta) = \frac{\theta}{2\Gamma(\theta)} a_{\theta}^{-b_{\theta}-1} z^{b_{\theta}-1} (1+z) \exp\left(-\frac{z}{a_{\theta}}\right), \quad z, \theta > 0,$$

where $a_{\theta} = \frac{\theta(\theta+4)}{2(\theta+2)}$ and $b_{\theta} = \frac{4}{\theta(\theta+4)}$. Under this parametrization, $E(Z)=1$ and $\text{Var}(Z)=\theta$.

Value

a vector of length n with the generated values.

Author(s)

Diego Gallardo and Marcelo Bourguignon.

References

Gallardo, D.I., Bourguignon, M. (2022) The multivariate weighted Lindley frailty model for cluster failure time data. Submitted.

Examples

```
rWL(10, theta=0.5)
```

```
tools.extrafrail
```

Print a summary for a object of the "extrafrail" class.

Description

Summarizes the results for a object of the "extrafrail" class.

Usage

```
## S3 method for class 'extrafrail'
summary(object, ...)
```

Arguments

```
object      an object of the "extrafrail" class.
...         for extra arguments.
```

Details

Supported frailty models are: - gamma frailty model - inverse gaussian frailty model - weighted frailty model

Value

A complete summary for the coefficients extracted from a "extrafrail" object.

Author(s)

Diego Gallardo and Marcelo Bourguignon.

References

Gallardo and Bourguignon (2022).

Examples

```
#require(frailtypack)
require(survival)
data(readmission, package="frailtypack")
fit <- frailty.fit(survival::Surv(time, event) ~ dukes + survival::cluster(id),
  dist.frail="WL", data = readmission)
summary(fit)
```

Index

`baseCH`, [2](#)

`frailty.fit`, [3](#)

`print.extrafrail (tools.extrafrail)`, [5](#)

`rWL`, [4](#)

`summary.extrafrail (tools.extrafrail)`, [5](#)

`tools.extrafrail`, [5](#)