

Package ‘lgr’

October 20, 2020

Type Package

Title A Fully Featured Logging Framework

Version 0.4.1

Maintainer Stefan Fleck <stefan.b.fleck@gmail.com>

Description A flexible, feature-rich yet light-weight logging framework based on 'R6' classes. It supports hierarchical loggers, custom log levels, arbitrary data fields in log events, logging to plaintext, 'JSON', (rotating) files, memory buffers. For extra appenders that support logging to databases, email and push notifications see the the package lgr.app.

License MIT + file LICENSE

URL <https://s-fleck.github.io/lgr/>

BugReports <https://github.com/s-fleck/lgr/issues/>

Depends R (>= 3.2.0)

Imports R6 (>= 2.4.0)

Suggests cli, covr, crayon, data.table, desc, future, future.apply, glue, jsonlite, knitr, rmarkdown, rotor (>= 0.3.0), rprojroot, testthat, tibble, tools, utils, whoami, yaml

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1.9000

Collate 'Filterable.R' 'utils-sfmisc.R' 'utils.R' 'Appender.R'
'Filter.R' 'log_levels.R' 'LogEvent.R' 'Layout.R' 'Logger.R'
'basic_config.R' 'default_functions.R' 'event_list.R'
'get_logger.R' 'lgr-package.R' 'logger_config.R'
'logger_tree.R' 'read_json_lines.R' 'simple_logging.R'
'use_logger.R' 'utils-formatting.R' 'utils-logging.R'
'utils-rd.R' 'utils-rotor.R'

NeedsCompilation no

Author Stefan Fleck [aut, cre] (<<https://orcid.org/0000-0003-3344-9851>>)

Repository CRAN

Date/Publication 2020-10-20 20:00:06 UTC

R topics documented:

AppenderBuffer	3
AppenderConsole	5
AppenderFile	6
AppenderFileRotating	9
AppenderFileRotatingDate	11
AppenderFileRotatingTime	12
AppenderMemory	14
AppenderTable	16
as.data.frame.LogEvent	17
basic_config	19
CannotInitializeAbstractClassError	21
colorize_levels	21
default_exception_handler	22
EventFilter	23
event_list	24
Filterable	26
FilterForceLevel	27
FilterInject	28
get_caller	29
get_logger	30
get_log_levels	31
is_filter	32
label_levels	33
Layout	33
LayoutFormat	35
LayoutGlue	38
LayoutJson	39
LogEvent	41
Logger	43
LoggerGlue	50
logger_config	52
logger_tree	53
pad_right	54
print.Appender	55
print.LogEvent	55
print.Logger	57
print.logger_tree	58
read_json_lines	59
simple_logging	59
standardize_threshold	61
suspend_logging	63

<i>AppenderBuffer</i>	3
toString.LogEvent	64
use_logger	64
with_log_level	65
Index	67

AppenderBuffer *Log to a memory buffer*

Description

An Appender that Buffers LogEvents in-memory and and redirects them to other Appenders once certain conditions are met.

Fields

- appenders, set_appenders() Like for a [Logger](#). Buffered events will be passed on to these Appenders once a flush is triggered
- flush_on_exit, set_flush_on_exit(x) TRUE or FALSE: Whether the buffer should be flushed when the Appender is garbage collected (f.e when you close R)
- flush_on_rotate, set_flush_on_rotate TRUE or FALSE: Whether the buffer should be flushed when the Buffer is full (f.e when you close R). Setting this to off can have slightly negative performance impacts.

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> [lgr::AppenderMemory](#) -> AppenderBuffer

Methods

Public methods:

- [AppenderBuffer\\$new\(\)](#)
- [AppenderBuffer\\$flush\(\)](#)
- [AppenderBuffer\\$clear\(\)](#)
- [AppenderBuffer\\$set_appenders\(\)](#)
- [AppenderBuffer\\$add_appender\(\)](#)
- [AppenderBuffer\\$remove_appender\(\)](#)
- [AppenderBuffer\\$format\(\)](#)

Method new(): The [Layout](#) for this Appender is used only to format console output of its \$show() method.

Usage:

```

AppenderBuffer$new(
  threshold = NA_integer_,
  layout = LayoutFormat$new(fmt = "%L [%t] %m", timestamp_fmt = "%H:%M:%S",
    colors = getOption("lgr.colors")),
  appenders = NULL,
  buffer_size = 1000,
  flush_threshold = NULL,
  flush_on_exit = TRUE,
  flush_on_rotate = TRUE,
  should_flush = NULL,
  filters = NULL
)

```

Method `flush()`: Sends the buffer's contents to all attached Appenders and then clears the Buffer

Usage:

```
AppenderBuffer$flush()
```

Method `clear()`: Clears the buffer, discarding all buffered Events

Usage:

```
AppenderBuffer$clear()
```

Method `set_appenders()`: Exactly like A [Logger](#), an [AppenderBuffer](#) can have an arbitrary amount of Appenders attached. When the buffer is flushed, the buffered events are dispatched to these Appenders.

Usage:

```
AppenderBuffer$set_appenders(x)
```

Arguments:

x single [Appender](#) or a list thereof. Appenders control the output of a Logger. Be aware that a Logger also inherits the Appenders of its ancestors (see vignette("lgr", package = "lgr") for more info about Logger inheritance).

Method `add_appender()`: Add an Appender to the AppenderBuffer

Add or remove an [Appender](#). Supplying a name is optional but recommended. After adding an Appender with `appender$add_appender(AppenderConsole$new(), name = "console")` you can refer to it via `appender$appenders$console`. `remove_appender()` can remove an Appender by position or name.

Usage:

```
AppenderBuffer$add_appender(appender, name = NULL)
```

Arguments:

appender a single [Appender](#)

name a character scalar. Optional but recommended.

Method `remove_appender()`: remove an appender

Usage:

```
AppenderBuffer$remove_appender(pos)
```

Arguments:

pos integer index or character name of the Appender(s) to remove

Method format():*Usage:*

```
AppenderBuffer$format(...)
```

See Also

[LayoutFormat](#)

Other Appenders: [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderFile](#), [AppenderTable](#), [Appender](#)

AppenderConsole	<i>Log to the console</i>
-----------------	---------------------------

Description

An Appender that outputs to the R console. If you have the package **crayon** installed log levels will be coloured by default (but you can modify this behaviour by passing a custom [Layout](#)).

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> AppenderConsole

Methods**Public methods:**

- [AppenderConsole\\$new\(\)](#)
- [AppenderConsole\\$append\(\)](#)

Method new():*Usage:*

```
AppenderConsole$new(  
  threshold = NA_integer_,  
  layout = LayoutFormat$new(fmt = "%L [%t] %m %f", timestamp_fmt = "%H:%M:%OS3",  
    colors = getOption("lgr.colors", list())),  
  filters = NULL  
)
```

Method append():*Usage:*

```
AppenderConsole$append(event)
```

See Also[LayoutFormat](#)Other Appenders: [AppenderBuffer](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderFile](#), [AppenderTable](#), [Appender](#)**Examples**

```
# create a new logger with propagate = FALSE to prevent routing to the root
# logger. Please look at the section "Logger Hierarchies" in the package
# vignette for more info.
lg <- get_logger("test")$set_propagate(FALSE)

lg$add_appender(AppenderConsole$new())
lg$add_appender(AppenderConsole$new(
  layout = LayoutFormat$new("[%t] %c(): [%n] %m", colors = getOption("lgr.colors"))))

# Will output the message twice because we attached two console appenders
lg$warn("A test message")
lg$config(NULL) # reset config
```

AppenderFile*Log to a file*

Description

A simple Appender that outputs to a file in the file system. If you plan to log to text files, consider logging to JSON files and take a look at [AppenderJson](#), which is a shortcut for AppenderFile preconfigured with [LayoutJson](#).

Super classes

```
lgr::Filterable -> lgr::Appender -> AppenderFile
```

Active bindings

file character scalar. path to the log file

data character scalar. Contents of file parsed to a data.frame if used with a [Layout](#) that supports parsing of log file data (notably [LayoutJson](#)).

data character scalar. Like \$data, but returns a data.table instead (requires the **data.table** package).

Methods**Public methods:**

- [AppenderFile\\$new\(\)](#)
- [AppenderFile\\$append\(\)](#)

- [AppenderFile\\$set_file\(\)](#)
- [AppenderFile\\$show\(\)](#)

Method new():*Usage:*

```
AppenderFile$new(
  file,
  threshold = NA_integer_,
  layout = LayoutFormat$new(),
  filters = NULL
)
```

Method append():*Usage:*

```
AppenderFile$append(event)
```

Method set_file(): Set a log file*Usage:*

```
AppenderFile$set_file(file)
```

Arguments:

file character scalar. Path to the log file. If file does not exist it will be created.

Method show(): Display the contents of the log file.*Usage:*

```
AppenderFile$show(threshold = NA_integer_, n = 20L)
```

Arguments:

threshold character or integer scalar. The minimum log level that should be displayed.

n integer scalar. Show only the last n log entries that match threshold.

Super classes

```
lgr::Filterable -> lgr::Appender -> lgr::AppenderFile -> AppenderJson
```

Methods**Public methods:**

- [AppenderJson\\$new\(\)](#)

Method new():*Usage:*

```
AppenderJson$new(
  file,
  threshold = NA_integer_,
  layout = LayoutJson$new(),
  filters = NULL
)
```

See Also

[LayoutFormat](#), [LayoutJson](#)

[LayoutFormat](#), [LayoutJson](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderTable](#), [Appender](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderTable](#), [Appender](#)

Examples

```
lg <- get_logger("test")
default <- tempfile()
fancy <- tempfile()
json <- tempfile()

lg$add_appender(AppenderFile$new(default), "default")
lg$add_appender(
  AppenderFile$new(fancy, layout = LayoutFormat$new("[%t] %c(): %L %m")), "fancy"
)
lg$add_appender(
  AppenderFile$new(json, layout = LayoutJson$new()), "json"
)

lg$info("A test message")

readLines(default)
readLines(fancy)
readLines(json)

# cleanup
lg$config(NULL)
unlink(default)
unlink(fancy)
unlink(json)
tf <- tempfile()
lg <- get_logger("test")$
  set_appenders(AppenderJson$new(tf))$
  set_propagate(FALSE)

lg$info("A test message")
lg$info("A test message %s strings", "with format strings", and = "custom_fields")

lg$appenders[[1]]$show()
lg$appenders[[1]]$data

# cleanup
lg$config(NULL)
unlink(tf)
```

AppenderFileRotating *Log to a rotating file*

Description

An extension of [AppenderFile](#) that rotates logfiles based on certain conditions. Please refer to the documentation of [rotor::rotate\(\)](#) for the meanings of the extra arguments

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> [lgr::AppenderFile](#) -> AppenderFileRotating

Active bindings

backups A data.frame containing information on path, file size, etc... on the available backups of file.

Methods

Public methods:

- [AppenderFileRotating\\$new\(\)](#)
- [AppenderFileRotating\\$append\(\)](#)
- [AppenderFileRotating\\$rotate\(\)](#)
- [AppenderFileRotating\\$prune\(\)](#)
- [AppenderFileRotating\\$set_file\(\)](#)
- [AppenderFileRotating\\$set_size\(\)](#)
- [AppenderFileRotating\\$set_max_backups\(\)](#)
- [AppenderFileRotating\\$set_compression\(\)](#)
- [AppenderFileRotating\\$set_create_file\(\)](#)
- [AppenderFileRotating\\$set_backup_dir\(\)](#)
- [AppenderFileRotating\\$format\(\)](#)
- [AppenderFileRotating\\$clone\(\)](#)

Method new():

Usage:

```
AppenderFileRotating$new(  
  file,  
  threshold = NA_integer_,  
  layout = LayoutFormat$new(),  
  filters = NULL,  
  size = Inf,  
  max_backups = Inf,  
  compression = FALSE,  
  backup_dir = dirname(file),  
  create_file = TRUE  
)
```

Arguments:

age, size, max_backups, fmt, overwrite, compression, backup_dir Please see [rotor::rotate\(\)](#) for the meaning of these arguments

Method append():*Usage:*

```
AppenderFileRotating$append(event)
```

Method rotate():*Usage:*

```
AppenderFileRotating$rotate(force = FALSE)
```

Method prune():*Usage:*

```
AppenderFileRotating$prune(max_backups = self$max_backups)
```

Method set_file():*Usage:*

```
AppenderFileRotating$set_file(file)
```

Method set_size():*Usage:*

```
AppenderFileRotating$set_size(x)
```

Method set_max_backups():*Usage:*

```
AppenderFileRotating$set_max_backups(x)
```

Method set_compression():*Usage:*

```
AppenderFileRotating$set_compression(x)
```

Method set_create_file():*Usage:*

```
AppenderFileRotating$set_create_file(x)
```

Method set_backup_dir():*Usage:*

```
AppenderFileRotating$set_backup_dir(x)
```

Method format():*Usage:*

```
AppenderFileRotating$format(color = false, ...)
```

Method clone(): The objects of this class are cloneable with this method.*Usage:*

```
AppenderFileRotating$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [rotor::rotate\(\)](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFile](#), [AppenderTable](#), [Appender](#)

AppenderFileRotatingDate

Log to a date-stamped rotating file

Description

This is a simpler version of [AppenderFileRotatingTime](#) when the timestamps do not need to include sub-day accuracy.

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> [lgr::AppenderFile](#) -> [lgr::AppenderFileRotating](#)
-> [AppenderFileRotatingDate](#)

Methods**Public methods:**

- [AppenderFileRotatingDate\\$new\(\)](#)
- [AppenderFileRotatingDate\\$clone\(\)](#)

Method new():

Usage:

```
AppenderFileRotatingDate$new(
  file,
  threshold = NA_integer_,
  layout = LayoutFormat$new(),
  filters = NULL,
  age = Inf,
  size = -1,
  max_backups = Inf,
  compression = FALSE,
  backup_dir = dirname(file),
  fmt = "%Y-%m-%d",
  overwrite = FALSE,
  create_file = TRUE,
  cache_backups = TRUE
)
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
AppenderFileRotatingDate$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[AppenderFileRotatingTime](#), [AppenderFileRotating](#), [rotor::rotate\(\)](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderFile](#), [AppenderTable](#), [Appender](#)

AppenderFileRotatingTime

Log to a time-stamped rotating file

Description

Log to a time-stamped rotating file

Log to a time-stamped rotating file

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> [lgr::AppenderFile](#) -> [lgr::AppenderFileRotating](#)
-> [AppenderFileRotating](#)

Active bindings

cache_backups TRUE or FALSE. If TRUE (the default) the list of backups is cached, if FALSE it is read from disk every time this appender triggers. Caching brings a significant speedup for checking whether to rotate or not based on the age of the last backup, but is only safe if there are no other programs/functions (except this appender) interacting with the backups.

Methods**Public methods:**

- [AppenderFileRotatingTime\\$new\(\)](#)
- [AppenderFileRotatingTime\\$rotate\(\)](#)
- [AppenderFileRotatingTime\\$set_age\(\)](#)
- [AppenderFileRotatingTime\\$set_fmt\(\)](#)
- [AppenderFileRotatingTime\\$set_overwrite\(\)](#)
- [AppenderFileRotatingTime\\$set_cache_backups\(\)](#)
- [AppenderFileRotatingTime\\$format\(\)](#)
- [AppenderFileRotatingTime\\$clone\(\)](#)

Method new():

Usage:

```
AppenderFileRotatingTime$new(  
  file,  
  threshold = NA_integer_,  
  layout = LayoutFormat$new(),  
  filters = NULL,  
  age = Inf,  
  size = -1,  
  max_backups = Inf,  
  compression = FALSE,  
  backup_dir = dirname(file),  
  fmt = "%Y-%m-%d--%H-%M-%S",  
  overwrite = FALSE,  
  create_file = TRUE,  
  cache_backups = TRUE  
)
```

Method rotate():

Usage:

```
AppenderFileRotatingTime$rotate(force = FALSE, now = Sys.time())
```

Method set_age():

Usage:

```
AppenderFileRotatingTime$set_age(x)
```

Method set_fmt():

Usage:

```
AppenderFileRotatingTime$set_fmt(x)
```

Method set_overwrite():

Usage:

```
AppenderFileRotatingTime$set_overwrite(x)
```

Method set_cache_backups(): set the cache_backups flag.

Usage:

```
AppenderFileRotatingTime$set_cache_backups(x)
```

Arguments:

x a logical scalar

Method format():

Usage:

```
AppenderFileRotatingTime$format(color = FALSE, ...)
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
AppenderFileRotatingTime$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[AppenderFileRotatingDate](#), [AppenderFileRotating](#), [rotor::rotate\(\)](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotating](#), [AppenderFile](#), [AppenderTable](#), [Appender](#)

AppenderMemory

Abstract class for logging to memory buffers

Description

NOTE: This is an *abstract class*. Abstract classes cannot be instantiated directly, but are exported for package developers that want to extend `lgr` - for example by creating their own [Appenders](#) or [Layouts](#). Please refer to the *see also* section for actual implementations of this class.

`AppenderMemory` is extended by Appenders that retain an in-memory event buffer, such as [AppenderBuffer](#) and [AppenderPushbullet](#) from the [lgrExtra](#) package.

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> `AppenderMemory`

Active bindings

`flush_on_exit` A logical scalar. Should the buffer be flushed if the Appender is destroyed (e.g. because the R session is terminated)?

`flush_on_rotate` A logical scalar. Should the buffer be flushed when it is rotated because `$buffer_size` is exceeded?

`should_flush` A function with exactly one arguments: `event`. `$append()` calls this function internally on the current [LogEvent](#) and flushes the buffer if it evaluates to TRUE.

`buffer_size` integer scalar ≥ 0 . Maximum number of [LogEvents](#) to buffer.

`flush_threshold` A numeric or character threshold. [LogEvents](#) with a `log_level` equal to or lower than this threshold trigger flushing the buffer.

`buffer_events` A list of [LogEvents](#). Contents of the buffer.

`buffer_events` A `data.frame`. Contents of the buffer converted to a `data.frame`.

`buffer_events` A `data.frame`. Contents of the buffer converted to a `data.table`.

Methods**Public methods:**

- [AppenderMemory\\$new\(\)](#)
- [AppenderMemory\\$append\(\)](#)
- [AppenderMemory\\$flush\(\)](#)
- [AppenderMemory\\$clear\(\)](#)
- [AppenderMemory\\$set_buffer_size\(\)](#)

- [AppenderMemory\\$set_should_flush\(\)](#)
- [AppenderMemory\\$set_flush_on_exit\(\)](#)
- [AppenderMemory\\$set_flush_on_rotate\(\)](#)
- [AppenderMemory\\$set_flush_threshold\(\)](#)
- [AppenderMemory\\$show\(\)](#)
- [AppenderMemory\\$format\(\)](#)

Method new():

Usage:

AppenderMemory\$new(...)

Method append():

Usage:

AppenderMemory\$append(event)

Method flush(): Sends the buffer's contents to all attached Appenders and then clears the Buffer

Usage:

AppenderMemory\$flush()

Method clear(): Clears the buffer, discarding all buffered Events

Usage:

AppenderMemory\$clear()

Method set_buffer_size(): Set the maximum size of the buffer

Usage:

AppenderMemory\$set_buffer_size(x)

Arguments:

x an integer scalar ≥ 0 . Number of [LogEvents](#) to buffer.

Method set_should_flush(): Set function that can trigger flushing the buffer

Usage:

AppenderMemory\$set_should_flush(x)

Arguments:

x A function with the single argument event. Setting x to NULL is a shortcut for `function(event) FALSE`. See active bindings.

Method set_flush_on_exit(): Should the buffer be flushed when the Appender is destroyed?

Usage:

AppenderMemory\$set_flush_on_exit(x)

Arguments:

x A logical scalar. See active bindings.

Method set_flush_on_rotate(): Should the buffer be flushed if buffer_size is exceeded?

Usage:

```
AppenderMemory$set_flush_on_rotate(x)
```

Arguments:

x A logical scalar. See active bindings.

Method `set_flush_threshold()`: Set threshold that triggers flushing

Usage:

```
AppenderMemory$set_flush_threshold(level)
```

Arguments:

level A numeric or character [threshold](#). See active bindings.

Method `show()`: Display the contents of the log table. Relies on the `$format_event` method of the [Layout](#) attached to this Appender.

Usage:

```
AppenderMemory$show(threshold = NA_integer_, n = 20L)
```

Arguments:

threshold character or integer scalar. The minimum log level that should be displayed.

n integer scalar. Show only the last n log entries that match threshold.

Method `format()`:

Usage:

```
AppenderMemory$format(color = FALSE, ...)
```

See Also

[LayoutFormat](#)

Other abstract classes: [AppenderTable](#), [Appender](#), [Filterable](#)

AppenderTable

Abstract class for logging to tabular structures

Description

NOTE: This is an *abstract class*. Abstract classes cannot be instantiated directly, but are exported for package developers that want to extend `lgr` - for example by creating their own [Appenders](#) or [Layouts](#). Please refer to the *see also* section for actual implementations of this class.

`AppenderTable` is extended by `Appenders` that write to a data source that can be interpreted as tables, (usually a `data.frame`). Examples are `AppenderDbi`, `AppenderRjdbc` and `AppenderDt` from the [lgrExtra](#) package.

Super classes

[lgr::Filterable](#) -> [lgr::Appender](#) -> `AppenderTable`

Active bindings

data character scalar. Contents of the table, parsed to a data.frame.

data character scalar. Like \$data, but returns a data.table instead (requires the **data.table** package).

Methods

Public methods:

- [AppenderTable\\$new\(\)](#)
- [AppenderTable\\$show\(\)](#)
- [AppenderTable\\$format\(\)](#)

Method new():

Usage:

```
AppenderTable$new(...)
```

Method show(): Show recent log entries

Usage:

```
AppenderTable$show(threshold = NA_integer_, n = 20L)
```

Arguments:

threshold an integer or character [threshold](#). Only show events with a log level at or below this threshold.

n a positive integer scalar. Show at most that many entries

Method format():

Usage:

```
AppenderTable$format(color = FALSE, ...)
```

See Also

Other abstract classes: [AppenderMemory](#), [Appender](#), [Filterable](#)

Other Appenders: [AppenderBuffer](#), [AppenderConsole](#), [AppenderFileRotatingDate](#), [AppenderFileRotatingTime](#), [AppenderFileRotating](#), [AppenderFile](#), [Appender](#)

as.data.frame.LogEvent

Coerce LogEvents to Data Frames

Description

Coerce LogEvents to data.frames, [data.tables](#), or [tibbles](#).

Usage

```
## S3 method for class 'LogEvent'
as.data.frame(
  x,
  row.names = NULL,
  optional = FALSE,
  stringsAsFactors = FALSE,
  ...,
  box_if = function(.) !(is.atomic(.) && identical(length(.), 1L)),
  cols_expand = NULL
)

as.data.table.LogEvent(
  x,
  ...,
  box_if = function(.) !(is.atomic(.) && identical(length(.), 1L)),
  cols_expand = "msg"
)

as_tibble.LogEvent(
  x,
  ...,
  box_if = function(.) !(is.atomic(.) && identical(length(.), 1L)),
  cols_expand = "msg"
)
```

Arguments

<code>x</code>	any R object.
<code>row.names</code>	NULL or a character vector giving the row names for the data frame. Missing values are not allowed.
<code>optional</code>	currently ignored and only included for compatibility.
<code>stringsAsFactors</code>	logical scalar: should character vectors be converted to factors? Defaults to FALSE (as opposed to <code>base::as.data.frame()</code>) and is only included for compatibility.
<code>...</code>	passed on to <code>data.frame()</code>
<code>box_if</code>	a function that returns TRUE or FALSE to determine which values are to be boxed (i.e. placed as single elements in a list column). See example
<code>cols_expand</code>	character vector. Columns to <i>not</i> box (even if <code>box_if()</code> returns TRUE). Vectors in these columns will result in multiple rows in the result (rather than a single list-column row). This defaults to "msg" for vectorized logging over the log message.

See Also

[data.table::data.table](#), [tibble::tibble](#)

Examples

```

lg <- get_logger("test")
lg$info("lorem ipsum")
as.data.frame(lg$last_event)

lg$info("LogEvents can store any custom log values", df = iris)
as.data.frame(lg$last_event)
head(as.data.frame(lg$last_event)$df[[1]])

# how boxing works

# by default non-scalars are boxed
lg$info("letters", letters = letters)
as.data.frame(lg$last_event)

# this behaviour can be modified by supplying a custom boxing function
as.data.frame(lg$last_event, box_if = function(.) FALSE)
as.data.frame(lg$last_event, cols_expand = "letters")

# The `msg` argument of a log event is always vectorized
lg$info(c("a vectorized", "log message"))
as.data.frame(lg$last_event)

lg$config(NULL)

```

basic_config

Basic Setup for the Logging System

Description

A quick and easy way to configure the root logger. This is less powerful than using `lgr$config()` or `lgr$set_*` (see [Logger](#)), but reduces the most common configurations to a single line of code.

Usage

```

basic_config(
  file = NULL,
  fmt = "%L [%t] %m",
  timestamp_fmt = "%Y-%m-%d %H:%M:%OS3",
  threshold = "info",
  appenders = NULL,
  console = if (is.null(appenders)) "all" else FALSE,
  console_fmt = "%L [%t] %m %f",
  console_timestamp_fmt = "%H:%M:%OS3",
  memory = FALSE
)

```

Arguments

file	character scalar: If not NULL a AppenderFile will be created that logs to this file. If the filename ends in <code>.jsonl</code> , the Appender will be set up to use the JSON Lines format instead of plain text (see AppenderFile and AppenderJson).
fmt	character scalar: Format to use if file is supplied and not a <code>.jsonl</code> file. If NULL it defaults to <code>"%L [%t] %m"</code> (see format.LogEvent)
timestamp_fmt	see format.POSIXct()
threshold	character or integer scalar. The minimum log level that should be processed by the root logger.
appenders	a single Appender or a list thereof.
console	logical scalar or a threshold (see above). Add an appender logs to the console (i.e. displays messages in an interactive R session)
console_fmt	character scalar: like <code>fmt</code> but used for console output
console_timestamp_fmt	character scalar: like <code>timestamp_fmt</code> but used for console output
memory	logical scalar. or a threshold (see above). Add an Appender that logs to a memory buffer, see also show_log() and AppenderBuffer

Value

the root Logger (`lgr`)

Examples

```
# log to a file
basic_config(file = tempfile())
unlink(lgr$appenders$file$file) # cleanup

basic_config(file = tempfile(fileext = "jsonl"))
unlink(lgr$appenders$file$file) # cleanup

# log debug messages to a memory buffer
basic_config(threshold = "all", memory = "all", console = "info")
lgr$info("an info message")
lgr$debug("a hidden message")
show_log()

# reset to default config
basic_config()
```

CannotInitializeAbstractClassError
Logger Error Conditions

Description

Logger Error Conditions

Usage

```
CannotInitializeAbstractClassError(class = parent.frame(2)[["classes"]])
```

Arguments

class	character scalar. The abstract class that was mistakenly tried to initialize. The default is to discover the class name automatically if called inside <code>\$initialize(){...}</code> in an <code>R6::R6</code> class definition
-------	--

Value

a condition object

colorize_levels *Colorize Levels*

Description

Colorize Levels

Usage

```
colorize_levels(x, colors = getOption("lgr.colors", NULL))
```

Arguments

x	numeric or character levels to be colored. Unlike in many other functions in <code>lgr</code> , character levels are <i>not</i> case sensitive in this function and leading/trailing whitespace is ignored to make it more comfortable to use <code>colorize_levels()</code> inside formatting functions.
colors	A list of functions that will be used to color the log levels (likely from <code>crayon::crayon</code>).

Value

a character vector with color ANSI codes

See Also

Other formatting utils: [label_levels\(\)](#)

Examples

```
cat(colorize_levels(c(100, 200)))  
cat(colorize_levels(c("trace", "warn ", "DEBUG")))
```

default_exception_handler

Demote an exception to a warning

Description

Throws a timestamped warning instead of stopping the program. This is the default exception handler used by [Loggers](#).

Usage

```
default_exception_handler(e)
```

Arguments

e an error condition object

Value

The warning as character vector

Examples

```
tryCatch(stop("an error has occurred"), error = default_exception_handler)
```

Description

EventFilters specify arbitrarily complex logic for whether or not a LogEvent should be processed by a [Logger](#) or [Appender](#). They are attached to Loggers/Appenders via their `$set_filter()` or `$add_filter()` methods. If any EventFilter evaluates to FALSE for a given event, that event is ignored - similarly to when it does not pass the objects' threshold.

Usually you do not need to instantiate a formal EventFilter object as you can just use any function that has the single argument event instead. If you need to implement more complex filter logic - for example a filter that is dependent on a dataset - it might be desirable to subclass EventFilter, as [R6::R6](#) objects can store data and functions together.

`.obj()` is a special function that can only be used within the `$filter()` methods of [EventFilters](#). It returns the [Logger](#) or [Appender](#) that the EventFilter is attached to.

Usage

```
.obj()
```

Modifying LogEvents with EventFilters

Since LogEvents are R6 objects with reference semantics, EventFilters can be abused to modify events before passing them on. lgr comes with a few preset filters that use this property: [FilterInject](#) (similar to [with_log_level\(\)](#)) and [FilterForceLevel](#) (similar to [with_log_value\(\)](#)).

NOTE: The base class for Filters is called EventFilter so that it doesn't conflict with `base::Filter()`. The recommended convention for Filter subclasses is to call them FilterSomething and leave out the Event prefix.

Methods

Public methods:

- [EventFilter\\$new\(\)](#)
- [EventFilter\\$clone\(\)](#)

Method `new()`: Initialize a new EventFilter

Usage:

```
EventFilter$new(fun = function(event) TRUE)
```

Arguments:

fun a function with a single argument event that must return either TRUE or FALSE. Any non-FALSE will be interpreted as TRUE (= no filtering takes place) and a warning will be thrown.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
EventFilter$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[is_filter\(\)](#)

Examples

```
lg <- get_logger("test")
f <- function(event) {
  cat("via event$.logger:", event$.logger$threshold, "\n") # works for loggers only
  cat("via .obj():      ", .obj()$threshold, "\n") # works for loggers and appenders
  TRUE
}
lg$add_filter(f)
lg$fatal("test")
lg$config(NULL)
```

event_list

A List of LogEvents

Description

An event_list is a class for list()s whose only elements are [LogEvents](#). This structure is occasionally used internally in lgr (for example by [AppenderBuffer](#)) and can be useful for developers that want to write their own Appenders.

Usage

```
event_list(...)

as_event_list(x, ...)

## S3 method for class 'list'
as_event_list(x, ..., scalarize = FALSE)

## S3 method for class 'LogEvent'
as_event_list(x, ..., scalarize = FALSE)

## S3 method for class 'data.frame'
as_event_list(x, na.rm = TRUE, ...)

as.data.table.event_list(x, na.rm = TRUE)

## S3 method for class 'event_list'
```



```

as.data.frame(
  x,
  row.names = NULL,
  optional = FALSE,
  stringsAsFactors = FALSE,
  na.rm = TRUE,
  ...
)

```

Arguments

...	for event elements to be added to the list, for the <code>as_*</code> () functions parameters passed on to methods.
x	any R object
scalarize	logical scalar. Turn LogEvents with non-scalar msg field into separate log events
na.rm	remove NA values before coercing a data.frame to an <code>event_list()</code> .
row.names	NULL or a character vector giving the row names for the data frame. Missing values are not allowed.
optional	currently ignored and only included for compatibility.
stringsAsFactors	logical scalar: should character vectors be converted to factors? Defaults to FALSE (as opposed to <code>base::as.data.frame()</code>) and is only included for compatibility.

Details

For convenience, `as.data.frame()` and `as.data.table()` methods exist for event lists.

Value

`event_list()` and `as_event_list()` return a flat list of [LogEvents](#). Nested lists get automatically flattened.

`as.data.frame` and `as.data.table` return a `data.frame` or `data.table` respectively

See Also

Other docs relevant for extending lgr: [LogEvent](#), [standardize_threshold\(\)](#)

Examples

```

e <- LogEvent$new(level = 300, msg = "a", logger = lgr)
as_event_list(e)
as_event_list(c(e, e))
# nested lists get automatically unnested
as_event_list(c(e, list(nested_event = e)))

# scalarize = TRUE "unpacks" events with vector log messages

```

```
e <- LogEvent$new(level = 300, msg = c("A", "B"), logger = lgr)
as_event_list(e, scalarize = FALSE)
as_event_list(e, scalarize = TRUE)
```

 Filterable

Abstract Class for Filterables

Description

Superclass for classes that have a `$filter()` method such as [Appenders](#) and [Loggers](#). See [EventFilter](#) for details.

NOTE: This is an *abstract class*. Abstract classes cannot be instantiated directly, but are exported for package developers that want to extend `lgr` - for example by creating their own [Appenders](#) or [Layouts](#). Please refer to the *see also* section for actual implementations of this class.

Active bindings

`filters` a list of all attached Filters.

Methods

Public methods:

- [Filterable\\$filter\(\)](#)
- [Filterable\\$add_filter\(\)](#)
- [Filterable\\$remove_filter\(\)](#)
- [Filterable\\$set_filters\(\)](#)

Method `filter()`: Determine whether the `LogEvent` `x` should be passed on to Appenders (TRUE) or not (FALSE). See also the active binding filters.

Usage:

```
Filterable$filter(event)
```

Arguments:

`event` a [LogEvent](#)

Method `add_filter()`: Attach a filter

Usage:

```
Filterable$add_filter(filter, name = NULL)
```

Arguments:

`filter` • a function with the single argument `event` that returns TRUE or FALSE;

- an [EventFilter R6::R6](#) object; or
- any R object with a `$filter()` method.

If a Filter returns a non-FALSE value, will be interpreted as TRUE (= no filtering takes place) and a warning will be thrown.

name character scalar or NULL. An optional name which makes it easier to access (or remove) the filter

Method `remove_filter()`: Remove a filter

Usage:

`Filterable$remove_filter(pos)`

Arguments:

pos character or integer scalar. The name or index of the Filter to be removed.

Method `set_filters()`: Set or replace (all) Filters of parent object. See [EventFilter](#) for how Filters work.

Usage:

`Filterable$set_filters(filters)`

Arguments:

filters a list (named or unnamed) of [EventFilters](#) or predicate functions. See [is_filter\(\)](#).

See Also

Other abstract classes: [AppenderMemory](#), [AppenderTable](#), [Appender](#)

FilterForceLevel	<i>Override the log level of all events processed by a Logger/Appender</i>
------------------	--

Description

Overrides the log level of the Appender/Logger that this filter is attached to to with level. See also [with_log_level\(\)](#). It is recommended to use filters that modify LogEvents only with Loggers, but they will also work with Appenders.

Super class

`lgr::EventFilter` -> FilterForceLevel

Public fields

level an integer [log level](#) used to override the log levels of each [LogEvent](#) processed by this filter.

Methods

Public methods:

- [FilterForceLevel\\$new\(\)](#)
- [FilterForceLevel\\$clone\(\)](#)

Method `new()`: Initialize a new FilterForceLevel

Usage:

```
FilterForceLevel$new(level)
```

Arguments:

level an integer or character [log level](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
FilterForceLevel$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
lg <- get_logger("test")

analyse <- function(){
  lg$add_filter(FilterForceLevel$new("info"), "force")
  on.exit(lg$remove_filter("force"))
  lg$error("an error with forced log level INFO")
}

analyse()
lg$error("an normal error")
lg$config(NULL) # reset config
```

FilterInject

Inject values into all events processed by a Logger/Appender

Description

Inject arbitrary values into all [LogEvents](#) processed by a Logger/Appender. It is recommended to use filters that modify LogEvents only with Loggers, but they will also work with Appenders.

Super class

```
lgr::EventFilter -> FilterInject
```

Public fields

values a named list of values to be injected into each [LogEvent](#) processed by this filter

Methods

Public methods:

- [FilterInject\\$new\(\)](#)
- [FilterInject\\$clone\(\)](#)

Method new(): Initialize a new FilterInject

Usage:

```
FilterInject$new(..., .list = list())
```

Arguments:

..., .list any number of named R objects that will be injected as custom fields into all [LogEvents](#) processed by the Appender/Logger that this filter is attached to. See also [with_log_value\(\)](#).

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
FilterInject$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
lg <- get_logger("test")

analyse <- function(){
  lg$add_filter(FilterInject$new(type = "analysis"), "inject")
  on.exit(lg$remove_filter("inject"))
  lg$error("an error with forced custom 'type'-field")
}

analyse()
lg$error("an normal error")
lg$config(NULL) # reset config
```

get_caller

Information About the System

Description

`get_caller()` Tries to determine the calling functions based on where.

Usage

```
get_caller(where = -1L)
```

```
get_user(fallback = "unknown user")
```

Arguments

where integer scalar (usually negative). Look up that many frames up the call stack
 fallback A fallback in case the user name could not be determined

Value

a character scalar.

See Also

[base::sys.call\(\)](#)
[whoami::whoami\(\)](#)

Examples

```
foo <- function() get_caller(-1L)
foo()
get_user()
```

 get_logger

Get/Create a Logger

Description

Get/Create a Logger

Usage

```
get_logger(name, class = Logger, reset = FALSE)

get_logger_glue(name)
```

Arguments

name a character scalar or vector: The qualified name of the Logger as a hierarchical value.
 class An [R6ClassGenerator](#) object. Usually Logger or LoggerGlue are the only valid choices.
 reset a logical scalar. If TRUE the logger is reset to an unconfigured state. Unlike `$config(NULL)` this also replaces a LoggerGlue with vanilla Logger. Please note that this will invalidate Logger references created before the reset call (see examples).

Value

a [Logger](#)

Examples

```
lg <- get_logger("log/ger/test")
# equivalent to
lg <- get_logger(c("log", "ger", "test"))
lg$warn("a %s message", "warning")
lg
lg$parent

if (requireNamespace('glue')){
  lg <- get_logger_glue("log/ger")
}
lg$warn("a {.text} message", .text = "warning")

# completely reset 'glue' to an unconfigured vanilla Logger
get_logger("log/ger", reset = TRUE)
# WARNING: this invalidates existing references to the Logger
try(lg$info("lg has been invalidated an no longer works"))

lg <- get_logger("log/ger")
lg$info("now all is well again")
```

get_log_levels

Manage Log Levels

Description

Display, add and remove character labels for log levels.

Usage

```
get_log_levels()

add_log_levels(levels)

remove_log_levels(level_names)
```

Arguments

levels	a named character vector (see examples)
level_names	a character vector of the names of the levels to remove

Value

a named character vector of the globally available log levels (add_log_levels() and remove_log_levels() return invisibly).

Default Log Levels

lgr comes with the following predefined log levels that are identical to the log levels of log4j.

Level	Name	Description
0	off	A log level of 0/off tells a Logger or Appender to suspend all logging
100	fatal	Critical error that leads to program abort. Should always indicate a stop() or similar
200	error	A severe error that does not trigger program abort
300	warn	A potentially harmful situation, like warning()
400	info	An informational message on the progress of the application
500	debug	Finer grained informational messages that are mostly useful for debugging
600	trace	An even finer grained message than debug
NA	all	A log level of NA/all tells a Logger or Appender to process all log events

Examples

```
get_log_levels()
add_log_levels(c(errorish = 250))
get_log_levels()
remove_log_levels("errorish")
get_log_levels()
```

is_filter

Check if an R Object is a Filter

Description

Returns TRUE for any R object that can be used as a Filter for [Loggers](#) or [Appenders](#):

- a function with the single argument event;
- an [EventFilter R6::R6](#) object; or
- any object with a \$filter(event) method.

Note: A Filter **must** return a scalar TRUE or FALSE, but this property cannot be checked by [is_filter\(\)](#).

Usage

```
is_filter(x)
```

Arguments

x any R Object

Value

TRUE or FALSE

See Also

[EventFilter](#), [Filterable](#)

label_levels	<i>Label/Unlabel Log Levels</i>
--------------	---------------------------------

Description

Label/Unlabel Log Levels

Usage

```
label_levels(levels, log_levels = getOption("lgr.log_levels"))  
unlabel_levels(labels, log_levels = getOption("lgr.log_levels"))
```

Arguments

levels	an integer vector of log levels
log_levels	named integer vector of valid log levels
labels	a character vector of log level labels. Please note that log levels are lowercase by default, even if many appenders print them in uppercase.

Value

a character vector for `label_levels()` and an integer vector for `unlabel_levels`

See Also

[get_log_levels\(\)](#)
Other formatting utils: [colorize_levels\(\)](#)

Examples

```
x <- label_levels(c(seq(0, 600, by = 100), NA))  
print(x)  
unlabel_levels(x)
```

Layout	<i>Abstract Class for Layouts</i>
--------	-----------------------------------

Description

Abstract Class for Layouts
Abstract Class for Layouts

Details

[Appenders](#) pass [LogEvents](#) to a Layout which formats it for output. For the Layouts included in lgr that means turning the LogEvent into a character string.

For each Appender exist one more more possible Layouts, but not every Layout will work with every Appender. See the package **lgrExtra** for examples for Layouts that return different data types (such as `data.frames`) and Appenders that can handle them.

Notes for developers

Layouts may have an additional `$read(file, threshold, n)` method that returns a character vector, and/or an `$parse(file)` method that returns a `data.frame`. These can be used by Appenders to `$show()` methods and `$data` active bindings respectively (see source code of [AppenderFile](#)).

Methods

Public methods:

- [Layout\\$format_event\(\)](#)
- [Layout\\$toString\(\)](#)
- [Layout\\$clone\(\)](#)

Method `format_event()`: Format a log event

Function that the Layout uses to transform a [LogEvent](#) into something that an [Appender](#) can write to an output destination.

Usage:

```
Layout$format_event(event)
```

Arguments:

event a [LogEvent](#)

Method `toString()`:

Usage:

```
Layout$toString()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Layout$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Layouts: [LayoutFormat](#), [LayoutGlue](#), [LayoutJson](#)

LayoutFormat

Format Log Events as Text

Description

Format Log Events as Text

Format Log Events as Text

Details

Format a [LogEvent](#) as human readable text using `format.LogEvent()`, which provides a quick and easy way to customize log messages. If you need more control and flexibility, consider using [LayoutGlue](#) instead.

see Fields

see Fields

see Fields

see Fields

Convert Layout to a character string Read a log file written using LayoutFormat

Format Tokens

This is the same list of format tokens as for `format.LogEvent()`

`%t` The timestamp of the message, formatted according to `timestamp_fmt`)

`%l` the log level, lowercase character representation

`%L` the log level, uppercase character representation

`%k` the log level, first letter of lowercase character representation

`%K` the log level, first letter of uppercase character representation

`%n` the log level, integer representation

`%p` the PID (process ID). Useful when logging code that uses multiple threads.

`%c` the calling function

`%m` the log message

`%f` all custom fields of `x` in a pseudo-JSON like format that is optimized for human readability and console output

`%j` all custom fields of `x` in proper JSON. This requires that you have **jsonlite** installed and does not support colors as opposed to `%f`

Super class

`lgr::Layout` -> LayoutFormat

Active bindings

`fmt` a character scalar containing format tokens. See [format.LogEvent\(\)](#).
`timestamp_fmt` a character scalar. See [base::format.POSIXct\(\)](#).
`colors` a named list of functions (like the ones provided by the package **crayon**) passed on on [format.LogEvent\(\)](#).
`pad_levels` "right", "left" or NULL. See [format.LogEvent\(\)](#).

Methods**Public methods:**

- [LayoutFormat\\$new\(\)](#)
- [LayoutFormat\\$format_event\(\)](#)
- [LayoutFormat\\$set_fmt\(\)](#)
- [LayoutFormat\\$set_timestamp_fmt\(\)](#)
- [LayoutFormat\\$set_colors\(\)](#)
- [LayoutFormat\\$set_pad_levels\(\)](#)
- [LayoutFormat\\$toString\(\)](#)
- [LayoutFormat\\$read\(\)](#)
- [LayoutFormat\\$clone\(\)](#)

Method new():*Usage:*

```
LayoutFormat$new(
  fmt = "%L [%t] %m",
  timestamp_fmt = "%Y-%m-%d %H:%M:%OS3",
  colors = NULL,
  pad_levels = "right"
)
```

Method format_event(): Format a LogEvent*Usage:*

```
LayoutFormat$format_event(event)
```

Arguments:

event a [LogEvent](#)

Method set_fmt():*Usage:*

```
LayoutFormat$set_fmt(x)
```

Method set_timestamp_fmt():*Usage:*

```
LayoutFormat$set_timestamp_fmt(x)
```

Method set_colors():

Usage:

```
LayoutFormat$set_colors(x)
```

Method set_pad_levels():

Usage:

```
LayoutFormat$set_pad_levels(x)
```

Method toString():

Usage:

```
LayoutFormat$toString()
```

Method read():

Usage:

```
LayoutFormat$read(file, threshold = NA_integer_, n = 20L)
```

Arguments:

threshold a character or integer threshold
n number of log entries to display

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
LayoutFormat$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Layouts: [LayoutGlue](#), [LayoutJson](#), [Layout](#)

Examples

```
# setup a dummy LogEvent
event <- LogEvent$new(
  logger = Logger$new("dummy logger"),
  level = 200,
  timestamp = Sys.time(),
  caller = NA_character_,
  msg = "a test message"
)
lo <- LayoutFormat$new()
lo$format_event(event)
```

LayoutGlue

*Format Log Events as Text via glue***Description**

Format a [LogEvent](#) as human readable text using `glue::glue`. The function is evaluated in an environment in which it has access to all elements of the [LogEvent](#) (see examples). This is more flexible than [LayoutFormat](#), but also more complex and slightly less performant.

Super class

`lgr::Layout` -> LayoutGlue

Active bindings

`fmt` A string that will be interpreted by `glue::glue()`

Methods**Public methods:**

- [LayoutGlue\\$new\(\)](#)
- [LayoutGlue\\$format_event\(\)](#)
- [LayoutGlue\\$set_fmt\(\)](#)
- [LayoutGlue\\$set_colors\(\)](#)
- [LayoutGlue\\$toString\(\)](#)
- [LayoutGlue\\$clone\(\)](#)

Method new():

Usage:

```
LayoutGlue$new(
  fmt = "{pad_right(colorize_levels(toupper(level_name)), 5)} [{timestamp}] msg"
)
```

Method format_event():

Usage:

```
LayoutGlue$format_event(event)
```

Method set_fmt():

Usage:

```
LayoutGlue$set_fmt(x)
```

Method set_colors():

Usage:

```
LayoutGlue$set_colors(x)
```

Method toString():*Usage:*

LayoutGlue\$string()

Method clone(): The objects of this class are cloneable with this method.*Usage:*

LayoutGlue\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

See Also

lgr exports a number of formatting utility functions that are useful for layout glue: [colorize_levels\(\)](#), [pad_left\(\)](#), [pad_right\(\)](#).

Other Layouts: [LayoutFormat](#), [LayoutJson](#), [Layout](#)

Examples

```
lg <- get_logger("test")$
  set_appenders(AppenderConsole$new())$
  set_propagate(FALSE)

lg$appenders[[1]]$set_layout(LayoutGlue$new())
lg$fatal("test")

# All fields of the LogEvent are available, even custom ones
lg$appenders[[1]]$layout$set_fmt(
  "{logger} {level_name}({level}) {caller}: {toupper(msg)} {{custom: {custom}}}"
)
lg$fatal("test", custom = "foobar")
lg$config(NULL) # reset logger config
```

LayoutJson

*Format LogEvents as JSON***Description**

A format for formatting LogEvents as [jsonlines](#) log files. This provides a nice balance between human- and machine-readability.

Super class

[lgr::Layout](#) -> LayoutJson

Active bindings

toJSON_args a list of values passed on to `jsonlite::toJSON()`

timestamp_fmt Used by `$format_event()` to format timestamps.

Methods

Public methods:

- `LayoutJson$new()`
- `LayoutJson$format_event()`
- `LayoutJson$set_toJSON_args()`
- `LayoutJson$set_timestamp_fmt()`
- `LayoutJson$toString()`
- `LayoutJson$parse()`
- `LayoutJson$read()`
- `LayoutJson$clone()`

Method `new()`:

Usage:

```
LayoutJson$new(toJSON_args = list(auto_unbox = TRUE), timestamp_fmt = NULL)
```

Method `format_event()`:

Usage:

```
LayoutJson$format_event(event)
```

Method `set_toJSON_args()`: Set arguments to pass on to `jsonlite::toJSON()`

Usage:

```
LayoutJson$set_toJSON_args(x)
```

Arguments:

x a named list

Method `set_timestamp_fmt()`: Set a format that this Layout will apply to timestamps.

Usage:

```
LayoutJson$set_timestamp_fmt(x)
```

Arguments:

- x
- NULL (the default): formatting of the timestamp is left to `jsonlite::toJSON()`,
 - a character scalar as for `format.POSIXct()`, or
 - a function that returns a vector of the same length as its (`POSIXct`) input. The returned vector can be of any type supported by `jsonlite::toJSON()`, but should usually be character.

Method `toString()`:

Usage:

```
LayoutJson$toString()
```


Method parse():*Usage:*

LayoutJson\$parse(file)

Method read():*Usage:*

LayoutJson\$read(file, threshold = NA_integer_, n = 20L)

Method clone(): The objects of this class are cloneable with this method.*Usage:*

LayoutJson\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

See Also[read_json_lines\(\)](#), <https://jsonlines.org/>Other Layouts: [LayoutFormat](#), [LayoutGlue](#), [Layout](#)**Examples**

```
# setup a dummy LogEvent
event <- LogEvent$new(
  logger = Logger$new("dummy logger"),
  level = 200,
  timestamp = Sys.time(),
  caller = NA_character_,
  msg = "a test message",
  custom_field = "LayoutJson can handle arbitrary fields"
)

# Default settings show all event fals
lo <- LayoutJson$new()
lo$format_event(event)
```

Description

A LogEvent is a single unit of data that should be logged. LogEvents are usually created by a [Logger](#), and then processed by one more [Appenders](#). They do not need to be instantiated manually except for testing and experimentation; however, if you plan on writing your own Appenders or Layouts you need to understand LogEvents.

Public fields

`level` integer. The [log_level](#) / priority of the LogEvent. Use the active binding `level_name` to get the character representation instead.

`timestamp` [POSIXct](#). The time when then the LogEvent was created.

`caller` character. The name of the calling function.

`msg` character. The log message.

`.logger` [Logger](#). A reference to the Logger that created the event (equivalent to `get_logger(event$logger)`).

Active bindings

`values` list. All values stored in the LogEvent, including all *custom fields*, but not including `event$.logger`.

`level_name` character. The [log_level](#) / priority of the LogEvent labelled according to `getOption("lgr.log_levels")`

`logger` character scalar. The name of the Logger that created this event, equivalent to `event$.logger$name`

Methods**Public methods:**

- [LogEvent\\$new\(\)](#)
- [LogEvent\\$clone\(\)](#)

Method `new()`: The arguments to `LogEvent$new()` directly translate to the fields stored in the LogEvent. Usually these values will be scalars, but (except for "logger") they can also be vectors if they are all of the same length (or scalars that will be recycled). In this case the event will be treated by the [Appenders](#) and [Layouts](#) as if several separate events.

Usage:

```
LogEvent$new(
  logger,
  level = 400,
  timestamp = Sys.time(),
  caller = NA,
  msg = NA,
  ...
)
```

Arguments:

`logger`, `level`, `timestamp`, `caller`, `msg` see **Public fields**.

... All named arguments in ... will be added to the LogEvent as **custom fields**. You can store arbitrary R objects in LogEvents this way, but not all Appenders will support them.

See [AppenderJson](#) for

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LogEvent$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

[as.data.frame.LogEvent\(\)](#)

Other docs relevant for extending lgr: [event_list\(\)](#), [standardize_threshold\(\)](#)

Examples

```
lg <- get_logger("test")
lg$error("foo bar")

# The last LogEvent produced by a Logger is stored in its `last_event` field
lg$last_event # formatted console output
lg$last_event$values # values stored in the event

# Also contains the Logger that created it as .logger
lg$last_event$logger
# equivalent to
lg$last_event$.logger$name

# This is really a reference to the complete Logger, so the following is
# possible (though nonsensical)
lg$last_event$.logger$last_event$msg
identical(lg, lg$last_event$.logger)
lg$config(NULL) # reset logger config
```

Logger

Loggers

Description

A Logger produces a [LogEvent](#) that contains a log message along with metadata (timestamp, calling function, ...) and dispatches it to one or more [Appenders](#) which are responsible for the output (console, file, ...) of the event. **lgr** comes with a single pre-configured Logger called the root Logger that can be accessed via `lgr$<...>`. Instantiation of new Loggers is done with [get_logger\(\)](#). It is advisable to instantiate a separate Logger with a descriptive name for each package/script in which you use **lgr**.

Super class

[lgr::Filterable](#) -> Logger

Active bindings

name A character scalar. The unique name of each logger, which also includes the names of its ancestors (separated by /).

threshold integer scalar. The threshold of the Logger, or if it NULL the threshold it inherits from its closest ancestor with a non-NULL threshold

propagate A TRUE or FALSE. The unique name of each logger, which also includes the names of its ancestors (separated by /).

`ancestry` A named logical vector of containing the propagate value of each Logger upper the inheritance tree. The names are the names of the appenders. `ancestry` is an S3 class with a custom `format()/print()` method, so if you want to use the plain logical vector use `unclass(lg$ancestry)`

`parent` a Logger. The direct ancestor of the Logger.

`last_event` The last LogEvent produced by the current Logger

`appenders` a list of all [Appenders](#) of the Logger

`inherited_appenders` A list of all appenders that the Logger inherits from its ancestors

`exception_handler` a function. See `$set_exception_handler` and `$handle_exception`

Methods

Public methods:

- `Logger$new()`
- `Logger$log()`
- `Logger$fatal()`
- `Logger$error()`
- `Logger$warn()`
- `Logger$info()`
- `Logger$debug()`
- `Logger$trace()`
- `Logger$list_log()`
- `Logger$config()`
- `Logger$add_appender()`
- `Logger$remove_appender()`
- `Logger$handle_exception()`
- `Logger$set_exception_handler()`
- `Logger$set_propagate()`
- `Logger$set_threshold()`
- `Logger$set_appenders()`
- `Logger$spawn()`

Method `new()`: **Loggers should never be instantiated directly with `Logger$new()`** but rather via `get_logger("name")`. This way new Loggers are registered in a global namespace which ensures uniqueness and facilitates inheritance between Loggers. If "name" does not exist, a new Logger with that name will be created, otherwise the function returns a Reference to the existing Logger.

`name` is potentially a "/" separated hierarchical value like `foo/bar/baz`. Loggers further down the hierarchy are descendants of the loggers above and (by default) inherit `threshold` and `Appenders` from their ancestors.

Usage:

```

Logger$new(
  name = "(unnamed logger)",
  appenders = list(),
  threshold = NULL,
  filters = list(),
  exception_handler = default_exception_handler,
  propagate = TRUE
)

```

Arguments:

name, appenders, threshold, filters, exception_handler, propagate See section Active bindings.

Method log(): Log an event.

If level passes the Logger's threshold a new [LogEvent](#) with level, msg, timestamp and caller is created. If the new LogEvent also passes the Loggers [Filters](#), it is be dispatched to the relevant [Appenders](#).

Usage:

```
Logger$log(level, msg, ..., timestamp = Sys.time(), caller = get_caller(-7))
```

Arguments:

level a character or integer scalar. See [log_levels](#).

msg character. A log message. If unnamed arguments are supplied in ..., msg is passed on to [base::sprintf\(\)](#) (which means "%" have to be escaped), otherwise msg is left as-is.

... *unnamed* arguments in ... must be character scalars and are passed to [base::sprintf\(\)](#).

Named arguments must have unique names but can be arbitrary R objects that are passed to [LogEvent\\$new\(\)](#) and will be turned into custom fields.

timestamp [POSIXct](#). Timestamp of the event.

caller a character scalar. The name of the calling function.

Method fatal(): Log an Event fatal priority

Usage:

```
Logger$fatal(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method error(): Log an Event error priority

Usage:

```
Logger$error(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method warn(): Log an Event warn priority

Usage:

```
Logger$warn(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method info(): Log an Event info priority

Usage:

```
Logger$info(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method debug(): Log an Event debug priority

Usage:

```
Logger$debug(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method trace(): Log an Event trace priority

Usage:

```
Logger$trace(msg, ..., caller = get_caller(-8L))
```

Arguments:

msg, ..., caller see \$log()

Method list_log(): list_log() is a shortcut for do.call(Logger\$log,x). See <https://github.com/s-fleck/joblog> for an R package that leverages this feature to create custom log event types for tracking the status of cron jobs.

Usage:

```
Logger$list_log(x)
```

Arguments:

x a named list that must at least contain the named elements level and timestamp

Examples:

```
lg <- get_logger("test")
lg$list_log(list(level = 400, msg = "example"))
```

Method config(): Load a Logger configuration.

Usage:

```
Logger$config(cfg, file, text, list)
```

Arguments:

cfg • a special list object with any or all of the the following elements: appenders, threshold, filters, propagate, exception_handler,

- the path to a YAML/JSON config file,
- a character scalar containing YAML/JSON,
- NULL (to reset the logger config to the default/unconfigured state)

file, text, list can be used as an alternative to cfg that enforces that the supplied argument is of the specified type. See [logger_config](#) for details.

Method `add_appender()`: Add an Appender to the Logger

Usage:

```
Logger$add_appender(appender, name = NULL)
```

Arguments:

`appender` a single [Appender](#)

`name` a character scalar. Optional but recommended.

Examples:

```
lg <- get_logger("test")
lg$add_appender(AppenderConsole$new(), name = "myconsole")
lg$appenders[[1]]
lg$appenders$myconsole
lg$remove_appender("myconsole")
lg$config(NULL) # reset config
```

Method `remove_appender()`: remove an appender

Usage:

```
Logger$remove_appender(pos)
```

Arguments:

`pos` integer index or character name of the Appender(s) to remove

Method `handle_exception()`: To prevent errors in the logging logic from crashing the whole script, Loggers pass errors they encounter to an exception handler. The default behaviour is to demote errors to [warnings](#). See also `set_exception_handler()`.

Usage:

```
Logger$handle_exception(expr)
```

Arguments:

`expr` expression to be evaluated.

Method `set_exception_handler()`: Set the exception handler of a logger

Usage:

```
Logger$set_exception_handler(fun)
```

Arguments:

`fun` a function with the single argument `e` (an error [condition](#))

Examples:

```
lgr$info(stop("this produces a warning instead of an error"))
```

Method `set_propagate()`: Should a Logger propagate events to the Appenders of its ancestors?

Usage:

```
Logger$set_propagate(x)
```

Arguments:

`x` TRUE or FALSE. Should [LogEvents](#) be passed on to the appenders of the ancestral Loggers?

Method `set_threshold()`: Set the minimum log level of events that a Logger should process

Usage:

```
Logger$set_threshold(level)
```

Arguments:

level character or integer scalar. The minimum [log level](#) that triggers this Logger

Method `set_appenders()`: Set the Logger's Appenders*Usage:*

```
Logger$set_appenders(x)
```

Arguments:

x single [Appender](#) or a list thereof. Appenders control the output of a Logger. Be aware that a Logger also inherits the Appenders of its ancestors (see `vignette("lgr", package = "lgr")` for more info about Logger inheritance).

Method `spawn()`: Spawn a child Logger. This is very similar to using `get_logger()`, but can be useful in some cases where Loggers are created programmatically*Usage:*

```
Logger$spawn(name)
```

Arguments:

name character vector. Name of the child logger `get_logger("foo/bar")$spawn("baz")` is equivalent to `get_logger("foo/bar/baz")`

Note

If you are a package developer you should define a new Logger for each package, but you do not need to configure it. The user of the package should decide how and where to output logging, usually by configuring the root Logger (new Appenders added/removed, Layouts modified, etc...).

See Also

[glue](#)

[get_logger\(\)](#)

Examples

```
# lgr::lgr is the root logger that is always available
lgr$info("Today is a good day")
lgr$fatal("This is a serious error")

# Loggers use sprintf() for string formatting by default
lgr$info("Today is %s", Sys.Date() )

# If no unnamed `...` are present, msg is not passed through sprintf()
lgr$fatal("100% bad") # so this works
lgr$fatal("%s% bad", 100) # if you use unnamed arguments, you must escape %

# You can create new loggers with get_logger()
tf <- tempfile()
```



```

lg <- get_logger("mylogger")$set_appenders(AppenderFile$new(tf))

# The new logger passes the log message on to the appenders of its parent
# logger, which is by default the root logger. This is why the following
# writes not only the file 'tf', but also to the console.
lg$fatal("blubb")
readLines(tf)

# This logger's print() method depicts this relationship.
child <- get_logger("lg/child")
print(child)
print(child$name)

# use formatting strings and custom fields
tf2 <- tempfile()
lg$add_appender(AppenderFile$new(tf2, layout = LayoutJson$new()))
lg$info("Not all %s support custom fields", "appenders", type = "test")
cat(readLines(tf), sep = "\n")
cat(readLines(tf2), sep = "\n")

# cleanup
unlink(c(tf, tf2))
lg$config(NULL) # reset logger config

# LoggerGlue
# You can also create a new logger that uses the awesome glue library for
# string formatting instead of sprintf

if (requireNamespace("glue")){

  lg <- get_logger_glue("glue")
  lg$fatal("blah ", "fizz is set to: {fizz}", foo = "bar", fizz = "buzz")
  # prevent creation of custom fields with prefixing a dot
  lg$fatal("blah ", "fizz is set to: {.fizz}", foo = "bar", .fizz = "buzz")

  #' # completely reset 'glue' to an unconfigured vanilla Logger
  get_logger("glue", reset = TRUE)

}

# Configuring a Logger
lg <- get_logger("test")
lg$config(NULL) # resets logger to unconfigured state

# With setters
lg$
  set_threshold("error")$
  set_propagate(FALSE)$
  set_appenders(AppenderConsole$new(threshold = "info"))

lg$config(NULL)

```

```

# With a list
lg$config(list(
  threshold = "error",
  propagate = FALSE,
  appenders = list(AppenderConsole$new(threshold = "info"))
))

lg$config(NULL) # resets logger to unconfigured state

# Via YAML
cfg <- "
Logger:
  threshold: error
  propagate: false
  appenders:
    AppenderConsole:
      threshold: info
"

lg$config(cfg)
lg$config(NULL)

## -----
## Method `Logger$list_log`
## -----

lg <- get_logger("test")
lg$list_log(list(level = 400, msg = "example"))

## -----
## Method `Logger$add_appender`
## -----

lg <- get_logger("test")
lg$add_appender(AppenderConsole$new(), name = "myconsole")
lg$appenders[[1]]
lg$appenders$myconsole
lg$remove_appender("myconsole")
lg$config(NULL) # reset config

## -----
## Method `Logger$set_exception_handler`
## -----

lgr$info(stop("this produces a warning instead of an error"))

```

Description

LoggerGlue uses `glue::glue()` instead of `base::sprintf()` to construct log messages. `glue` is a very well designed package for string interpolation. It makes composing log messages more flexible and comfortable at the price of an additional dependency and slightly less performance than `sprintf()`.

Details

`glue()` lets you define temporary named variables inside the call. As with the normal `Logger`, these named arguments get turned into custom fields; however, you can suppress this behaviour by making named argument start with a `"."`. Please refer to `vignette("lgr", package = "lgr")` for examples.

Super classes

```
lgr::Filterable -> lgr::Logger -> LoggerGlue
```

Methods

Public methods:

- `LoggerGlue$fatal()`
- `LoggerGlue$error()`
- `LoggerGlue$warn()`
- `LoggerGlue$info()`
- `LoggerGlue$debug()`
- `LoggerGlue$trace()`
- `LoggerGlue$log()`
- `LoggerGlue$list_log()`
- `LoggerGlue$spawn()`

Method `fatal()`:

Usage:

```
LoggerGlue$fatal(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method `error()`:

Usage:

```
LoggerGlue$error(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method `warn()`:

Usage:

```
LoggerGlue$warn(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method `info()`:

Usage:

```
LoggerGlue$info(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method debug():*Usage:*

```
LoggerGlue$debug(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method trace():*Usage:*

```
LoggerGlue$trace(..., caller = get_caller(-8L), .envir = parent.frame())
```

Method log():*Usage:*

```
LoggerGlue$log(  
  level,  
  ...,  
  timestamp = Sys.time(),  
  caller = get_caller(-7),  
  .envir = parent.frame()  
)
```

Method list_log():*Usage:*

```
LoggerGlue$list_log(x)
```

Method spawn():*Usage:*

```
LoggerGlue$spawn(name)
```

logger_config

Logger Configuration Objects

Description

logger_config() is an S3 constructor for logger_config objects that can be passed to the \$config method of a [Logger](#). You can just pass a normal list instead, but using this constructor is a more formal way that includes additional argument checking.

Usage

```
logger_config(  
  appenders = NULL,  
  threshold = NULL,  
  filters = NULL,  
  exception_handler = NULL,  
  propagate = TRUE  
)
```

```

as_logger_config(x)

## S3 method for class 'list'
as_logger_config(x)

## S3 method for class 'character'
as_logger_config(x)

```

Arguments

appenders	see Logger
threshold	see Logger
filters	see Logger
exception_handler	see Logger
propagate	see Logger
x	any R object. Especially: <ul style="list-style-type: none"> • A character scalar. This can either be the path to a YAML file or a character scalar containing valid YAML • a list containing the elements <code>appenders</code>, <code>threshold</code>, <code>exception_handler</code>, <code>propagate</code> and <code>filters</code>. See the section <i>Fields</i> in Logger for details. • a <code>Logger</code> object, to clone its configuration.

Value

a list with the subclass "logger_config"
a logger_config object

See Also

<https://yaml.org/>

logger_tree

Logger Tree

Description

Displays a tree structure of all registered Loggers.

Usage

```
logger_tree()
```

Value

data.frame with subclass "logger_tree"

Symbology

- unconfigured Loggers are displayed in gray (if your terminal supports colors and you have the package **crayon** installed).
- If a logger's threshold is set, it is displayed in square brackets next to its name (reminder: if the threshold is not set, it is inherited from next logger up the logger tree).
- If a logger's propagate field is set to FALSE an red hash (#) sign is displayed in front of the logger name, to imply that it does not pass LogEvents up the tree.

Examples

```
get_logger("fancymodel")
get_logger("fancymodel/shiny")$
  set_propagate(FALSE)

get_logger("fancymodel/shiny/ui")$
  set_appenders(AppenderConsole$new())

get_logger("fancymodel/shiny/server")$
  set_appenders(list(AppenderConsole$new(), AppenderConsole$new()))$
  set_threshold("trace")

get_logger("fancymodel/plumber")

if (requireNamespace("cli")){
  print(logger_tree())
}
```

pad_right

Pad Character Vectors

Description

Pad Character Vectors

Arguments

x	a character vector
width	integer scalar. target string width
pad	character scalar. the symbol to pad with

Examples

```
pad_left("foo", 5)
pad_right("foo", 5, ".")
pad_left(c("foo", "foooooo"), pad = ".")
```

print.Appender	<i>Print an Appender object</i>
----------------	---------------------------------

Description

The print() method for Loggers displays the most important aspects of the Appender.

Usage

```
## S3 method for class 'Appender'
print(x, color = requireNamespace("crayon", quietly = TRUE), ...)
```

Arguments

x	any R Object
color	TRUE or FALSE: Output with color? Requi<- the Package crayon
...	ignored

Value

print() returns x (invisibly), format() returns a character vector.

Examples

```
# print most important details of logger
print(lgr$console)
```

print.LogEvent	<i>Print or Format Logging Data</i>
----------------	-------------------------------------

Description

Print or Format Logging Data

Usage

```
## S3 method for class 'LogEvent'
print(
  x,
  fmt = "%L [%t] %m %f",
  timestamp_fmt = "%Y-%m-%d %H:%M:%S",
  colors = getOption("lgr.colors"),
  log_levels = getOption("lgr.log_levels"),
  pad_levels = "right",
  ...
)
```

```

)

## S3 method for class 'LogEvent'
format(
  x,
  fmt = "%L [%t] %m %f",
  timestamp_fmt = "%Y-%m-%d %H:%M:%S",
  colors = NULL,
  log_levels = getOption("lgr.log_levels"),
  pad_levels = "right",
  ...
)

```

Arguments

x	a LogEvent
fmt	A character scalar that may contain any of the tokens listed bellow in the section Format Tokens.
timestamp_fmt	see format.POSIXct()
colors	A list of functions that will be used to color the log levels (likely from crayon::crayon).
log_levels	named integer vector of valid log levels
pad_levels	right, left or NULL. Whether or not to pad the log level names to the same width on the left or right side, or not at all.
...	ignored

Value

x for print() and a character scalar for format()

Format Tokens

- %t The timestamp of the message, formatted according to timestamp_fmt)
- %l the log level, lowercase character representation
- %L the log level, uppercase character representation
- %k the log level, first letter of lowercase character representation
- %K the log level, first letter of uppercase character representation
- %n the log level, integer representation
- %p the PID (process ID). Useful when logging code that uses multiple threads.
- %c the calling function
- %m the log message
- %f all custom fields of x in a pseudo-JSON like format that is optimized for human readability and console output
- %j all custom fields of x in proper JSON. This requires that you have **jsonlite** installed and does not support colors as opposed to %f

Examples

```

# standard fields can be printed using special tokens
x <- LogEvent$new(
  level = 300, msg = "a test event", caller = "testfun()", logger = lgr
)
print(x)
print(x, fmt = c("%t (%p) %c: %n - %m"))
print(x, colors = NULL)

# custom values
y <- LogEvent$new(
  level = 300, msg = "a gps track", logger = lgr,
  waypoints = 10, location = "Austria"
)

# default output with %f
print(y)

# proper JSON output with %j
if (requireNamespace("jsonlite")){
  print(y, fmt = "%L [%t] %m %j")
}

```

print.Logger

Print a Logger Object

Description

The `print()` method for Loggers displays the most important aspects of the Logger.

You can also print just the ancestry of a Logger which can be accessed with `logger$ancestry()`. This returns a named character vector whose names correspond to the names of the Loggers logger inherits from. The TRUE/FALSE status of its elements correspond to the propagate values of these Loggers.

Usage

```

## S3 method for class 'Logger'
print(x, color = requireNamespace("crayon", quietly = TRUE), ...)

## S3 method for class 'Logger'
format(x, color = FALSE, ...)

## S3 method for class 'ancestry'
print(x, color = requireNamespace("crayon", quietly = TRUE), ...)

## S3 method for class 'ancestry'
format(x, color = FALSE, ...)

```

Arguments

x	any R Object
color	TRUE or FALSE: Output with color? Requi<- the Package crayon
...	ignored

Value

print() returns x (invisibly), format() returns a character vector.

Examples

```
# print most important details of logger
print(lgr)
# print only the ancestry of a logger
lg <- get_logger("AegonV/Aerys/Rheagar/Aegon")
get_logger("AegonV/Aerys/Rheagar")$set_propagate(FALSE)

print(lg$ancestry)
unclass(lg$ancestry)
```

print.logger_tree *Print Logger Trees*

Description

Print Logger Trees

Usage

```
## S3 method for class 'logger_tree'
print(x, color = requireNamespace("crayon", quietly = TRUE), ...)

## S3 method for class 'logger_tree'
format(x, color = FALSE, ...)
```

Arguments

x	a logger_tree
color	logical scalar. If TRUE terminal output is colorized via the package crayon ?
...	passed on to cli::tree()

Value

x (invisibly)

read_json_lines	<i>Read a JSON logfile</i>
-----------------	----------------------------

Description

Read a JSON logfile

Usage

```
read_json_lines(file, ...)
```

Arguments

file	character scalar. path to a JSON logfile (one JSON object per line)
...	passed on to <code>jsonlite::stream_in()</code>

Value

a data.frame

See Also

[LayoutJson](#)

simple_logging	<i>Simple Logging</i>
----------------	-----------------------

Description

`lgr` provides convenience functions managing the root `Logger`. These are designed chiefly for interactive use and are less verbose than their R6 method counterparts.

`threshold()` sets or retrieves the threshold for an [Appender](#) or [Logger](#) (the minimum level of log messages it processes). It's `target` defaults to the root logger. (equivalent to `lgr::lgr$threshold` and `lgr::lgr$set_threshold`)

`console_threshold()` is a shortcut to set the threshold of the root loggers [AppenderConsole](#), which is usually the only `Appender` that manages console output for a given R session. (equivalent to `lgr::lgr$appenders$console$threshold` and `lgr::lgr$appenders$console$set_threshold`)

`add_appender()` and `remove_appender()` add `Appenders` to `Loggers` and other `Appenders`. (equivalent to `lgr::lgr$add_appender` and `lgr::lgr$remove_appender`)

`show_log()` displays the last `n` log entries of an `Appender` (or a `Logger` with such an `Appender` attached) with a `$show()` method. Most, but not all `Appenders` support this function (try [AppenderFile](#) or [AppenderBuffer](#)).

`show_data()` and `show_dt()` work similar to `show_log()`, except that they return the log as `data.frame` or `data.table` respectively. Only Appenders that log to formats that can easily be converted to `data.frames` are supported (try [AppenderJson](#) or [AppenderBuffer](#)).

The easiest way to try out this features is by adding an `AppenderBuffer` to the root logger with `basic_config(memory = TRUE)`.

Usage

```
log_exception(code, logfun = lgr$fatal, caller = get_caller(-3))
```

```
threshold(level, target = lgr::lgr)
```

```
console_threshold(level, target = lgr::lgr$appenders$console)
```

```
add_appender(appender, name = NULL, target = lgr::lgr)
```

```
remove_appender(pos, target = lgr::lgr)
```

```
show_log(threshold = NA_integer_, n = 20L, target = lgr::lgr)
```

```
show_dt(target = lgr::lgr)
```

```
show_data(target = lgr::lgr)
```

Arguments

<code>code</code>	Any R code
<code>logfun</code>	a function for processing the log request, usually <code>lgr\$info()</code> , <code>lgr\$debug()</code> , etc... .
<code>caller</code>	a character scalar. The name of the calling function
<code>level</code>	integer or character scalar: the desired log level
<code>target</code>	a Logger or Appender or the name of a Logger as character scalar
<code>appender</code>	an Appender
<code>name</code>	character scalar. An optional name for the new Appender.
<code>pos</code>	integer index or character names of the appenders to remove
<code>threshold</code>	character or integer scalar. The minimum log level that should be processed by the root logger.
<code>n</code>	integer scalar. Show only the last n log entries that match threshold

Value

`threshold()` and `console_threshold()` return the [log_level](#) of target as integer (invisibly)

`add_appender()` and `remove_appender()` return target.

`show_log()` prints to the console and returns whatever the target Appender's `$show()` method returns, usually a character vector, `data.frame` or `data.table` (invisibly).

`show_data()` always returns a `data.frame` and `show_dt()` always returns a `data.table`.

Examples

```
# Get and set the threshold of the root logger
threshold("error")
threshold()
lgr$info("this will be suppressed")
lgr$error("an important error message")

# you can also specify a target to modify other loggers
lg <- get_logger("test")
threshold("fatal", target = lg)
threshold(target = lg)

# If a Logger's threshold is not set, the threshold is inherited from
# its parent, in this case the root logger (that we set to error/200 before)
threshold(NULL, target = lg)
threshold(target = lg)

# Alternative R6 API for getting/setting thresholds
lg$set_threshold("info")
lg$threshold
lg$set_threshold(300)
lg$threshold
lg$set_threshold(NULL)
lg$threshold

# cleanup
lgr$config(NULL)
lg$config(NULL)

# add Appenders to a Logger
add_appender(AppenderConsole$new(), "second_console_appender")
lgr$fatal("Multiple console appenders are a bad idea")
remove_appender("second_console_appender")
lgr$info("Good that we defined an appender name, so it's easy to remove")

# Reconfigure the root logger
basic_config(memory = TRUE)

# log some messages
lgr$info("a log message")
lgr$info("another message with data", data = 1:3)

show_log()
show_data()

# cleanup
lgr$config(NULL)
```

Description

These are helper functions for verifying log levels and converting them from their character to their integer representations. This is primarily useful if you want to build your own [Loggers](#), [Appenders](#) or [Layouts](#) and need to handle log levels in a way that is consistent with **lgr** .

Usage

```
standardize_threshold(
  x,
  log_levels = c(getOption("lgr.log_levels"), c(all = NA_integer_, off = 0L))
)

is_threshold(x)

standardize_log_level(x, log_levels = getOption("lgr.log_levels"))

is_log_level(x)

standardize_log_levels(x, log_levels = getOption("lgr.log_levels"))

is_log_levels(x)
```

Arguments

`x` a character or integer scalar, or vector for `standardize_log_levels`
`log_levels` named integer vector of valid log levels

Value

An unnamed integer vector

See Also

Other docs relevant for extending `lgr`: [LogEvent](#), [event_list\(\)](#)

Examples

```
standardize_threshold("info")
standardize_threshold("all")
is_threshold("all")
is_threshold("foobar")

standardize_log_level("info")
# all is a valid threshold, but not a valid log level
try(is.na(standardize_log_level("all")))
is_log_level("all")

# standardized_log_level intentionally only works with scalars, because many
# functions require scalar log level inputs
```

```
try(standardize_log_level(c("info", "fatal")))

# You can still use standardize_log_levels() (plural) to work with vectors
standardize_log_levels(c("info", "fatal"))
```

suspend_logging	<i>Suspend All Logging</i>
-----------------	----------------------------

Description

Completely disable logging for all loggers. This is for example useful for automated test code. `suspend_logging()` globally disables all logging with `lgr` until `unsuspend_logging()` is invoked, while `without_logging()` and `with_logging()` temporarily disable/enable logging.

Usage

```
suspend_logging()

unsuspend_logging()

without_logging(code)

with_logging(code)
```

Arguments

code Any R code

Value

`suspend_logging()` and `unsuspend_logging()` return `NULL` (invisibly), `without_logging()` and `with_logging()` returns whatever code returns.

Examples

```
lg <- get_logger("test")

# temporarily disable logging
lg$fatal("foo")
without_logging({
  lg$info("everything in this codeblock will be suppressed")
  lg$fatal("bar")
})

# globally disable logging
suspend_logging()
lg$fatal("bar")
with_logging(lg$fatal("foo")) # log anyways
```

```
# globally enable logging again
unsuspend_logging()
lg$fatal("foo")
```

toString.LogEvent	<i>Convert a LogEvent to a character string</i>
-------------------	---

Description

Convert a LogEvent to a character string

Usage

```
## S3 method for class 'LogEvent'
toString(x, ...)
```

Arguments

x	a LogEvent
...	ignored

Value

a character scalar

Examples

```
toString(LogEvent$new(logger = lgr::lgr))
```

use_logger	<i>Setup a Simple Logger for a Package</i>
------------	--

Description

This gives you a minimal logger with no appenders that you can use inside your package under the name lg (e.g. lg\$fatal("test")). use_logger() does not modify any files but only prints code for you to copy and paste.

Usage

```
use_logger(
  pkg = desc::desc_get("Package",
    rprojroot::find_package_root_file("DESCRIPTION"))[[1]]
)
```


Arguments

pkg character scalar. Name of the package. The default is to try to get the Package name automatically using the packages **rprojroot** and **desc**

Value

a character scalar containing R code.

Examples

```
use_logger("testpkg")
```

with_log_level *Inject Values into Logging Calls*

Description

with_log_level temporarily overrides the log level of all [LogEvents](#) created by target [Logger](#).

Usage

```
with_log_level(level, code, logger = lgr::lgr)
```

```
with_log_value(values, code, logger = lgr::lgr)
```

Arguments

level integer or character scalar: the desired log level

code Any R code

logger a [Logger](#) or the name of one (see [get_logger\(\)](#)). Defaults to the root logger (lgr::lgr).

values a named list of values to be injected into the logging calls

Details

These functions abuses lgr's filter mechanic to modify LogEvents in-place before they passed on the Appenders. Use with care as they can produce hard to reason about code.

Value

whatever code would return

Examples

```
with_log_level("warn", {
  lgr$info("More important than it seems")
  lgr$fatal("Really not so bad")
})
with_log_value(
  list(msg = "overriden msg"), {
    lgr$info("bar")
    lgr$fatal("FOO")
  })
```

Index

- * **Appenders**
 - AppenderBuffer, 3
 - AppenderConsole, 5
 - AppenderFile, 6
 - AppenderFileRotating, 9
 - AppenderFileRotatingDate, 11
 - AppenderFileRotatingTime, 12
 - AppenderTable, 16
- * **Layouts**
 - Layout, 33
 - LayoutFormat, 35
 - LayoutGlue, 38
 - LayoutJson, 39
- * **abstract classes**
 - AppenderMemory, 14
 - AppenderTable, 16
 - Filterable, 26
- * **developer tools**
 - CannotInitializeAbstractClassError, 21
- * **docs relevant for extending lgr**
 - event_list, 24
 - LogEvent, 41
 - standardize_threshold, 61
- * **formatting utils**
 - colorize_levels, 21
 - label_levels, 33
 - .obj (EventFilter), 23
- add_appender (simple_logging), 59
- add_log_levels (get_log_levels), 31
- Appender, 4–6, 8, 11, 12, 14, 16, 17, 20, 23, 27, 34, 47, 48, 59, 60
- AppenderBuffer, 3, 4, 6, 8, 11, 12, 14, 17, 20, 24, 59, 60
- AppenderConsole, 5, 5, 8, 11, 12, 14, 17, 59
- AppenderFile, 5, 6, 6, 9, 11, 12, 14, 17, 20, 34, 59
- AppenderFileRotating, 5, 6, 8, 9, 12, 14, 17
- AppenderFileRotatingDate, 5, 6, 8, 11, 11, 14, 17
- AppenderFileRotatingTime, 5, 6, 8, 11, 12, 12, 17
- AppenderJson, 6, 20, 42, 60
- AppenderJson (AppenderFile), 6
- AppenderMemory, 14, 17, 27
- Appenders, 14, 16, 26, 32, 34, 41–45, 62
- AppenderTable, 5, 6, 8, 11, 12, 14, 16, 16, 27
- as.data.frame.event_list (event_list), 24
- as.data.frame.LogEvent, 17
- as.data.frame.LogEvent(), 43
- as.data.table.event_list (event_list), 24
- as.data.table.LogEvent (as.data.frame.LogEvent), 17
- as_event_list (event_list), 24
- as_logger_config (logger_config), 52
- as_tibble.LogEvent (as.data.frame.LogEvent), 17
- base::as.data.frame(), 18, 25
- base::Filter(), 23
- base::format.POSIXct(), 36
- base::sprintf(), 45, 51
- base::sys.call(), 30
- basic_config, 19
- basic_config(memory = TRUE), 60
- CannotInitializeAbstractClassError, 21
- cli::tree(), 58
- colorize_levels, 21, 33
- colorize_levels(), 39
- condition, 47
- console_threshold (simple_logging), 59
- crayon::crayon, 21, 56
- data.table::data.table, 18
- data.tables, 17

- default_exception_handler, 22
- event_list, 24, 43, 62
- EventFilter, 23, 26, 27, 32
- EventFilters, 23, 27
- Filter (EventFilter), 23
- Filterable, 16, 17, 26, 32
- FilterForceLevel, 23, 27
- FilterInject, 23, 28
- Filters, 45
- format.ancestry (print.Logger), 57
- format.LogEvent, 20
- format.LogEvent (print.LogEvent), 55
- format.LogEvent(), 35, 36
- format.Logger (print.Logger), 57
- format.logger_tree (print.logger_tree), 58
- format.POSIXct(), 20, 40, 56
- get_caller, 29
- get_log_levels, 31
- get_log_levels(), 33
- get_logger, 30
- get_logger(), 43, 48, 65
- get_logger(name), 44
- get_logger_glue (get_logger), 30
- get_user (get_caller), 29
- glue::glue, 38
- glue::glue(), 38, 51
- is_filter, 32
- is_filter(), 24, 27, 32
- is_log_level (standardize_threshold), 61
- is_log_levels (standardize_threshold), 61
- is_threshold (standardize_threshold), 61
- jsonlite::stream_in(), 59
- jsonlite::toJSON(), 40
- label_levels, 22, 33
- Layout, 3, 5, 6, 16, 33, 37, 39, 41
- LayoutFormat, 5, 6, 8, 16, 34, 35, 38, 39, 41
- LayoutGlue, 34, 35, 37, 38, 41
- LayoutJson, 6, 8, 34, 37, 39, 39, 59
- Layouts, 14, 16, 26, 42, 62
- Layouts (Layout), 33
- lgr::Appender, 3, 5–7, 9, 11, 12, 14, 16
- lgr::AppenderFile, 7, 9, 11, 12
- lgr::AppenderFileRotating, 11, 12
- lgr::AppenderMemory, 3
- lgr::EventFilter, 27, 28
- lgr::Filterable, 3, 5–7, 9, 11, 12, 14, 16, 43, 51
- lgr::Layout, 35, 38, 39
- lgr::Logger, 51
- log_level, 20, 27, 28, 48, 60
- log_exception (simple_logging), 59
- log_level, 14, 42, 60
- log_level (get_log_levels), 31
- log_levels, 45
- log_levels (get_log_levels), 31
- LogEvent, 14, 25–28, 34–36, 38, 41, 43, 45, 56, 62, 64
- LogEvent\$new(), 45
- LogEvents, 14, 15, 24, 25, 28, 29, 34, 47, 65
- LogEvents (LogEvent), 41
- Logger, 3, 4, 19, 23, 30, 41, 42, 43, 52, 53, 59, 60, 65
- logger_config, 46, 52
- logger_tree, 53, 58
- LoggerGlue, 50
- Loggers, 22, 26, 32, 62
- Loggers (Logger), 43
- pad_left (pad_right), 54
- pad_left(), 39
- pad_right, 54
- pad_right(), 39
- POSIXct, 40, 42, 45
- print.ancestry (print.Logger), 57
- print.Appender, 55
- print.LogEvent, 55
- print.Logger, 57
- print.logger_tree, 58
- R6::R6, 21, 23, 26, 32
- R6ClassGenerator, 30
- read_json_lines, 59
- read_json_lines(), 41
- remove_appender (simple_logging), 59
- remove_log_levels (get_log_levels), 31
- rotor::rotate(), 9–12, 14
- show_data (simple_logging), 59
- show_dt (simple_logging), 59
- show_log (simple_logging), 59
- show_log(), 20

- simple_logging, [59](#)
- standardize_log_level
 - (standardize_threshold), [61](#)
- standardize_log_levels
 - (standardize_threshold), [61](#)
- standardize_threshold, [25](#), [43](#), [61](#)
- suspend_logging, [63](#)
- system_infos (get_caller), [29](#)

- threshold, [16](#), [17](#)
- threshold (simple_logging), [59](#)
- tibble::tibble, [18](#)
- tibbles, [17](#)
- toString.LogEvent, [64](#)

- unlabel_levels (label_levels), [33](#)
- unsuspend_logging (suspend_logging), [63](#)
- use_logger, [64](#)

- warnings, [47](#)
- whoami::whoami(), [30](#)
- with_log_level, [65](#)
- with_log_level(), [23](#), [27](#)
- with_log_value (with_log_level), [65](#)
- with_log_value(), [23](#), [29](#)
- with_logging (suspend_logging), [63](#)
- without_logging (suspend_logging), [63](#)