

# Package ‘mailtoR’

July 22, 2025

**Type** Package

**Title** Creates a Friendly User Interface for Emails Sending in 'shiny'

**Version** 0.1.0

**Author** Mohamed El Fodil Ihaddaden

**Maintainer** Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

**Description** Allows the user to generate a friendly user interface for emails sending.  
The user can choose from the most popular free email services ('Gmail', 'Outlook', 'Yahoo') and his default email application.  
The package is a wrapper for the 'Mailtoui' 'JavaScript' library. See <<https://mailtoui.com/#menu>> for more information.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Imports** htmltools, glue, utils

**RoxygenNote** 7.1.0

**URL** <https://github.com/feddelegrand7/mailtoR>

**BugReports** <https://github.com/feddelegrand7/mailtoR/issues>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-06-25 11:50:05 UTC

## Contents

mailtoR . . . . .	2
use_mailtoR . . . . .	3

<b>Index</b>	<b>4</b>
--------------	----------

---

`mailtoR`*Create a friendly user interface for sending emails*

---

**Description**

Create a friendly user interface for sending emails

**Usage**

```
mailtoR(email, text, subject = NULL, cc = NULL, bcc = NULL, body = NULL)
```

**Arguments**

<code>email</code>	the emails of the recipients
<code>text</code>	the link text that will be displayed on the ui
<code>subject</code>	the subject of the email. Defaults to NULL
<code>cc</code>	the emails of the CC (carbon copy) recipients. Defaults to NULL
<code>bcc</code>	the emails of the BCC (blind carbon copy) recipients. Defaults to NULL
<code>body</code>	the body of the email. Defaults to NULL

**Value**

a user interface for sending emails

**Examples**

```
if (interactive()) {  
  
  ui <- fluidPage(  
    mailtoR(email = "",  
            text = "click here to send an email"),  
    use_mailtoR()  
  )  
  
  server <- function(input, output){  
  
  }  
  
  shinyApp(ui, server)
```

```
}
```

---

use\_mailtoR

*Enable the MailtoUI javascript library*

---

### **Description**

The function activates the capabilities of the MailtoUI javascript library. The user needs to set it at the end of the shiny ui.

### **Usage**

```
use_mailtoR()
```

### **Value**

called for the side effect of activating the MailtoUI library

### **Examples**

```
# Put the function at the bottom of the ui  
use_mailtoR()
```

# Index

`mailtoR`, 2

`use_mailtoR`, 3