

Package ‘outrigger’

March 24, 2026

Type Package

Title Outrigger Regression

Version 1.1.0

Maintainer Elliot H. Young <ey244@cam.ac.uk>

Description Performs outrigger local polynomial regression/ distributional adaptation, using a score-matching spline estimator of the conditional score function.
Details of the method can be found in Young, Shah and Samworth (2026) <[doi:10.48550/arXiv.2603.11282](https://doi.org/10.48550/arXiv.2603.11282)>.

License GPL-3

Encoding UTF-8

Imports Rcpp, np, mgcv, RColorBrewer

LinkingTo Rcpp

Suggests testthat (>= 3.0.0)

RoxygenNote 7.2.3

NeedsCompilation yes

Author Elliot H. Young [cre],
Rajen D. Shah [aut],
Richard J. Samworth [aut]

Repository CRAN

Date/Publication 2026-03-24 10:10:15 UTC

Contents

outrigger	2
score_plots	3
Index	4

outrigger

Performs outrigger regression at a point x

Description

Performs outrigger regression at a point x

Usage

```
outrigger(
  formula,
  data,
  xtest,
  degree = 0,
  bandwidth = NULL,
  kernel = "epan",
  lambda = NULL,
  folds = 5,
  scoregranality = 1,
  score_df = 10,
  verbose = TRUE
)
```

Arguments

formula	formula (as in e.g. lm).
data	data frame.
xtest	datapoint(s) for local estimation.
degree	degree of polynomial.
bandwidth	bandwidth parameter. If NULL a rule-of-thumb bandwidth is selected by least-squares cross-validation for the standard local polynomial estimator.
kernel	kernel for local polyomial. Default is epanechnikov kernel.
lambda	orthogonalisation parameter. By default takes $\lambda = 4(1 + 0.5 \log(n))$.
folds	number of folds for cross-fitting. Default is 5.
scoregranality	the number of bins to split covariate-space $ X - x \leq \lambda h$ for conditional score estimation.
score_df	number of degrees of freedom for score matching splines used for conditional score estimation. Input can be a numeric value (e.g. 10 on larger datasets, 6 on smaller datasets) or "cross-validation" or "cross-validation-quick", in which case score-matching-CV will be performed (may be computationally costly).
verbose	suppresses messages of progress. Default is TRUE.

Value

If x is a single point, return a list containing:

`prediction` The outrigger local polynomial estimator $\hat{f}(x)$ at x .

`fitted_vector` For the local linear outrigger estimator, the full fitted vector at x

`standardlocpol_fitted_vector` The fitted vector for the standard local polynomial

`score_plot_metadata` Data used for score_plotting to plot the fitted conditional score functions

If x is a vector of points, return a dataset with points x and associated outrigger fitted values.

`score_plots`

Plots the fitted score functions learnt in an outrigger fit.

Description

Plots the fitted score functions learnt in an outrigger fit.

Usage

```
score_plots(fitted_outrig, plot_together = TRUE)
```

Arguments

`fitted_outrig` a fitted object from `outrigger`

`plot_together` a logical denoting whether all score function estimators (across all covariate bins) should be plotted together. Default is TRUE.

Value

No return value, called for plotting the estimated score function.

Index

outrigger, 2

score_plots, 3