

Package ‘sacRebleu’

April 30, 2024

Type Package

Title Metrics for Assessing the Quality of Generated Text

Version 0.1.3

Date 2024-04-05

Description Implementation of the BLEU-Score in 'C++' to evaluate the quality of generated text. The BLEU-Score, introduced by Papineni et al. (2002) <[doi:10.3115/1073083.1073135](https://doi.org/10.3115/1073083.1073135)>, is a metric for evaluating the quality of generated text. It is based on the n-gram overlap between the generated text and reference texts. Additionally, the package provides some smoothing methods as described in Chen and Cherry (2014) <[doi:10.3115/v1/W14-3346](https://doi.org/10.3115/v1/W14-3346)>.

License GPL (>= 2)

SystemRequirements Rust tool chain w/ cargo, libclang/llvm-config

Depends R (>= 4.2.0)

Imports checkmate, Rcpp (>= 1.0.12), tok

LinkingTo Rcpp

URL <https://github.com/LazerLambda/sacRebleu>

BugReports <https://github.com/LazerLambda/sacRebleu/issues>

Suggests knitr, rmarkdown, hfhub, testthat (>= 3.0.0), withr

Config/testthat/edition 3

RoxygenNote 7.2.3

VignetteBuilder knitr

Encoding UTF-8

Language en-US

Config/rextendr/version 0.3.1

NeedsCompilation yes

Author Philipp Koch [aut, cre]

Maintainer Philipp Koch <PhillKoch@protonmail.com>

Repository CRAN

Date/Publication 2024-04-30 08:40:03 UTC

R topics documented:

<i>bleu_corpus</i>	2
<i>bleu_corpus_ids</i>	3
<i>bleu_sentence</i>	4
<i>bleu_sentence_ids</i>	5
<i>validate_arguments</i>	6
<i>validate_references</i>	7

Index

8

<i>bleu_corpus</i>	<i>This function applies tokenization based on the 'tok' library and computes the BLEU score. An already initialized tokenizer can be provided using the 'tokenizer' argument or a valid huggingface identifier (string) can be passed. If the identifier is used only, the tokenizer is newly initialized on every call.</i>
--------------------	---

Description

This function applies tokenization based on the 'tok' library and computes the BLEU score. An already initialized tokenizer can be provided using the 'tokenizer' argument or a valid huggingface identifier (string) can be passed. If the identifier is used only, the tokenizer is newly initialized on every call.

Usage

```
bleu_corpus(
  references,
  candidates,
  tokenizer = "bert-base-cased",
  n = 4,
  weights = NULL,
  smoothing = NULL,
  epsilon = 0.1,
  k = 1
)
```

Arguments

<i>references</i>	A list of a list of reference sentences ('list(list(c(1,2,...)), list(c(3,5,...))))'.
<i>candidates</i>	A list of candidate sentences ('list(c(1,2,...), c(3,5,...))'.
<i>tokenizer</i>	Either an already initialized 'tok' tokenizer object or a huggingface identifier (default is 'bert-base-cased')
<i>n</i>	N-gram for BLEU score (default is set to 4).
<i>weights</i>	Weights for the n-grams (default is set to 1/n for each entry).

smoothing	Smoothing method for BLEU score (default is set to 'standard', 'floor', 'add-k' available)
epsilon	Epsilon value for epsilon-smoothing (default is set to 0.1).
k	K value for add-k-smoothing (default is set to 1).

Value

The BLEU score for the candidate sentence.

Examples

```
cand_corpus <- list("This is good", "This is not good")
ref_corpus <- list(list("Perfect outcome!", "Excellent!"), list("Not sufficient.", "Horrible."))

tok <- tok::tokenizer$from_pretrained("bert-base-uncased")
bleu_corpus <- bleu_corpus(ref_corpus, cand_corpus, tok)
```

bleu_corpus_ids	<i>Computes BLEU score (Papineni et al., 2002).</i>
-----------------	---

Description

'bleu_sentence_ids' computes the BLEU score for a corpus and its respective reference sentences. The sentences must be tokenized before so they are represented as integer vectors. Akin to 'sacrebleu' ('Python'), the function allows the application of different smoothing methods. Epsilon- and add-k-smoothing are available. Epsilon-smoothing is equivalent to 'floor' smoothing in the sacre-BLEU implementation. The different smoothing techniques are described in Chen et al., 2014 (<https://aclanthology.org/W14-3346/>).

Usage

```
bleu_corpus_ids(
  references,
  candidates,
  n = 4,
  weights = NULL,
  smoothing = NULL,
  epsilon = 0.1,
  k = 1
)
```

Arguments

references	A list of a list of reference sentences ('list(list(c(1,2,...)), list(c(3,5,...)))').
candidates	A list of candidate sentences ('list(c(1,2,...), c(3,5,...))').
n	N-gram for BLEU score (default is set to 4).

<code>weights</code>	Weights for the n-grams (default is set to 1/n for each entry).
<code>smoothing</code>	Smoothing method for BLEU score (default is set to 'standard', 'floor', 'add-k' available)
<code>epsilon</code>	Epsilon value for epsilon-smoothing (default is set to 0.1).
<code>k</code>	K value for add-k-smoothing (default is set to 1).

Value

The BLEU score for the candidate sentence.

Examples

```
cand_corpus <- list(c(1,2,3), c(1,2))
ref_corpus <- list(list(c(1,2,3), c(2,3,4)), list(c(1,2,6), c(781, 21, 9), c(7, 3)))
bleu_corpus_ids_standard <- bleu_corpus_ids(ref_corpus, cand_corpus)
bleu_corpus_ids_floor <- bleu_corpus_ids(ref_corpus, cand_corpus, smoothing="floor", epsilon=0.01)
bleu_corpus_ids_add_k <- bleu_corpus_ids(ref_corpus, cand_corpus, smoothing="add-k", k=1)
```

<code>bleu_sentence</code>	<i>Compute BLEU for a Sentence with Tokenization</i>
----------------------------	--

Description

This function applies tokenization based on the 'tok' library and computes the BLEU score. An already initialized tokenizer can be provided using the 'tokenizer' argument or a valid huggingface identifier (string) can be passed. If the identifier is used only, the tokenizer is newly initialized on every call.

Usage

```
bleu_sentence(
  references,
  candidate,
  tokenizer = "bert-base-cased",
  n = 4,
  weights = NULL,
  smoothing = NULL,
  epsilon = 0.1,
  k = 1
)
```

Arguments

<code>references</code>	A list of reference sentences.
<code>candidate</code>	A candidate sentence.
<code>tokenizer</code>	Either an already initialized 'tok' tokenizer object or a huggingface identifier (default is 'bert-base-cased')

n	N-gram for BLEU score (default is set to 4).
weights	Weights for the n-grams (default is set to 1/n for each entry).
smoothing	Smoothing method for BLEU score (default is set to 'standard', 'floor', 'add-k' available)
epsilon	Epsilon value for epsilon-smoothing (default is set to 0.1).
k	K value for add-k-smoothing (default is set to 1).

Value

The BLEU score for the candidate sentence.

Examples

```
cand <- "Hello World!"
ref <- list("Hello everyone.", "Hello Planet", "Hello World")

tok <- tok::tokenizer$from_pretrained("bert-base-uncased")
bleu_standard <- bleu_sentence(ref, cand, tok)
```

bleu_sentence_ids *Computes BLEU-Score (Papineni et al., 2002).*

Description

'bleu_sentence_ids' computes the BLEU score for a single candidate sentence and a list of reference sentences. The sentences must be tokenized before so they are represented as integer vectors. Akin to 'sacrebleu' ('Python'), the function allows the application of different smoothing methods. Epsilon- and add-k-smoothing are available. Epsilon-smoothing is equivalent to 'floor' smoothing in the sacrebleu implementation. The different smoothing techniques are described in Chen et al., 2014 (<https://aclanthology.org/W14-3346/>).

Usage

```
bleu_sentence_ids(
  references,
  candidate,
  n = 4,
  weights = NULL,
  smoothing = NULL,
  epsilon = 0.1,
  k = 1
)
```

Arguments

<code>references</code>	A list of reference sentences.
<code>candidate</code>	A candidate sentence.
<code>n</code>	N-gram for BLEU score (default is set to 4).
<code>weights</code>	Weights for the n-grams (default is set to 1/n for each entry).
<code>smoothing</code>	Smoothing method for BLEU score (default is set to 'standard', 'floor', 'add-k' available)
<code>epsilon</code>	Epsilon value for epsilon-smoothing (default is set to 0.1).
<code>k</code>	K value for add-k-smoothing (default is set to 1).

Value

The BLEU score for the candidate sentence.

Examples

```
ref_corpus <- list(c(1,2,3,4))
cand_corpus <- c(1,2,3,5)
bleu_standard <- bleu_sentence_ids(ref_corpus, cand_corpus)
bleu_floor <- bleu_sentence_ids(ref_corpus, cand_corpus, smoothing="floor", epsilon=0.01)
bleu_add_k <- bleu_sentence_ids(ref_corpus, cand_corpus, smoothing="add-k", k=1)
```

validate_arguments *Validate Arguments*

Description

Validate Arguments

Usage

```
validate_arguments(weights, smoothing, n)
```

Arguments

<code>weights</code>	Weight vector for 'bleu_corpus_ids' and 'bleu_sentence_ids' functions
<code>smoothing</code>	Smoothing method for 'bleu_corpus_ids' and 'bleu_sentence_ids' functions
<code>n</code>	N-gram for 'bleu_corpus_ids' and 'bleu_sentence_ids' functions

Value

A list with the validated arguments (weights and smoothing)

`validate_references` *Validate References*

Description

Validate References

Usage

```
validate_references(references, target)
```

Arguments

<code>references</code>	A list of reference sentences.
<code>target</code>	A vector of target lengths.

Value

A boolean value indicating if the references are valid.

Index

`bleu_corpus`, [2](#)
`bleu_corpus_ids`, [3](#)
`bleu_sentence`, [4](#)
`bleu_sentence_ids`, [5](#)
`validate_arguments`, [6](#)
`validate_references`, [7](#)