

Package ‘tabnet’

June 23, 2021

Title Fit 'TabNet' Models for Classification and Regression

Version 0.2.0

Description Implements the 'TabNet' model by Sercan O. Arik et al (2019) <[arXiv:1908.07442](https://arxiv.org/abs/1908.07442)> and provides a consistent interface for fitting and creating predictions. It's also fully compatible with the 'tidymodels' ecosystem.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.1

URL <https://github.com/mlverse/tabnet>

BugReports <https://github.com/mlverse/tabnet/issues>

Imports torch (>= 0.4.0), hardhat, magrittr, glue, progress, rlang, methods, tibble, coro, vctrs

Suggests testthat, modeldata, recipes, parsnip, dials, withr, knitr, rmarkdown, vip, tidyverse, ggplot2, dplyr, tidyr, purrr

VignetteBuilder knitr

NeedsCompilation no

Author Daniel Falbel [aut, cre],
RStudio [cph],
Christophe Regouby [ctb]

Maintainer Daniel Falbel <daniel@rstudio.com>

Repository CRAN

Date/Publication 2021-06-22 22:00:02 UTC

R topics documented:

autoplot.tabnet_explain	2
autoplot.tabnet_fit	3
decision_width	4
resolve_data	5
tabnet	5

tabnet_config	7
tabnet_explain	9
tabnet_fit	10
tabnet_pretrain	12

Index	16
--------------	-----------

autoplot.tabnet_explain

Plot tabnet_explain mask importance heatmap

Description

Plot tabnet_explain mask importance heatmap

Usage

```
autoplot.tabnet_explain(
  object,
  type = c("mask_agg", "steps"),
  quantile = 1,
  ...
)
```

Arguments

object	A tabnet_explain object as a result of <code>tabnet_explain()</code> .
type	a character value. Either "mask_agg" the default, for a single heatmap of aggregated mask importance per predictor along the dataset, or "steps" for one heatmap at each mask step.
quantile	numerical value between 0 and 1. Provides quantile clipping of the mask values
...	not used.

Details

Plot the tabnet_explain object mask importance per variable along the predicted dataset. type="mask_agg" output a single heatmap of mask aggregated values, type="steps" provides a plot faceted along the n_steps mask present in the model. quantile=.995 may be used for strong outlier clipping, in order to better highlight low values. quantile=1, the default, do not clip any values.

Value

A ggplot object.

Examples

```
library(ggplot2)
data("attrition", package = "modeldata")
attrition_fit <- tabnet_fit(Attrition ~. , data=attrition, epoch=15)
attrition_explain <- tabnet_explain(attrition_fit, attrition)
# Plot the model aggregated mask interpretation heatmap
autoplot(attrition_explain)
```

autoplot.tabnet_fit *Plot tabnet_fit model loss along epochs*

Description

Plot tabnet_fit model loss along epochs

Usage

```
autoplot.tabnet_fit(object, ...)
```

```
autoplot.tabnet_pretrain(object, ...)
```

Arguments

object	A tabnet_fit or tabnet_pretrain object as a result of tabnet_fit() or tabnet_pretrain() .
...	not used.

Details

Plot the training loss along epochs, and validation loss along epochs if any. A dot is added on epochs where model snapshot is available, helping the choice of from_epoch value for later model training resume.

Value

A ggplot object.

Examples

```
library(ggplot2)
data("attrition", package = "modeldata")
attrition_fit <- tabnet_fit(Attrition ~. , data=attrition, valid_split=0.2, epoch=15)
```

```
# Plot the model loss over epochs
autoplot(attrition_fit)
```

decision_width	<i>Parameters for the tabnet model</i>
----------------	--

Description

Parameters for the tabnet model

Usage

```
decision_width(range = c(8L, 64L), trans = NULL)
attention_width(range = c(8L, 64L), trans = NULL)
num_steps(range = c(3L, 10L), trans = NULL)
feature_reusage(range = c(1, 2), trans = NULL)
num_independent(range = c(1L, 5L), trans = NULL)
num_shared(range = c(1L, 5L), trans = NULL)
momentum(range = c(0.01, 0.4), trans = NULL)
mask_type(values = c("sparsemax", "entmax"))
```

Arguments

range	the default range for the parameter value
trans	whether to apply a transformation to the parameter
values	possible values for factor parameters

These functions are used with tune grid functions to generate candidates.

Value

A dials parameter to be used when tuning TabNet models.

resolve_data	<i>Transforms input data into tensors</i>
--------------	---

Description

Transforms input data into tensors

Usage

```
resolve_data(x, y)
```

Arguments

x	a data frame
y	a response vector

tabnet	<i>Parsnip compatible tabnet model</i>
--------	--

Description

Parsnip compatible tabnet model

Usage

```
tabnet(  
  mode = "unknown",  
  epochs = NULL,  
  penalty = NULL,  
  batch_size = NULL,  
  learn_rate = NULL,  
  decision_width = NULL,  
  attention_width = NULL,  
  num_steps = NULL,  
  feature_reusage = NULL,  
  virtual_batch_size = NULL,  
  num_independent = NULL,  
  num_shared = NULL,  
  momentum = NULL  
)
```

Arguments

mode	A single character string for the type of model. Possible values for this model are "unknown", "regression", or "classification".
epochs	(int) Number of training epochs.
penalty	This is the extra sparsity loss coefficient as proposed in the original paper. The bigger this coefficient is, the sparser your model will be in terms of feature selection. Depending on the difficulty of your problem, reducing this value could help.
batch_size	(int) Number of examples per batch, large batch sizes are recommended. (default: 1024)
learn_rate	initial learning rate for the optimizer.
decision_width	(int) Width of the decision prediction layer. Bigger values gives more capacity to the model with the risk of overfitting. Values typically range from 8 to 64.
attention_width	(int) Width of the attention embedding for each mask. According to the paper $n_d=n_a$ is usually a good choice. (default=8)
num_steps	(int) Number of steps in the architecture (usually between 3 and 10)
feature_reusage	(float) This is the coefficient for feature reusage in the masks. A value close to 1 will make mask selection least correlated between layers. Values range from 1.0 to 2.0.
virtual_batch_size	(int) Size of the mini batches used for "Ghost Batch Normalization" (default=128)
num_independent	Number of independent Gated Linear Units layers at each step. Usual values range from 1 to 5.
num_shared	Number of shared Gated Linear Units at each step Usual values range from 1 to 5
momentum	Momentum for batch normalization, typically ranges from 0.01 to 0.4 (default=0.02)

Value

A TabNet parsnip instance. It can be used to fit tabnet models using parsnip machinery.

Threading

TabNet uses torch as its backend for computation and torch uses all available threads by default.

You can control the number of threads used by torch with:

```
torch::torch_set_num_threads(1)
torch::torch_set_num_interop_threads(1)
```

See Also

tabnet_fit

Examples

```
if (torch::torch_is_installed()) {  
  library(parsnip)  
  data("ames", package = "modeldata")  
  model <- tabnet() %>%  
    set_mode("regression") %>%  
    set_engine("torch")  
  model %>%  
    fit(Sale_Price ~ ., data = ames)  
}
```

tabnet_config

Configuration for TabNet models

Description

Configuration for TabNet models

Usage

```
tabnet_config(  
  batch_size = 256,  
  penalty = 0.001,  
  clip_value = NULL,  
  loss = "auto",  
  epochs = 5,  
  drop_last = FALSE,  
  decision_width = NULL,  
  attention_width = NULL,  
  num_steps = 3,  
  feature_reusage = 1.3,  
  mask_type = "sparsemax",  
  virtual_batch_size = 128,  
  valid_split = 0,  
  learn_rate = 0.02,  
  optimizer = "adam",  
  lr_scheduler = NULL,  
  lr_decay = 0.1,  
  step_size = 30,  
  checkpoint_epochs = 10,  
  cat_emb_dim = 1,  
  num_independent = 2,  
  num_shared = 2,  
  momentum = 0.02,  
  pretraining_ratio = 0.5,  
  verbose = FALSE,
```

```

    device = "auto",
    importance_sample_size = NULL
)

```

Arguments

batch_size	(int) Number of examples per batch, large batch sizes are recommended. (default: 1024)
penalty	This is the extra sparsity loss coefficient as proposed in the original paper. The bigger this coefficient is, the sparser your model will be in terms of feature selection. Depending on the difficulty of your problem, reducing this value could help.
clip_value	If a float is given this will clip the gradient at clip_value. Pass NULL to not clip.
loss	(character or function) Loss function for training (default to mse for regression and cross entropy for classification)
epochs	(int) Number of training epochs.
drop_last	(bool) Whether to drop last batch if not complete during training
decision_width	(int) Width of the decision prediction layer. Bigger values gives more capacity to the model with the risk of overfitting. Values typically range from 8 to 64.
attention_width	(int) Width of the attention embedding for each mask. According to the paper $n_d=n_a$ is usually a good choice. (default=8)
num_steps	(int) Number of steps in the architecture (usually between 3 and 10)
feature_reusage	(float) This is the coefficient for feature reusage in the masks. A value close to 1 will make mask selection least correlated between layers. Values range from 1.0 to 2.0.
mask_type	(character) Final layer of feature selector in the attentive_transformer block, either "sparsemax" or "entmax". Defaults to "sparsemax".
virtual_batch_size	(int) Size of the mini batches used for "Ghost Batch Normalization" (default=128)
valid_split	(float) The fraction of the dataset used for validation.
learn_rate	initial learning rate for the optimizer.
optimizer	the optimization method. currently only 'adam' is supported, you can also pass any torch optimizer function.
lr_scheduler	if NULL, no learning rate decay is used. if "step" decays the learning rate by lr_decay every step_size epochs. It can also be a torch:lr_scheduler function that only takes the optimizer as parameter. The step method is called once per epoch.
lr_decay	multiplies the initial learning rate by lr_decay every step_size epochs. Unused if lr_scheduler is a torch::lr_scheduler or NULL.
step_size	the learning rate scheduler step size. Unused if lr_scheduler is a torch::lr_scheduler or NULL.

checkpoint_epochs	checkpoint model weights and architecture every checkpoint_epochs. (default is 10). This may cause large memory usage. Use 0 to disable checkpoints.
cat_emb_dim	Embedding size for categorical features (default=1)
num_independent	Number of independent Gated Linear Units layers at each step. Usual values range from 1 to 5.
num_shared	Number of shared Gated Linear Units at each step Usual values range from 1 to 5
momentum	Momentum for batch normalization, typically ranges from 0.01 to 0.4 (default=0.02)
pretraining_ratio	Ratio of features to mask for reconstruction during pretraining. Ranges from 0 to 1 (default=0.5)
verbose	(bool) wether to print progress and loss values during training.
device	the device to use for training. "cpu" or "cuda". The default ("auto") uses to "cuda" if it's available, otherwise uses "cpu".
importance_sample_size	sample of the dataset to compute importance metrics. If the dataset is larger than 1e5 obs we will use a sample of size 1e5 and display a warning.

Value

A named list with all hyperparameters of the TabNet implementation.

tabnet_explain	<i>Interpretation metrics from a TabNet model</i>
----------------	---

Description

Interpretation metrics from a TabNet model

Usage

```
tabnet_explain(object, new_data)
```

Arguments

object	a TabNet fit object
new_data	a data.frame to obtain interpretation metrics.

Value

Returns a list with

- M_explain: the aggregated feature importance masks as detailed in TabNet's paper.
- masks a list containing the masks for each step.

Examples

```
if (torch::torch_is_installed()) {  
  
  set.seed(2021)  
  
  n <- 1000  
  x <- data.frame(  
    x = runif(n),  
    y = runif(n),  
    z = runif(n)  
  )  
  
  y <- x$x  
  
  fit <- tabnet_fit(x, y, epochs = 20,  
                  num_steps = 1,  
                  batch_size = 512,  
                  attention_width = 1,  
                  num_shared = 1,  
                  num_independent = 1)  
  
  ex <- tabnet_explain(fit, x)  
  
}
```

tabnet_fit

Tabnet model

Description

Fits the **TabNet: Attentive Interpretable Tabular Learning** model

Usage

```
tabnet_fit(x, ...)  
  
## Default S3 method:  
tabnet_fit(x, ...)  
  
## S3 method for class 'data.frame'  
tabnet_fit(  
  x,  
  y,  
  tabnet_model = NULL,  
  config = tabnet_config(),  
  ...,
```

```

    from_epoch = NULL
  )

## S3 method for class 'formula'
tabnet_fit(
  formula,
  data,
  tabnet_model = NULL,
  config = tabnet_config(),
  ...,
  from_epoch = NULL
)

## S3 method for class 'recipe'
tabnet_fit(
  x,
  data,
  tabnet_model = NULL,
  config = tabnet_config(),
  ...,
  from_epoch = NULL
)

```

Arguments

x	<p>Depending on the context:</p> <ul style="list-style-type: none"> • A data frame of predictors. • A matrix of predictors. • A recipe specifying a set of preprocessing steps created from <code>recipes::recipe()</code>. <p>The predictor data should be standardized (e.g. centered or scaled). The model treats categorical predictors internally thus, you don't need to make any treatment.</p>
...	Model hyperparameters. Any hyperparameters set here will update those set by the config argument. See <code>tabnet_config()</code> for a list of all possible hyperparameters.
y	<p>When x is a data frame or matrix, y is the outcome specified as:</p> <ul style="list-style-type: none"> • A data frame with 1 numeric column. • A matrix with 1 numeric column. • A numeric vector.
tabnet_model	A previously fitted TabNet model object to continue the fitting on. if NULL (the default) a brand new model is initialized.
config	A set of hyperparameters created using the <code>tabnet_config</code> function. If no argument is supplied, this will use the default values in <code>tabnet_config()</code> .
from_epoch	When a <code>tabnet_model</code> is provided, restore the network weights from a specific epoch. Default is last available checkpoint for restored model, or last epoch for in-memory model.

formula	A formula specifying the outcome terms on the left-hand side, and the predictor terms on the right-hand side.
data	When a recipe or formula is used, data is specified as: <ul style="list-style-type: none"> • A data frame containing both the predictors and the outcome.

Value

A TabNet model object. It can be used for serialization, predictions, or further fitting.

Fitting a pre-trained model

When providing a parent `tabnet_model` parameter, the model fitting resumes from that model weights at the following epoch:

- last fitted epoch for a model already in torch context
 - Last model checkpoint epoch for a model loaded from file
 - the epoch related to a checkpoint matching or preceding the `from_epoch` value if provided
- The model fitting metrics append on top of the parent metrics in the returned TabNet model.

Threading

TabNet uses torch as its backend for computation and torch uses all available threads by default.

You can control the number of threads used by torch with:

```
torch::torch_set_num_threads(1)
torch::torch_set_num_interop_threads(1)
```

Examples

```
if (torch::torch_is_installed()) {
  data("ames", package = "modeldata")
  fit <- tabnet_fit(Sale_Price ~ ., data = ames, epochs = 1)
}
```

tabnet_pretrain

Tabnet model

Description

Pretrain the **TabNet: Attentive Interpretable Tabular Learning** model on the predictor data exclusively (unsupervised training).

Usage

```

tabnet_pretrain(x, ...)

## Default S3 method:
tabnet_pretrain(x, ...)

## S3 method for class 'data.frame'
tabnet_pretrain(
  x,
  y,
  tabnet_model = NULL,
  config = tabnet_config(),
  ...,
  from_epoch = NULL
)

## S3 method for class 'formula'
tabnet_pretrain(
  formula,
  data,
  tabnet_model = NULL,
  config = tabnet_config(),
  ...,
  from_epoch = NULL
)

## S3 method for class 'recipe'
tabnet_pretrain(
  x,
  data,
  tabnet_model = NULL,
  config = tabnet_config(),
  ...,
  from_epoch = NULL
)

```

Arguments

x	Depending on the context: <ul style="list-style-type: none"> • A data frame of predictors. • A matrix of predictors. • A recipe specifying a set of preprocessing steps created from <code>recipes::recipe()</code>. <p>The predictor data should be standardized (e.g. centered or scaled). The model treats categorical predictors internally thus, you don't need to make any treatment.</p>
...	Model hyperparameters. Any hyperparameters set here will update those set by

	the config argument. See <code>tabnet_config()</code> for a list of all possible hyperparameters.
<code>y</code>	(optional) When <code>x</code> is a data frame or matrix , <code>y</code> is the outcome
<code>tabnet_model</code>	A pretrained TabNet model object to continue the fitting on. if NULL (the default) a brand new model is initialized.
<code>config</code>	A set of hyperparameters created using the <code>tabnet_config</code> function. If no argument is supplied, this will use the default values in <code>tabnet_config()</code> .
<code>from_epoch</code>	When a <code>tabnet_model</code> is provided, restore the network weights from a specific epoch. Default is last available checkpoint for restored model, or last epoch for in-memory model.
<code>formula</code>	A formula specifying the outcome terms on the left-hand side, and the predictor terms on the right-hand side.
<code>data</code>	When a recipe or formula is used, data is specified as: <ul style="list-style-type: none"> • A data frame containing both the predictors and the outcome.

Value

A TabNet model object. It can be used for serialization, predictions, or further fitting.

outcome

Outcome value are accepted here only for consistent syntax with `tabnet_fit`, but by design the outcome, if present, is ignored during pre-training.

pre-training from a previous model

When providing a parent `tabnet_model` parameter, the model pretraining resumes from that model weights at the following epoch:

- last pretrained epoch for a model already in torch context
- Last model checkpoint epoch for a model loaded from file
- the epoch related to a checkpoint matching or preceding the `from_epoch` value if provided
The model pretraining metrics append on top of the parent metrics in the returned TabNet model.

Threading

TabNet uses torch as its backend for computation and torch uses all available threads by default.

You can control the number of threads used by torch with:

```
torch::torch_set_num_threads(1)
torch::torch_set_num_interop_threads(1)
```

Examples

```
if (torch::torch_is_installed()) {  
  data("ames", package = "modeldata")  
  pretrained <- tabnet_pretrain(Sale_Price ~ ., data = ames, epochs = 1)  
}
```

Index

attention_width (decision_width), 4
autoplot.tabnet_explain, 2
autoplot.tabnet_fit, 3
autoplot.tabnet_pretrain
 (autoplot.tabnet_fit), 3

decision_width, 4

feature_reusage (decision_width), 4

mask_type (decision_width), 4
momentum (decision_width), 4

num_independent (decision_width), 4
num_shared (decision_width), 4
num_steps (decision_width), 4

recipes::recipe(), 11, 13
resolve_data, 5

tabnet, 5
tabnet_config, 7
tabnet_config(), 11, 14
tabnet_explain, 9
tabnet_explain(), 2
tabnet_fit, 10
tabnet_fit(), 3
tabnet_pretrain, 12
tabnet_pretrain(), 3
torch::lr_scheduler, 8