

Package ‘zeallot’

January 28, 2018

Type Package

Title Multiple, Unpacking, and Destructuring Assignment

Version 0.1.0

Description Provides a `%<-%` operator to perform multiple, unpacking, and destructuring assignment in R. The operator unpacks the right-hand side of an assignment into multiple values and assigns these values to variables on the left-hand side of the assignment.

URL <https://github.com/nteetor/zeallot>

BugReports <https://github.com/nteetor/zeallot/issues>

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 6.0.1

VignetteBuilder knitr

Suggests testthat, knitr, rmarkdown, purrr, magrittr

NeedsCompilation no

Author Nathan Teetor [aut, cre],
Paul Teetor [ctb]

Maintainer Nathan Teetor <nathanteetor@gmail.com>

Repository CRAN

Date/Publication 2018-01-28 16:14:13 UTC

R topics documented:

destructure	2
operator	3
zeallot	7

Index	8
--------------	----------

`destructure`*Destructure an object*

Description

`destructure` is used during unpacking assignment to coerce an object into a list. Individual elements of the list are assigned to names on the left-hand side of the unpacking assignment expression.

Usage

```
destructure(x)
```

Arguments

`x` An R object.

Details

If `x` is atomic `destructure` expects `length(x)` to be 1. If a vector with length greater than 1 is passed to `destructure` an error is raised.

New implementations of `destructure` can be very simple. A new `destructure` implementation might only strip away the class of a custom object and return the underlying list structure. Alternatively, an object might `destructure` into a nested set of values and may require a more complicated implementation. In either case, new implementations must return a list object so `%<-%` can handle the returned value(s).

See Also

[%<-%](#)

Examples

```
# data frames become a list of columns
destructure(
  data.frame(x = 0:4, y = 5:9)
)

# strings are split into list of characters
destructure("abcdef")

# dates become list of year, month, and day
destructure(Sys.Date())

# create a new destructure implementation
shape <- function(sides = 4, color = "red") {
  structure(
    list(sides = sides, color = color),
    class = "shape"
  )
}
```

```
}

## Not run:
# cannot destructure the shape object yet
c(sides, color) %<-% shape()

## End(Not run)

# implement `destructure` for shapes
destructure.shape <- function(x) {
  list(x$sides, x$color)
}

# now we can destructure shape objects
c(sides, color) %<-% destructure(shape())

sides # 4
color # "red"

c(sides, color) %<-% destructure(shape(3, "green"))

sides # 3
color # 'green'
```

operator

Multiple assignment operators

Description

Assign values to name(s).

Usage

```
x %<-% value
```

```
value %->% x
```

Arguments

x	A name structure, see section below.
value	A list of values, vector of values, or R object to assign.

Value

%<-% and %->% invisibly return value.

These operators are used primarily for their assignment side-effect. %<-% and %->% assign into the environment in which they are evaluated.

Name Structure

the basics

At its simplest, the name structure may be a single variable name, in which case `%<-%` and `%->%` perform regular assignment, `x %<-% list(1, 2, 3)` or `list(1, 2, 3) %->% x`.

To specify multiple variable names use a call to `c()`, for example `c(x, y, z) %<-% c(1, 2, 3)`.

When value is neither an atomic vector nor a list, `%<-%` and `%->%` will try to destructure value into a list before assigning variables, see [destructure\(\)](#).

object parts

Like assigning a variable, one may also assign part of an object, `c(x, x[[1]]) %<-% list(list(), 1)`.

nested names

One can also nest calls to `c()` when needed, `c(x, c(y, z))`. This nested structure is used to unpack nested values, `c(x, c(y, z)) %<-% list(1, list(2, 3))`.

collector variables

To gather extra values from the beginning, middle, or end of value use a collector variable. Collector variables are indicated with a `...` prefix, `c(...start, z) %<-% list(1, 2, 3, 4)`.

skipping values

Use `.` in place of a variable name to skip a value without raising an error or assigning the value, `c(x, ., z) %<-% list(1, 2, 3)`.

Use `...` to skip multiple values without raising an error or assigning the values, `c(w, ..., z) %<-% list(1, NA, NA, 4)`.

default values

Use `=` to specify a default value for a variable, `c(x, y = NULL) %<-% tail(1, 2)`.

When assigning part of an object a default value may not be specified because of the syntax enforced by R. The following would raise an "unexpected '=' ..." error, `c(x, x[[1]] = 1) %<-% list(list())`.

See Also

For more on unpacking custom objects please refer to [destructure\(\)](#).

Examples

```
# basic usage
c(a, b) %<-% list(0, 1)

a # 0
b # 1

# unpack and assign nested values
c(c(e, f), c(g, h)) %<-% list(list(2, 3), list(3, 4))

e # 2
f # 3
g # 4
h # 5

# can assign more than 2 values at once
```

```
c(j, k, l) %<-% list(6, 7, 8)

# assign columns of data frame
c(erupts, wait) %<-% faithful

erupts # 3.600 1.800 3.333 ..
wait   # 79 54 74 ..

# assign only specific columns, skip
# other columns
c(mpg, cyl, disp, ...) %<-% mtcars

mpg   # 21.0 21.0 22.8 ..
cyl   # 6 6 4 ..
disp  # 160.0 160.0 108.0 ..

# skip initial values, assign final value
TODOs <- list("make food", "pack lunch", "save world")

c(..., task) %<-% TODOs

task # "save world"

# assign first name, skip middle initial,
# assign last name
c(first, ., last) %<-% c("Ursula", "K", "Le Guin")

first # "Ursula"
last  # "Le Guin"

# simple model and summary
mod <- lm(hp ~ gear, data = mtcars)

# extract call and fstatistic from
# the summary
c(modcall, ..., modstat, .) %<-% summary(mod)

modcall
modstat

# unpack nested values w/ nested names
fibs <- list(1, list(2, list(3, list(5))))

c(f2, c(f3, c(f4, c(f5)))) %<-% fibs

f2 # 1
f3 # 2
f4 # 3
f5 # 5

# unpack first numeric, leave rest
c(f2, fibcdr) %<-% fibs
```

```

f2      # 1
fibcdr  # list(2, list(3, list(5)))

# swap values without using temporary variables
c(a, b) %<-% c("eh", "bee")

a # "eh"
b # "bee"

c(a, b) %<-% c(b, a)

a # "bee"
b # "eh"

# unpack `strsplit` return value
names <- c("Nathan,Maria,Matt,Polly", "Smith,Peterson,Williams,Jones")

c(firsts, lasts) %<-% strsplit(names, ",")

firsts # c("Nathan", "Maria", ..
lasts  # c("Smith", "Peterson", ..

# handle missing values with default values
parse_time <- function(x) {
  strsplit(x, " ")[[1]]
}

c(hour, period = NA) %<-% parse_time("10:00 AM")

hour   # "10:00"
period # "AM"

c(hour, period = NA) %<-% parse_time("15:00")

hour   # "15:00"
period # NA

# right operator
list(1, 2, "a", "b", "c") %>-% c(x, y, ...chars)

x      # 1
y      # 2
chars  # list("a", "b", "c")

# magrittr chains, install.packages("magrittr") for this example
if (requireNamespace("magrittr", quietly = TRUE)) {
  library(magrittr)

  c("hello", "world!") %>%
    paste0("\n") %>%
    lapply(toupper) %>%
    c(greeting, subject)

```

```
greeting # "HELLO\n"  
subject  # "WORLD!\n"  
}
```

zeallot

Multiple, unpacking, and destructuring assignment in R

Description

zeallot provides a `%<-%` operator to perform multiple assignment in R. To get started with zeallot be sure to read over the introductory vignette on unpacking assignment, `vignette('unpacking-assignment')`.

Author(s)

Maintainer: Nathan Teetor <nathanteetor@gmail.com>

Other contributors:

- Paul Teetor [contributor]

See Also

[%<-%](#)

Index

`%->%` (operator), [3](#)

`%<-%` (operator), [3](#)

`destructure`, [2](#)

`destructure()`, [4](#)

operator, [3](#)

`zeallot`, [7](#)

`zeallot-package` (`zeallot`), [7](#)